BBB-U-521B
July 22, 1975
SUPERSEDING
BBB-U-521A
October 16, 1958

FEDERAL SPECIFICATION

UNIFORM, MAN'S (GUARDS AND POLICE)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE

1.1 This specification covers one type of all purpose weight uniform made from worsted serge fabric, composed of a wool and polyester blended yarn, intended for use by police and building guards.

1.2 Size and color. Uniforms covered by this specification shall be of the size and color specified (see 3.2.1.1, and 6.1).

2. APPLICABLE DOCUMENTS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

R-N-91 - Naphthalene, Technical
V-B-871 - Button, Sewing Hole, and Button, Staple, (Plastic).
V-F-106 - Fasteners, Slide, Interlocking.
V-T-276 - Thread, Cotton.
V-T-301 - Thread, Silk.
DDD-L-20 - Label; for Clothing, Equipage, and Tentage (General Use).
DDD-T-86 - Tape, Textile; Cotton, General Purpose (Unbleached, Bleached, or Dyed).
PPP-B-636 - Boxes, Shipping, Fiberboard.

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).
Fed. Std. No. 191 - Textile Test Methods.
Fed. Std. No. 751 - Stitches, Seams and Stitchings.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at The General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standard:

MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

American Society for Testing Materials (ASTM) Standard:

Test Method D 276 - Identification of Fibers in Textiles.

(Applications for copies should be addressed to the American Society for Testing Materials, 1916 Race Street, Philadelphia, PA 19103.)

Standard Color Card of America:

(Application for copies should be addressed to the Color Association of the United States, Inc., 200 Madison Avenue, New York, New York 10016.)

National Motor Freight Traffic Association, Incorporated, Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Association, Inc., Tariff Order Section, 1616 P Street, NW, Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Preproduction sample. When specified (see 6.2), before production is commenced, a sample of the uniform required shall be submitted or made available to the contracting officer or his authorized representative for approval. Approval of the preproduction sample authorizes commencement of production but does not relieve the supplier of responsibility for compliance with all provisions of this specification. The preproduction sample shall be manufactured in the same facilities to be utilized for the manufacture of the production items.

3.2 Material.

3.2.1 Cloth (body). The cloth shall have a fiber content of 55 percent polyester and 45 percent wool with a plus or minus tolerance of 4 percent for either polyester or wool. The yarn used in the fabrication of the cloth shall be an intimate blend of polyester and wool. Cloth shall conform to the physical requirements of table I.

3.2.1.1 Color. Unless otherwise specified, (see 6.1), the color shall be Midnight, Cable No. 70090 of the Standard Color Card of America or equal and shall match the approved standard shade under artificial daylight having a color temperature of 7500° Kelvin and shall be a good approximation to the standard shade under incandescent lamplight at 2800°.

3.2.1.2 Colorfastness. The cloth shall show good colorfastness to light, crocking, dry cleaning, wet dry cleaning, and perspiration, when tested as specified in table VII.

3.2.1.3 Shrinkage. The cloth shall not shrink more than 2 percent in either the warp or filling directions when tested for shrinkage in dry cleaning, sponging, and relaxation, as specified in table VII.

TABLE I. Physical requirements

Weave	Ply of yarns		Yarns per in.1/		Wt. per Sq. yd. 2/	Breaking strength (minimum)	
	Warp	Filling	Warp	Filling		Warp	Filling
					Ounces	Pounds	Pounds
2/2 Twill	2	2	72	55	9.0	175	150

1/ A minus tolerance of 2 yarns per inch in either direction and any plus tolerance will be permitted.
2/ A plus or minus tolerance of 3 percent will be permitted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.

3.2.2 Coat and sleeve lining. The coat and sleeve lining shall be rayon or acetate 2/1 twill weave cloth and shall weigh not less than 4 ounces per square yard. The yarns per inch shall be not less than 142 in the warp and not less than 66 in the filling. The breaking strength shall be not less than 115 pounds in the warp and not less than 50 pounds in the filling. The lining shall have a residual shrinkage of not more than 2 percent in either the warp or filling direction when tested for shrinkage in sponging and dry cleaning. The color shall be either dark blue or black and shall show good colorfastness to perspiration, dry cleaning, and wet dry cleaning (see 4.3).

3.2.3 Coat interlining (fronts).

3.2.3.1 Body canvas. The body canvas shall be plain weave and shall weigh not less than 7.5 ounces per square yard. The yarns per inch shall be not less than 44 in the warp and shall be not less than 34 in the filling. The warp yarns shall be 2-ply cotton and the filling yarns shall be single-ply rayon and horse or goat hair. The filling yarn shall consist of not less than 10 percent horse or goat hair. The canvas shall have a residual shrinkage of not more than 2 percent in either the warp or filling direction when tested for shrinkage to dry cleaning and sponging (see 4.3).

3.2.3.2 Chest canvas. The chest canvas shall be plain weave and shall weigh not less than 6 ounces per square yard. The yarns per inch shall be not less than 44 in the warp and shall be not less than 30 in the filling. The warp yarns shall be single-ply cotton and the filling yarns shall be single-ply rayon and horsehair or goat hair. The filling yarn shall consist of not less than 10 percent horsehair or goat hair. The canvas shall have a residual shrinkage of not more than 2 percent in either the warp or filling direction when tested for shrinkage to dry cleaning and sponging (see 4.3).

3.2.3.3 Reinforcing canvas. The reinforcing canvas shall be cotton and shall weight not less than 5.2 ounces per square yard and shall have not less than 52 ends per inch in the warp and shall have not less than 43 picks per inch in the filling. The reinforcing canvas shall be black and shall show good colorfastness to perspiration, dry cleaning, and wet dry cleaning (see 4.3).

3.2.3.4 Felt. The felt padding for the chest shall contain not less than 40 percent wool and shall weigh not less than 3.1 ounces per square yard (see 4.3).

3.2.3.5 Shoulder padding. The shoulder padding shall be of bleached or unbleached cotton, laminated batting approximately 7/8-inch thick.

3.2.4 Cuff interlining. The interlining of the sleeve cuffs shall be cotton wigan cloth weighing not less than 3.3 ounces per square yard, and shall have not less than 54 yarns per inch in the warp and shall have not less than 46 yarns per inch in the filling. The wigan shall be black and shall show good colorfastness to dry cleaning and wet dry cleaning (see 4.3).

3.2.5 Pocketing cloth.

3.2.5.1 For trousers. The pocketing cloth for the trousers shall be unbleached-cotton or polyester cotton drill weighing not less than 7.5 ounces per square yard and shall have a breaking strength of not less than 112 pounds in the warp and not less than 70 pounds in the filling (see 4.3).

3.2.5.2 For breast pockets. The breast pockets shall be lined with black cotton silesia weighing not less than 4.0 ounces per square yard and having a breaking strength of not less than 44 pounds in both the warp and filling directions (see 4.3).

3.2.6 Badge plate. The badge plate shall be 100 percent wool felt weighing not less than 5 ounces per square yard. Unless otherwise specified (see 6.1), the color of the badge plate shall be the same as the coat cloth (see 4.3).

3.2.7 Stay tape. The stay tape shall be tape, cotton, unbleached, 3/8 to 5/8-inch wide, and shall conform to the requirements of table I of DDD-T-86 except it shall be preshrunk and shall have a residual shrinkage of not more than one percent when tested in accordance with method 5580 of table VII.

3.2.8 Piping. The piping shall be the same material as the lining of the coat and sleeve (see 3.2.2), except leather piping shall be used for the button of the sleeves, the inside breast pockets, and hip pockets, when specified in the Invitation for Bids.

3.2.9 Thread.

3.2.9.1 Cotton. Cotton thread, as designated in table II, shall show good colorfastness to light, dry cleaning, wet dry cleaning, and perspiration and shall otherwise be in accordance with the requirements of V-T-276.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.

TABLE II. Thread

Type	Cord	Ticket Number	Color	Use
1C2	3	000	Black	Machine
1B2	3	40	White	Hand basting
1A2	3	60	White	Machine basting
1B2	4	12	Black	Buttons
1A2	3	50	White	Interlining

3.2.9.2 Silk and rayon. Silk or rayon thread shall be used for sleeve edges, bartacks, and fellings. The silk thread shall conform to ~~Federal Specification~~ V-T-301, for type B, 3 cord machine twist. Rayon thread shall be equal in strength to the specified silk thread.

3.2.10 Metal hooks. When metal hooks are specified (see 6.1), they shall be certified as noncorrosive steel, and shall have a gun-metal finish. The dimensions of the hooks shall be suitable for support of a Sam Brown belt.

3.2.11 Insignia. Unless otherwise specified (see 6.1), insignia shall be made from yellow-gold rayon braid 9/32 inch wide (see 3.4).

3.2.12 Chevrons. Chevrons shall be made of light blue wool stripes stitched on a good grade of dark blue wool felt, and unless otherwise specified (see 6.1), the outline of the stripes shall be embroidery stitched with multi-filament, white rayon or synthetic thread.

3.2.13 Gimp. The cotton gimp used for botton holes shall be known as a number 8 gimp and have a glazed finish. The breaking strength shall be not less than 6.8 pounds and the length per pound shall be not less than 2120 yards. The color of the gimp shall be black.

3.2.14 Hanger loops. The hanger loops shall be made of black cotton or synthetic braid 1/4 inch wide and shall have a breaking strength of not less than 75 pounds (see 4.3).

3.2.15 Labels. Coats and trousers shall have a contractor's label and a size label conforming to the requirements of classes 2 and 3, respectively, of DDD-L-20.

3.2.15.1 Contractor's label. The contractor's label shall measure not less than 2-3/4 by 2-1/2 inches. The nomenclature shall be printed in letters 3/16 inch in height and the remaining information in letters 1/8 inch in height. A blank space shall be provided for the inspector's stamp. The label content shall be as follows:

Nomenclature
Contractor's name
Date and number of contract
Specification title and number
Stock number
Name of contracting bureau or agency

Note: At the option of the contractor the word "size" may be included in the legend. This shall not, however, be construed to mean that the size label may be omitted.

3.2.15.2 Size label. The size label shall measure not less than 1-1/2 by 1-1/2 inches, and shall contain the word SIZE followed by the proper numerical size designation, and the word NAME followed by a space for the owner's name. The size of the garment shall be marked in numerals not less than 1/4 inch in height and the words SIZE and NAME 1/8 inch in height. For example:

SIZE: 34
NAME: _____

3.2.15.3 Content label. Each coat and trousers shall be labeled in accordance with the Textile Fiber Products Identification Act of 1960. The legend of this label may be incorporated in the contractors label or separate labels may be used at the option of the contracts.

3.2.16 Slide fastener. Slide fasteners shall be type I; style 1, cam lock; size L; short tap pull; of brass or zinc; with any dark colored cloth tape, conforming to V-F-106.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.

3.3 Construction.

3.3.1 Coats. The coats shall be single breasted with turn-down collars and shoulder straps, and shall have 16 silver or gold-color metal buttons. There shall be four 34 line buttons provided down the front of each coat; four 24 line buttons, one on each pocket; two 24 line buttons, one on each shoulder strap; six 24 line buttons, three on each sleeve. Coats shall be half lined and have normal concave shoulders, moderately fitted waist, and flared skirt, to permit the carrying of a revolver underneath. The flared skirt of the coat shall have a vent on each side. Coats shall have a 3/4 inch outlet of body and lining material at each side, center, and sleeve seam. When specified (see 6.1), the coats shall be furnished with two metal hooks attached thereto, one on the right and one on the left side of the coat properly placed to support the Sam Browne belt. Collar of coats shall extend to a point not less than 1/8 inch and not more than 3/8 inch below the top of the shirt collar at the center of the back. Under-collar cloth shall be all wool and the color shall be dark blue or black. The collar shall contain good quality collar canvas. Both under-collar cloth and canvas shall be securely felled. The edges of the coat front shall have a 3/8 to 5/8 inch stay tape running the length and stitched to the canvas front. The outer edge of the stay tape shall be stitched by the stitching of the front edges of the coat using stitch type 301. A contractor's label shall be stitched on all four sides to the lining, positioned on top edge approximately 1/4 inch below center of the piping of the inside right breast pocket (see 3.2.15.1). The size label (see 3.2.15.2) shall be stitched on all four sides to the center of the inside back at collar seam. The label shall be plainly visible. A content label (see 3.2.15.3) when a separate label is used, shall be stitched on all four sides to the lining, positioned on top edge approximately 1/4 inch below center of the piping of the inside left breast pocket.

3.3.2 Coat interlining (fronts). A wool-felt padding approximately 12 by 7 inches shall be stitched to the upper back edge of the chest canvas with two rows of stitching using stitch type 302. A reinforcement of black canvas shall be stitched onto the front edge of the body canvas with eight rows of stitching, using stitch type 304. This reinforcement shall be 23 (plus or minus 1/2) inches long and 7 (plus or minus 1/4) inches wide at the top and 5 (plus or minus 1/4) inches at the bottom. The chest canvas and body canvas shall be cut on the bias and sewed with three clamps; one on the shoulder, one under the arm, and one upward toward the arm. The chest canvas shall be securely stitched to the body canvas with five rows of stitching, using stitch type 304. The chest canvas shall be not less than 16 inches long at the lapel and tapering to 11 (plus or minus 1/4) inches at the armhole. The canvas fronts shall be sized in proportion to the coat sizes. The completed canvas fronts shall be cold water shrunk and hung to dry by natural process. The fronts shall then be pressed to conform to the shape of the front of the coat.

3.3.3 Pockets. Each coat shall have two inside breast pockets, one on the right side and one on the left, not less than 5-1/2 inches wide and 6 inches deep. The inside breast pockets shall be piped. Each coat shall have two outside patch pockets, one on each breast; and two pockets in the skirt of the coat, one on the right side and one on the left side. The two breast pockets shall be approximately 5-1/4 inches wide and 6 inches deep, with center pleat 1-1/2 (plus 1/8, minus 1/16) inches wide, and shall have 3-pointed pocket flaps approximately 2-3/8 inches wide from top to center point. The two skirt pockets shall be regular style (not patch) approximately 7 inches wide and 7 inches deep, and shall be provided with 3-pointed flaps approximately 2-7/8 inches wide from top to center point. The flaps of each pocket shall button with 24 line, silver or gold-color buttons, and the flaps shall be lined with the same material as used for lining the inside of the coat (see 3.2.2).

3.3.4 Shoulder straps. Shoulder straps shall be of the same material as the coat and shall be of standard size. One shall be neatly inserted in each shoulder seam, stitched down with a cross stitch, using stitch type 301, approximately 2 inches from the shoulder seam and each shall button with one 24 line silver or gold-color button located so that the edge of the button is approximately 1/2 inch from the edge of the collar. Shoulder straps shall be underlined with the same material used for lining the inside of the coats (see 3.2.2).

3.3.5 Badge plate. Unless otherwise specified (see 6.1), the badge plate shall be the same color as the coat cloth, and shall be approximately 2-1/2 inches long and 1-3/4 inches wide. Two round metal eyelets shall be placed approximately 1/2 inch from each end of the plate and an equal distance from the sides of the plate. The eyelets shall have an opening of 3/16 inch and shall measure 1-3/8 inches from each other, measuring center to center. The badge plate shall be securely stitched to the coat cloth using stitch type 301.

3.3.6 Coat buttons. The coat buttons shall consist of an ornamental shell of one piece construction with an embossed design of the regular United States Army insignia and shall be silver or gold-color as required, with a clear matte finish. The buttons shall be 36 and 24 line in diameter. The 36 line buttons shall have a regular shank and the 24 line button shall have a short shank.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.

3.3.7 Lapels. The coats shall have a notched lapel of self material approximately 8 inches long from the collar notch to the first button, and when pressed shall measure approximately 3 inches wide at the widest point.

3.3.8 Sleeves. The width and length of the sleeves shall be proportioned to the size of the individual's upper arm, and when finished, the sleeves shall extend 1/2 inch below the top joint of the thumb, and shall be fully lined with the same material as the coat lining (see 3.2.2). The bottom of the sleeves shall be turned in for a distance of approximately 1 inch and stitched with one row of silk stitching 1/8 of an inch from the edge, using stitch type 301, or may be stitched by hand. The stitching shall be stayed with stay tape (see 3.2.8). Sleeve linings shall be securely tacked with sewing thread to sleeves at seams, and hand-felled at cuffs and armholes.

3.3.9 Trousers. The trousers shall be made in accordance with the Browne method and shall be of the same cloth as that specified for the coats, with plain seams, and two 1/4 cut side pockets with an opening of not less than 7-1/2 inches and a depth of not less than 7 inches and two hip pockets 5-1/2 (plus or minus 1/4) inches long and 6 (plus or minus 1/4) inches deep. The trouser legs shall have slant bottoms so as to be 1/2 inch longer in the back than in front, with not less than a 2 inch turnunder. The trousers shall be cut sufficiently full to provide for an outlet measuring at least 2 inches at the top of the back seam at the waistband. It shall taper to at least 3/4 inch at the crotch and continue the length of each leg inseam. When finished, the trouser legs shall extend to 1-1/2 inches from the bottom of the back of the heel, or when stock size or special measurement garments are ordered, the length of trouser legs shall be as specified. The trousers shall have a waistband not less than 2-1/2 inches wide, reinforced with buckram or non-roll material faced with silesia (see 3.2.5.2) of pearl gray color. There shall be not less than four patches of non-slip rubber or synthetic rubber measuring not less than 2 inches long and 1 inch wide placed at equidistant locations around the waistband and securely sewn. The waistband shall be open-lined at the back to permit easy alteration. The legs of the trousers, with a waist size of 36 and a 32 inch inseam, shall measure 20 (plus or minus 1/2) inches at the bottom. Other sizes and lengths shall have proportionate widths at the knees and bottoms. The fly shall be provided with buttons or slide fastener, as specified (see 6.1). When buttons are used there shall be six buttons hand sewn on the fly of the trousers placed in the proper position to correspond to the buttonholes. The buttonholes shall be 5/8 inch eyelets and taper bar type worked over gimp using a handstitch or stitch type 401. When slide fasteners are used (see 3.2.16) the right and left chain of the fastener shall be attached to the right and left fly piece respectively with sewing thread by use of a good commercial stitching, and there shall be a two button closure on the waistband. A contractor's label (see 3.2.15.1) shall be stitched on all four sides to the outside (inside of trousers) and center of the right hip pocket. A size label (see 3.2.15.2) shall be stitched on all four sides to the waistband lining above the right hip pocket. The content label, when a separate label is used, shall be stitched on all four sides to the left end of the waistband (see 3.2.15.3).

3.3.9.1 Belt loops. There shall be 7 belt loops, one of which shall be placed over the top of the back seam and the others spaced equidistant to each other. Belt loops shall be made of the face material, finished 2-1/2 (plus or minus 1/8) inches long and 1 (with a plus or minus tolerance of 1/16) inch wide, folded, and both ends securely stitched in the proper position on the waistband using seam type EFH-1 and stitch 406.

3.4 Stitches, seams, and stitching. The stitch and seam types specified herein are those covered by Fed. Std. No. 751. When stitch type 401 is used, the loops, that is the underside stitch, shall be to the inside.

TABLE III. Stitches type, number of stitches, and thread size

Stitch	Number of stitches (minimum)	Thread	
		Top	Lower
301	12 per inch	40/3	40/3
304	6 per inch	50/3	50/3
406	12 per inch	60/3	60/3
Buttonholes, 401 or by hand	70 per buttonhole	000	000
Bartack	21 per tack	000	000
Buttons	15 per button	12/4	12/4

3.5 Pressing and cleaning. Coats and trousers shall be pressed smooth. The trouser legs shall be creased in the center, with the seams matching at the bottoms. All thread ends shall be trimmed. All loose threads, pin tickets, spots, and stains shall be removed.

3.6 Assembly. The uniform shall be assembled by good commercial operations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.

3.7 Workmanship. Workmanship shall be first class. There shall be no raw edges of cloth showing in any part of the finished garment. The garments shall be free from defects which affect appearance or which might impair serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Inspection lot. Unless otherwise specified in the invitation for bids, all uniforms submitted at one time shall be considered a lot for purposes of inspection and tests.

4.1.2 Sampling for inspection. A random sample of uniforms shall be taken from each lot in accordance with table IV.

TABLE IV. Sampling for inspection

Number of uniforms in lot	Number of uniforms in inspection sample	Acceptance number (defective)	Rejection number (defective)
300 and under	35	3	4
301 to 500	50	4	5
501 to 800	75	6	7
801 to 1300	110	8	9
1301 to 3200	150	11	12
3201 to 8000	225	17	18
8001 to 22000	300	20	21

4.1.3 Sampling for test. When inspection is made by the Government at the factory, samples of any materials, components, etc., entering into the manufacture of the uniforms covered herein, shall be selected by the Government inspector in accordance with table V and tested to determine their conformance with the requirements of this specification. When inspection is not made at the factory by the Government and when specified in the Invitation for Bids, the manufacturer shall submit sample units of product of the size (dimension) specified in table VI. The number of units of product (sample size) submitted shall be as specified in column 2, table V.

TABLE V. Sampling for tests

Number of uniforms in lot	Number of uniforms in test sample	Acceptance number (defective)	Rejection number (defective)
192 and under	2	0	1
193 to 360	3	0	1
361 to 960	4	0	1
961 and over	5	0	1

4.2 Inspection. Each of the samples selected in accordance with table IV shall be visually and dimensionally inspected to determine their compliance with the requirements of this specification. Samples shall be inspected for color, dimension, button type, slide fasteners, construction, insignia, stitches, seams and stitching, labeling, assembling, pressing and cleaning, and workmanship. The number of defectives acceptable shall be as specified in table IV.

4.3 Tests. Each of the components selected for test in accordance with table V or 4.1.3 shall be tested for the properties specified in table VI. The number of defectives acceptable shall be as specified in table V. The methods of testing specified in Fed. Std. No. 191, wherever applicable, and as listed in table VII shall be followed. The physical values specified in section 3 apply to the average of the determinations made on a unit of product for test purposes as specified in the applicable test methods.

4.4 Compliance criteria.

4.4.1 Inspection. Any uniform in the sample for inspection failing to conform to the requirements for which the inspection was made shall be considered defective. If the number of defective uniforms in the sample exceeds the acceptance number for that sample the entire lot from which the sample was taken shall be considered to have failed to meet the requirements of this specification.

4.4.2 Tests. Any uniform in the sample for tests failing to conform to the requirements for which tests were made shall be considered defective. If the number of defective uniforms in the sample exceeds the acceptance number for that sample, the entire lot from which the sample was taken shall be considered to have failed to meet the requirements of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.

TABLE VI. Testing of components

	Weave	Weight per square yard	Yarns per inch	Yarn ply	Tensile strength	Colorfastness to light	Colorfastness to crocking	Colorfastness to dry cleaning	Colorfastness to wet dry cleaning	Colorfastness to perspiration	Shrinkage in dry cleaning	Shrinkage in sponging	Shrinkage, relaxation	Identification of rayon	Identification of wool	Identification of acetate	Identification of cotton	Identification of horsehair	Wool grade	Yards per pound	Tests specified in V-T-276	V-T-301	DDD-T-86	V-B-871	DDD-L-20	V-P-106	Thickness	Size of unit of product
Fabrics:																											
Serge	X	X	X	X	X	X	X	X	X	X	X	X	X		X												2-1/2 yds.
Lining	X	X	X		X									X		X	X										1 yd.
Canvas (chest)	X	X	X	X	X			X	X		X	X					X										1/2 yd.
Canvas (body)	X	X	X	X	X			X	X		X	X					X										1/2 yd.
Canvas (reinforcing)	X	X	X	X	X			X	X	X	X	X					X										1/4 yd.
Wigman cloth	X	X	X		X			X	X		X	X					X										1/4 yd.
Drill (pockets)	X	X	X		X						X	X					X										1/2 yd.
Silesia (pockets)	X	X	X		X						X	X					X										1/2 yd.
Gimp																			X								240 yds.
Felt:																											
Chest		X													X												6 in. sq.
Badge plate		X													X												6 in. sq.
Chevron stripes															X												6 in. sq.
Shoulder padding																	X								X		5 in. sq.
Hanger loops	X				X												X										5 yds.
Insignia														X													1 yd.
Thread:																											
Cotton						X		X	X	X										X							720 yds.
Silk and rayon																					X						720 yds.
Labels																						X					15 ea. type
Stay tape											X	X											X				6 yds.
Buttons, trouser																								X			40
Fasteners, slide																										X	5

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.

TABLE VII. Test methods

Test	Requirement Reference	Method
Standard conditions	(see footnote as indicated)	Section 4/
Weave	3	Visual
Weight per square yard	4	5041
Yarns per inch	5	5050
Ply	6	Visual
Breaking strength	7	5100
Colorfastness:		
Light	8	5660
Crocking	9	5651
Dry cleaning	10	5620
Perspiration	11	5680
Shrinkage in dry cleaning	12	5580
Shrinkage in sponging	12	5590
Shrinkage, relaxation; wool cloth	13	5558
Identification of rayon	14	1500
Identification of acetate	15	1510
Identification of wool	16	1100
Identification of cotton	17	1200
Identification of fibers in Textiles 2/	18	D276-49
Colorfastness to wet dry cleaning	19	5622
Yards per pound	20	4010
Breaking strength, yarn	21	4100

1/ Fed. Std. No. 191.
2/ American Society for Testing Materials Standard.
3/ Paragraph 3.2.1, 3.2.2, 3.2.3.1, 3.2.3.2, 3.2.3.3, 3.2.4, 3.2.5.1, 3.2.5.2, and 3.2.14.
4/ Paragraphs 3.2.1, 3.2.2, 3.2.3.1, 3.2.3.2, 3.2.3.3, 3.2.4, 3.2.5.1, 3.2.5.2, 3.2.3.4, and 3.2.6.
5/ Paragraphs 3.2.1, 3.2.2, 3.2.3.2, 3.2.3.1, 3.2.3.3, and 3.2.4.
6/ Paragraphs 3.2.1, 3.2.3.2, and 3.2.3.1.
7/ Paragraphs 3.2.1, 3.2.2, 3.2.5.1, 3.2.5.2, and 3.2.14.
8/ Paragraphs 3.2.1.2, and 3.2.9.1.
9/ Paragraph 3.2.1.2.
10/ Paragraphs 3.2.1.2, 3.2.2, 3.2.3.3, 3.2.4, and 3.2.9.1.
11/ Paragraphs 3.2.1.2, 3.2.2, 3.2.3.3, and 3.2.9.1.
12/ Paragraphs 3.2.1.3, 3.2.2, 3.2.3.1, and 3.2.3.2.
13/ Paragraph 3.2.1.3.
14/ Paragraph 3.2.2.
15/ Paragraph 3.2.2.
16/ Paragraphs 3.2.1, 3.2.3.4, 2.3.6, and 3.2.12.
17/ Paragraphs 3.2.3.1, 3.2.3.2, 3.2.3.3, 3.2.4,.3.2.5.1, 3.2.5.2, 3.2.13, 3.2.14, 3.2.3.5 and 3.2.5.2
18/ Paragraphs 3.2.3.2, and 3.2.3.1.
19/ Paragraphs 3.2.1.2, 3.2.2, 3.2.3.3, 3.2.4, and 3.2.9.1.
20/ Paragraph 3.2.13.
21/ Paragraph 3.2.13.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.1).

5.1.1 Level A and B. The coat shall be folded as follows: Spread coat out flat with the outside up. Bring both ends of shoulders and sleeves together to meet at center back of jacket. Fold fronts over to meet at center back of jacket. Fold coat in half along the length, then fold in half across the length. The folded coat should measure approximately 15 inches by 11 inches. The trousers shall be folded as follows: Fold trousers in half along the length with the fly inside the fold. Fold trousers again in quarters across the length. Place folded trousers inside the last fold of the jacket. Each folded uniform shall be completely wrapped in a good grade of tissue paper and then packaged in a 200 pound

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.

test, RSC style box conforming to PPP-B-636, class domestic. The approximate outside dimensions shall be 15-3/8 inches in length, 11-5/8 inches in width, and 3-3/8 inches in depth. One ounce of flaked naphthalene conforming to R-N-91, or its equivalent, shall be evenly distributed throughout the box, and the container completely sealed along the length with a 2 inch gummed-paper tape.

5.1.2 Level C. The uniform shall be packaged in accordance with the manufacturer's commercial practice.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.1).

5.2.1 Level A. Four uniforms of one class, packaged as specified in 5.1, shall be packed two tiers of two boxes each, flat in each shipping container, with the length of the boxes parallel to the end panels of the shipping container. The shipping container shall conform to the requirements of PPP-B-636, class weather resistant. The box shall be waterproof sealed with tape. Closure and strapping shall be in accordance with the appendix to the box specification.

5.2.2 Level B. Four uniforms shall be packed as specified in 5.2.1, except that the shipping container shall be class domestic. Closure and strapping shall be in accordance with the appendix to the box specification.

5.2.3 Level C. The uniforms shall be packed to insure carrier acceptance and safe delivery at destination at lowest rates, in containers complying with the Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.3 Marking. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123 or MIL-STD-129, as applicable.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

a. Title, number, and date of this specification.
b. Size and color (1.2, 3.2.1.1, 6.2).
c. Color of uniform buttons (3.3.6).
d. Piping (3.2.8).
e. Insignia (3.2.11).
f. Stitching of chevrons (3.2.12).
g. Whether a vent and metal hooks are required (3.3.1).
h. Option in badge plate construction (3.3.5).
i. Whether buttons or slide fasteners are required (3.3.9).
j. Inspection lot (4.2.2).
k. Whether samples of components are required (4.1.3).
l. When samples of component parts are not to be submitted (6.4).
m. Service stripes, insignia, chevrons (6.5).
n. Level of packaging and packing (5.1 and 5.2).

6.2 The invitation for bids shall either state the location and date the individual measurements shall be taken, or if the agency concerned will furnish the stock sizes or measurement charts when ordering from the resulting contract.

6.3 Standard sample. For access to a standard sample of the uniform, address the procuring office issuing the invitation for bids.

6.4 Unless otherwise specified, each bidder shall submit with his bid a sample (see Table VI) of the materials he proposes to use in constructing the uniforms.

6.5 Particulars regarding service stripes, insignia, and chevrons will be furnished when measurements are taken, or when ordering from the resulting contract.

6.6 The Department of Defense does not have a review interest in this specification

Preparing activity:

GSA-FSS

Orders for this publication are to be placed with [illegible] nistration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.