RR-K-195J
January 29, 1986
SUPERSEDING
RR-K-195H
February 23, 1978

FEDERAL SPECIFICATION

KETTLE, STEAM-JACKETED, (STAINLESS STEEL, STEAM HEATED)

This specification is approved by the Assistant Administrator, Office of the Federal Supply and Services, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers stainless steel, steam-jacketed kettles heated by an external supply of steam.

1.2 Classification. Steam-jacketed kettles shall be of the following types, styles, capacities, and classes, as specified (see 6.2):

1.2.1 Types and styles.

Type I - Deep, 2/3 jacketed.

Style 1	-	Leg mounted, stationary.
Capacities	-	10, 20, 30, 40. 60, 80, and 100 gallons
Style 2	-	Wall mounted, stationary.
Capacities	-	10, 20, 30, 40, 60, 80, and 100 gallons
Style 3	-	Pedestal mounted, stationary.
Capacities	-	10, 20, 30, 40, 60, 80, and 100 gallons
Style 4	-	Pedestal mounted, tilting.
Capacities	-	10, 20, 30, 40, 60, and 80 gallons
Style 5	-	Table mounted, tilting.
Capacities	-	2-1/2, 5, and two-5 gallon, 7-1/2, and 10 gallons
Style 8	-	Wall mounted, tilting.
Capacities	-	10, 20, 30, 40, 60, and 80 gallons
Style 9	-	Leg mounted, tilting.
Capacities	-	10, 20, 30, 40, 60, 80, and 100 gallons

AMSC N/A FSC 7310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:09Z
Check the source to verify that this is the currentversion before use.

Type II - Shallow, fully jacketed.

Style 1	-	Leg mounted, stationary.
Capacities	-	20, 25, 40, 60, and 80 gallons
Style 2	-	Pedestal mounted, stationary.
Capacities	-	20, 25, 40, 60, and 80 gallons
Style 3	-	Wall mounted, tilting.
Capacities	-	20, 25, 40, and 60 gallons
Style 4	-	Wall mounted, stationary.
Capacities	-	20, 25, 40, and 60 gallons

Class A - Insulated (not applicable to type I, style 5).
Class B - Noninsulated.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

QQ-B-654	-	Brazing Alloys, Silver
RR-T-25	-	Table, Steam-Jacketed Kettle
PPP-B-566	-	Boxes, Folding, Paperboard
PPP-B-601	-	Boxes, Wood, Cleated-Plywood
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-B-665	-	Boxes, Paperboard, Metal Edged and Components
PPP-B-676	-	Boxes, Setup
PPP-B-1055	-	Barrier Material, Waterproofed, Flexible
PPP-F-320	-	Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes
PPP-P-291	-	Paperboard, Wrapping and Cushioning

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Commercial Item Descriptions as outlined under General Information in the Index of Federal Specifications, Standards and Commercial Item Descriptions. The Index, which includes cumulative bimonthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.)

(Single copies of this specification and other Federal specifications and commercial item descriptions required by activities outside the Federal Government for bidding purposes are available without charge from General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:09Z
Check the source to verify that this is the currentersion before use.

(Federal Government activities may obtain copies of Federal standardization documents and the Index of Federal Specifications, Standards and Commercial Item Descriptions from established distribution points in their agencies.)

Military Specifications:

MIL-C-11133	-	Crate, Wood, Open, Wirebound
MIL-B-26195	-	Boxes, Wood-Cleated, Skidded, Load-Bearing Base
MIL-C-52950	-	Crates, Wood, Open and Covered

Military Standards:

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Government publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Sanitation Foundation (NSF)

Standard No. 4 - Commercial Cooking and Hot Food Storage Equipment

Food Service Equipment (Annual Listing)

(Application for copies should be addressed to the National Sanitation Foundation, 3475 Plymouth Road, P.O. Box 1468, Ann Arbor, MI 48106.)

American Society for Testing and Materials (ASTM)

A 167	-	Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet and Strip
A 240	-	Heat-Resisting Chromium and Chromium-Nickel Stainless Steel Plate, Sheet and Strip for Pressure Vessels
D 3951	-	Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

The American Society of Mechanical Engineers (ASME)

Section VIII, Div. 1, Pressure Vessel

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:09Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Codes and standards. The Kettles shall conform to the applicable requirements of ASME Section VIII, Division 1, Pressure Vessels, and NSF Standard No. 4. Satisfactory evidence that these requirements have been met shall be submitted to the contracting officer or his authorized representative prior to the start of production (see 4.3).

3.2 Materials and components. Materials and components shall be as specified herein. Materials not definitely specified shall be of the quality normally used by the manufacturer provided the completed item complies with all the provisions of this specification (see 6.3).

3.2.1 Stainless steel. Stainless steel shall conform to types 302, 304, 304L of ASTM A 167, or ASTM A 240 as applicable.

3.2.2 Insulation. Insulation shall be fibrous glass felt, nominal density 3 pounds per cubic foot.

3.2.3 Pipe, brass. Pipe for water connections shall be seamless brass, standard weight, Iron Pipe Size (IPS) with National Pipe Taper (NPT) threaded ends.

3.2.4 Fittings, bronze. Pipe fittings used with brass pipe shall be bronze rated at 120 pounds.

3.2.5 Valves. Globe valves and gate valves shall be designed for use with saturated steam and the valve bodies shall have threaded ends. The globe valves shall have a slip-on type disc holder with a replaceable composition disc suitable for hot or cold water service or for use with any working pressure up to 125 psig. The steam working pressure shall be cast on the side of the valve.

3.2.6 Check valve. The check valve shall be a horizontal swing-type with ground metal to metal seating, for steam pressure up to 125 psig.

3.3 Design. Kettles shall be of the type, style, class, and capacity indicated in 1.2. The kettles shall consist primarily of an inner hemispherical or sloping bottom shaped body with a steam jacket on the outside. The kettle shall be designed in accordance with Section VIII. Div. 1, of the ASME Code for a maximum allowable working pressure of 35 psig, except that for kettles intended for shipboard use (see 6.2), the maximum allowable working pressure

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

shall be 55 psig. The kettle body, cover, base, legs (and brackets if applicable) shall be fabricated from stainless steel. The outer wall and bottom of the steam jacket shall be stainless steel.

3.4 Construction. The steam jacketed kettles shall be constructed as specified herein and shall be in conformance to the dimensions specified in tables I and II. Material thickness specified are not intended to preclude heavier gauge materials. Stainless steel plate, sheet, and strip used in the construction of the kettles shall be as specified in 3.2.1 except that the stainless steel parts fabricated by welding shall be type 304 or type 304L only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions, type I

Measurement	Table mounting, tilting										
	2-1/2 Gallons	5 Gallons	7-1/2 Gallons	10 Gallons	10 Gallons	20 Gallons	30 Gallons	40 Gallons	60 Gallons	80 Gallons	100 Gallons
	inches										
Height to rim of kettle top 2/	14-3/4-19-1/4	15-1/4-20-1/2	15-3/4-21-3/4	22-1/2-24	30-39	32-40	34-42	36-43	39-46	44-48	43-51
Size of steam outlet (IPS)	3/8 or 1/2	3/8 or 1/2	3/8 or 1/2	3/8 or 1/2	1/2	1/2	1/2	1/2	1/2	1/2 or 3/4	1/2 or 3/4
Size of steam inlet (IPS)	3/8 or 1/2	3/8 or 1/2	3/8 or 1/2	3/8 or 1/2	1/2 or 3/4	1/2 or 3/4	1/2 or 3/4	3/4	3/4	3/4 or 1	3/4 or 1
Clearance of draw-off outlet above floor (minimum) (floor models only)	N/A	N/A	N/A	N/A	11-1/4 or 12	11-1/4 or 12	11-1/4 or 12	11-1/4 or 12	11-1/4or 12	11-1/4 or 12	11-1/4 or 12
Spout clearance 1/ (style 5)	3-3/8-8-5/8	4-1/2-8-1/2	4-1/4-7-7/8	4-6	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Nominal metal thickness of insulation casing (class A)	0.0625	0.0625	0.0625	0.0625	0.0625	0.0625	0.0625	0.0781	0.0781	0.0781	0.0781

1/ Spout clearance is defined as the distance from the bottom of the legs to the spout lip when kettle is tilted 90 degrees from upright position.

2/ Heights shown are recommended installation heights for kettles.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T12:09Z
Check the source to verify that this is the current version before use.

TABLE II. Dimensions, type II

Measurement	20 Gallons	25 Gallons	40 Gallons	60 Gallons	80 Gallons
	inches				
Height to rim of kettle top 1-/	31-37	31-37	35-38	36-41	36-43
Size of steam inlet (IPS)	1/2 or 3/4	3/4 or 1	3/4 or 1	1	1
Size of steam outlet (IPS)	1/2	1/2 or 3/4	1/2 or 3/4	3/4	3/4
Clearance of drawoff outlet above floor (minimum) (floor models only)	12	12	12	12	12

1/ Heights shown are recommended installation heights for Kettles.

3.4.1 Kettle body and steam jacket. The kettle body shall be cylindrical with a hemispherical or sloping bottom and shall be fabricated from type 302 or 304 stainless steel specified in 3.2.1. The kettle body shall be seamless drawn from one piece of material or die formed and welded in sections. The top edge shall be formed in a 1/2 inch minimum, half round, open radius, or a fully closed and welded bead or a double sealed welding hem. The top of the kettle body shall fit the flange on the cover. The bottom of the kettle body shall be provided with an opening to the drawoff tube and shall be located to allow complete drainage. The outer wall and bottom of the steam jacket shall be fabricated of stainless steel specified in 3.2.1. The steam jacket shall be formed of one piece or welded in segments, and the top shall be welded to the body. The drawoff tube shall pass through the steam jacket and shall be welded thereto to form a leakproof joint.

3.4.2 Insulation. Class A kettles shall be insulated with the material specified in 3.2.2. The insulation shall be minimum 1 inch thick and shall cover the kettle body and steam jacket on the outside. Insulation shall be contained in a stainless steel outer casing. The casing shall be flared at the top to meet the kettle body and be continuously fillet welded or bolted thereto.

3.4.3 Cover. A cover shall be provided with all nontilting kettles. When specified (see 6.2), tilting kettles shall be provided with covers. Covers shall be formed from type 302 or 304 stainless steel specified in 3.3.1 and

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

shall be a minimum of 0.050 inches in thickness. The covers shall be of a one or two piece construction, as applicable and shall fit the radius at the top edge of the kettle body.

3.4.3.1 One-piece cover. Covers for tilting kettles shall be one-piece lift-off type. Nontilting kettles shall be provided with a one-piece hinged cover. The hinges shall be the offset type located at the back or side of the kettle. The cover shall be flanged to prevent distortion or permanent set as a result of normal use. The cover shall be dished for rigidity and hinged for ease of raising to the open position. The hinged construction shall be such that it will hold the cover in the raised position. When specified (see 6.2), one-piece covers on 60, 80, and 100 gallon kettles shall be provided with one or more stainless steel actuators with fully enclosed counter-balancing springs. Spring tension shall be adjustable and the cover shall be removable from the mechanism for cleaning.

3.4.3.2 Two-piece cover. When specified (see 6.2), nontilting kettles of 60, 80, and 100 gallon capacities shall be provided with a two-piece cover. The cover shall be provided with two offset hinges at the back of the kettle and two hinges located beyond the centerline of the kettle. The cover shall be flanged to prevent distortion or permanent set and may have a gutter approximately 1-3/8 inches in from the outer edge. Each section of the cover shall open 110 degrees from the closed position and shall rest in this position on stops provided on the back of the center hinges. The back section of the cover shall also be movable for cleaning, and shall be capable of turning up and back on the offset hinges. A sanitary shield shall be located on the rear of the front section and the front edge of the back section shall be flanged up to prevent dirt and foreign matter from entering the kettle through the hinged joints.

3.4.4 Handle. Each cover shall be provided with a stainless steel handle designed to minimize the possibility of the operator burning his hand. A plastic knob may be provided on the handle. The handle shall be secured to the cover with a continuous fillet weld only. For shipboard use the handle shall have a 1/4 inch diameter hole for attachment of a lifting rope.

3.4.5 Drawoff assembly. Unless otherwise specified herein, nontilting kettles shall be provided with a tangent drawoff assembly, consisting of a tube and sanitary-type valve located at the bottom of the kettle body. Tilting kettles shall not be provided with a drawoff assembly.

3.4.5.1 Outlet strainer and strainer hook. The drawoff outlet shall be provided with an outlet strainer and strainer hook. The strainer and strainer hook shall be fabricated of stainless steel. The strainer shall be perforated with 1/4 inch holes located on maximum 9/16 inch centers. The strainer shall be welded to a stay which shall extend downward and fit snugly into the drawoff. A stainless steel ring or open loop shall be welded to the top side of the strainer to be used as a catch for the strainer hook. The strainer hook shall be made from 3/16 inch diameter stainless steel rod, 6 inches longer than the overall depth of the kettle, and shall be provided with a loop or tee handle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

3.4.5.2 Tube and valve for drawoff assembly. The tube and valve size and drawoff capacity for the drawoff assembly shall be as specified in table II. When specified (see 6.2), the drawoff tube shall have a 3 inch outside diameter and the valve shall have a nominal 3 inches in diameter for the nontilting 20 gallons and greater capacity kettles. Drawoff assemblies shall be located tangent, with the lowest point inside the body.

TABLE III. Drawoff, assembly

Drawoff, tube and valve diameters (inches)	Capacity (gallons)
1-1/2	10
1-1/2	20
1-1/2	30
2	40
3	60
3	80

3.4.5.2.1 Tube. The drawoff tube shall be formed of one piece of seamless stainless steel tube and shall be welded to the bottom of the body and to the steam jacket where the tube pierces it. The tube shall maintain the same section throughout its length and shall be flush with the round opening in the drawoff valve.

3.4.5.2.2 Valve. The drawoff valve shall be a sanitary, angle, compression disc type fabricated of type 304 stainless steel. The valve shall be soldered to the drawoff tube by means of a retessed sanitary joint or may be bolted to a face plate. The solder shall conform to QQ-B-654. The stem for the 2 and 1-1/2 inch valve shall be provided with a fiber-impregnated plastic handle not less than 2-1/8 inches in diameter or a bar type handle not less than 5-inches in length. The 3 inch valve shall have a wheel type metal handle with a diameter of not less than 5-inches or a bar type handle of not less than 6 inches in length. The valve shall be designed so that it can be disassembled for cleaning without the use of tools. "V" or modified "V" threads shall not be used in the valve.

3.4.6 Safety valve. Kettles shall be provided with a chromium plated brass safety valve. The valve shall be set at the factory in accordance with the Section VIII, Div. 1, Pressure Vessel for the maximum operating pressure specified herein. The safety valve shall be provided with a minimum 18 inch long brass pull chain with a finger pull ring attached or an operating lever that essentially serves the same purpose. The valve shall be provided with a reversible lifting lever and shall be capable of being rotated 350 degrees without disturbing the valve setting. The safety valve shall meet ASME requirements and shall be suitable for saturated steam. The safety valve for tilting kettles shall be located on the inlet side of the kettle between the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

gear housing and the steam line or be attached to the kettle body. The safety valve for nontilting kettles shall be secured to the kettle by means of a stainless steel boss, fillet welded to the steam jacket, and be complete with or without a street elbow and a 4 inch blow down tube. The 4 inch blow down tube shall divert any steam discharge in a downward direction.

3.4.7 Steam inlet and outlet. The steam inlet and outlet shall be of the size specified in table I. The connections, except for tilting kettles, shall be made through type 304 stainless steel bosses, fillet welded to the jacket. Class A kettles shall be provided with a pipe nipple of sufficient length to extend through the insulated casing.

3.4.7.1 Tilting kettles. The steam inlet and outlet shall be through the trunnions. Trunnions shall be hollow and shall be arranged to allow tilting of the kettle without decreasing the steam supply pressure or causing leakage Tube and fittings when used for inlet and outlet connections shall be type 302 or 304 stainless steel.

3.4.8 Kettle mountings.

3.4.8.1 Leg mounted. Leg mounted kettles shall be provided with stainless steel tubular legs conforming to the sizes. Unless otherwise specified (see 6.2), kettles shall be without leg bracing. Kettles shall have three legs except the 100 gallon size which shall have four legs. The bottom of each leg shall be connected to a stainless steel floor flange having not less than three equally spaced holes to receive hold-down bolts.

3.4.8.1.1 Kettles without bracing. Legs shall be a minimum of 1-1/4 inch IPS for kettle sizes 10 thru 100 gallons. Legs shall be welded to the outside kettle bottom or have sockets to receive the legs. Sockets shall be threaded on the inside to receive the legs. Each leg shall have the top end threaded for a minimum distance of 1-3/4 inches with IPS straight threads and shall be provided with a locknut. Floor flanges shall be welded to the legs.

3.4.8.1.2 Kettles with bracing. Legs shall be as specified in 3.4.8.1.1 or shall be minimum 1-1/2 inch diameter tube with a 0.0625 inch wall thickness for kettles of 10 through 40 gallons capacity and minimum 2 inch diameter with a 0.0625 inch wall thickness for kettles of 60, 80, and 100 gallons capacity. When bracing is provided, legs shall be welded to the sockets and to the bracing. The bottom of each leg shall be fitted with an adjustable foot terminating in a welded floor flange.

3.4.8.2 Wall mounted. Wall mounted kettles shall be furnished with a wall-bracket or in-wall carrier support in accordance with the manufacturer's standard practice unless either a wall-bracket or in-wall carrier is definitely specified (see 6.2). Wall-brackets and in-wall carrier supports shall be capable of supporting the weight of the kettle plus a load of 2-1/2 times the capacity weight of water it is intended to hold, without deformation when tested as specified in 4.4.1.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:09Z
Check the source to verify that this is the currentversion before use.

3.4.8.2.1 Wall-brackets. The brackets shall be an open bracket of stainless steel plate or sheet or a stainless steel enclosed sheet steel bracket, or a stainless steel tubular bracket, as specified (see 6.2). The enclosed style shall consist of a structural steel supporting frame fully enclosed by a stainless steel outer covering. The frame shall have provisions for securing necessary valves, fittings, and piping. The front or top of the housing shall be provided with close-fitting openings for steam control valves, tilting handwheels, and other necessary controls. A removable access panel shall be provided for servicing enclosed components. The bracket shall have provisions for securing the kettle to the wall by bolting or welding. Brackets for stationary kettles shall be welded to the kettle body or insulation jacket. Brackets for tilting kettles shall be joined to the kettle at the trunnions. Each bracket designed for wall mounting by welding shall be provided with not less than one erection hole for holding the kettle in place while welding the bracket to the wall or bulkhead. Each bracket designed for wall mounting by bolting shall be provided with at least three bolt holes.

3.4.8.2.2 In-wall carrier. The in-wall carrier support shall consist of two horizontal in-floor supports and two vertical in-wall supports welded together. The carrier shall be designed to support the fully loaded kettle and to stand any additional loading imposed when the contents of the kettle are in motion due to stirring, agitation, or pouring, as applicable. The floor and in-wall supports shall be fabricated of minimum 5 by 1-7/8 by 3/8 inch carbon steel channels. The horizontal channels shall not be less than 24 inches long and the vertical channels shall be of a length suitable for attaining a drawoff or spout clearance of 12 inches minimum, from the floor when the kettle is mounted thereon. The vertical channels shall be connected by welded steel braces at the top and bottom. The vertical channels shall be provided with bolts or studs located and sized to receive the wall bracket specified in 3.4.8.2.1. All hardware necessary for wall mounting shall be provided with the supports.

3.4.8.3 Pedestal mounted (stationary). Stationary pedestal mounted kettles shall be provided with a pedestal base in accordance with the manufacturer's standard design. The pedestal shall be fabricated of 0.050 inch thick stainless steel and shall be welded to the steam jacket. The base shall be provided with not less than four equally spaced holes to receive hold-down bolts.

3.4.8.4 Pedestal mounted (tilting). Tilting pedestal mounted kettles shall be provided with a pedestal base and trunnions for tilting. The pedestal shall be fabricated of 0.0625 inch thick stainless steel. Trunnions shall be provided at 90 degrees from the center of the pouring lip and fastened to the kettle body. The trunnion support to the right, when facing the pouring lip of the kettle, shall include a housing in which the tilting gear and worm assembly are mounted. The base shall be provided with not less than four equally spaced holes to receive hold-down bolts.

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T12:09Z
Check the source to verify that this is the currentversion before use.

3.4.8.4.1 Tilting mechanism. The tilting mechanism shall provide a smooth quick-acting, self-locking, tilting operation of at least 90 degrees from the normal operating position and shall hold the kettle at any position within the 90 degrees. Tilting shall be controlled by an inclosed gear and worm assembly operated by a handwheel or crank. The housing for the enclosed gear and worm assembly shall be stainless steel. The gear assembly shall be provided with antifriction bearings or bronze bushings, and when required, oil seals shall be provided. An oil filler plug or lubrication fitting shall be provided in the housing. The handwheel or crank shall be chromium plate aluminum, chromium-plated steel, or chromium plate cast iron. A chromium-plated pivoting handle shall be provided on the rim of the handwheel for easy operation. The handwheel shaft shall be stainless steel.

3.4.8.5 Table mounted (tilting). Tilting, table mounted kettles shall be provided with two vertical supports and provisions for securing the kettle to a table top (see 6.1). The kettles shall be provided with trunnions which will allow at least 90 degrees of tilt from the normal position. Tilting shall be by means of a handle attached to the side of the kettle body. The handle shall have a knob or protective device to prevent the operator from being burned. Height from bottom of vertical supports to spout when the kettle is in tilted position shall conform to requirements of table I. When specified (see 6.2), the style and size of steam-jacketed tables shall be provided in accordance with RR-T-25.

3.4.9 Basket inserts. Each table mounted kettle shall be provided with a stainless steel wire basket or stainless steel perforated basket with 3/8 inch diameter holes sized for insertion into the kettle. Openings between the wires shall be not greater than 3/8 inch to retain smaller vegetable such as cut-up beans and carrots. When specified (see 6.2), a three basket stainless steel insert with three nylon mesh bags shaped to the contour of the baskets shall be provided with the type I, 40, 60, and 80 gallon kettles.

3.4.10 Water supply connection. Unless otherwise specified (see 6.2 and 3.4.11), a swing spout water supply connection shall be provided. The spout shall be a combination swing spout and faucet or a swing spout with a nominal 3/4 inch IPS globe valve inserted directly below the mounting bracket. The swing spout supplied with tilting kettles shall be mounted on a stainless steel bracket that is independent of the kettle body. The swing spout shall be chromium-plated brass or stainless steel. The swing spout assembly for nontilting kettles shall be mounted on a 0.0625 inch thick stainless steel bracket which shall be attached to the kettle. The bracket shall be positioned on the right side of the kettle when facing the kettle drawoff. The bracket and swing spout shall be positioned so that the outlet end of the spout has a 1-1/2 inch minimum clearance above the top rim of the kettle.

3.4.11 Water metering device. When specified (see 6.2), electric or mechanical water metering devices in the quantity required, shall be furnished. Each device shall be designed to serve not more than two kettles. All operating components of the meter shall be enclosed in a splash-proof stainless case. The

Source: https://assist.dla.mil -- Downloaded: 20261O-26T12:09Z
Check the source to verify that this is the currentversion before use.

case shall have provisions so that the unit may be attached to either a stand, a wall bracket, or a kettle bracket as specified (see 6.2). The devices shall be equipped with a chromium-plated brass swing spout and water inlet connection. An electrical outlet, actuating switch, and fuse connection with plastic cover shall be provided. The dial shall be marked in 1 or 2 gallon increments up to at least 60 gallons and shall have a manually operated dial setting knob. The device shall automatically shut off when the selected dial amount has been dispensed (see 4.4.2). The metering head shall allow dispensing at the rate of 2 gallons per minute to at least 20 gallons per minute with a plus or minus 2 percent accuracy. When connected to an incoming water pressure of 40 pounds per square inch the meter shall dispense not less than 12 gallons per minute (see 4.4.2). Unless otherwise specified (see 6.2), the electric water metering device shall be suitable for operation on a nominal 120 volt, single phase, 60 hertz, system.

3.4.12 Steam line valves and fittings. Unless otherwise specified (see 6.2), the following valves and fittings shall be provided with each kettle: Globe-type inlet valve; gate-type stop valve and automatic steam trap; discharge check valve; discharge strainer; safety valve; and the necessary fittings to connect these components. The components may be provided separately or may be factory installed. Globe and gate valves shall be as specified in 3.2.5. Tilting kettles shall be provided with a Y-strainer in the steam supply line.

3.4.12.1 Discharge strainer. The discharge strainer shall be basket or "Y" type, rated at 125 pounds and shall be the same size as the pipe lines in which they are installed. The strainer body shall be constructed of gray cast iron, with the bottoms drilled and plugged. The body shall have an arrow clearly cast on the side to indicate the direction of flow. Each strainer shall be equipped with a removable cover and sediment basket. The basket shall be fabricated from brass screen wire or sheet brass having a thickness of 0.0253 inch, perforated to provide a net free area through the basket of at least four times that of the entering pipe. The flow shall be into the basket, and out through the perforations.

3.4.13 Welding. Welding of stainless steel shall be made with welding rod having a chemical composition compatible with that of the welded material (see 3.4).

3.4.14 Measuring stick. Unless otherwise specified (see 6.2), a graduated stainless steel measuring stick not less than 1 inch wide shall be furnished with all kettles except type I, style 5. The stick shall be shaped to the contour of the kettle and shall fit over the rim. The stick shall be graduate in 1 gallon intervals for 10, 20, and 25 gallon kettles; graduated in 2 gallon intervals for 30, 40, and 60 gallon kettles; and graduated in 5 gallon intervals for kettles over 60 gallon capacity. Every fifth graduation shall be marked numerically.

3.5 Maintenance access. Provisions shall be made to allow access to inspect, service, replace, and adjust any component of the kettles. Adjustment, repair or replacement of any component shall not require disassembly or removal of other components.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

3.6 Marking for identification.

3.6.1 Civil agency. Unless otherwise specified (see 6.2) marking shall be in accordance with the manufacturer's standard commercial practice.

3.6.2 Data-name plates. The kettles shall be furnished with a data name plate in accordance with the applicable requirements of MIL-STD-130 except the requirements for; (a) Methods of applying, (b) Identification tags, (c) Information not required and (d) Optional marking information shall not apply. The data plates shall be made of minimum 20 gauge corrosion-resisting metal and attached to the kettle by rivets, screws or welding in such a manner as to meet the applicable National Sanitation Foundation sanitary requirements for this equipment. The plate shall contain the following information which shall be stamped, engraved or applied by photosensitive means:

National Stock Number
Procurement Instrument Identification Number
Specification Data
Manufacturer's Name, Address and Telephone Number
Supplier's Name, Address and Telephone Number (List only if different from Manufacturer)
Manufacturer's Model Number
Government Approved Manual Number (See 6.2)

Each plate shall be placed so that it is readily visible to the operator during normal operating use and so as to not adversely affect the life and utility of the item.

3.6.2.1 Instruction plate for Military use. Each kettle intended for Military use, except type I, style 5 shall have a user's instruction plate permanently attached to the front of the kettle. When type I, style 5 kettles are procured, an instruction plate for attachment to the table shall be furnished with each kettle. The instruction plates shall be fabricated of 0.025 inch corrosion-resistant metal. The plate shall contain the following information etched, embossed, or die stamped thereon in legible characters, except that on kettles for shipboard use (see 6.2) the maximum allowable working pressure shall be 55 psig and instruction 1 shall be 55 psig in lieu of 35 psig shown. The words "STEAM-JACKETED KETTLE" shall be not less than 3/16 inch high and the words "USER'S INSTRUCTIONS", shall be not leas than 1/8 inch high. All other characters shall be not less than 3/32 inch high.

STEAM-JACKETED KETTLE

USER'S INSTRUCTIONS

1. Caution - Steam supply should not exceed 35 psig.
2. Do not tamper with or obstruct the safety valve.
3. Do not clean with abrasive materials.
4. Wash kettle before and after each use with hot soapy water and rinse thoroughly with clean hot water.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:09Z
Check the source to verify that this is the current version before use.

5. Leave cover and drain open when not in use.
6. Do not turn on steam unless water or food is in kettle.
7. Do not put water in hot dry kettle.
8. When heating a cold kettle, turn the steam on gradually, thus allowing the kettle to become warm before full pressure is applied. After kettle becomes warm, and before applying full pressure, open the safety valve momentarily to release any air trapped within the jacket.
* 9. Clean strainer, drawoff valve, and drawoff tube thoroughly after each use. To clean drawoff valve and tube remove the front end of the valve and brush-scrub with hot water.

*NOTE: Not applicable to tilting kettles.

3.7 Finish. All exposed valves and fittings and the swing type water spout, when not fabricated of stainless steel, shall be chromium plated. In-wall carrier and floor support shall be covered with not less than one coat of rust-resisting primer applied in accordance with the manufacturer's standard practice.

3.8 Workmanship. The kettle shall be complete and clean and free of scratches, dents, breaks, sharp edges and corners, deformities, burrs, and slivers. All pipe connections shall be drawn tight and shall be free of crossed or stripped threads.

3.8.1 Rivets. Rivets, when used, shall be tight, and rivet heads and peened ends shall be round and in full contact with the surfaces of the joined metal. There shall be no empty rivet holes.

3.8.2 Welding. Welding shall be continuous, smooth, uniform, sound, and free of burn holes, cracks, fractures, undercutting, excessive metal buildup, and splatter. All scale and flux shall be removed and the welds shall be finished to blend with the adjacent joined metal surfaces.

3.8.3 Castings. Castings shall be sound and free of blowholes, shrinkage, porosity, or warping which might render the castings unsound.

3.8.4 Threaded fasteners. All threaded fasteners shall be drawn tight and shall not have crossed or stripped threads.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

4.2 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with the provisions set forth in MIL-STD-105.

4.2.1 Components and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.2.2 In-process inspections.

4.2.2.1 Insulation. Examination shall be made of the insulation material to determine conformance to the density requirements of 3.2.2 and thickness and installation requirements of 3.4.2. Whenever nonconformance is noted correction shall be made to the affected items and the lot in-process.

4.2.2.2 Priming. The in-wall carrier and floor support shall be examined to determine conformance to the priming coat requirements of 3.7. Whenever nonconformance is noted correction shall be made to the affected item and the lot in-process.

4.2.3 End item inspection. The lot shall consist of all kettles of one type, style, capacity, and class offered for inspection at one time. The sample unit shall be one completely fabricated kettle.

4.2.3.1 Visual examination. Examination of the end item for defects shall be in accordance with table III. The inspection level shall be II with an acceptable quality level (AQL), expressed in terms of defects per hundred units, of 2.5 for major defects and 6.5 for total (major and minor combined) defects.

TABLE III. Classification of defects

Examine	Defect	Classification Major	Minor
Finish (general)	Dirty, rust, scale.	X	
	Pits, scratches.	X	
	Valves, fittings, and swing type water spouts not chromium-plated.	X	
	Stainless steel components not finished in accordance with manufacturer's standard practice	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

TABLE III. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Construction and workmanship (applicable to all components and assemblies)	Any component not accessible for servicing, where required.	X	
	Any component fractured, split, or malformed.	X	
	Any component missing, loose, or not in proper alignment.	X	
	Any functioning component that required abnormal force to operate.	X	
	Any adjustable assembly that cannot be adjusted.	X	
	Any adjustable assembly not properly adjusted to perform the intended function.	X	
	Parts not connected or joined as specified, or poorly accomplished.	X	
Castings	Blowhole, porosity, shrinkage, unsound, warped.	X	
Soldering (if applicable)	Missing, not adherent or incomplete.	X	
	Not clean (flux or flux residue not removed).	X	
	Not smooth, or contains pinholes.	X	
Welding	Not type specified, missing, incomplete, burn holes, cracked, fractured, not fused, not smooth.	X	
	Slag inclusion, slight undercut, not uniform, scale or flux deposits not removed.	X	
Threaded fasteners	Missing, loose, crossed or stripped threads.	X	
Rivets	Loose, heads and peened ends not round.	X	
	Empty rivet holes, head and peened ends not in full contact with joined metal.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

TABLE III. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Construction body	Not provided with pouring lip (tilting kettles only).	X	
	Top rim not as specified.	X	
Covers	Hinges not located as specified.	X	
	Gutter not provided.	X	
	Stops not provided as specified (two-piece cover).	X	
Strainer and hook	Strainer not perforated as specified.	X	
	Stay not snug fit in outlet.	X	
	Handle not as specified.		X
Safety valve	Not tagged as specified.	X	
	Not located as specified.	X	
Kettle mountings (leg mounted)	Number of legs not as specified.	X	
	Socket and leg threads not as specified	X	
	Lock nut missing.		X
	Floor flange not as specified.	X	
Kettle mounting (wall mounted)	Sheet steel bracket or tubular bracket not as specified.	X	
	Mounting holes not provided (bolt mounted).	X	
	Erection hole missing (weld mounted).	X	
Pedestal mounted (stationary)	Not continuously fillet welded to steam jacket.	X	
	Base not provided with required holes for bolting.		X
Pedestal mounted (tilting)	Not located as specified.	X	
	Housing not as specified.	X	
	Base not provided with required holes for bolting.		X
	Tilting mechanism not self-locking.	X	

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:09Z
Check the source to verify that this is the currentversion before use.

Table III. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Pedestal mounted (tilting) cont'd	Mechanism will not hold kettle in position within 90 degrees.	X	
	Oil filler plug or lubrication fitting missing in housing.	X	
	Handwheel or crank not as specified.	X	
Table mounted (tilting)	Not one-piece liftoff cover (when required).		X
	Kettle does not tilt to 90 degrees .	X	
	Kettle will not return to upright position.	X	
Swing spout	Not as specified (when required).	X	
	Bracket not as specified or not located correctly.		X
	Clearance between outlet end of spout and top rim of kettle not 1-1/2 inch minimum (check visually, measure if in doubt).	X	
Valves and fittings	Not required amount and type (if specified).	X	
Water metering device (when applicable)	Not inclosed as specified.		X
	Swing spout not as specified.	X	
	Dial not marked as specified.	X	
	Electric outlet not as specified.	X	
Instruction plate (when applicable)	Missing, incomplete, not legible.	X	
	Not specified type, not in proper location, plate not fabricated of specified material.	X	
Data-name plates	Omitted or not as specified		X
	Information incomplete or not legible		X
	Not located so as to be readily visible to operator		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

4.2.3.2 Dimensional examination. An examination shall be made to determine compliance with dimensions specified. Any nonconformance shall be considered a defect. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

4.2.3.3 End item testing. One item selected at random from the production lot shall be tested as specified in 4.4.1 and 4.4.2. Failure of any test shall be cause for rejection of the end item involved.

4.2.4 Packaging inspection. An examination shall be made to determine that the preservation, packing, and marking comply with the section 5 requirements. Defects shall be as indicated in table IV. The sample unit shall be one shipping container fully packaged. The lot shall be the number of containers offered for inspection at one time. The inspection level shall be S-4 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

TABLE IV. Packaging defects

Examine	Defect
Markings, exterior and interior	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Component missing, damaged, or otherwise defective.
Workmanship	Blocking and cushioning inadequate, improper, or missing; bolts improperly affixed.

4.3 Certification examination. Certification, certified test reports or listing marks for standards, submitted in accordance with 3.1 shall be examined and validated as proof of compliance. Prior to Government approval of first shipment the contractor shall submit to the contracting officer or his authorized representative for approval certification that the kettles he proposes to furnish meet the applicable requirements of ASME and NSF as follows:

4.3.1 ASME certification. The contractor shall submit satisfactory evidence to the contracting officer or his authorized representative that the kettles he proposes to furnish meets the applicable requirements of Section VIII Div. 1, Pressure Vessels, as follows:

(1) A certificate stating that the kettles bear the ASME stamp shall be submitted prior to the approval of the first shipment.

4.3.2 NSF. Acceptable evidence of meeting the requirements of NSF shall be:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" and display of the NSF seal on the finished kettle, or

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

(2) A certification for the kettle issued by NSF under their special one-time contract evaluation/certification service, or

(3) A certified test report acceptable to the Surgeon General of the Procuring Activity from an independent testing laboratory, indicating the kettles have been tested and conform to the NSF Standard No. 4.

4.4 Methods of inspection.

4.4.1 Load test. (Wall mounted kettles) The kettle shall be mounted on a wall bracket or on an in-wall carrier support, as applicable, in the normal operation position. A load equal to 2-1/2 times the weight of water the kettle is intended to hold shall be applied to the kettle. The weight shall remain in place for not less than 10 minutes. The wall bracket or the in-wall carrier shall be examined, the load removed, and the wall bracket or in-wall carrier re-examined to determine compliance with the support and deformation requirements of 3.4.8.2. Any nonconformance to the requirements of 3.4.8.2 shall constitute failure of this test.

4.4.2 Water meter. The metering device shall be connected to 40 psig incoming water pressure. The dial shall be set at the 36 gallon mark. A container shall be placed under the spout and the meter started and allowed to run until it shuts off automatically. The time required from start to automatic shutoff shall be recorded, and the quantity of water delivered to the container shall be measured to determine compliance with the automatic shutoff, minimum water quantity, and accuracy requirements of 3.5.11. Any nonconformance to the requirements of 3.5.11 shall constitute failure of this test.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Disassembly. Projecting, detachable components, such as drawoff valve. handles, fittings. safety valve, and swing spout, shall be detached from the kettle in order to reduce cube and prevent damage while in transit.

5.1.1.2 Kettle. The outlet strainer shall be wrapped in minimum 30-Pound basis weight (24 by 36 - 500) kraft paper and the wrap secured with pressure-sensitive paper tape or plastic tape. The wrapped strainer shall be secured in place within the kettle with pressure-sensitive tape. The wire basket insert shall be secured and cushioned within the kettle to prevent move-ment or vibration and contact with each other (for tricompartmented baskets) or with interior surfaces of the kettles. When covers are provided, they shall be closed and sealed with pressure-sensitive tape. When covers are not provided, each kettle weighing more than 65 pounds shall be provided with a cover made

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

from waterproof paper conforming to PPP-B-1055, except that paper shall impart no objectionable odor or flavor; or minimum 0.003 inch thick polyethylene film. These covers shall also be sealed with pressure-sensitive tape. All openings leading into the kettle, such as steam lines and drawoff tubes, shall be sealed with pressure-sensitive tape. Kettles weighing more than 65 pounds shall have projecting components, such as handles and hinges not detached from the kettle, covered with paperboard conforming to PPP-P-291 and the paperboard secured with cord, twine, or tape. Tilting type kettles shall be secured in the upright position to prevent movement while in transit. Components of the kettle that are free to move shall be secured in such a manner as to prevent movement or damage while in transit.

5.1.1.3 Component parts of a kettle. Detached valves, handles, fittings, and spouts, other detached components, strainer hook, and water metering device shall be individually wrapped in paperboard as specified in 5.1.1.2, or unit packed in a box or boxes conforming to PPP-B-566, PPP-B-636, PPP-B-665, or PPP-B-676. When components are packed more than one to a box, they shall be prevented from contacting each other by the use of fiberboard or paperboard inserts or individually wrapped in paperboard as specified in 5.1.1.2. Each box shall be securely closed in accordance with the appendix of the applicable box specification.

5.1.1.3.1 Detached valves, handles, fittings. The detached valves, handles, fittings and spouts, other detached components, strainer hook, and water metering device of a kettle, unit packed as specified in 5.1.1.3, shall now be packed together in a snug-fitting fiberboard box conforming to style optional, type CF or SF, class domestic or weather-resistant (see 5.2.1.2 and 5.2.2.2) of PPP-B-636. Each box shall be securely closed in accordance with the appendix of the box specification.

5.1.2 Commercial. The kettles shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

5.2.1 Level A packing.

5.2.1.1 Kettles weighing 65 pounds or less. Each kettle (together with detached components) weighing 65 pounds or less, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping contain conforming to style RSC-L, grade V2s of PPP-B-636. Folding die-cut, or built-up fiberboard pads or other suitable means shall be used to immobilize the contents. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of the container specification.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:09Z
Check the source to verify that this is the currentversion before use.

5.2.1.2 Kettles weighing more than 65 pounds . Each kettle (together with detached components) weighing more than 65 pounds preserved as specified in 5.1, shall be packed in a shipping container conforming to over-seas type of PPP-B-601; class 2, style 2 of PPP-B-621; or type II, style A or B, class 1 or 2, of MIL-B-26195. The kettle shall be secured as specified in 5.2.1.2.1. A minimum clearance of 1 inch shall be maintained between the top and all sides of each kettle and the interior of the shipping container. The fiberboard box containing detached components shall be class weather-resistant (see 5.1.1.3.1) waterproofed in accordance with the appendix of the box specification, and secured in the unused portion of the shipping container. Each nailed-wood or cleated-plywood shipping container shall be provided with skids and closed and strapped in accordance with the applicable container specification. Alternatively, shipping containers may be used that conform to type IV or type I, style A depending upon weight of contents of MIL-C-52950 with the contents waterproofed in accordance with the appendix.

5.2.1.2.1 Securing of kettles. Each kettle shall be securely bolted to the bottom of the shipping container with minimum 5/16 inch diameter carriage bolts passing through the skids or through load bearing members attached to the inside surface of the bottom of the container. Each bolt shall be provided with a lockwasher located under the nut. Standmounted kettle shall be bolted in the upright position with not less than two bolts through each leg flange. Pedestal-mounted kettles shall be bolted in the upright position with not less than four bolts. Wall-mounted kettles shall be positioned on their side with mounting bracket on the bottom of the shipping container and bolted or when sufficient holes are not provided, the bracket shall be blocked to the bottom of the container in a manner as to preclude movement while in transit. Added precautions shall be taken to immobilize the covers of wall-mounted kettles while in transit. Table-mounted kettles shall be mounted on a minimum 3/8 inch thick plywood base, with dimensions approximating the inside length and width of the shipping container. The plywood base shall be bolted, as specified herein, to the bottom of the shipping container with a minimum of four bolts. Lumber blocking shall be used under the plywood base to provide a minimum of 1/4 inch clearance between the steam lines of the kettle and the bottom of the container.

5.2.1.3 Wall and floor supports. Unless otherwise specified, wall and floor supports shall be packed separately to insure carrier acceptance and safe delivery at destination at the lowest transportation rates for such supplies. When specified (see 6.2), wall and floor supports shall be packed in the same shipping container as the kettle (see 5.2.1.1, 5.2.1.2, 5.2.2.1, and 5.2.2.2).

5.2.2 Level B packing.

5.2.2.1 Kettles weighing 65 pounds or less. Each kettle (together with detached components) weighing 65 pounds or less, preserved as specified in 5.1 shall be packed in a snug fitting fiberboard shipping container conforming to style RSC-L, type CF, variety SW or type SF, class domestic of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

Folding die-cut, or built up fiberboard pads or other suitable means shall be used to immobilize the contents. Closure shall be in accordance with method II of the appendix of PPP-B-636.

5.2.2.1.1 Weather-resistant shipping containers. When specified (see 6.2) the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with method III, as specified in PPP-B-636 and closed in accordance with the appendix of the box specification.

5.2.2.2 Kettles weighing more than 65 pounds . Each kettle (together with detached components) weighing more than 65 pounds, preserved as specified in 5.1, shall be packed in a shipping container conforming to domestic type, style A or B of PPP-B-601; class 1, style 2 of PPP-B-621, type I, style A or B, class 1 or 2 of MIL-B-26195, type III, style 1, 2, or 2A of MIL-C-11133; or type I, style B or type IV depending upon dimensions and weight of contents, of MIL-C-52950. The kettle shall be secured as specified in 5.2.1.2.1. A minimum clearance of 1 inch shall be maintained between the top and all sides of each kettle and the interior of the shipping container. The fiberboard box containing detached components shall be class domestic (see 5.1.1.3.1) and shall be secured in an unused portion of the shipping container Each nailed wood or cleated plywood shipping container shall be provided with skids and closed and strapped in accordance with the applicable container specification and the appendix thereto. Each kettle packed in an open nailed wood crate or wirebound crate conforming to MIL-C-52950 or MIL-C-11133, respectively, shall be covered with a shroud fabricated of minimum 60-pound basis-weight (24 by 36 - 500) kraft paper.

5.2.2.3 Wall and floor supports. Wall and floor supports shall be packed as specified in 5.2.1.3.

5.2.3 Commercial packing. Kettles, preserved as specified in 5.1, and wall and floor supports shall be packed in accordance with ASTM D 3951.

5.4 Marking.

5.4.1 Civil agencies. In addition to any special marking required by the contract, unit packs and shipping containers shall be marked in accordance with FED-STD-123 or ASTM D 3951, as applicable.

5.4.2 Military activities. In addition to any special marking required by the contract, unit packs and shipping containers shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable. Special handling markings applicable to arrows and the words "This Side Up" shall apply.

6. NOTES

6.1 Intended use. The kettles are intended for use in food service facilities ashore and on board ship. The type I, style 5 kettles are intended to be mounted on the table covered by RR-T-25.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:09Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

a. Title, number, and date of this specification.
b. Type, style, capacity and when applicable class required (see 1.2).
c. When kettles are for shipboard use (see 3.4 and 3.6.2.1).
d. When a cover is required for tilting type kettles (see 3.4.3).
e. When a two-piece hinged cover is required for nontilting 60, 80 or 100 gallon kettles (see 3.4.3.2).
f. When an actuator is required for one-piece covers on 60, 80, or 100 gallon kettles (see 3.4.3.1).
g. When the drawoff tube and valve on nontilting, 20 gallon and greater capacity kettles shall be 3 inch diameter and size (see 3.4.5.2).
h. When leg bracing is required (see 3.4.8.1).
i. Type of wall bracket required (see 3.4.8.2, 3.4.8.2.1 and 3.4.8.2.2).
j. When style and size of steam-jacketed kettle table is required (see 3.4.8.5).
k. Electrical characteristics, if other than specified (see 3.4.11).
l. When a three-basket insert is required for type I, 40, 60, and 80 gallon kettles (see 3.4.9).
m. When a swing spout is not required (see 3.4.10).
n. When water metering devices are required, the number required and whether to be attached to a stand, a wall bracket or a kettle bracket (see 3.4.11).
o. When steam line valves and fittings are not required (see 3.4.12).
p. When no measuring devices are required (see 3.4.14).
q. Marking for civil agencies if other than specified (see 3.6.1).
r. Government approved manual number to be included on data name plate (see 3.6.2)
s. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
t. When wall and floor supports are packed with kettle (see 5.2.1.3).
u. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1.1).

6.3 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

MILITARY INTEREST:

Custodians

Army - GL
Navy - YD
Air Force - 99

Review activities

Army - MD
Navy - SA
DLA - GS

User activities

Army - CE
Navy - MC

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA - FSS
NIH
VA - OSS

PREPARING ACTIVITY:

Army - GL

Project No. 7310-0689

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

US ARMY NATICK RESEARCH
and DEVELOPMENT CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research
and Development Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
RR-K-195J	Kettle, Steam-Jacketed, (Stainless Steel, Steam Heated)

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:09Z
Check the source to verify that this is the current version before use.