53

S-S-710H
January 23, 1976
SUPERSEDING
Fed. Spec. S-S-710H
December 12, 1969

FEDERAL SPECIFICATION

STEAM TABLES (COMMERCIAL, HEAVY DUTY, STEAM, GAS, OR ELECTRICALLY HEATED)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers stainless steel steam tables heated by steam, gas, or electricity, and provided with food pans and soup tureens.

1.2 Classification.

1.2.1 Steam tables. Steam tables shall be of the following types, styles, and sizes as specified (see 6.2).

Types:

I	-	Steam heated
II	-	Electric heated
III	-	Gas heated

Styles:

1	-	With protector shelf
2	-	Without protector shelf

Sizes:

1	-	Four table-top openings
2	-	Five table-top openings
3	-	Six table-top openings

1.2.2 Pans and tureens. Pans and tureens procured separately shall be as specified in 3.6.10 and 3.6.10.2, respectively, and shall be of the sizes shown in table II (see 6.2).

FSC 7310

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:19Z
Check the source to verify that this is the current version before use.

1.2.3 Protector shelf. Protector shelves procured separately shall be as specified in 3.6.11 (see 6.2).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

UU-P-268	-	Paper, Kraft, Untreated, Wrapping.
WW-P-541	-	Plumbing Fixtures (Land Use) (General Specifications).
WW-T-696	-	Traps; Steam and Air.
WW-T-799	-	Tube, Copper, Seamless, (For use with Solder-Flared or Compression-Type Fittings).
WW-V-51	-	Valve, Bronze; Angle, Check, and Globe 125, 150 and 200 Pound, Screwed, Flanged, or Solder (For Land Use).
WW-V-54	-	Valve, Gate, Bronze (125, 150, and 200 Pound, Threaded Ends, Flange Ends, Solder End and Brazed Ends, For Land Use).
PPP-B-601	-	Boxes, Wood, Cleated-Plywood.
PPP-B-621	-	Boxes, Wood, Nailed and Lock Corner.
PPP-B-636	-	Boxes, Shipping, Fiberboard.
PPP-C-650	-	Crates, Wood, Open and Covered.
PPP-C-843	-	Cushioning Material, Cellulosic.
PPP-F-320	-	Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.
PPP-P-291	-	Paperboard, Wrapping, Cushioning.
PPP-T-60	-	Tape: Packaging, Waterproof.

Federal Standard:

FED-STD-123	-	Marking for Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:19Z
Check the source to verify that this is the current version before use.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specifications:

MIL-V-13811 - Varnish, Waterproofing, Electrical, Ignition.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-130 - Identification Marking of U.S. Military Property.
MIL-STD-1186 - Cushioning, Anchoring, Bracing, Blocking, and Waterproofing, with Appropriate Test Methods.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

American Gas Association, Inc. (A.G.A.)

Directory of Approved Appliances and Listed Accessories.

(Application for copies should be addressed to the American Gas Association, Inc., 1032 East 62nd Street, Cleveland, OH 44103.)

American National Standards Institute (ANSI) Inc. Standard

Z21.31 - Approval Requirements for Gas Counter Appliances.

(Application for copies should be addressed to the American National Standards Institute, 1430 Broadway, New York, NY 10018 or the American Gas Association, Inc., 1032 East 62nd Street, Cleveland, OH 44103.)

American Society for Testing and Material (ASTM) Standards

A 167 - Stainless and Heat Resisting Chromium Nickel Steel Plate, Sheet and Strip.
A 176 - Stainless and Heat Resisting Chromium Steel Plate, Sheet, and Strip.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

National Fire Protection Association (NFPA)

No. 70 - National Electrical Code.

(Application for copies should be addressed to the National Fire Protection Association, 60 Batterymarch Street, Boston, MA 02110.)

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

National Sanitation Foundation (NSF) Standards

No. 2 - Food Service Equipment.
4 - Commercial Cooking and Hot Food Storage Equipment.

Listing of Food Service Equipment.

(Application for copies should be addressed to the National Sanitation Foundation, P.O. Box 1468, Ann Arbor, MI 48106.)

Underwriters' Laboratories, Inc. (UL)

Standard No. 197 - Commercial Electrical Cooking Appliances.

(Application for copies should be addressed to the Underwriters' Laboratories, Inc., 207 East Ohio Street, Chicago, IL 60611; Walt Whitman Road, Melville, L.I. NY 11746; or 1655 Scott Blvd., Santa Clara, CA 95050.)

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), the supplier shall furnish a sample steam table for first article inspection and approval (see 4.3 and 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

3.2 Standard product. The steam tables shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product with any added features needed to comply with the requirements of this specification. Modifications to add features shall not incorporate different parts unless such parts are used on other current commercial models. Standard or modified commercial products furnished in accordance with this specification shall be identifiable by all regular manufacturer's or commercial service organizations servicing the brand involved. Service organizations shall be capable of providing complete parts and repair services on models furnished to the government consistent with their normal commercial practices.

3.3 Codes and standards. All steam tables shall conform to NSF No. 2. Type III (gas heated) and type II (electric heated) steam tables shall also conform to NSF Standard No. 4 and UL Standard No. 197. Type III (gas heated) steam tables shall conform to USASI Standard No. Z21.31.

3.3.1 Compliance. Prior to approval of the first article, if one is submitted, or prior to commencing production, the supplier shall submit to the contracting officer or his authorized representative that steam tables he proposes to furnish under this specification meet the applicable requirements of NSF Standard Nos. 2 and 4, ANSI Standard No. Z21.31, and UL Standard No. 197 requirements as follows:

3.3.1.1 ANSI. Acceptable evidence of meeting the applicable requirements of Z21.31 shall be a photostatic copy of the A.G.A. Certificate of Approval, a listing in the A.G.A. "Directory of Approved Appliances and Listed Accessories", or a certified test report from a nationally recognized independent testing laboratory acceptable to the Government indicating compliance with Z21.31.

3.3.1.2 NSF. Acceptable evidence of meeting the requirements of NSF shall be:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" or display of the NSF seal on the finished steam tables, or
(2) A certification for the steam tables issued by NSF under their special one-time contract evaluation/certification service, or
(3) A certified test report from a recognized independent testing laboratory acceptable to the medical department of the service for which the steam tables are being procured, indicating that the steam tables have been tested and conform to NSF Standard Nos. 2 and 4.

3.3.1.3 UL. Acceptable evidence of meeting the requirements of UL shall be the UL label, a UL listing mark, or a certified test report from a recognized independent testing laboratory acceptable to the Government indicating that the steam tables have been tested and conform with UL Standard No. 197.

3.4 Materials and components. Materials and components shall be as specified herein. Materials not definitely specified shall be of the quality normally used by the manufacturer for his standard commercial steam tables, provided the completed item complies with all provisions of this specification.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:19Z
Check the source to verify that this is the currentversion before use.

3.4.1 Stai sheets, and strips. Stainless steel plates, sheets, and s to type 300 series of ASTM A 167. Stainless steel used fo shall be either type 300 or type 400 series of ASTM A 167 an tively.

3.4.2 Drain fitting shall conform to part C, type II of WW-P-541/5A e le overflow tube shall be supplied in lieu of a rubber stop

3.4.3 Copp e used for the steam heating coils shall conform to ty

3.4.4 Glob valve shall conform to type I, class A, end connections - h of WW-V-51.

3.4.5 Gate lve shall conform to type I, class A of WW-V-54.

3.4.6 Chec valve shall conform to type IV, class A, end connections - h of WW-V-51.

3.4.7 Trap nform to type I, style B of WW-T-696.

3.5 Design l be designed to keep food hot on dining hall service the food pans in hot water contained in a water tank ater shall be heated by an external supply of steam (type ts (type II), or gas burners (type III). Steam tables ar table top openings sized to accommodate standard 12 in size cafeteria pans, and also smaller sizes down to steam tables shall be enclosed on three sides with the pen and provided with a lower shelf. The steam table sh legs with adjustable feet. Style 1 steam tables shall b ndow-lined protector shelf covering the full length of . Electrical wiring on all steam tables shall meet the A No. 70 and shall be classified as suitable for use in ation.

3.5.1 Dimen shall conform to the dimensions of table I.

Overall dimensions

Size	Length ±1/4 inch	Width ± 1/4 inch	Height 1/
1	5/8	30	34
2	1/2	30	34
3	3/8	30	34

1/ Height sho idpoint of adjustment.

on

)

3).

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:19Z
Check the source to verify that this is the currenversion before use.

3.6 Construction. Steam tables, including shelves, pans and soup tureens shall be made of stainless steel specified in 3.4.1. The completely assembled steam tables shall support the weight of four (size 1), five (size 2), six (size 3) fully loaded tureens without permanent visible deformation when tested as specified in 4.6.6.

3.6.1 Body frame. The body frame shall be fabricated of angles and channels welded to form an integral unit. There shall be not less than three horizontal channels supporting the water pan. Channels shall extend the full width of the frame and shall be supported by vertical members, front and back. The body frame shall be drilled to receive six legs with adjustable feet.

3.6.2 Shelf frame. The shelf shall be supported by a frame fabricated of channels or angles.

3.6.3 Body. Panels for enclosing the frame shall be 0.050 inch (18 gage) sheet. Front and ends shall be enclosed from the table top to the shelf. The attendant's side shall have one full length panel extending from the table top to below the bottom of the water tank. There shall be at least 15 inches clearance between the bottom of this panel and the top of the shelf. Panels shall be wrapped around body frame members at corners and shall be welded securely in place.

3.6.4 Shelf. The shelf shall be 0.0625 inch (16 gage) and shall extend the full length of the table. Shelf edges shall be flanged for rigidity and to allow for welding to the frame and outer panels. The flange on the attendant's side shall be turned down. Holes shall be provided for the water inlet an overflow lines and for necessary electric, steam, or gas lines, as required.

3.6.5 Table top. The table top shall be one piece of 0.0625 inch (16 gage) sheet. Openings for food pans shall be die formed with raised edges and shall be 11-7/8 inches wide by 19-7/8 inches long with a plus tolerance of 1/8 inch and a minus tolerance of zero. Size 1, 2, and 3 steam tables shall have 4, 5, and 6 openings for food pans, respectively, with not less than a 2 inch space between openings. The left end, when viewed from the attendant's side shall have holes to receive water inlet piping. The outside edges of the table top shall be turned down 90 degrees to fit closely over the body panels.

3.6.6 Water tank. The water tank shall be 0.0625 inch (16 gage) sheet and may be either seamless drawn or one piece welded construction. The tank shall be the width of the table, of a length to accommodate insertion of all food-pans and 9 inches plus or minus 1/4 inch deep. Openings for drainage and electric elements or steam pipes as necessary shall be made. The tank shall be formed or installed that the drain end is a minimum of 1/8 inch lower than the opposite end. When tested as specified in 4.6.4 the water tank and fitting joints shall not leak.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:19Z
Check the source to verify that this is the currentversion before use.

3.6.7 Faucet. The water inlet faucet shall be mounted on the table top at the attendant's left. The faucet shall be a swing type with a 4 arm handle and shall be mounted in place such that there is a minimum clearance of 1 inch between the spout discharge and table top. The faucet shall be chrome plated brass or stainless steel. Piping to the faucet shall be located between the outer panel and the water tank. When tested as specified in 4.6.4, pipe joints and fittings shall not leak.

3.6.8 Overflow. The overflow tube shall extend 6 inches above the inside tank bottom. The tube shall be removable standing waste type. The waste outlet fitting shall conform to 3.4.2.

3.6.9 Legs. A leg with an adjustable splashproof foot shall be located at each corner of the steam table. The legs shall be secured to the body-frame by bolting. Legs and feet shall provide at least 6 inches of clearance between the lowest part of the cabinet-bottom and the floor. Height adjustment shall be at least one inch.

3.6.9.1 Size 1. Size 1 steam tables shall be provided with four legs. Each leg shall extend from the floor to the body frame.

3.6.9.2 Sizes 2 and 3. Sizes 2 and 3 steam tables shall be provided with six legs, four legs shall be located at each of the four corners and one leg shall be located midway along the length of the front and back. All legs shall extend from the floor to the body frame except the leg located at the center of of the table on the attendants side. The center leg on the attendants side may extend from the floor to the body frame or from the floor to the bottom of the shelf with a center support extending from the shelf up to the body frame. The center support shall be installed directly above the leg. The center support and center leg may be secured by bolting.

3.6.10 Food pans. The food pans shall be fabricated of stainless steel specified in 3.4.1, and shall fit into the openings provided in the table top. The length and width of the food pans shall be such that one full size pan, two 1/2 size pans, or three 1/3 size pans shall fit into any one of the rectangular table top openings. The pans shall be seamless drawn and shall conform to table II. The top of the pans shall be provided with a horizontal flange or semirolled edge. The flange width shall be such that when one full size pan, two 1/2 size pans, or three 1/3 size pans are inserted in normal use position, the rectangular openings shall be completely covered. The edge of the flange shall be turned down and the four corners shall be square or finished with a maximum 3/8 inch radius. The sides of the pans shall permit nesting of pans of the same size. The quantity and size of pans to be furnished for each size steam table shall be in accordance with table II, except for the full size extra deep food pans. When specified (see 6.2), a full size extra deep food pan shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:19Z
Check the source to verify that this is the current version before use.

TABLE II. Food pans and tureen sizes, capacities, and metal thicknesses

Pan and tureen size	Quantity per steam table			Outside depth (+0 -1/8 inch)	Capacity (± 10 percent)	Starting metal Thickness (nominal)	Minimum metal thickness after forming
	Size 1	Size 2	Size 3			Stainless steel	Stainless steel
				Inches	Quarts	Inch	Inch
Full size, shallow	5	5	7	2-1/2	7-1/2	0.0375	0.028
Full size, deep	2	3	3	4-1/8	15	.0375	.028
Full size, extra deep	-	-	-	619-3/4	.0375	.028	
One-half size	4	6	8	6	10-3/4	.0375	.020
One-third size	3	3	3	6	6-1/2	.0375	.020
Tureen	1	2	2	8	32	.050	.028

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T11:19Z
Check the source to verify that this is the current version before use.

3.6.10.1 Pan cover. When specified (see 6.2), the food pans shall be provided with a flat, one piece overlapping cover of stainless steel specified in 3.4.1, of the same thickness as the pan. The cover shall be provided with a [illegible] strap type handle located at the top center of the cover. The cover shall have a lip to fit the flange on the pan.

3.6.10.2 Soup tureen. The bottom length and width of the soup tureen shall be such that the tureen will fit into any of the rectangular table top openings. The sides shall be formed with a shoulder to support the tureen on the table top. The shoulder shall be located so as to limit the depth of the tureen below the shoulder to maximum 6 inches. The quantity of tureens to be furnished for each size steam tables shall be in accordance with table II.

3.6.10.2.1 Tureen cover. Each soup tureen shall be provided with a flat, one piece overlapping cover of stainless steel specified in 3.4.1.

3.6.11 Protector shelf. The style 1 steam table shall be provided with a protector shelf located at the front of the steam table. The shelf shall extend the entire length of the table. The top of the shelf shall be 16 inches, plus or minus 1/4 inch above the table top. The shelf shall be secured to the table by at least two studs with lock-washers and nuts. The studs shall extend through the framing of the steam table body. The glass front shall be 1/4 inch plate glass in three equal sections, with provisions for replacing the glass in event of breakage. The framework shall be fabricated of minimum 1 by 1 by 1/16 inch thick stainless steel square tube. The top shall be not thinner than 0.0781 inch (14 gage) stainless steel specified in 3.4.1 and shall be at least 12 inches wide. The protector shelf shall provide a 6 inch, plus or minus 1/4 inch opening between the table top and glass front.

3.6.12 Type I, steam heated. Each type I steam table shall be provided with a globe valve (see 3.4.4) for the steam inlet line; a gate valve (see 3.4.5), strainer, check valve (see 3.4.6) and trap (see 3.4.7) for the condensate return line. Threads on valves and fittings shall be nominal 3/4 inch with American Standard Taper Pipe Threads. This equipment shall be furnished, but not installed by the supplier.

3.6.12.1 Steam coil. The coil shall be fabricated from nominal 7/8 inch outside diameter by .065 wall thickness copper tube specified in 3.4.3. Except for necessary clearances, the coil shall extend the length of the water tank and shall consist of four lengths of tube. Unless otherwise specified (see 6.2), saturated steam shall be used and the steam system shall be designed for operation at a pressure not exceeding 40 pounds per square inch gage. Combination coil supports and hold down straps shall be provided with

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

coil supports securely welded to the water tank. Straps shall be removable and shall have room for expansion of the coil. Coil inlet and outlet shall be threaded and provided with gaskets and locknuts where the coil enters and leaves the tank. The coil shall slope towards the outlet end for drainage. The coil shall not leak when subjected to a hydrostatic test of 3 times the steam working pressure but not less than 125 psig water pressure test as specified in 4.6.1.

3.6.12.2 Thermostat (type I steam tables). The type I steam tables shall be equipped with one steam thermostat designed to automatically control the steam supply as temperature variations occur within the water tank. The moveable parts and renewable seat shall be stainless steel, specified in 3.4.1. The thermostat shall be so installed that the sensing tube or bulb does not come in contact with the heating coils. The temperature range shall be not less than 175 degrees F nor more than 225 degrees F with variations from the thermostat setting of not more than plus or minus 7 degrees F when tested as specified in 4.6.5. Thermostat shall be mounted so that all knobs are flush with the exterior side surface of the water tank.

3.6.13 Type II, electric heated. Unless otherwise specified (see 6.2), the electric heated steam table shall be designed for operation on a nominal 208 volt, single-phase, 60 hertz, alternating current system. Provision shall be made for grounding the steam table.

3.6.13.1 Heating elements. Each type II steam table shall be provided with immersion type heating elements designed for the specified voltage with wattage ratings within 5 percent of that specified in table III when tested as specified in 4.6.3.1. The elements shall be located so as not to come in contact with or interfere with, the insertion or removal of the food pans or soup tureens. A minimum space of 3/4 inch shall be provided under each element for ease of cleaning.

TABLE III. Heating elements

Steam table size	Wattage rating per steam table	Number of heating elements
1	5,000	2
2	6,000	2
3	9,000	3

3.6.13.2 Thermostats (type II steam tables). Each heating element shall be equipped with a thermostat for controlling temperature of the water in the water tank. The sensing tubes shall be located 1 inch plus or minus 1/4 inch, above the bottom of the water pan. The thermostats shall automatically control water temperature. The operating range shall be not less than 60 F nor more

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:19Z
Check the source to verify that this is the current version before use.

than 250 F with variations from the cutout temperature of the thermostat of not more than plus or minus 7 F at the maximum temperature setting when tested as specified in 4.6.5. The thermostats shall be mounted on a formed panel constructed of minimum 0.0711 inch thick stainless steel specified in 3.4.1. The panel shall be mounted under tha water tank panel at the attendant's side so that the outside of the thermostat body or knobs are flush with the exterior side surface of the panel. The inclosure for the conductors connecting the thermostats and elements shall be electrical metallic conduit.

3.6.13.3 Low water cutoff. Heating elements shall incorporate a cutoff to open the energized electrical circuits when the heating elements are exposed to air at low water level (see 4.6.3.2). The cutoff shall be designed for 50-60 cycles, a voltage range of 208-230, and shall be equipped with a manual reset button. The cutoff shall be inclosed in a stainless steel box, located for ease of servicing.

3.6.14 Type III, gas heated. Each gas heated steam table shall be equipped with a manifold, a ground joint type union, a flat head gas cock for installation in the gas supply line, and fuel system components as specified in 3.6.14.1. An aperture for viewing burner flame shall be furnished on attendant's side. Flame deflector plates shall be located under the water tank above the burners. No gas carrying joint shall depend on cement or similar material for mechanical strength or primary tightness. All joint compound shall be resistant to gas. The gas burner input in Btu per hour shall conform to the requirements of table IV when tested as specified in 4.6.2.

TABLE IV. Gas rating

Steam table size	Total Btu input per steam table (minimum)	Number of burners
1	33,000	2
2	39,000	3
3	52.000	4

3.6.14.1 Fuel system. Each gas-heated steam table shall be designed to provide a large flame-impingement area, or flame deflector plates for large concentrated gas flames, to prevent hot spots on the water pan. The fuel system, including burners shall be designed to burn natural gas or liquefied petroleum gas. Burner gas valves and pilot gas valves shall be of the fixed orifice type having interchangeable orifice hoods or bushings. The manufacturer shall furnish two bushings for each valve, one drilled for natural gas, the other for liquid petroleum gas, and shall also provide instructions for conversion from one type of gas to the other. The valve hoods or bushings shall be color coded as follows: Natural gas unpainted brass; liquefied petroleum gas black.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:19Z
Check the source to verify that this is the currenversion before use.

3.6.14.1.1 Gum protective devices. The constant burning gas pilots designed to use natural gas shall be provided with gum protective devices.

3.6.14.1.2 Automatic ignition. Automatic ignition shall insure safe ignition and re-ignition of gas. All gas burners shall be equipped with a manually-lighted standing pilot system. The pilot shall be furnished with a safety shutoff device. In the event that the source of ignition fails, the device shall automatically interrupt the flow of gas to the main burner under its supervision and the flow of gas to the pilot.

3.6.14.2 Thermostats (type III steam tables). Each burner shall be equipped with a modulating gas thermostat of the remote sensing bulb and capillary tube type for controlling water temperature in the water tank. Thermostats shall control the flow of gas to the burner it serves and shall be mounted as specified in 3.6.13.2. The sensing elements shall be secured 1 inch plus or minus 1/4 inch above the bottom of the water tank. Thermostats shall be suitable for the type of gas and Btu rating specified. The operating range shall be not less than 60 F nor more than 250 F with variations from the thermostat setting of not more than plus or minus 5 F when tested as specified in 4.6.5.

3.6.15 Identification marking. Steam tables, food pans, and soup tureens shall be permanently marked in accordance with MIL-STD-130 with the manufacturer's name, trade name, or trademark of such known character as to be readily identifiable with said manufacturer. The surfaces opposite identification markings on food pans and soup tureens shall show no signs of penetration, unevenness or distortion. Steam table markings shall be shown on a photosensitive anodized aluminum nameplate, or may be indented, etched, or embossed on a stainless steel nameplate.

3.6.16 Instructions. The steam tables shall be provided with a user's instruction plate. The instructions shall be etched or die stamped on a stainless steel plate of not less than 0.0241 inch thickness or shown on a photosensitive anodized aluminum plate. The plate shall be permanently attached to the attendant's side of the table and shall contain the following instructions and heading:

USERS' INSTRUCTIONS

1. Fill steam table pan to proper level with hot water before turning on heat.
2. Keep appliance clean. Do not allow grease or stains to remain on metal parts. Do not use steel wool for cleaning. Use a brush with cleaning powders and hot water to remove food particles and sediment.
3. After serving, turn off heat, drain water compartment, and thoroughly clean inside of compartment of all food particles and sediment.
4. Wash and rinse all food pans and soup tureens after use, and disinfect as instructed by those in authority.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

3.7 Repair and maintenance. Provisions shall be made to allow for ready adjustment, service, and replacement of electrical power or gas burning components, valves, or thermostats, without disturbing or disassembling any major component or equipment. In addition, there shall be free access to inspect, service, and adjust any component or equipment as provided for by this specification or as indicated by the component or equipment manufacturer, without requiring disassembly of any other major component or equipment on the steam table.

3.8 Finish. The steam table, protector shelves, pans, and soup tureens shall be smooth on all surfaces and edges, and free from rough grind marks, trimming marks, pits, scale, and die marks. Stainless steel finish shall conform to the requirements of the referenced NSF standards.

3.9 Workmanship. Steam tables, food pans and soup tureens shall be free from dirt and other harmful extraneous material, burrs, slivers, rough die, tool and grind marks, dents and cracks. External surfaces shall be free from sharp edges and corners except where corners are required.

3.9.1 Metal fabrication. Metal used in the fabrication of the steam tables, food pans, and soup tureens shall provide for original quality surface finish and shall be free from kinks and unspecified bends. Forming and shearing shall not cause damage to the metal and shall be done neatly and accurately. Corners shall be square and true and all bends of a major nature shall be made with dies or fixtures to insure uniformity of size and shape.

3.9.2 Welding. The surface of parts to be welded shall be free from rust, scale, paint, grease and other foreign matter. Welds shall be smooth and free of cracks, burn holes, undercuts or incomplete fusion. All scale and flux shall be removed from the finish weld area.

3.9.3 Fastening devices. Threaded fastener and rivet holes shall be accurately punched or drilled and have burrs removed. Threaded fasteners shall not be broken, cracked or stripped and be securely torqued. Rivets shall fill the hole completely and the heads shall be in full contact with the surface of the member and concentric with the hole.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:19Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

1. First article inspection (see 4.3).
2. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required, it shall be examined for defects in table V and for compliance with dimensions specified, and tested as specified in 4.6.1 through 4.6.7. Failure to pass all tests shall be cause for rejection of the first article. The presence of any defects listed in table V or any dimension not within specified requirements shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with the provisions set forth in MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.2 End item inspection. The inspection lot shall consist of all steam tables of one type, style and size or food pans, tureens, or protector shelf when procured as a seperate end item offered for inspection at one time.

4.4.2.1 Visual examination. The steam table or food pans, tureens, or protector shelf when procured as a separate end item shall be examined for defects in table V. The inspection level shall be level II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE V. Classification of defects

Examine	Defect	Classification Major	Classification Minor
Standard product	Item not in accordance with manufacturer's standard product	X	
Finish	Stainless steel finish not as specified		X
	Evidence of discoloration, or stains	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

TABLE V. Classification of defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Construction and workmanship general	Component missing	X	
	Any component fractured, bent, buckled, dented, punctured, or malformed	X	
	Misplaced or not in proper alignment	X	
	Not constructed as specified	X	
	Not fabricated of material specified	X	
	Any component not readily accessible for servicing where required		X
	Any burr, sliver, sharp edge, rough die, tool, gouge, trim, or grind marks	X	
Welding and brazing (where required)	Missing	X	
	Incomplete, burn holes, cracked or porous	X	
	Slag inclusion, undercut, not smooth and uniform		X
	Scale or flux deposits not removed		X
	Not free from rust, scale, paint, grease and other foreign matter	X	
Soldering (when applicable)	Missing, not adherent, or incomplete	X	
	Not clean (flux or flux residue not removed), not smooth (surface not finished neatly) or pinholes in solder		X
Fastening devices	Missing, cracked, or stripped	X	
	Fastener loose		X
	Fastener improperly torqued	X	
	Rivet holes not accurately punched	X	
	Rivet not peened properly		X
Thermostats	Operating range not as specified	X	
	Not mounted in the specified manner		X
Tureen	Top edge of body not properly flanged		X
	Bulge at side		X
	Cover does not fit flush (flange uneven more than 1/16 inch)	X	
Food pan	Lip flange uneven (more than 1/16 inch)	X	
	Not seamless	X	
	Edge not properly flanged		X
	Bulge at sides or bottom more than 1/8 inch		X
	Corners not rounded		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

TABLE V. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Steam table	Thermostat body or knobs extend beyond exterior side surface of panel (check visually)		X
	Cutoff interferes with insertion of food pans or tureen	X	
	Openings for food pans not cut evenly (check visually)	X	
	Body top sags or bulges more than 1/8 inch (check visually)		X
	Body top overlap does not cover all four corners		X
	Body does not fit rigidly on stand		X
	Openings around faucet hole flange in body		X
	Vent holes missing from serving side (gas models only)	X	
	One or more deflector plates, missing from water tank (gas models only)	X	
	No allowance for expansion or contraction of deflector plates (holes must be elongated)		X
	Water tank not made from single piece of sheet metal		X
	Water tank not supported on at least three channels	X	
	Water tank drain not embossed		X
	Faucet binds on swivel		X
	Panels uneven and do not completely cover frame		X
	Bulges in top of panels preventing good fit to table body		X
	Adjustable leg out of alignment		X
Steam coils (when applicable)	Any pipe or fitting damaged	X	
	Combination coil support and hold down straps not loose fit on tubing or not located as specified		X
	Coils not properly sloped for drainage	X	
	Inlet and outlet holes not properly located		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

TABLE V. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Gas burners and gas valves (when applicable)	Burners not correctly lined up on valve, flange, or supports	X	
	Burner air shutter plate binds (hard to adjust)		X
	Incorrect number and marking of orifice hoods or bushings	X	
Electric heating elements (when applicable)	Nameplate indicates incorrect electrical characteristics	X	
	Not type specified	X	
	Bent out of space	X	
Electrical wiring	Not in accordance with NEC	X	
	Loose pieces (if any) not removed from inside burner		X
	Two or more ports not drilled	X	
	Valve handle too tight (hard to operate)	X	
Gas piping	Pipe joints visibly cemented	X	
Marking, identification, instruction plates	Missing, incomplete, not legible, not as specified	X	

4.4.2.2 Dimensional examination. Examination shall be made of the steam table or food pans, tureens, or protector shelf when procured as a separate and item for compliance with dimensions specified. Any dimensions not within the specified requirements shall constitute a defect. The inspection level shall be S-2 with an AQL of 4.0 defects, expressed in terms of defects per hundred units.

4.4.2.3 Testing of the end product. A random sample of the end item shall be selected in accordance with 4.4 using inspection level S-4. The sample shall be tested as specified in 4.6.3.1 and 4.6.3.2 for type II units and 4.6.4 through 4.6.7 for all types. Failure of any one sample to pass any test shall be cause for rejection of the entire lot. When a first article is not required, the initial production unit shall be tested in accordance with 4.6.1 through 4.6.7, as applicable. Failure of any one sample to pass any tests shall be cause for rejection of the entire lot.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:19Z
Check the source to verify that this is the current version before use.

4.4.3 Inspection of preparation for delivery. An examination shall be made to determine that preservation, packaging, packing, and marking as required by section 5 are complied with. Defects shall be as indicated in table VI. The sample unit shall be one shipping container fully prepared for delivery. The inspection level shall be S-4 with an AQL of 6.5 defects, expressed in terms of defects per hundred units. The lot shall be the number of containers offered for inspection at one time.

TABLE VI. Examination of preparation for delivery

Examination	Defect
Markings, exterior and interior	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Preservation	Preservative improperly applied or missing
Material	Component missing, damaged, or otherwise defective

4.4.3.1 Examination of shipping containers. When shipping containers are required to be in accordance with PPP-B-601, PPP-B-621, PPP-B-636, or PPP-C-650, examination for defects in closure and strapping shall be in accordance with the applicable container specification. Examination for defects in cushioning, blocking, and bracing, and waterproofing shall be in accordance with MIL-STD-1186.

4.5 Certificate examination. Certificates of compliance, certified test reports, approval labels or listing marks for codes and standards, as applicable, that are submitted as proof of compliance with the specification requirements shall be examined and validated.

4.6 Tests.

4.6.1 Steam coil. The steam coil shall be hydrostatically tested with three times the steam working pressure but not less than 125 psig water pressure for a period of 15 minutes and observations made to determine conformance with leak tightness requirement of 3.6.12.1. Nonconformance shall constitute failure of this test.

4.6.2 Gas burner input. Connect gas meter in series with the gas supply line and the inlet side of the steam table. Obtain from the local gas company the heating value of the gas to be used expressed in Btu per hour. Check whether the gas valve hoods are correct for the type of gas to be used and that the gas burners are tight. Fill the steam table water tank with water until it runs out the overflow tube, with the water running.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:49Z
Check the source to verify that this is the current version before use.

Ignite the gas burners and operate at full capacity. The burner input in Btu per hour can be obtained by multiplying the cubic feet of gas flow per [illegible] conformance to table III. Any nonconformance shall constitute failure of this test.

4.6.3 Electric heated table.

4.6.3.1 Wattage rating. Fill tank with water up to the top of overflow tube. The steam table shall be connected to a power source having the same electrical characteristics. Voltage and wattage readings shall be taken at the equipment power terminals. From these readings the calculated watts input at the specified voltage shall be determined. This calculated wattage shall be checked to determine that it does not vary more than plus or minus 5 percent from the ratings specified in 3.6.13.1. Any nonconformance shall constitute failure of this test.

4.6.3.2 Low water cutoff test type II steam tables. After performing tests of 4.6.5, 4.6.4 and 4.6.3.1, in order listed gradually lower the water level (as by removing the overflow tube) until the heating elements are exposed, and check operation of the low water cutoff, as specified in 3.6.13.3. Failure of the cutoff to break the energized circuits to the heating elements shall constitute failure of this test.

4.6.4 Leakage test. With at least 3 inches of water in the water tank and with the water running, check for leaks in the tank, at the piping connections, and where piping enters the water tank to determine conformance with water tightness requirements of 3.6.6 and 3.6.7. Any nonconformance shall constitute failure of this test.

4.6.5 Thermostat accuracy and control. The steam table shall be filled with water until it runs out the overflow tube. The temperature of the water shall be measured adjacent to the sensor with a thermometer accurate within plus or minus one degree F. With the heat applied, the thermostat dial shall be set approximately 20 degrees F below that of boiling water (210 to 212 degrees F) until conditions of equilibrium have been established. The temperature of the water in the tank is then to be raised at a rate of no more than 5 degrees every five minutes until a vigorous boil occurs in the water tank. Measure maximum and minimum water temperatures for three "off-on" cycles of the thermostat. The cutout temperature setting of the thermostat shall be within the accuracy and control requirements of 3.6.12.2, 3.6.13.2, and 3.6.14.2, as applicable, when the water in the tank is at the maximum average temperature (boiling vigorously at 210-212 degrees F). Any non-conformance shall constitute failure of this test.

4.6.6 Structural strength. The water tank shall be filled with water to overflow level. A tureen shall be placed in each table top opening and filled with water. The steam table shall be allowed to stand for one hour with the load. At the end of this time the tureen and water pan shall be emptied and the steam table examined for conformance to the strength requirements of 3.6. Any nonconformance shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:19Z
Check the source to verify that this is the current version before use.

4.6.7 Capacity test. Food pans or tureens of each size shall be filled with water. The contents of the filled pan or tureen shall be measured in a calibrated beaker or container. Any nonconformance with the applicable requirement of table II shall constitute failure of this test.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Disassembly. The swivel faucet, legs, protector shelf, or any other component parts that protrude outside the normal outline of the steam tables except exterior mounted thermostat control knobs, shall be detached.

5.1.1.2 Preservation.

5.1.1.2.1 Protection of wiring. All exposed wiring shall be coated with varnish conforming to MIL-V-13811. Care shall be exercised to see that the varnish is not applied to any electric points or contacts.

5.1.1.2.2 Sealing of openings. All openings into heating elements and control boxes shall be sealed with tape conforming to PPP-T-60.

5.1.1.3 Packaging.

5.1.1.3.1 Plumbing, fixtures, table legs, and food containers. Each food pan shall be completely form wrapped in 30 pound kraft paper conforming to grade B of UU-P-268. Plumbing fixtures and table legs shall be completely wrapped in cushioning material or paperboard conforming to PPP-C-843 or PPP-P-291, respectively. The wrapped food pans shall be nested in the most compact manner. The wrapped plumbing fixtures shall be placed within the nested food pans, and together with the tureen or tureens shall be packaged in snug-fitting fiberboard box or boxes conforming to style RSC, V3c of PPP-B-636. The contents shall be cushioned as necessary to prevent movement while in transit. Each box shall be closed in accordance with the appendix of PPP-B-636.

5.1.1.3.2 Protector shelf. Each protector shelf shall have the front and back surfaces of the glass front covered with cushioning material or paperboard as specified in 5.1.1.3.1. The cushioning material for glass shall be in the form of a blanket having a minimum thickness of 1/2 inch. The wrap shall be secured with tape as specified herein. The attaching hardware shall be secured in place on the protector shelf and cushioned. Each wrapped protector shelf shall then be completely wrapped in a scored corrugated fiberboard sheet fabricated from material conforming to type CF, class weather-resistant, variety SW, grade V3c of PPP-F-320. The wrap shall be sealed on all openings with tape conforming to PPP-T-60.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:19Z
Check the source to verify that this is the currentversion before use.

5.1.2 Level C. Tables, protector shelves, and food containers shall be preserved and packaged to afford adequate protection against damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice, when it meets these requirements.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Steam table. Each steam table including all disassembled component parts, preserved and packaged as specified in 5.1, shall be packed in a shipping container conforming to overseas type of PPP-B-601 or class 2 style 2 or 4 of PPP-B-621. Protector shelf for style 1 tables shall be packed inverted, with shelf down. Packaged components shall be packed into voids within the steam table and secured in such a manner as to prevent movement or damage while in transit. The contents of each shipping container shall be cushioned, blocked and braced, and waterproofed in accordance with MIL-STD-1186. Each shipping container shall be provided with skids, and shall be closed, and strapped in accordance with the applicable container specification.

5.2.1.2 Protector shelf (when procured as a separate item). Each protector shelf, packaged as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to overseas type of PPP-B-601 or class 2, style 2 or 4 of PPP-B-621. The protector shelf shall be blocked, braced, and cushioned in such a manner as to prevent movement or damage while in transit. Closure and strapping shall be in accordance with the appendix of the applicable container specification.

5.2.1.3 Food containers (when procured as a separate item). Food pans and soup tureens, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, V2s of PPP-B-636. The weight of contents of each shipping container shall not exceed 65 pounds. Each shipping container shall be closed, and sealed by means of waterproofed tape, and reinforced with flat strapping or tape banding in accordance with the appendix of PPP-B-636.

5.2.2 Level B.

5.2.2.1 Steam table. Each steam table, including all disassembled component parts, preserved and packaged as specified in 5.1, shall be packed in a shipping container conforming to type II, style B of PPP-B-650; domestic type, style A or B of PPP-B-601; or class 1, style 2 or 4 of PPP-B-621. The protector shelf for style 1 tables shall be packed inverted, with shelf down. Packaged components shall be packed into voids within the steam table and secured in such a manner as to prevent movement or damage while in transit. The contents of each shipping container shall be cushioned and blocked and braced in accordance with MIL-STD-1186. Each shipping container shall be provided with skids as specified in the applicable container specification, except that skids for crates shall be placed under each crossmember.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

5.2.2.2 Protector shelf (when procured as a separate item). Each protector shelf, packaged as specified in 5.1, shall be packed and secured in a shipping container conforming to domestic type, style A or B of PPP-B-601; or class 1, style 2 or 4 of PPP-B-621. The protector shelf shall be blocked, braced, and cushioned in such a manner as to prevent movement or damage while in transit.

5.2.2.3 Food containers (when procured as separate items). Food pans and soup tureens, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, variety SW, or type SF, class domestic of PPP-B-636. The weight of the contents of each shipping container shall not exceed 65 pounds. Closure shall be in accordance with method II of the appendix of PPP-B-636.

5.2.2.3.1 When specified (see 6.2), the shipping container shall be V3c, V3s, or V4s, fabricated and closed in accordance with PPP-B-636.

5.2.3 Level C. Tables, protector shelves, and food containers, preserved and packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Marking.

5.3.1 Civil agencies. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with FED-STD-123.

5.3.2 Military requirements. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

5.3.3 In addition to marking specified, interior packages and shipping containers having a protector shelf or shelves shall be marked with the word "CLASS" and in accordance with the fragile item and arrow marking requirements of MIL-STD-129.

6. NOTES

6.1 Intended use. The steam tables covered herein are intended for use in feeding lines in permanent installations to keep food hot, but are not intended to reheat or cook food.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type, style, and size of steam table required (see 1.2.1).
(c) Capacity of food pans and tureens, if procured separately (see 1.2.2).
(d) Size of steam table with which a separately procured protector shelf will be used (see 1.2.3).
(e) When a first article is not required (see 3.1).
(f) When an extra deep full size steam table pan is required (see 3.6.10).
(g) When covers are required for food pans, and number of covers required (see 3.6.10.1).
(h) Steam if other than specified (see 3.6.12.1).
(i) Electrical characteristics, if other than specified (see 3.6.13).
(j) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.3.1).
(k) Selection of the applicable levels of preservation, packaging, and packing (see 5.1 and 5.2).

6.3 First article. When a first article is required (for DOD procurement only), it shall be inspected and approved under the appropriate provisions of ASPR 7-104.55 of the Armed Services Procurement Regulations. The first article should be a first unit of production and should consist of one unit. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for inspection and approval of the first article.

6.4 Contract Data Requirements. Any data items to be delivered under any contract for items covered by this specification should be specifically called for in the contract in accordance with the applicable regulations of the procuring activity.

Custodians:

Army - GL
Navy - YD
Air Force - 84

Review activities

Army - MD, CE
Navy - MC

Preparing activity:

Army - GL

Civil Agency Interest:

GSA - FSS

Project No. 7310-0317

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 50 cents each.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:19Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	d. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

NSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in mitting comments and suggestions for improvements. All users of military standardization documents are invited to provide gest' ns. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and ailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was oo rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the roblems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an cknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being onsidered.

IOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of pecification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization o waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

FFICIAL BUSINESS
ENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Officer in Charge
Navy Clothing & Textile Research Facility
(Code 50)
21 Strathmore Road
Natick, MA 01760

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:19Z
Check the source to verify that this is the current version before use.