ZZ-D-800B
April 11, 1973
SUPERSEDING
Int. Fed. Spec. ZZ-D-00800A(GSA-FSS)
September 1, 1966

FEDERAL SPECIFICATION

DUSTPAN (RUBBER)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE

1.1 This specification covers one type of rubber dustpan with the short handle open pattern, used for collecting light debris from the floor with the aid of a brush or broom.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

Federal Specifications:

PPP-B-636 - Box, Fiberboard.
PPP-B-640 - Boxes, Fiberboard, Corrugated, Triple-Wall.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Services Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies).

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc. Agent:

National Motor Freight Classification

FSC 7290

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American Trucking Association, Inc., Tariff Order Section, 1616 P Street, N.W. Washington, D.C. 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical Society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Material. The rubber used in the dust pans shall be either of natural rubber or synthetic rubber or a combination thereof.

3.2 Design and construction. The dustpans shall be so constructed that the front edge shall be in continuous contact with the floor when the pan is in use or when applied to the floor with slight downward pressure applied to the handle. The weight of the pan shall not be less than 1 lb. 1 oz. The design shall be such that when sweeping light debris from the floor into the dustpan it shall be convenient to handle by the user. The composition shall consist of a hard, natural or synthetic rubber or a mixture of natural and synthetic rubber molded to suitable shape for its intended use. Minimum dimensions and tolerances shall be in accordance with table I. Pans having a blade thickness of 3/32 inch shall have molded integral corrugations for reinforcement sufficient to retain its original shape when in use and to prevent permanent deformation when tested to the requirements of paragraph 4.4.

3.2.1 Handle. The handle shall be integrally molded with back edge of pan and designed to conveniently retain the debris in the pan when held by the operator. The handle shall have a means for hanging the dustpan on a wall surface when not in use.

TABLE I. Dimensions, minimum

Size	Front edge	Back edge	Side edge	Sides		
				Front height (1)	Back height	Handle length (2)
Inches	Inches	Inches	Inches	Inch	Inches	Inches
11-1/2	11-1/2	8-1/2	6-1/2	1/8	1-1/4	3-1/2

1/ Measured at a point not greater than 1/4 inch from the front edge.
2/ Measured from the top back edge parallel to handle.

3.3 Color. Unless otherwise specified (see 6.2) the dustpan shall be of the manufacturers standard color.

3.4 Identification marking. Dustpans shall be legibly identified with the name or trademark of the manufacturer.

3.5 Workmanship. The dustpans shall be free from blisters, sharp edges, fins or any other defects which might affect the function or serviceability of the unit.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specifications where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling. The sample size levels shall be in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.

4.2.1 Lot. Unless otherwise specified (see 6.2), a lot shall consist of all dustpans submitted for inspection at one time.

4.2.2 Sampling for dimensional and visual inspection of end item. Sampling of dustpans for these characteristics shall be in accordance with S-3.

4.2.3 Sampling for test. Samples for tests shall be in accordance with level S-2.

4.3 Inspection.

4.3.1 End item. The dustpans selected in 4.2.2 shall be examined in accordance with table II. The acceptable quality level's (AQL's) for defects listed in table II shall be 4.0 percent defective for major defects and 6.5 percent defective for minor defects.

TABLE II. Classification of defects

Defects	Major	Minor
Dimensions less than those specified in table I.	X	
Dustpan have blister, sharp edges, fins.		X
No provisions for hanging.		X
Not one-piece construction.		X
Front edge of blade not in continous contact with level surface.	X	
Corrugations not as specified.		X
Damage or defects affecting function or serviceability.	X	
Damage or defects not affecting function or serviceability.		X

4.3.2 Examination of preparation for delivery. An examination shall be made to determine that the packaging, packing and marking comply with the requirements in section 5 of this specification. Defects shall be scored in accordance with table III. For examination of interior packaging the sample unit shall be one shipping container fully prepared for delivery selected at random just prior to the closing operations. Sampling shall be in accordance with MIL-STD-105. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 with an acceptable quality level (AQL) of 4.0 defects per hundred units.

TABLE III. Classification of preparation for delivery defects

Examine	Defects
Marking	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Materials	Any component missing, or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling. Distortion of container.

4.4 Test.

4.4.1 Samples selected for test in accordance with 4.2.3 shall be subject to the test of 4.4.2 with an AQL of 2.5 percent defective.

4.4.2 Procedure. Dustpans shall be held by the handle with the bottom 18 ± 2 inches above a concrete slab and dropped from this height to the slab six (6) times. It shall be placed in a horizontal position on a level surface which is 30 inches above a concrete slab and pushed slowly over the edge of this surface so that the handle and pan proper go over the edge at approximately the same time. The sample shall be permitted to fall freely to the slab. Each of these tests shall be repeated six times. Evidence of permanent distortion, cracking or chipping of a pan after tests, conducted in accordance with the sampling plan of section 4, shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. The dustpans furnished in quanitites as specified (see 6.2) shall be packed in a close-fitting box conforming to PPP-B-636, V3c or PPP-B-640, class 2. Cushioning and blocking shall be provided. The box shall be closed and strapped in accordance with the appendix to the applicable specification.

5.1.2 Level B. Six (6) dustpans shall be packed in a close-fitting box conforming to PPP-B-636, class-domestic. Cushioning and blocking shall be provided. The box shall be closed in accordance with appendix to the box specification.

5.1.3 Level C. The dustpan shall be packed to insure carrier acceptance and safe delivery at destination in containers complying with the National Motor Freight Classification rules or the Uniform Freight Classification rules, as applicable.

5.2 Marking.

5.2.1 Civil agencies. In addition to markings required by the contract or order, the shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.2.2 Military activities. In addition to markings required by the contract or order, the shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use.

6.2 Ordering data. Purchasers should select the preferred options offered herein and include the following data in procurement documents:

(a) Title, number and date of this specification.
(b) Color if other than specified (see 3.3).
(c) Lot size if other than specified (see 4.2.1).
(d) Level of packing required (see 5.1).

User interest:

Army - GL

Preparing activity:

GSA-FSS

Civil Agency Coordinating Activity:

GSA-FSS

Orders for this publication are to be placed with the General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 10 cents each.

Source: https://assist.dla.mil -- Downloaded: 20260-26T12:28Z
Check the source to verify that this is the current version before use.