The documentation and process conversion measures necessary to comply with this revision shall be completed by 15 May 2024.

INCH-POUND

MIL-PRF-19500/102C
w/AMENDMENT 1
15 February 2024
SUPERSEDING
MIL-PRF-19500/102C
12 January 2020

PERFORMANCE SPECIFICATION SHEET

TRANSISTOR, NPN, SILICON, HIGH-POWER
* TYPES 2N1016, QUALITY LEVEL JAN

Inactive for new design after 7 June 1999.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for a high-power, NPN, silicon transistor. One level of product assurance (JAN) is provided for each device type.

1.2 Physical dimensions. See figure 1.

1.3 Maximum ratings. Unless otherwise specified T_A = +25°C.

Types	P_T T_C = +45°C (1)	$R_{\theta JC}$	V_{CBO}	V_{EBO}	V_{CEO}	I_C	T_J and T_{STG}
	W	°C/W	V dc	V dc	V dc	A dc	°C
2N1016B	150	0.7	100	25	100	7.5	
2N1016C	150	0.7	150	25	150	7.5	
2N1016D	150	0.7	200	25	200	7.5	65 to +150
* 2N1016B-2	150	0.7	100	20	100	7.5	
* 2N1016C-2	150	0.7	150	20	150	7.5	
* 2N1016D-2	150	0.7	200	20	200	7.5	

(1) Derate linearly 1.428 W/°C for T_C > +45°C. For temperature-power derating curves, see figure 2.

1.4 Primary electrical characteristics. Unless otherwise specified T_A = +25°C.

Limits	h_{FE} at V_{CE} = 4.0 V dc				$V_{CE(sat)}$
	h_{FE1} I_C = 2.0 A dc	h_{FE2} I_C = 5.0 A dc	h_{fe} I_C = 5 A dc	f_{hfe} I_C = 5 A dc	I_C = 5 A dc I_B = 1 A dc
				kHz	V dc
Min	20	10	5	20	
* Max	80	60			2.5


Comments, suggestions, or questions on this document should be addressed to DLA Land and Maritime, VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A
* DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

FSC 5961

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:11Z
Check the source to verify that this is the current version before use.

Symbol	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
A	1.24	1.28	31.5	32.51	
B		1.130		28.7	
C	.50	.56	12.70	14.22	
D	.55	.58	13.97	14.73	
E	.045	.055	1.14	1.40	4
F	.73	.80	18.54	20.32	
G	.07	.14	1.78	3.56	
H	.13	.19	3.30	4.83	
J	.014	.024	0.36	0.61	
K	.14	.17	3.56	4.32	
L	.10	.14	2.54	3.56	
M	.48	.52	12.19	13.21	
N	.35	.40	8.89	10.16	
P	.09	.11	2.29	2.79	4
R	.050	.060	1.27	1.52	3
S	.81	.85	20.57	21.59	
T					2
U	.14	.17	3.56	4.32	



NOTES:

1. Dimension are in inches. Millimeters are given for general information only.
2. The ASME thread reference is 5/16−24 UNF−2A.
3. Diameter of hole or slot out either side of terminal.
4. Two terminals. Terminal diameter uncontrolled above the seating plane.
5. Reference point for temperature measurement.
6. The collector shall be internally connected to the mounting base.

* FIGURE 1. Physical dimensions for TO-82 package.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:11Z
Check the source to verify that this is the current version before use.

1.5 Part or Identifying Number (PIN). The PIN is in accordance with MIL-PRF-19500, and as specified herein. See 6.4 for PIN construction example and 6.5 for a list of available PINs.

1.5.1 JAN certification mark and quality level. The only quality level designator for encapsulated devices that is applicable for this specification sheet is the base quality level "JAN" that uses no modifiers.

1.5.2 Device type. The designation system for the devices covered by this specification sheet is as follows.

1.5.2.1 First number and first letter symbols. The transistors of this specification sheet use the first number and letter symbols "2N".

1.5.2.2 Second number symbols. The second number symbols for the transistors covered by this specification sheet are "1016".

* 1.5.3 Suffix symbols. The suffix letters "B", "C" and "D" are incorporated in the PIN for this specification sheet to indicate an electrically modified version of the base type. The suffix symbol “-2” indicates a lower V_{EBO} maximum rating from the base type.

1.5.4 Lead finish. The lead finishes applicable to this specification sheet are listed on QPDSIS-19500.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATION

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 - Test Methods for Semiconductor Devices.

(Copies of these documents are available online at https://quicksearch.dla.mil.)

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:11Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturers list before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

3.4 Interface and physical dimensions. The interface and physical dimensions shall be as specified in MIL-PRF-19500 and on figure 1 herein.

3.4.1 Lead finish. Lead finish shall be solderable as defined in MIL-PRF-19500. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

3.5 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, and table I.

3.6 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table I herein.

3.7 Marking. Marking shall be in accordance with MIL-PRF-19500.

3.8 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Conformance inspection (see 4.3 and table I).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500, MIL-STD-750 and as specified herein.

4.2.2 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not request the performance of table II tests, the tests specified in table II herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

4.2.3 Thermal impedance. The thermal impedance measurements shall be performed in accordance with method 3131 of MIL-STD-750 using the guidelines in that method for determining I_M, I_H, t_H, t_{SW}, t_{MD} (and V_H where appropriate). See table II, group E, subgroup 4 herein.

4.3 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500, and as specified herein.

4.3.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-PRF-19500, and table I herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:11Z
Check the source to verify that this is the current version before use.

4.3.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VIB (JAN) of MIL-PRF-19500, and as follows.

Subgroup	Method	Condition
B3	1027	V_{CB} = 30 V dc, I_C = 2.39 A dc.

4.3.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VII of MIL-PRF-19500, and as follows.

Subgroup	Method	Condition
C2	2036	Test condition A; weight = 5 pounds ±1 ounce (2.26 kg ±28.3 g), application time = 15 s Test condition D2; torque = 40 inch-pound (4.5 N-m); application time = 15 s. Test condition D1; torque = 5 inch-ounce (0.035 N-m); application time = 15 s; tubulated leads only.
C5	3151	$R_{\theta JC}$ (see 1.3).
C6	1026	1,000 hours, V_{CB} = 30 V dc, power and ambient temperature shall be applied to the device to achieve T_J = +150°C minimum, and minimum power dissipation of 75 percent of max rated P_T (see 1.3 herein); n = 45, c = 0. The sample size may be increased and the test time decreased as long as the devices are stressed for a total of 45,000 device hours minimum, and the actual time of test is at least 340 hours.

4.4.5 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-IX of MIL-PRF-19500 and as specified in table II herein.

4.5 Method of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:11Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

	Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
		Method	Conditions		Min	Max	
	Subgroup 1						
	Visual and mechanical examination	2071					
	Subgroup 2						
	Thermal impedance 2/	3131	See 4.2.3	$Z_{\theta JX}$			°C/W
	Breakdown voltage, collector to emitter	3011	Bias condition D, I_C = 200 mA dc	$V_{(BR)CEO}$			
	2N1016B				100		V dc
	2N1016C				150		V dc
	2N1016D				200		V dc
	Collector to emitter cutoff current	3041	Bias condition A, V_{EB} = −1.5 V dc	I_{CEX1}			
	2N1016B		V_{CE} = 100 V dc			1.0	mA dc
	2N1016C		V_{CE} = 150 V dc			1.0	mA dc
	2N1016D		V_{CE} = 200 V dc			1.0	mA dc
	Collector to base cutoff current	3036	Bias condition D, V_{EB} = 1.5 V dc	I_{CBO}			
	2N1016B		V_{CB} = 100 V dc			1.0	mA dc
	2N1016C		V_{CB} = 150 V dc			1.0	mA dc
	2N1016D		V_{CB} = 200 V dc			1.0	mA dc
	Emitter to base cutoff current	3061	Bias condition D	I_{EBO1}			
*	2N1016B, 2N1016C, 2N1016D		V_{EB} = 25 V dc			1.0	mA dc
*	2N1016B-2, 2N1016C-2, 2N1016D-2		V_{EB} = 20 V dc			1.0	mA dc
	Collector to emitter voltage (saturated)	3071	I_C = 5 A dc, I_B = 1 A dc	$V_{CE(sat)1}$		2.5	V dc
	Base emitter voltage (saturated)	3066	Test condition A, I_C = 5 A dc, I_B = 1 A dc	$V_{BE(sat)1}$		4.0	V dc
	Forward-current transfer ratio	3076	V_{CE} = 4 V dc, I_C = 2 A dc	h_{FE1}	20	80	
*	Forward-current transfer ratio	3076	V_{CE} = 4 V dc, I_C = 5 A dc	h_{FE2}	10	60	
*	Forward-current transfer ratio	3076	V_{CE} = 4 V dc, I_C = 7.5 A dc	h_{FE3}	6	45	

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:11Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

	Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
		Method	Conditions		Min	Max	
	Subgroup 2 – continued						
*	Small-signal short- circuit forward-current transfer ratio	3206	V_{CE} = 4 V dc, I_C = 5 A dc f = 1 kHz	h_{fe}	5		
	Small-signal short- circuit forward-current transfer ratio cutoff frequency	3301	V_{CE} = 4 V dc, I_C = 5 A dc	f_{hfe}	20		kHz
	Subgroup 3						
	High temperature operation		T_C = +150°C				
	Emitter to base cutoff current	3061	Bias condition D	I_{EBO2}			
*	2N1016B, 2N1016C, 2N1016D		V_{EB} = 25 V dc			10	mA dc
*	2N1016B-2, 2N1016C-2, 2N1016D-2		V_{EB} = 20 V dc			10	mA dc
	Collector to emitter cutoff current	3041	Bias condition A, V_{EB} = −1.5 V dc	I_{CEX2}			
	2N1016B		V_{CE} = 100 V dc			10	mA dc
	2N1016C		V_{CE} = 150 V dc			10	mA dc
	2N1016D		V_{CE} = 200 V dc			10	mA dc
	Low-temperature operation		T_C = −55°C				
	Forward-current transfer ratio	3076	V_{CE} = 4 V dc, I_C = 5 A dc	h_{FE4}	10	35	
	Subgroup 4						
	Pulse response		See figure 3. I_C = 5 A dc, V_{EB} = 6 V dc, V_{CE} = 12 V dc; I_{B1} and I_{B2} = 1.5 A dc	$t_d + t_r$		10	µs
	Pulse response		See figure 3. I_C = 5 A dc, V_{EB} = 6 V dc, V_{CE} = 12 V dc; I_{B1} and I_{B2} = 1.5 A dc	$t_s + t_f$		15	µs
	Subgroups 5, 6, and 7						
	Not applicable						


1/ For sampling plan, see MIL-PRF-19500.
2/ This test required for the following end-point measurements only:
Group B, subgroups 2 and 3 (JAN).
Group C, subgroup 2 and 6.
Group E, subgroup 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:11Z
Check the source to verify that this is the current version before use.

TABLE II. Group E inspection (all quality levels) - for qualification only.

Inspection	MIL-STD-750		Sample plan
	Method	Conditions	
Subgroup 1			45 devices, c = 0
Temperature cycling (air to air)	1051	Test condition C, 500 cycles.	
Hermetic seal	1071	Fine and gross leak	
Electrical measurements		See table I, subgroup 2 herein.	
Subgroup 2			45 devices, c = 0
Blocking life	1048	T_A = +125°C, t = 1,000 hours +65, −0 hours; V_{CB} = 80 percent of rated voltage.	
Electrical measurements		See table I, subgroup 2 herein.	
Subgroup 4			Sample size, N/A
Thermal impedance curves	3131	See MIL-PRF-19500, table E-IX, group E, subgroup 4.	
Subgroup 5			
Not applicable			
Subgroup 8			45 devices, c = 0
Reverse stability	1033	Condition B.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:11Z
Check the source to verify that this is the current version before use.



NOTES:

1. Top curve is thermal runaway loci and cannot be used as a derate design curve since it exceeds the maximum ratings for this part. Operating under this curve using these mounting conditions assures the device will not have a thermal runaway. This is the true inverse of the worst case thermal resistance value extrapolated out to the thermal runaway point.
2. Derate design curve constrained by the maximum junction temperature ($T_J \leq +150°C$) and power rating specified. (See 1.3 herein.)
3. Derate design curves chosen at $T_J \leq +125°C$, and +110°C to show power rating where most users want to limit T_J in their application.

FIGURE 2. Derating for all devices.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:11Z
Check the source to verify that this is the current version before use.




FIGURE 3. Pulse response test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:11Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.


b. Packaging requirements (see 5.1).

c. Lead finish (see 3.4.1).

d. The complete PIN, see 1.5 and 6.4.

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML 19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from DLA Land and Maritime, ATTN: VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil. An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at https://qpldocs.dla.mil.

6.4 PIN construction example. The PINs for encapsulated devices and are constructed using the following forms.



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:11Z
Check the source to verify that this is the current version before use.

* 6.5 List of PINs. The following is a list of possible PINs available for encapsulated devices and covered by this specification sheet.

Quality level "JAN"	JAN2N1016B	JAN2N1016C	JAN2N1016D
	JAN2N1016B-2	JAN2N1016C-2	JAN2N1016D-2

* 6.6 Amendment notations. The margins of this specification are marked with asterisks to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army − CR
Navy –SH
Air Force − 85
NASA − NA
DLA − CC

Review activities:
Army − AR, MI
Navy − AS, MC
Air Force − 19

Preparing activity:
DLA − CC

(Project 5961-2024-011)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:11Z
Check the source to verify that this is the current version before use.