MIL-S-19500/91(SigC)
Amendment 1
1 July 1960

MILITARY SPECIFICATION

SEMICONDUCTOR DEVICE
DIODE, SILICON, POWER RECTIFIER
TYPE 1N2153

This Amendment forms a part of Military Specification MIL-S-19500/91(SigC), 2 Nov 59

Page 1, paragraph 1.1 table, (i(surge)) column: Delete "50" pertaining to Absolute Maximum value and substitute "---"; delete "---" pertaining to Minimum value and substitute "50".

Page 2, paragraph 3.6: In line 2, delete "I, II, and III" and substitute "I and II".

Page 2, paragraph 4.3: In line 2, delete "I, II, and III" and substitute "I and II".

Page 3, Table I, Subgroup 2, Surge current: Delete, including all columnar data associated with this test.

Page 4, Subgroup 2, End Points, Forward voltage: In Min column, insert "---"; in Max column, insert "1.5"; in Unit column, insert "Vdc".

Page 5, Subgroup 4, End points, Forward voltage: In Max column, delete "75" and substitute "1.5"; in Unit column, delete "uAdc and substitute "Vdc".

Page 5, Subgroup 5: As the first listed test in the subgroup, effect the following insertions: in Ref Par column, insert "60.1.15"; in Test column, insert "Surge current"; in Conditions column, insert "I_F = 5Adc" and "Vac = 420" and "f = 60 cps"; in Sym column, insert "i (surge)"; in Min column, insert "50"; in Max column, insert "---"; in Unit column, insert "Adc".

Page 6, Table III: Delete the number and title of the table and substitute "Table II. Group B inspection-(Continued)."

Page 8, Note 7(c): In last line, delete "III" and substitute "II".

Page 8, Note 8: In first line, delete "on table III" and substitute "in table II".

FSC 5960

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:10Z
Check the source to verify that this is the current version before use.