INCH POUND
MIL-PRF-3098/47H
27 August 1997
SUPERSEDING
MIL-C-3098/47G
9 November 1983

PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR69A/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-3098.

Pertinent characteristics: 2.9 MHz to 25 MHz; fundamental; noncontrolled; antiresonance.



Inches	mm	Inches	mm
.001	.03	.183	4.65
.002	.05	.192	4.88
.008	.20	.402	10.21
.017	.43	.435	11.05
.150	3.81	.500	12.70
		.530	13.46

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with MIL-PRF-3098.

FIGURE 1. Crystal unit - CR69A/U.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:31Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions, marking, and configuration: See figure 1.

Frequency range: 2.9 MHz to 25 MHz, inclusive.

Capacitance, shunt: 7 pF, maximum.

Frequency tolerances:

Primary operating temperature range: ±20 parts per million (ppm).

Secondary operating temperature range: ±30 ppm.

Equivalent resistance: See table I.

Mode of oscillation: Fundamental.

Antiresonance, load capacitance: 30.0 pF ±0.5 pF.

Operating temperature ranges (noncontrolled):

Primary: -40°C to +90°C, inclusive.

Secondary: -55°C to -40°C, and +90°C to +105°C, inclusive.

Rated drive level: 1.0 mW, maximum.

Shock:

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Vibration: Method 204, MIL-STD-202, test condition A.

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Thermal shock:

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Aging:

Frequency change permitted: ±5 ppm.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:31Z
Check the source to verify that this is the current version before use.

TABLE I. Equivalent resistance.

Frequency range, inclusive	Maximum resistance
MHz	Ohms
2.90 to 3.75	180
3.75+ to 4.75	120
4.75+ to 6.00	75
6.00+ to 7.00	50
7.00+ to 10.00	30
10.00+ to 25.00	25

Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - CR
Navy - EC
Air force - 85

Review activities:
Army - AR, MI, SM
Navy - AS, CG, MC, OS, SH
Air Force - 11, 17, 19, 99
DLA - CC

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5955-0697-27)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:31Z
Check the source to verify that this is the current version before use.