INCH-POUND
MIL-PRF-3098/51J
13 April 2010
SUPERSEDING
MIL-PRF-3098/51H
9 December 2004

PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR74/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-3098.

Pertinent characteristics: 45 MHz to 125 MHz; fifth mechanical overtone; controlled; series resonance.




FIGURE 1. Crystal unit - CR74/U.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:32Z
Check the source to verify that this is the current version before use.

Ltr	Inches		mm	
	Min	Max	Min	Max
A	---	.183	---	4.65
B	---	.435	---	11.05
C	---	.402	---	10.21
D	---	.530	---	13.46
E	.500	---	12.70	---
F	.016	.019	0.41	0.48
G	---	.150	---	3.81
H	.184	.200	4.67	5.08

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with MIL-PRF-3098.

FIGURE 1. Crystal unit - CR74/U - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:32Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions, marking, and configuration: See figure 1.

Frequency range: 45 MHz to 125 MHz, inclusive.

Capacitance, shunt: 4.5 pF ±0.5 pF.

Frequency tolerance:

Operating temperature range: ±10 ppm.

Frequency stability: ±2.5 ppm.

Equivalent resistance: 20 ohms, minimum; 50 ohms, maximum.

Mode of oscillation: Fifth mechanical overtone.

Temperature ranges:

Operating (controlled): +80°C to +90°C, inclusive.

Operable: -55°C to +80°C, inclusive.

Reference temperature: +85°C ±1°C.

Rated drive level: 1.0 mW, maximum.

Resonance: Series.

Unwanted mode: Twice main mode.

Shock (specified pulse):

Frequency change permitted: ±3 ppm.

Equivalent resistance change permitted: ±15 percent.

Vibration high frequency: Method 204 of MIL-STD-202, test condition A.

Frequency change permitted: ±3 ppm.

Equivalent resistance change permitted: ±15 percent.

Thermal shock:

Frequency change permitted: ±3 ppm.

Equivalent resistance change permitted: ±15 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:32Z
Check the source to verify that this is the current version before use.

Aging:

Frequency change permitted: ±3 ppm.

Part or Identifying Number (PIN): CR74/U (followed by specified frequency), see 1.2 of MIL-PRF-3098.

Reference documents. In addition to MIL-PRF-3098, this document references the following:

MIL-STD-202

The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - EC
Air Force - 99
DLA - CC

Review activities:
Army - AR, MI, SM
Navy - AS, CG, MC, OS, SH
Air Force - 19, 84

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5955-2009-060)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:32Z
Check the source to verify that this is the current version before use.