MIL-C-3098/54C
23 June 1975
SUPERSEDING
MIL-C-3098/54B
29 May 1969


MILITARY SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR-73/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the crystal unit described herein shall consist of this document and the latest issue of Specification MIL-C-3098.

Pertinent characteristics: 17 to 61 MHz; third overtone; noncontrolled; series.



INCHES	MM	INCHES	MM
.002	.05	.040	1.02
.003	.08	.175	4.45
.008	.20	.183	4.65
.010	.25	.192	4.88
.015	.38	.238	6.05
.025	.64	.435	11.05
.030	.76	.530	13.46

NOTES:
1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. The type designation, frequency, and code designating characters shall be not less than .038 (.97 mm) in height and not less than .027 (.69 mm) in width.
4. The pin undercut may be omitted.

Ⓒ denotes change

FSC 5955

Source: https://assist.dla.mil -- Downloaded: 202640-16T16:33Z
Check the source to verify that this is the current version before use.

TABLE I. Requirements.

Requirement	Specified value or condition
Holder	HC-29/U (MIL-H-10056/16)
Dimensions, marking, and configuration	See figure
Frequency range	17 to 61 MHz, inclusive
Frequency tolerance	±30 PPM
Capacitance, shunt	17.0 to 30.0 MHz - 3.5 ±0.5 pF 30.0+ to 61.0 MHz - 4.0 ±0.5 pF
Equivalent resistance	17.0 to 30.0 MHz - 40 ohms, max 10 ohms, min 30.0+ to 61.0 MHz - 30 ohms, max 5 ohms, min
Mode of oscillation	Third mechanical overtone
Unwanted modes	Method II, twice main mode resistance
Operating temperature range	-55° to +105° C, inclusive
Government reference standard test set	TS-683/TSM
Drive level, rated	17.0 to 30.0 - 2.0 ±0.4 mW
Shock (specified pulse):	
Frequency change permitted	±3 PPM
Equivalent resistance change permitted	±15 percent
Vibration: 1/	
Frequency change permitted	±3 PPM
Equivalent resistance change permitted	±15 percent
Temperature run:	
Frequency change permitted	±3 PPM
Equivalent resistance change permitted	±15 percent
Aging:	
Frequency change permitted	3 PPM

1/ Method 204 of MIL-STD-202, test condition A.

NOTE: NATO guidance type NXT49.

Custodians:
Army - EL
Navy - EC
Air Force - 84

Review activities:
Army - EL, MI, MU, SG, SM
Navy - EC
Air Force - 11, 85
DSA - ES

User activities:
Army -
Navy - AS, MC, SH
Air Force - 17, 19

Preparing activity:
Army - EL

Agent:
DSA - ES

(Project 5955-0408-28)

Source: https://assist.dla.mil -- Downloaded: 202610-16T16:33Z
Check the source to verify that this is the current version before use.