INCH POUND
MIL-PRF-3098/54E
27 August 1997
SUPERSEDING
MIL-C-3098/54D
10 April 1995

PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR73/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-3098.

Pertinent characteristics: 17 MHz to 61 MHz; third mechanical overtone; noncontrolled; series resonance.

Inches	mm
.002	.05
.003	.08
.008	.20
.010	.25
.015	.38
.025	.64
.030	.76
.040	1.02
.175	4.45
.183	4.65
.192	4.88
.238	6.05
.435	11.05
.530	13.34



NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with MIL-PRF-3098.
4. The pin undercut may be omitted.

FIGURE 1. Crystal unit - CR73/U.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:33Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions, marking, and configuration: See figure 1.

Frequency range: 17.0 MHz to 61.0 MHz, inclusive.

Frequency tolerances: ±30 parts per million (ppm).

Rated drive level: 1.0 mW, maximum.

Resonance: Series.

Equivalent resistance: 17 MHz to 30.0 MHz - 40 ohms, maximum and 10 ohms, minimum.
30.0+ MHz to 61 MHz - 30 ohms, maximum and 5 ohms, minimum.

Unwanted modes: Method II, twice main mode resistance.

Mode of oscillation: Third mechanical overtone.

Operating temperature ranges: -55°C to +105°C, inclusive.

Capacitance, shunt: 17 MHz to 30 MHz - 3.5 pF ±0.5 pF.
30.0+ MHz to 61.0 MHz - 4.0 pF ±0.5 pF.

Shock (specified pulse):

Frequency change permitted: ±3 ppm.

Equivalent resistance change permitted: ±15 percent.

Thermal shock:

Frequency change permitted: ±3 ppm.

Equivalent resistance change permitted: ±15 percent.

Vibration: Method 204 of MIL-STD-202, test condition A.

Frequency change permitted: ±3 ppm.

Equivalent resistance change permitted: ±15 percent.

Aging:

Frequency change permitted: ±3 ppm.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:33Z
Check the source to verify that this is the current version before use.

Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - CR
Navy - EC
Air force - 85

Review activities:
Army - AR, MI
Navy - AS, MC, SH
Air Force - 17, 19

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5955-0697-30)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:33Z
Check the source to verify that this is the current version before use.