MIL-D-37206
Amendment-3
20 November 1975

SUPERSEDING
Amendment-2
21 July 1975

MILITARY SPECIFICATION

DRESSES, WOMAN'S

COTTON-POLYESTER, STATIC RESISTANT, PLEATED FRONT

This amendment forms part of Military Specification MIL-D-37206, dated 30 October 1974, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 3

3.1.1.2 Pockets, yokes, half belts, tie cords, facings, flap, tunnel and snap fastener reinforcing patch, lines 1 and 2: Delete "yokes".

Page 4

3.2 Design. line 1: Delete "yoke" and substitute "facing".

3.3.1 Cutting, line 9: After "facing" add "except for the facing in the neck area".

Page 7

Table II (Continued):

a. Delete "(Cont'd)' after Table II.

b. Operation 3a:

1. Line 2: Delete "for".
2. Line 3: Delete entirely.

c. Operation 3b, line 2: Delete and substitute "6 ± 1/4 inches wide and 6 ±.

FSC 6532

Source: https://assist.dla.mil -- Downloaded: 20261 0-21T10:11Z
Check the source to verify that this is the current version before use.

Page 8

Table II (Cont'd):

a. Operation 5:

1. Title: Delete "yoke" and substitute "neck facing".

2. Operation 5a, lines 1, 3, 5 and 6: Delete "yoke" and substitute "front neck facing".

3. Operation 5c, line 2: Delete "yoke" and substitute "front neck facing".

b. Operation 6a, line 8: Delete entirely and substitute "be governed by the requirements of operation 8c".

Page 9

Table II (Cont'd):

a. Operation 8c,line 9: After "edge" add "The tie cord shall extend beyond each tunnel opening a minimum of 18 inches on each side.

b. Operation 9:

1. Title, line 1: Delete "yokes" and substitute "neck facings".

2. Operation 9a, line 1: Delete "yokes" and substitute "back neck facings".

Page 10

Table II (Cont'd):

a. Operation 9 continued:

1. Operation 9b:

(a) Line 2: Delete "yokes" and substitute "back neck facings".

(b) Lines 2 and 3: Delete "the amount specified by the patterns and substitute "approximately 3/8 inch".

2. Operation 9c, line 1: Delete "yokes" and substitute "facings".

Source: https://assist.dla.mil -- Downloaded: 20261O-21T10:11Z
Check the source to verify that this is the current version before use.

b. Operation 10b:

1. Line 1: After "side" add "(the opposite side from where the stud portion of the snap fasteners are to be located)".

2. Line 7: Delete "yoke" and substitute "facing".

c. Operation 11a:

1. Line 7: Delete "yoke" and substitute "facing".

2. Line 8: After "back" add "The width of the hem shall be 1/2 $\pm$ 1/16 inch".

Page 11

Table II (Cont'd), Operation 12a, line 7: Delete "yoke" and substitute "facing".

Page 12

Table II (Cont'd):

a. Operation 13a, line 3: Delete "yokes" and substitute "facings".

b. Operation 14a:

1. Line 2: Delete entirely.

2. Line 3: Delete "patterns".

Page 13

Table II (Cont'd):

a. Operation 16a, line 5: Delete "yokes" and substitute "facings".

b. Operation 18a and b: Delete entirely and substitute the following:

"18 Attach the snap fasteners.

a. Attach the first stud on the left back flap as indicated by the patterns (approximately in the center of the opening). After facing and binding of the neck area of the left back flap, attach the second stud in line with the first stud just below the neck binding. The stud may touch or slightly

Source: https://assist.dla.mil -- Downloaded: 20260-21T10:11Z
Check the source to verify that this is the current version before use.

overlap the neck binding. The third stud shall be approximately centered and located in the neck flap facing and flap side hem approximately 2-1/4 inches from the second stud (measured center to center). The snap fastener patch shall also be caught between the first stud and eyelet located approximately in the center of the flap (see operation 12b).

b. Attach the three sockets with the pronged ring on the right side of the back opening, two approximately centered in the hemmed portion, in such a manner that they shall align and mate with the three studs on the left back flap without causing any distortion, twisting or puckering of the backs (see Figure 1)".

Page 15

Table III: Delete entirely and substitute the following:

TABLE III
DRESS DIMENSION IN INCHES

LOCATION	SIZE 26-28	30-32	34-36	38-40	42-44	46-48	TOLERANCE
BUST	18	20	22	24	26	28	± 1/2
WAIST	15	17	19	21	23	25	± 1/2
HIPS	20	22	24	26	28	30	± 1/2
LENGTH	40-1/2	41	42	43	43	43	± 1/2
SWEEP	48	52	56	60-1/2	64-1/2	68-1/2	± 1

3.5.1 Identification, line 3: After "information" add "and if desired the washing information specified in 3.5.2".

Page 31

4.3.5 Procedure for measuring, lines 6 and 7: Delete entirely and substitute the following:

"a. The bust dimension shall be taken approximately 2 inches below the bottom of the sleeve opening from side fold to side fold".

Page 34

6.4 Patterns:

a. Line 6: Delete "yokes" and substitute "neck facings".

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:11Z
Check the source to verify that this is the current version before use.

b. Lines 11, 12, 13 and 14: Delete "yoke" and substitute "neck facing".

c. Lines 15 and 16: Delete entirely.

Custodians:
Army - MD
Navy - MS
Air Force - 03

Preparing activity:
Defense Supply Agency - DM

Project No. 6532-1110

is

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:11Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:11Z
Check the source to verify that this is the current version before use.