MILITARY SPECIFICATION

HEMORRHOIDAL SUPPOSITORIES

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers Hemorrhoidal Suppositories (See 6.2).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

PPP-B-566	Box, Folding, Paperboard.
PPP-B-585	Box, Wood, Wirebound.
PPP-B-601	Box, Wood, Cleated-Plywood.
PPP-B-621	Box, Wood, Nailed and Lock-Corner.
PPP-B-636	Box, Fiberboard.
PPP-B-676	Box, Setup.
PPP-C-186	Containers, Packaging and Packing for Drugs, Chemicals, and Pharmaceuticals. (See 6.3)

Military

MIL-L-10547	Liners, Case, and Sheet, Overwrap; Water-Vaporproof or Waterproof, Flexible.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:12Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposals shall apply.

U.S. DEPARTMENT OF HEALTH, EDUCATION, AND WELFARE,
FOOD AND DRUG ADMINISTRATION

Federal Food, Drug, and Cosmetic Act and
Regulations Promulgated Thereunder.

(Application for copies should be addressed to the Food and Drug Administration, Washington, DC 20204.)

U. S. PHARMACOPEIAL CONVENTION, INC.

The United States Pharmacopeia.

(Application for copies should be addressed to the Mack Publishing Company, Easton, PA 18042.)

National Formulary.

(Application for copies should be addressed to the Mack Publishing Company, Easton, PA 18042.)

3. REQUIREMENTS

3.1 Material. Shall be bullet-shaped, emollient, rectal suppositories which melt at body temperature.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:12Z
Check the source to verify that this is the current version before use.

3.1.1 Formula. Each 2.71 Gram suppository shall be formulated to contain the following:

Bismuth Subgallate, N.F.	2.25%
Bismuth Resorcin Compound	1.75%
Nicaraguan Balsam	3.00%
Zinc Oxide, U.S.P.	11.01%
Boric Acid, N.F.	5.00%
Suppository Base of Synthetic Cocoa Butter	50.46%
Theobroma Oil, U.S.P.	6.30%
White Wax, U.S.P.	6.00%
Bismuth Subiodide	0.019%
Calcium Phosphate Dibasic, N.F., Hydrous	13.00%
Lithium Phosphate Tribasic	0.17%
F.D. & C. Blue No. 2 Lake, B3061 in Hydrogenated Vegetable Oil	0.80%
Amaranth, U.S.P. in Hydrogenated Vegetable Oil	0.24%

3.1.1.1 Batch formulation sheet. The batch formulation sheet (raw material ingredient weighing specifications) for each lot shall be reviewed to determine conformance with the formulation specified in 3.1.1 of this document.

3.1.2 Uniformity of mixture. Uniformity of mixture shall show little or no unmixed color or uncolored areas when cut longitudinally.

3.1.3 Softening point. Softening point shall be 31° to 36° C., when tested as specified in 4.5.1.

3.1.4 Ignition residue. Ignition residue shall be 24% to 26%, when tested as specified in 4.5.2.

3.1.5 Warming test. The suppositories shall retain shape after warming at 37° C. for 1 hour. The degree of flattening may not exceed 9 mm when measured across the diameter of the suppository. The test shall be conducted as specified in 4.5.3.

3.1.6 Weight variation. Ten (10) suppositories, selected at random, shall weigh not less than 26.4 Grams and not more 28.6 Grams.

3.1.7 Boric acid content. The boric acid content shall be not less than 122 mg and not more than 149 mg per suppository, when assayed as specified in 4.5.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:12Z
Check the source to verify that this is the current version before use.

3.1.8 Zinc oxide content. The zinc oxide content shall be not less than 268 mg and not more than 328 mg per suppository, when assayed as specified in 4.5.5.

3.1.9 Total bismuth salts (as Bi_2O_3) content. The total bismuth salt content (as Bi_2O_3) shall be not less than 52 mg and not more than 62 mg per suppository, when assayed as specified in 4.5.6.

3.1.10 Accelerated aging test. The suppositories shall show no mottling (defined as rainbow effect, streaking, and color separation), no change in color, or crystallization on the surface, when subjected to the test specified in 4.5.7.

3.2 Ingredients.

3.2.1 Bismuth Subgallate. The Bismuth Subgallate used in the manufacture of the suppositories shall be in accordance with the tests, standards, and requirements of the N.F. XI, which was official from October 1, 1960, to August 31, 1965.

3.2.2 Bismuth Resorcin Compound. The Bismuth Resorcin Compound shall consist of equal quantities of Bismuth Oxide, Anhydrous, Dense, and Resorcinol, U.S.P., thoroughly mixed and milled to a fine powder, and shall comply with the following:

3.2.2.1 Bismuth Resorcin Compound.

3.2.2.1.1 Identification. Shall yield qualitative reactions for bismuth and resorcin as described in 4.5.8.1.

3.2.2.1.2 Mesh. 98% minimum of a 25 gram sample shall pass through a No. 80 sieve.

3.2.2.1.3 Microscopic Examination (100X). Shall show uniformly mixed, very fine, broken crystals with no sharp edges when a thin dry mount is examined.

3.2.2.1.4 Assay. Shall assay 47.5 to 52.5 percent Bismuth Oxide when assayed as specified in 4.5.8.2.

3.2.2.2 Bismuth Oxide, Anhydrous, Dense. The Bismuth Oxide, Anhydrous, Dense, used in the Bismuth Resorcin Compound shall be in accordance with the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:12Z
Check the source to verify that this is the current version before use.

3.2.2.2.1 Identification. Add a few ml of concentrated HNO_3 to about 0.5 Gram of the Bismuth Oxide. Dilute the solution with water. A white precipitate colored brown by hydrogen sulfide shows the presence of bismuth.

3.2.2.2.2 Solution. 0.5 Gram of the powder shall be completely soluble in a few ml of concentrated HNO_3.

3.2.2.2.3 Lead. Shall conform to the U.S.P. test as applied to Bismuth Subcarbonate.

3.2.2.2.4 Arsenic. Shall conform to the U.S.P. test as applied to Bismuth Subcarbonate.

3.2.2.2.5 Assay. Shall be not less than 98% Bismuth Oxide when assayed as specified in 4.5.8.3.

3.2.3 Nicaraguan Balsam. The Nicaraguan Balsam shall consist of Peruvian Balsam, N.F., and Benzyl Benzoate, N.F., so that the final mixture shall be in accordance with the following:

3.2.3.1 Specific gravity. Shall be 1.11 to 1.16 when determined in a pycnometer at 25° C.

3.2.3.2 Cinnamein saponification value. Shall be 225 to 275, when determined using the N.F. method as described under Peruvian Balsam.

3.2.4 Other ingredients. All other ingredients entering into the finished suppository shall be USP or NF quality or, if not included in either of these compendia, the ingredients shall be of the highest pharmaceutical grade.

3.3 Delivery. Not more than 4 months shall have elapsed from the date of manufacture of the suppositories, to the date of delivery to the Government.

3.4 Workmanship. The material and its containers shall be free from defects which detract from their appearance or may impair their serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Supplier responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspection set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:12Z
Check the source to verify that this is the current version before use.

4.1.1 Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government, upon the Government's request, at any time, or from time to time, during the performance of the contract and, (i) as to any expiration dated item, for the expiration dating period (potency period) specified by the contractor for such item, or such longer period as may be required by regulation of any federal agency; or (ii) as to non-dated items, for not less than 3 years after delivery of the items to the Government.

4.1.2 No company supplying any ingredient(s) to the contractor will be considered an acceptable facility for the performance of any inspection requirements specified herein.

4.2 Lot. For purposes of this specification, a lot, batch or control is that single, uniform, and homogeneous quantity of such suppositories from one formulation, subjected to the same compounding and manufacturing operation, and filled into final containers.

4.3 Sampling. Sampling shall be conducted in accordance with the procedures set forth in MIL-STD-105 with an inspection level of S-2 and an acceptable quality level (AQL) of 1.0 percent defective for major defects.

4.3.1 For raw material and end item testing. Noncompliance with any of the following is cause for rejection.

Table I. For Raw Material and End Item Testing

Characteristic	Requirement Paragraph	Inspection level*	Minimum Sample
Uniformity of mixture	3.1.2	S-2	5
Softening point	3.1.3	S-2	5
Ignition residue	3.1.4	S-2	5
Warming test	3.1.5	S-2	5
Weight variation	3.1.6	S-2	10
Boric acid content	3.1.7	S-2	10
Zinc oxide content	3.1.8	S-2	5
Total bismuth salts content	3.1.9	S-2	5
Accelerated aging test	3.1.10	S-2	12
Ingredients**			
Bismuth Subgallate	3.2.1		
Bismuth Resorcin Compound	3.2.2.1		
Bismuth Oxide, Anhydrous Dense	3.2.2.2.		
Nicaraguan Balsam	3.2.3		

* Where possible, the same sample shall be used for two or more tests.
** Sufficient quantities of each of the raw materials shall be selected from each lot to perform tests indicated in applicable test methods. Failure of any sample to comply with test requirements shall be cause for rejection of the lot represented.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:12Z
Check the source to verify that this is the current version before use.

4.4 Examination. The Hemorrhoidal Suppositories shall be examined to determine compliance with all requirements of this specification. Nonconformance will be permitted to the extent indicated in 4.3 and 4.3.1.

4.4.1 Classification of defects. Examination will be conducted in accordance with the following classification of defects:

Table II. Classification of Defects

Major*	
101	Suppository not free of foreign matter.
102	Suppository not bullet shaped.
103	Suppository not homogeneous (when surface is viewed and the suppository is subsequently cut longitudinally.)
104	Suppository not free of breaks, pits or other irregularities in appearance.

* Inspection is not restricted to the classified possible defects listed above.

4.5 Tests.

4.5.1 Softening point.

Refrigerate sample at least 24 hours and run test immediately on removal from cooling unit.

Apparatus.

Brass plate having a thickness of 0.11 inch; with four (4) holes each having a diameter of 0.375 inch. Steel balls 0.250 inch diameter; weight 1.026 to 1.030 Gram.

Water bath. Approximately 600 ml of water in a 1000 ml beaker.

Thermometer. ASTM 36C, 45 mm, 1 mm, calibrated from -2° C. to 68° C. in 0.2° C. intervals.

Procedure.

Insert a suppository into each hole of the apparatus and cut off excess material so that the suppository mass just fills the hole. Make certain the entire diameter of each hole in the plate is filled with material. Place steel ball on the center of the mass filling the hole and suspend in the water bath at room temperature; placing the plate approximately midway in the water. The top of the bulb of the thermometer shall be near the top of the plate. Mechanically agitate or stir the water bath while heating. Gradually raise the temperature (temperature rise should be at 2° C. per minute at softening point) of the water bath until each ball drops through each hole in the plate. Record the temperature for each drop. These temperatures are recorded as the softening point. Each temperature reading shall be within the specified range.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:12Z
Check the source to verify that this is the current version before use.

4.5.2 Ignition residue.

Weigh, accurately, about 0.7 Gram sample (about 1/4 suppository), and cautiously ignite in a porcelain crucible until all carbon is burned off. Cool, add a few drops of HNO_3, evaporate to dryness on the steam bath, and re-ignite to constant weight. Cool in a desiccator and weigh.

4.5.3 Warming test.

Place 2 suppositories horizontally on the bottom of a 150-ml beaker or equivalent and warm at 37.5° C. for 1 hour. Examine the suppositories visually after 1 hour and measure the degree of flattening as observed through the bottom of the beaker with a mm ruler.

4.5.4 Boric acid.

Place 6 suppositories into a 250-ml Erlenmeyer flask. Add 100 ml of 3:1 glycerin-alcohol solution (SD 30 alcohol may be used) previously neutralized to phenolphthalein T.S. Add a magnetic stirrer bar, cover with a watch glass and heat on a gyrotherm or equivalent heating apparatus to boiling. Add about 5 mg of phenolphthalein powder and titrate with 1N NaOH to a pink endpoint. Then add an additional 50 ml of 3:1 glycerin-alcohol solution, heat to boiling and continue titration with 1N NaOH to a pink endpoint.

Calculation:

$$\frac{B \times 61.84}{6} = \text{mg boric acid per suppository.}$$

Where B = total ml of 1N NaOH used.

4.5.5 Zinc oxide content.

Place 3 suppositories into a 250 ml separatory funnel. Add 125 ml of ether, 3 ml of conc. HCl and 10 ml of purified water. Shake until the suppositories are uniformly dispersed, then shake for an additional 5-minute period. Allow the two layers to separate and draw off the aqueous layer through a No. 597, 9 cm, S and S filter paper, or equivalent, into a 200-ml volumetric flask. Repeat this extraction procedure 3 additional times, using 3 ml of conc. HCl and 10 ml purified water each time.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:12Z
Check the source to verify that this is the current version before use.

Dilute the combined acid filtrates to volume with purified water and mix well. Pipet 50 ml of this solution (retain remainder for Bismuth assay) into a 250-ml Erlenmeyer flask. Add 50 ml purified water and 5 Gram NH_4Cl, warm on a steam bath or hot plate to a temperature of about 90° C. Titrate, while hot, with 0.05M Potassium Ferrocyanide solution using 2% aqueous Uranyl Acetate solution as an external indicator. Run a blank determination on 100 ml of purified water containing 5 Gram NH_4Cl and 3 ml HCl.

Calculation:

$$\frac{(A-B) \times C \times 4 \times 1000}{3} = \text{mg of Zinc Oxide per suppository.}$$

Where

A = ml of M/20 Potassium Ferrocyanide consumed in titration of the sample.

B = ml of M/20 Potassium Ferrocyanide consumed in titration of the blank.

C = Zinc Oxide equivalence factor.

Note: The Zinc Oxide equivalence factor is defined as the grams of ZnO equivalent to 1 ml of M/20 Potassium Ferrocyanide solution. It is determined by titration of a 200 mg sample of Zinc Oxide, U.S.P., dissolved in 6 ml conc. HCl and 100 ml purified water containing 5 Gram of NH_4Cl. Prior to weighing the 200 mg sample of Zinc Oxide, U.S.P., the Zinc Oxide should be ignited for for a few minutes to drive off any absorbed water.

4.5.6 Total bismuth salts content.

Transfer 100 ml of the filtrate retained in the zinc assay into a 250-ml beaker, then pass H_2S through the solution until all the Bismuth has been precipitated as Bismuth Sulfide. Filter the solution, quantitatively, through a tared medium porosity sintered glass filter. Wash the precipitate with purified water and then with alcohol followed by ether. Cover the precipitate with carbon disulfide and allow to stand for 15 minutes. Remove the carbon disulfide by suctions and dry the residue for 2 hours at 100° C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:12Z
Check the source to verify that this is the current version before use.

Calculation:

$\frac{A \times 0.906 \times 2}{3}$ = mg Bi_2O_3 per suppository.

Where A = mg of Bi_2S_3.

4.5.7 Accelerated aging test.

Place twelve (12) foil-wrapped suppositories horizontally in a Petri dish, cover with a Petri dish cover and palce the Petri dish in an oven at $43^{\circ} \pm 2^{\circ}$ C. At the end of one (1) hour, remove the Petri dish and allow suppositories to cool to room temperature. When cool, place the Petri dish into a refrigerator to solidify the suppositories. Remove the solidified suppositories, unwrap, and examine.

Note: The formation of cavities, white spots, or pinpoint dark spots in the suppositories subjected to the above test is not cause for rejection.

4.5.8 Ingredients.

4.5.8.1 Identification (Bismuth Resorcin Compound).

Shake about 0.5 Gram of the sample with 50 ml of distilled water. Filter and add 3 drops of ferric chloride T.S. to 10 ml of the filtrate; a bluish-violet color, which becomes brownish-yellow on the addition of ammonia T.S. shall show presence of Resorcinol. Wash the residue on the filter paper with a little distilled water. Transfer the residue to a test tube and dissolve in 1 or 2 ml of concentrated HNO_3. Dilute the solution with water. A white precipitate, which is colored brown by H_2S shows presence of Bismuth.

4.5.8.2 Assay (Bismuth Oxide in Bismuth Resorcin Compound).

Accurately weigh 0.5 to 1 Gram of sample in a tared porcelain crucible. Ignite at low temperature without melting. Cool. Take up the residue in 2 or 3 ml of HNO_3, added dropwise, evaporate to dryness on the steam bath, ignite to Bi_2O_3, cool, and weigh.

4.5.8.3 Assay (Bismuth Oxide, Anhydrous).

Dry about 1 Gram of Bismuth Oxide over sulfuric acid for 18 hours, weigh accurately in a tared porcelain crucible, and ignite to constant weight.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:12Z
Check the source to verify that this is the current version before use.

4.6 Examination for preparation for delivery. An examination shall be made to determine whether the packaging, packing, and marking comply with the requirements of Section 5. Defects shall be scored as specified in Table III. Sampling shall be in accordance with MIL-STD-105. The sample unit shall be one container fully prepared for delivery. The lot shall be the number of containers offered for inspection at one time. The inspection level shall be S-2 and the acceptable quality level shall be 4.0 defects per hundred units. For labeling, the acceptance number shall be zero.

Table III. Examinaton for Preparation for Delivery

Examination	Defect
Containers	Not as specified.
Quantity	Quantity in interior packages and shipping containers not as specified.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, tape improperly applied, or containers distorted.
Markings	Omitted, incorrect, illegible, improper size, location, sequence, or method of application.

NOTE: The above table is only applicable to the unit, intermediate and exterior containers.

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery shall be in accordance with all applicable requirements of PPP-C-186 and as specified herein.

5.2 Packaging. Packaging shall be level A or C as specified (see 6.1).

5.2.1 Level A.

5.2.1.1 Immediate container. One suppository shall be packaged in an immediate container considered acceptable to the Food and Drug Administration (FDA) and shall be of such compatibility that neither the contents nor the container are altered in any way by each other. One package containing twelve immediate containers shall constitute one unit of issue.

5.2.1.2 Unit package. Twelve individually packaged suppositories shall be packaged in a box of appropriate size and design except that commercial colors are acceptable. The box may be overwrapped in clear material (cellophane) which shall be secured to prevent accidental opening.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:12Z
Check the source to verify that this is the current version before use.

5.2.1.3 Intermediate package. Six unit packages shall be packaged in a snug-fitting box constructed in accordance with PPP-B-566, PPP-B-636, type CF, class domestic or PPP-B-676 except that commercial colors are acceptable. Closure shall be adequate to prevent spilling of contents under normal handling. As an alternate, the intermediate package may be a complete wrap of clear material (cellophane). Wrapping shall be secured to prevent accidental opening.

5.2.2 Level C. Units shall be packaged in standard commercial containers of the size and kind commonly used, which will afford the degree of protection required for shipment and use of the product for its intended purpose.

5.3 Packing.

5.3.1 Level A. Twenty-four intermediate packages shall be packed in an exterior container designed for a type 2 load and constructed in accordance with PPP-B-585 class 3, style 3; PPP-B-601, overseas type; PPP-B-621, class 2; or PPP-B-636, class weather-resistant. Closure and strapping shall be as specified in the appendix of the applicable box specification.

5.3.1.1 Case liner. Each level A wood box shall be lined with a waterproof case liner conforming to MIL-L-10547. Closure and sealing shall conform to applicable paragraphs of appendix thereto. Case liner shall not be required for fiberboard boxes. Each fiberboard box shall be waterproofed in accordance with 30.4 of PPP-B-636.

5.3.2 Level B. Twenty-four intermediate packages shall be packed in an exterior container designed for a type 2 load and constructed in accordance with PPP-B-636, type CF, class domestic. Closure shall conform to method II as specified in PPP-B-636.

5.3.3 Level C. The subject commodity shall be packed in substantial commercial (export when applicable) containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate, to point of delivery called for in the contract or purchase order.

5.4 Marking.

5.4.1 Labeling. Labeling shall be in accordance with the requirements of the Federal Food, Drug and Cosmetic Act, and shall include the information required below:

5.4.1.1 Immediate container. Each immediate container label shall bear label information in accordance with commercial practice.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:12Z
Check the source to verify that this is the current version before use.

5.4.1.2 Unit packages. Each unit package label shall bear the following:

(a) labeling information in accordance with commercial practice.

(b) the National Stock Number.

(c) the date of manufacture.

NOTES: (1) The National Stock Number shall not be preceded by any prefix.

(2) Strip labeling may be used.

(3) Label adhesion test shall not apply.

5.4.2 Intermediate package. Each intermediate package shall be marked in accordance with MIL-STD-129. Lot (control) number, contract or purchase order number and name of contractor shall be shown. The date of manufacture shall be shown in lieu of the date packed. Marking shall include the legend: "STORE AT CONTROLLED ROOM TEMPERATURE (59° - 86° F.)."

NOTE: When wrapping (cellophane) is used as the intermediate package, the required information may be printed on a label, inserted within the wrapper in such a manner as to permit ready identification.

5.4.3 Exterior container. Exterior container shall be marked in accordance with MIL-STD-129. Lot (control) number shall be shown. The date of manufacture shall be shown in lieu of the date packed. Marking shall include the legend: "STORE AT CONTROLLED ROOM TEMPERATURE (59° - 86° F.)."

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) the National Stock Number.
(c) Selection of applicable levels of packaging and packing (See 5.2 and 5.3).

6.2 This specification covers the following item(s):

National Stock No.	Item Identification
6505-00-721-8944	HEMORRHOIDAL SUPPOSITORIES, 12s.

6.3 All references to PPP-C-186 refer to Interim Federal Specification PPP-C-00186B which is mandatory for use until superceded by a revision.

6.4 This specification does not cover all types, classes, grades, or sizes of the commodity indicated by the title of this specification, or those which are commercially available, but is intended to cover the types which are normally procured to meet Military requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:12Z
Check the source to verify that this is the current version before use.

Custodians:
Army - MD
Navy - MS
Air Force - 03

Preparing activity:
Defense Supply Agency - DM

Project No. 6505-1360
cs

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:12Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE: MIL-H-37210 HEMORRHOIDAL SUPPOSITORIES

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:12Z
Check the source to verify that this is the current version before use.

FOLD

DEFENSE PERSONNEL SUPPORT CENTER
2800 South 20th Street
Philadelphia, PA. 19101

POSTAGE AND FEES PAID
DEFENSE SUPPLY AGENCY
DoD - 304



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

HEADQUARTERS, DEFENSE PERSONNEL SUPPORT CENTER
ATTN: DIRECTORATE OF MEDICAL MATERIEL, CODE ATT
2800 SOUTH 20TH STREET
PHILADELPHIA, PA 19101

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:12Z
Check the source to verify that this is the current version before use.