MILITARY SPECIFICATION

SURVIVAL KIT, INDIVIDUAL

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers a kit containing specified medical and survival items for individuals stranded in isolated areas.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

L-P-375	Plastic Film, Flexible, Vinyl Chloride.
L-P-378	Plastic Sheet and Strip, Thin Gauge, Polyolefin.
L-P-390	Plastic Molding and Extrusion Material, Polyethylene and Copolymers (Low, Medium, and High Density).
EE-B-575	Bouillon, (Soup and Gravy Bases).
EE-M-101	Match, Safety and Match Non-Safety (Strike Anywhere).
QQ-A-250/1	Aluminum Alloy 1100, Plate and Sheet.
PPP-B-566	Boxes, Folding, Paperboard
PPP-B-636	Boxes, Shipping, Fiberboard.
PPP-B-676	Boxes, Setup.
PPP-T-60	Tape, Packaging, Waterproof
PPP-T-97	Tape, Pressure-Sensitive Adhesive Filament Reinforced.

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.

FSC 6545

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:11Z
Check the source to verify that this is the current version before use.

DRAWING

Defense Personnel Support Center (DPSC)

24336 SURVIVAL KIT, INDIVIDUAL

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3 REQUIREMENTS

3.1 Components The survival kit shall consist of a molded polyethylene container packed with the components listed on the Drawing.

3.2 Materials Except as specified herein, materials shall conform to the applicable portions of the specifications, standards, and drawings specified herein and shall be capable of meeting the requirements shown therein. When materials are not specifically designated, those used shall be of the highest commercial quality and entirely suitable for the purpose intended.

3.2.1 Plastic for containers Containers shall be molded of polyethylene plastic conforming to the requirements of L-P-390 for type I, class 1. The thickness of the plastic shall be 0.050 - 0.072 inch. The plastic shall be semi-rigid and sufficiently transparent as to permit labels and identification cards, printed as specified herein, to be read through two thicknesses of material without difficulty. Plastic shall be sufficiently flexible to conform to the shape of the packaged material at the open ends of the container shells, while retaining its molded shape at the closed ends.

3.2.2 Polyethylene bags. The polyethylene bags used to contain individual components shall be fabricated of clear natural color lay-flat tubing conforming to the requirements of L-P-378, Type I, Class 1. The minimum average wall thickness of the bag shall be 0.003 inch with no less than 80% of the nominal wall thickness at any point Both seam and closure shall be heat sealed to prevent moisture from entering or to prevent escape of fluid contents in the event of leakage, excess air shall have been excluded from the sealed bag so that bag conforms to the shape of the component therein To insure a minimum of excess material, the width of commercially available tubing shall be of a dimension which shall closely fit the individual component to be enclosed. The length of the tubing between seals shall be the minimum to contain the component. Excess tubing beyond the seals shall be cut off. Each sealed bag containing an individual item shall be capable of passing the leakage test specified in 4.3.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:11Z
Check the source to verify that this is the current version before use.

3.2.3 Tape for handles. Tape for top and bottom section handles, shall conform to the requirements of PPP-T-97, Type II, class B. Length of handle for top section shall be 9 inches ± 1/4 inch, length of handle for bottom section shall be 8-1/2 inches ± 1/4 inch A length of suitable plastic tape shall be applied as a shield to the exposed adhesive area of each handle.

3.3 Kit contents At the time of kit assembly, all components within the kit shall have sufficient remaining shelf life to support the assembled kit through its first 12 months.

3 3.1 Government furnished components. The components listed below shall be furnished to the contractor by the Government. On receipt of the required quantity of each of the potency dated components, the contractor shall determine from the marked expiration date(s) that at least 12 months potency remains beyond his predetermined assembly date The contractor shall determine, when applicable, that each component is legibly marked

NSN	Item Identification	Expiration Dated Potency(P) Items
6505-00-118-1948	Aspirin Tablets, USP, 0.324 Gram, 100s	P
6505-00-183-9419	Sodium Sulfacetamide Ophthalmic Ointment, USP, 10%, 1/8 oz. (3.5 Gram)	P
6505-00-914-3593	Povidone-Iodine Solution, NF, 10%, 1/2 fl. oz. (14.8 cc), 50s	P
6510-00-200-3080	Compress and Bandage, Camouflaged, 4 by 4 inches.	
6510-00-782-6426	Adhesive Tape, Surgical, Camouflaged, 1 inch by 1 yard, 100s.	P
6510-00-913-7909	Bandage, Adhesive, 3/4 by 3 inches, 300s.	*
6850-00-985-7166	Water Purification Tablet, Iodine, 8 mg, 50s	**

* Difference between predetermined date of assembly and date of manufacture shall not exceed 23 months
** Not less than 12 months remaining from predetermined assembly date to retest date.

3 3 2 Contractor furnished components. The components specified herein shall be furnished by the contractor

3.3.2.1 Aluminum foil. Foil shall be alloy 1100 and shall conform to QQ-A-250/1, temper 0 (Annealed). Shall be 0.003 inch thick, minimum, and shall be furnished in 12 ± 1/8 by 12 ± 1/8 inch squares. Each square shall be folded into a smaller square approximately 3 inches by 3 inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:11Z
Check the source to verify that this is the current version before use.

3.3.2.2 Fish hooks and line. One fish hook shall be snelled with a nominal six (6) inch leader to each end of a nine (9) pound test nylon fishing line six (6) yards ± 3 inches long. Both fish hooks shall be size number 6, Carlisle type. The fish hooks shall be attached to a suitably sized polyethylene core around which the fishing line shall be evenly wound to make a thin, flat package 2 inches ± 1/8 inch long by 1 inch ± 1/8 inch wide. The wrapped line shall not bulge at the center of the plastic core. The package shall be wrapped to prevent the hooks from puncturing or tearing other items in the kit, and the line from unraveling. The package shall be labeled as to contents.

3.3.2.3 Matches, safety, humidity resistant, 20s. The matches shall conform to the requirements of EE-M-101 for type II, class 2. An assembled booklet shall be 2 ± 1/16 inches long, 1-1/2 ± 1/16 inches wide, and 1/4 ± 1/8 inch thick at the match tip end of the booklet. Each booklet shall be packaged individually in a bag made of clear polyethylene, as specified in 3.2.2. Closures of the bag shall be effected by heat sealing. Closures shall be well sealed to prevent moisture from affecting the matches. The cover of each booklet of matches shall be legibly marked as follows:

" MATCHES
Store in
plastic bag
when not in use"

3.3.2.4 Soaped tissues, wrapped, 3s. Three soaped tissues, approximately 4-1/2 inches by 4-1/2 inches, shall be folded together to form a thin, flat, rectangular pack approximately 2-1/2 inches by 1-3/4 inches. Each package, together with a label, shall be inserted in a plastic bag (3.2.2). The label shall be marked as follows:

"SOAPED TISSUES

Dampen skin, rub with tissue, rinse and dry"

The plastic bag shall be closed by heat sealing to prevent moisture from entering the bag and affecting the tissues.

3.3.2.5 Soup and gravy base, instant, chicken flavored 7 gram envelope. The chicken flavored instant soup and gravy base envelopes shall conform to the requirements of EE-B-575, Type II, Class 1, Style A. In addition to the information for Military agencies required to be printed on the envelope in accordance with Section 5 of EE-B-575, the month and year of manufacture shall also be printed on each envelope. As an alternate, the contractor for the survival kit shall legibly print the month and year of manufacture on the envelope in a contrasting color. No more than three months shall have elapsed from the date of manufacture of the chicken flavored soup and gravy base to the date of assembly of the survival kit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:11Z
Check the source to verify that this is the current version before use.

3.3.2.6 Tropical chocolate bar, 1 oz The bar shall weigh a nominal 1 oz. net, and consist of chocolate, sugar, non-fat solids, cocoa butter, Vitamin B, and artificial flavoring. Each bar shall be individually wrapped in a moisture-proof glassine paper and shall be labeled as to contents. Each bar shall measure a nominal 3 inches long by 1-1/4 inches wide by 1/2 inch thick Chocolate bar shall be Hershey Food Corporation's "Hershey's Tropical Bar". In addition, the month and year of manufacture shall be legibly printed or stamped on each wrapped bar by the manufacturer or kit contractor. Location of the additional marking is optional, but shall not obliterate existing markings No more than 3 months shall have elapsed from the date of manufacture of the bars to the date of assembly of the survival kit. Each bar shall be packaged in a polyetylene bag as specified in 3.2.2.

3.4 Construction of plastic kit container. The kit container shall be fabricated of polyethylene as specified in 3.2 1, and molded in accordance with the requirements shown on DPSC Drawing 24336, revised 5 March 1975 Removal of the telescopic top section from the bottom section shall be facilitated by the use of tape handles (see 3.2.3) positioned as shown on the drawing. Each handle shall provide the specified finger space and be securely affixed to its respective section.

3.5 Identification card. The identification card shall provide a listing of the kit contents. The list shall include, where applicable, the National Stock Number, item identification, quantity, use, and dosage, as shown on the Drawing. This information shall be printed with waterproof ink on a strip of waterproof paper approximately 3 inches wide by 6 inches long Minimum type size shall be 5 point The identification card shall be positioned "U" shaped over the tops of components of a fully loaded bottom section in such a manner that the information can be read through the container of the assembled kit. The ends of the card shall not protrude beyond the edges of the top section Only when the card size is insufficient to permit printing the entire contents or one side, may all or part of the components listed on the drawing as having obvious usages be printed on the back of the card. Each identification card shall be capable of passing the immersion test specified in 4.3.2

3.6 Preparation for assembly.

3.6 1 Aspirin tablets, USP, 0 324 Gram, 100s A card of 10 tablets shall be accordian foldec, each tablet slightly offset from the tablet above and below it, to form a packet of suitable size. The packet shall be secured in the middle by a neoprene rubber band.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:11Z
Check the source to verify that this is the current version before use.

3.6.2 Compress and bandage, camouflaged, 4 by 4 inches. Each compress in its polyethylene package shall be removed from its outer cardboard carton before inserting into the kit container.

3.6.3 Government furnished components requiring additional protection. Each of the components listed below shall be packaged in a polyethylene bag as specified in 3.2.2.

NSN	Brief Item Identification
6505-00-183-9419	Sodium Sulfacetamide Ophthalmic Ointment after removal from its individual carton.
6505-00-914-3493	Povidone-Iodine Solution.
6505-00-985-7166	Water Purification Tablet

3.7 Assembly. The contractor shall insert in the lower section of the container the designated quantity of each component listed on the Drawing. The instruction card shall then be bent "U" shaped over the tops of the components, and the top section of the container added

3.8 Workmanship. Workmanship shall be first class throughout. The individual components, as well as the completely assembled kits, shall be free from defects which detract from their appearance or may impair their serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Records. Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government, upon the Government's request, at any time, or from time to time, during the performance of the contract and for a period of three years after delivery of the supplies to which such records relate.

4.1.2 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual or auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:11Z
Check the source to verify that this is the current version before use.

4.1.3 Certificates of quality. Certificates of quality, supplied by the manufacturer of the container, matches, polyethylene bags, soup and gravy base, and tape for handles, may be furnished in lieu of actual performance of such testing by the contractor, provided lot identity has been maintained and can be demonstrated to the Government. The certificate shall include the name of the contractor, the contract number, the name of the manufacturer or supplier, the NSN, the item identification, the name of the component/material, the lot number, the lot size, the sample size, the date of testing, the test method, individual test results, and the specification requirements.

4.2 Quality conformance inspection. The examinations and tests required to assure conformance of those items or lots of items to be offered for acceptance are classified as specified in tables I and II (see 4.2.1 and 4.2.2) and 4.2.3.

4.2.1 Sampling for examination. Sampling for examination shall be conducted in accordance with MIL-STD-105. The inspection levels and acceptable quality levels shall be as indicated in Table I. Unit of product for examination purposes shall be one survival kit.

TABLE I Sampling for examination

Examination	Inspection level	AQL (percent defective)
Major	1	1.0
Minor	1	4.0

4.2.2 Examination.

4.2.2.1 Examination product The survival kit shall be examined for defects including, but not limited to, those listed in table II

TABLE II. Classification of defects

Major	
101	Any component missing
102	Top section of kit container does not fit over bottom section
103	Kit container not sufficiently transparent for identification card to be read.
104	Handles not securely adhered to appropriate container section.
105	Any component leaking, torn, or broken.
106	Labeling on component missing or illegible.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:11Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects(Cont'd)

Major	
107	Plastic bag containing component, or kit, not sealed.
108	Plastic bag containing component, or kit, damaged.
109	Printing on identification card incorrect or illegible.
Minor	
201	Handle positioning not as specified.
202	Excessive air trapped in sealed plastic bags.
203	Excessive plastic beyond heat sealed on plastic bag not removed.

4.2.2 2 Packaging inspection. An inspection shall be made to determine compliance with the packaging, packing and marking requirements of section 5. Sampling shall be in accordance with MIL-STD-105. Defects shall be scored as specified in table III. The sample unit shall be one container fully prepared for delivery The lot shall be the number of containers offered for inspection at one time. The inspection level shall be S-2 with AQL of 4.0 expressed in terms of percent defective.

TABLE III Examination of preparation for delivery

Examine	Defect
Contents	Not as specified.
Container	Not as specified.
Marking	Omitted, incorrect; illegible; improper size, location, sequence or method of application
Material	Component missing or damaged.
Workmanship	Bulging or distortion of containers

4 2 2 2 1 Inspection of closure, waterproofing and banding of container When the shipping container is required to comply with PPP-B-636, the inspection for defects in closure, waterproofing or banding shall be in accordance with the appendix of the box specification.

4.2 3 Sampling for tests. Sampling for tests shall be conducted in accordance with MIL-STD-105, Inspection Level S-2, Acceptable Quality Level 4 0. Unit of product for test purposes shall be one kit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:11Z
Check the source to verify that this is the current version before use.

4.2.4 Sampling unit usage. Where possible, the same sample unit shall be used for the determination of two or more test characteristics.

4.3 Tests. Tests shall be conducted to determine compliance with specification requirements.

4.3.1 Leakage test. Sealed, filled polyethylene bags (see 3.2.2) shall be submerged to a depth of one foot in tap water for 15 minutes. Bags shall be removed, opened, and examined for evidence of leakage of water.

4.3.2 Immersion test. Two copies of the Identification card (see 3.5) shall be fully immersed in tap water for 24 hours. There shall be no deleterious effects such as running ink or shredded paper.

5 PACKAGING

5.1 Packaging requirements. Packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A.

5.1.1.1 Unit package. Each kit (components in rigid plastic case) shall be packaged in a bag fabricated of virgin polyethylene conforming to L-P-375. The tubing shall have an average thickness of not less than 0.004 inch with no wall thickness at any point below 0.0035 inch. Excess air shall be evacuated from the bag and the closure effected by heat sealing. The bag shall be of sufficient length so that the heat seal closure shall be 1-3/4 inches ± 1/8 inch from the bottom of the plastic kit container positioned in the bag. The unit shall be further packaged in a snug fitting box constructed in accordance with PPP-B-566 or PPP-B-676. Closure of the box shall be secured to prevent spilling of contents.

5.1.2 Level C. Each kit shall be packaged in a polyethylene bag as specified in 5.1.1.1 and further packaged in a snug fitting box that will afford adequate protection against physical damage during shipment from supply source to the first receiving activity.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.1).

5.2.1 Level A.

5.2.1.1 Exterior container. Ninety six unit packages shall be packed in an exterior container designed for a type 2 load and constructed in accordance with PPP-B-636, type CF, class weather-resistant, grade V3c. Closure, strapping and waterproofing shall be as specified in the appendix of PPP-B-636. NOTE: The box shall contain top and bottom pads fabricated of fiberboard conforming to type CF, class domestic of PPP-B-636. When unit packages are stacked in two or more tiers, a pad shall be interposed between each tier. Strapping shall not be required for shipments forwarded to a receiving activity within the continental limits of the United States for storage or redistribution.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:11Z
Check the source to verify that this is the current version before use.

5.2.2 Level B.

5.2.2.1 Exterior container. Ninety six unit packages shall be packed in an exterior container designed for a type 2 load and constructed in accordance with PPP-B-636, type CF, class domestic and having a minimum bursting strength of 200 pounds The box shall contain top, bottom and tier pads as specified in 5.2 1.1 Closure shall be as specified in the appendix of PPP-B-636.

5.2.3 Level C. The packaged kits shall be packed in shipping containers that will afford adequate protection against damage during direct shipment from the supply source to the first receiving activity. These packs shall conform to the applicable carrier rules and regulations.

5.3 Marking

5.3.1 Unit package Each unit package shall be marked in accordance with MIL-STD-129 Type II shelf life marking as specified in MIL-STD-129 shall be shown. The inspection test date shall be that of the item with the shortest remaining potency at the date of assembly

5.3.2 Exterior container. Exterior container shall be marked in accordance with MIL-STD-129. Type II shelf life marking as specified in 5.3.1 shall also be shown.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following.

(a) Title, number, and date of this specification.
(b) National Stock Number (NSN).
(c) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.2 Sample for transparency. The bidders shall submit to the contracting officer for evaluation of transparency, two strips, each approximately 3 inches by 4 inches by 0.050 inches thick, of the plastic material to be used in the fabrication of the container.

6.3 This specification covers the following item appearing in the Federal Supply Catalog.

National Stock Number	Item Identification
6545-00-139-3671	Survival Kit, Individual

Custodians:
Army - MD
Navy - MS
Air Force - 03

Preparing activity:
Defense Supply Agency - DM

Project No. 6545-0024

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:11Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No 22-R255

INSTRUCTIONS The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay or will otherwise enhance use of the document DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government Fold on lines on reverse side, staple in corner, and send to preparing activity Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements Attach any pertinent data which may be of use in improving this document If there are additional papers attach to form and place both in an envelope addressed to preparing activity

DOCUMENT IDENTIFIER AND TITLE

MIL-S-37205 - SURVIVAL KIT, INDIVIDUAL

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1 HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2 COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3 IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO (If "Yes" in what way?

4 REMARKS

SUBMITTED BY (Printed or typed name and address - Optional)

TELEPHONE NO

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:11Z
Check the source to verify that this is the current version before use.

FOLD

DEFENSE PERSONNEL SUPPORT CENTER
2800 South 20th Street
Philadelphia, PA 19101

POSTAGE AND FEES PAID
DEFENSE SUPPLY AGENCY
DoD - 304

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

HEADQUAPTERS, DEFENSE PERSONNEL SUPPOPT CENTER
ATTN DIRECTORATE OF MEDICAL MATERIEL, CODE ATT
2800 SOUTH 20TH STREET
PHILADELPHIA, PA 19101

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:11Z
Check the source to verify that this is the current version before use.