MILITARY SPECIFICATION

BALLISTICS COMPUTER SUBASSEMBLY: 10552928
(CANT UNIT)

This amendment forms a part of Military Specification MIL-B-60871(MU), dated 4 March 1968.

Paragraph 3.4.2: Delete last sentence

Paragraph 4.2: Delete and substitute:

"4.2 First article (initial production) approval.- The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of three (3) cant units plus three (3) each of all items covered by SQAP. The sample shall be manufactured in the same manner, using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

4.2.1 Government testing.- When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials.

4.2.2 Contractor testing.- When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by the contractor for all the requirements of the contract. The sample and a record of this inspection, including certificates of conformance for materials, shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection."

Paragraph 4.4.3: Delete and substitute:

"4.4.3 Failure of sample.- Should any one item of a special sampling fail to meet the specified test requirements, acceptance of the represented inspection lot shall be suspended by the Government until necessary corrections have been made by the contractor and resubmitted items have been approved (see 4.2.3)."

FSC 1220

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:02Z
Check the source to verify that this is the current version before use.

* Paragraph 4.5.3, Item No. 4, Description: Delete last sentence and substitute; "Provisions for instantaneous release from a 20° position and return to the horizontal position without overtravel."

* Paragraph 4.6.8.2: Delete and substitute

"4.6.8.2 Magnet and damping.- To determine conformance to 3.6.2, physically rotate the cant housing, in either direction, to a point at least 20 degrees about the centerline of the resolver axis by means of the test fixture. At this point of rotation, instantaneously release the test fixture to permit it to return to zero cant, without overtravel. The magnet arm shall return to its normal gravity controlled position within one cycle of oscillation as specified in 3.6.2. One cycle of oscillation shall be determined by observing the oscilloscope null on the test circuit."

* Paragraph 4.6.8.3, first sentence: Delete "4.4.2" and substitute "4.5.3".

*The outside margins have been marked to indicate where additions to the previous amendment have been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notations and relationship to the last previous issue.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A150

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:02Z
Check the source to verify that this is the current version before use.