INCH-POUND

MIL-C-48475B(AR)
AMENDMENT 3
24 November 1993
SUPERSEDING
AMENDMENT 2
22 SEPTEMBER 1987

MILITARY SPECIFICATION

CIRCUIT CARD ASSEMBLY: 11732369 SELF TEST

This amendment forms a part of MIL-C-48475B(AR), dated 30 June 81, and is approved for use by the U.S. Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

* 2.1: Drawings, under Inspection Equipment, add: "(REF)" following each inspection equipment drawing.

PAGE 5

Table I: Delete item 3.2 in its entirety.

PAGE 8

* 3.3.1, line 1: Delete "2.5" and substitute "2.6".

* 3.3.2: Delete in its entirety and substitute :

"3.3.2 Pwr OK and comp fail output. With power (Table 1, items 2.1, 2.2, 2.3, 2.4 (tolerance: ±0.1 vdc) 2.5 and 2.6) applied, the loads (Table I, item 1) applied, points P19-B and P1-5A tied together, the bit signal removed from P1-15B (OPEN).

a. With the minus DC reference (Table I, item 2.5) set to -10.050 ± 0.015 vdc, the Pwr OK output at P1-25A shall be +10.0 ± 0.8 vdc and the comp fail output at P1-24A shall be 23.4 ± 1.1 vdc.

Distribution Statement A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:28Z
Check the source to verify that this is the current version before use.

b. With the minus DC reference voltage (Table I, item 2.5) set to -9.950 ± 0.015 vdc, the Pwr OK output at P1-25A shall be +10.0 ± 0.8 vdc.

c. With the minus DC reference voltage (Table I, item 2.5) set to -7.30 ± 0.1 vdc, the Pwr OK output at P1-25A shall be 0.2 ± 0.2 vdc and the comp fail output at P1-24A shall be 0.3 ± 0.3 vdc.

d. With the minus DC reference voltage (Table I, item 2.5) set to -14.30 ± 0.10 vdc, the Pwr OK output at P1-25A shall be 0.2 ± 0.2 vdc."

PAGE 9

* 3.3.5a, line 2 and 3: Delete "(1.0 ± 0.5 vdc)" and substitute "(0.5 ± 0.5 vdc)".

PAGE 12

* 3.3.10:

Line 8: In equation for V_{TP4}, delete "$V_{TP4}(0)$" and substitute "Offset".

Line 18: Delete "$V_{TP4}(0)$ =" and substitute "Offset =".

Add item j following item i as follows:

"j. $|V_{TP4}$ - Offset| is the absolute value of TP4 derived from the transfer function minus the offset."

Line 22: (Equation for "ΔV_{TP4}" was changed by Amendment 1. This Amendment reinstates the original equation in the basic specification).

PAGE 13

* Table II, column 2: Delete "P1-1A 1/, 8/" and substitute "P1-4A 1/, 8/".

PAGE 14

* Table II, column 6 (Output Conditions at Pin P1-24A (Comp Fail), items 1, 5, 6, 9, 10, 11, 12: Delete "0.7 Vdc" and substitute "0.7 vdc max".

* Table II, column 6, items 2, 4 and 7: Delete "21 ± 2 Vdc" and substitute "24 ± 2 vdc".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:28Z
Check the source to verify that this is the current version before use.

PAGE 15

* 3.3.10, line 3 and 4: (Items a and b were changed by Amendment 1. This Amendment reinstates items a and b as they are in the basic specification).

PAGE 16

* Table III, column 8 (Output Conditions at Pins), item 2: Delete "21 ± 2 Vdc" and substitute "24 ± 2 vdc".

* Table III, column 8, item 1 and 6: Delete "2 Vdc" and substitute "2 vdc max".

PAGE 19

* Table IV, column 6 (Output Conditions at Pin P1-20B(System OK)), item 1: Delete "2 vdc" and substitute "2 vdc max".

PAGE 21

* Table V, column 6 (P1-19A 3/(RF Fail)), item 1: Delete "2vdc" and substitute "2 vdc max".

* Table V, column 7 (P1-23A 3/(GCU Fail)) and 8 (P1-22A 3/(CU Fail), item 3: Delete "2 vdc" and substitute "2 vdc max".

PAGE 26

* 4.6.1: Delete in its entirety and substitute:

"4.6.1 Test equipment. The test equipment in table IX may be used where specified to perform the required test. If alternate test equipment is to be used, the contractor shall submit inspection equipment designs for review and approval in accordance with the terms of the contract (see 6.4)."

PAGE 30

* Add new paragraph 6.4 as follows:

"6.4 Submission of contractor inspection equipment designs for approval. Submit copies of designs as required to: Commander, U.S Army ARDEC, ATTN: SMCAR-QAF-I, Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:28Z
Check the source to verify that this is the current version before use.

NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AR

Preparing Activity:
Army - AR

(Project 1220-A447)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:28Z
Check the source to verify that this is the current version before use.