MIL-C-63129(AR)
AMENDMENT 3
2 November 1978
SUPERSEDING
AMENDMENT 2
8 August 1978

MILITARY SPECIFICATION

CARTRIDGE, 40MM, RED SMOKE, GROUND MARKER, M713

LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-C-63129(AR), dated 14 March 1977.

PAGE 4

*Add the following paragraph:

"3.6 X-ray examination of ballistic samples. - Prior to forwarding the sample cartridges for ballistic testing, they shall be x-rayed for critical and major defects. A critical defect is defined as no delay assembly or delay assembly above face of fuze support.

PAGE 4 and 5

Paragraph 4.3.3.1. -

e. Delete "Mean velocity or standard deviation fail the applicable requirement (average)" and substitute "e Mean velocity or standard deviation fail the applicable requirement at ambient phase only. Informational at hot and cold phases."

PAGE 8

Paragraph 4.4.2.1. - Add the following Major Defect characteristic:

"105 - Stake missing or improper 0.40% 3.2 visual." (prior to assembling tape)

FSC: 1310

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:17Z
Check the source to verify that this is the current version before use.

PAGE 9

*Paragraph 4.4.2.2. -

Major 102. - Delete "50 2.50%" and substitute "4 per hr. **"

Under NOTES add:

"** If any sample fails to comply with the drawing requirement, the hours production represented by the sample shall be rejected."

PAGE 13

Paragraph 4.4.3.1

(a) Delete "moisture content" throughout and substitute "total volatiles"

(b) After eight (8) delete "of each"

Paragraph 4.4.3.3. - Delete "examined visually with," and substitute "examined visually without"

PAGE 17

*Add the following paragraph:

"4.4.3.10. X-ray examination of ballsitic samples. - Prior to forwarding the sample cartridges for ballistic testing, they shall be x-rayed for critical and major defects. If any critical defect is found, the sample sahll be removed and the lot rejected including the ballistic samples and 100% x-ray examination of the lot shall be performed prior to submitting a new ballistic sample. If any major defect is found, it shall be noted and the sample forwarded for testing."

PAGE 14 and 15

Paragraph 4.4.3.5.4. -

e. Delete "Mean velocity or standard deviation fail the applicable requirement (average)" and substitute "e Mean velocity or standard deviation fail the applicable requirement at ambient phase only. Informational at hot and cold phases."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:17Z
Check the source to verify that this is the current version before use.

PAGE 16 and 17

Paragraph 4.4.3.9.4. -

e. Delete "Mean velocity or standard deviation fail the applicable requirement (average)" and substitute "e Mean velocity or standard deviation fail the applicable requirement at ambient phase only. Informational at hot and cold phases."

Paragaraph 4.5.1 and 4.5.1.1. - Delete "moisture content" throughout and substitute "total volatiles"

PAGE 19

*Add the following paragraph:

"4.5.8 X-rayed examination of ballistic samples. - The sample cartridges, prior to forwarding for ballistic testing, shall be subjected to x-ray examination using approved x-ray equipment."

* The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous amendment.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 1310-A129

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:17Z
Check the source to verify that this is the current version before use.