INCH-POUND

MIL-D-51091J(EA)
AMENDMENT 3
28 February 1990
SUPERSEDING
AMENDMENT 2
29 December 1988

# MILITARY SPECIFICATION

## DECONTAMINATING APPARATUS, POWER DRIVEN, SKID-MOUNTED, MULTIPURPOSE, NONINTEGRAL, 500-GALLON, M12A1

*This amendment forms a part of MIL-D-51091J(EA), dated 16 December 1986, and is approved for use by the U.S. Army Chemical Research, Development and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.*

PAGE 3

3.3.2: Delete in its entirety and substitute the following:

"**3.3.2 Fuel tank.** The unpainted tank shall not leak, except at the fuel quantity transmitter screw holes when subjected to an internal air pressure of 2 to 3 pounds per square inch gage (psig) when tested as specified in 4.4.4.1."

PAGE 8

5.1.1.2:

Lines 3, 4 and 5: Delete the following sentence: "The interior surfaces of the tanks and fittings including the gasoline tank, shall be completely coated with preservative oil conforming to grade 2, MIL-L-21260."

AMSC N/A FSC 4230

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:50Z
Check the source to verify that this is the current version before use.

PAGE 9

5.1.1.7, lines 6, 7, 8 and 9: Delete "The blending-agitator hose, shall then be stowed within the suction hose. Both hoses, together, shall then be installed, coiled, within the holding brackets on top of the tank unit." and substitute "The blending-agitator hose, shall then be coiled and stowed within the hopper assembly. The suction hose shall then be installed, coiled, within the holding brackets on top of the tank unit."

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 4230-A089



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:50Z
Check the source to verify that this is the current version before use.