MIL-D-63122A(AR)
17 December 1979
SUPERSEDING
MIL-D-63122(AR)
7 September 1977

MILITARY SPECIFICATION

DISPENSER, GENERAL PURPOSE, AIRCRAFT: M130

This Specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This Specification covers the inspection and testing of the M130 Aircraft General Purpose Dispenser hereafter referenced to as the dispenser system.

2. APPLICABLE DOCUMENTS

2.1 Issue of documents. - The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)

DRAWINGS (See 6.3)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

9311430	-	M130 System

FSC: 1095

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:16Z
Check the source to verify that this is the current version before use.

9313708 - Packing and Marking for Drum, Metal, Shipping for M130 Aircraft General Purpose Dispenser

U.S. ARMY MATERIEL DEVELOPMENT AND READINESS COMMAND

19-48-4138/109-20 PA1000 - Unitization Procedures for Boxed Ammunition and Components on Skidded Bases

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Assembly. The dispenser system shall comply with all requirements specified on Drawing (Dwg.) 9311430, and all associated drawings and applicable specifications.

3.3 Functioning. The dispenser system shall function as specified herein.

3.3.1 Arm. The dispenser shall respond to input signals only when a 22.5 to 30.0 volt, direct current (dc), arm signal is present.

3.3.2 Chaff/flare count. A chaff count signal or a flare count signal shall be generated each time a chaff or flare is dispensed. These signals shall be 20.0 to 30.0 volts dc.

3.3.3 Dispense output. Each of the thirty outputs of the dispenser shall provide 5.0 $\pm$ 0.75 amperes dc firing signal into a resistive load of 1.0 $\pm$ 0.1 ohm for 15 milliseconds minimum.

3.3.4 Flare misfire. Failure of a signal flare to eject or ignite shall result in firing of the next sequential flare. This capability shall be limited to three flare dispense actions only.

3.3.5 Stray voltage. There shall be no stray voltage between any of the 30 firing contacts and ground (dispenser chassis) when tested in accordance with 4.5.2.1.

3.3.6 Power loss. In case of power loss, the system shall retain the position of the next payload to be fired.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:16Z
Check the source to verify that this is the current version before use.

3.4 First article inspection. First article inspection shall be performed using the technical provisions in the applicable component specification (See 3.3, 3.4, 3.5 and 3.6). Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.5 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. All parts and assemblies shall be clean and free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required), corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part or assembly, nor shall they be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings and stampings shall be neat and sharply defined. Required packing shall be dry and packaging operations performed in a through workmanlike manner.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsiblity for inspection and standard quality assurance provisions. Unless otherwise specified herein, or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspections shall be conducted on this item.

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2 and 4.3.3. The first article sample shall consist of the following items in sample quantities as indicated below:

Part Description	Drawings	Quantity
M130 System	9311430	2

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:16Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63122(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Dispenser, General Purpose, Aircraft M130 (Drawing 9311430) Electrical Tests	2		3.3	4.5.2

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23 10:21:02
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. (See MIL-A-48078). Unless otherwise specified in the Classification of Defects and Test Tables in this specification, sampling plans for major and minor defects shall be in accordance with MIL-STD-105. Equipment necessary for the performance of the inspection listed shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:16Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63122A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Packing and Marking for, Drum, Metal Shipping for M130 Aircraft General Purpose Dispenser		9313708
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Cushions missing or not secured		0.40%	3.2	Visual
102	Contents not thoroughly dry		0.40%	3.2	Visual
103	Any component missing, damaged or improperly assembled		0.40%	3.2	Visual
104	Air Leakage Test		0.40%	3.2	Visual
Minor					
201	Marking missing, incorrect or illegible		0.65%	3.2	Visual
202	Fillers insufficient, loose contents		0.65%	3.2	Visual
203	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:16Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

4.4.3.1 Electrical tests. Major Defect. A sample of 20 dispenser systems shall be selected from each lot and subjected to the electrical tests as specified in 4.5.2 using equipment in accordance with 4.4.4. If any dispenser system fails to meet the requirements, the lot shall be rejected.

4.4.3.2 Air leakage test (See Dwg. 8806652). Major Defect. This test shall be performed 100% and as specified in 4.5.1 using equipment in accordance with 4.4.4. Any drum which fails the test shall be classified defective and removed from the lot.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the table starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and 6.4 herein.

4.5 Test methods and procedures

4.5.1 Air leakage test. The drums shall be tested using the procedures on drawing (Dwg) 8806652.

4.5.2 Electrical tests.

4.5.2.1 Stray voltage check. (See 3.3.5) This test is to be performed on the M130 without the payload module connected to the dispenser. Using approved test equipment, apply 28 $\pm$ 4 VDC to the system. The dispenser shall be tested for 0.0 $\pm$ 0.2 volts maximum across a 3.0 $\pm$ .5 ohm load at any two of the 30 fire output terminals in each of the following four modes:

a. Safety pin (flag assembly) inserted
Safe/Arm (S&A) switch at SAFE
Selector switch at C

b. Safety pin inserted
(S&A) switch at SAFE
Selector switch at F

c. S&A swtich at ARM
Selector switch at C

d. Safety pin removed
S&A switch at ARM
Selector switch at F

In the event that the voltage is not less than the specified value, the dispenser system shall be classified defective and removed from the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:16Z
Check the source to verify that this is the current version before use.

4.5.2.2 Functional test. The dispenser system shall be subjected to the following test (See 3.3.3).

To Test Safe Circuits

a. Assure that:
S&A switch is in SAFE position
Ripple fire switch is OFF
Manual-Program switch is in Manual position
Both counters at 30
Safety pin installed in Electronic Module
Selector swtich at C on Dispenser

b. Apply 28 + 2 volts dc to Dispenser Control Panel

c. Press-to-test ARM lamp. Arm lamp lights. If arm lamp fails to light, replace lamp. If replaced lamp fails to light, reject dispenser system.

d. Set S&A switch to ARM. ARM lamp should not light.

e. Test integrity of safety pin by pressing DISPENSE buttons. No affect on system shall be observed.

f. Set S&A switch to SAFE.

g. Remove safety pin.

h. Test integrity of S&A switch by pressing DISPENSE buttons. No affect on system shall be observed (See 3.3.1).

To Test Chaff Mode

i. Set S&A switch to ARM.

j. Press remote chaff firing button.
A firing pulse shall be indicated. (See 3.3.3).
Chaff counter shall read 29. (See 3.3.2).

k. Reset dispenser and rest chaff counter to 30.

l. Set Manual-Program switch to PGRM and set chaff program on Electronic Module as follows:

Burst Count	3
Burst Interval	.4
Salvo Count	2
Salvo Interval	2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:16Z
Check the source to verify that this is the current version before use.

m. Press chaff DISPENSE button.
Six firing indications shall be observed.

To Test Flare Mode

n. Reset Dispenser and set selector swtich to F.

o. Assure flare counter on Control Panel still reads 30.

p. Press remote flare firing button. Firing indications shall appear in groups of three (since Flare Sensor is not receiving infrared flare output See 3.3.4).

To Test System Memory

q. Remove safety pin from Electronic Module.

r. Set S&A switch to ARM.

s. Press remote flare firing button once;
Flare counter shall read 27.
Firing indications of payload numbers 1, 2 and 3 shall be observed.

t. Remove voltage source from Control Panel and reapply after 2 seconds.
Flare counter shall still read 27. (See 3.3.6).

Test completed. Reject any M130 system that fails any of the above procedures

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 Level A. Preservation and packaging shall be in accordance with Dwg. 9313708.

5.2 Packing.

5.2.1 Level A. Packing shall be in accordance with Dwg. 9313708.

5.3 Marking.

5.3.1 Level A. Marking shall be in accordance with Dwg. 9313708.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:16Z
Check the source to verify that this is the current version before use.

5.4 Unitization.

5.4.1 Level A. Unitization of the M130 Dispenser as packed in 5.2.1 shall be in accordance with Dwg. 19-48-4138/109-20 PA1000 (DARCOM Ammo Center).

6. NOTES

6.1 Intended use. The M130 Aircraft General Purpose Dispenser is intended to dispense chaff and flare countermeasures for Army aircraft.

6.2 Ordering data. Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Provisions for submission of first article samples.

c. Provisions of MIL-A-48078.

6.3 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under cognizance of ARRADCOM.

6.4 Submission of inspection equipment designs for approval. (See MIL-A-48078). Submit equipment designs as required, to Commander, U.S Army Armament Research and Development Command, ATTN: DRDAR-QAA-I, Dover, New Jersey 07801.

6.5 Distribution of ammunition data cards. Distribution of data cards shall include the following: Commander, U.S Army Armament Research and Development Command (ARRADCOM) ATTN: DRDAR-QAA-M, Dover, New Jersey 07801.

6.6 Changes from previous issue. Asterisks are not used in this revision with respect to the previous issue, due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project No: 1095-A125

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:16Z
Check the source to verify that this is the current version before use.