MILITARY SPECIFICATION

HANDLING TOOL: H-4202

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of handling tool entitled Handling Tool, Fuze Assembly: H-4202 which is used with the Honest John warhead section.

2 APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

PPP-T-60 - Tape, Pressure-sensitive Adhesive, Waterproof, for Packaging.

MILITARY

MIL-T-5021 - Tests; Aircrart Welding Operator's Certification.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1168 - Lot Numbering of Ammunition.
MIL-STD-1169 - Packaging, Packing and Marking for Inert Ammunition Components.

DRAWINGS

ORDNANCE CORPS

8850240 - Handling Tool, Fuze Assembly: H-4202
EL-8817627 - Equipment Lists.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The handling tool shall comply with all requirements specified on the drawing (dwg) 8850240, with all requirements specified herein, and with the requirements of all applicable speciications to the extent specified on the drawing and herein.

3.3 Static load. The handling tool shall be capable of supporting a 75 pound load without evidence of permanent distortion, cracked welds, or other physical damage as could be experienced by the rubber pad when tested as specified in 4.3.1.

3.4 Paint adhesion. The painted surface shall adhere to the base material without evidence of peeling, flaking, or chipping when tested as specified in 4.3.2.

3.5 Welding. Welds shall be reasonably smooth and free from craters. They shall exhibit characteristics of fusion, penetration, and soundness of weld deposit representative of good welding practice. They shall be free from irregularities which indicate lack of good practice on the part of the operator. All welding fluxes, scale, weld spatter, guide, and basic solution shall be removed prior to application of any finish coat.

3.5.1 Welding operators. All fusion welding shall be performed by operators who are currently certified as Class "B" welders in accordance with MIL-T-5021.

3.6 Workmanship.

3.6.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.6.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.6.3 Burrs. Parts shall be free from burrs.

3.6.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.6.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection.

4.2.1 Lot formation.

4.2.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.2.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.2.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table I and Table II), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

Table I
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table II
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

4.2.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.2.2.1.1 Handling tool, fuze assembly: H-4202 (see dwg 8850240.

Categories	Characteristics	Method of Inspection
Critical:		
	1. Crack in weld	Visual
	2. Improper weld (see 3.5)	Visual
Major:		
	101. Diameter of rod material	Gage
	102. Width of inside bend maximum (max.)	Gage
	103. Distance from bend to end of rod	Gage
	104. Distance from inner edge of rod end to face of tool body	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

105. Finish improper.....Visual
106. Rubber handle damaged or loose.....Visual/Manual
107. Tape missing or loose.....Visual/Manual
108. Objective evidence relative to material missing or improper (see 3.1).....Visual

Minor:

201. Evidence of poor workmanship (see 3.6).....Visual

4.2.2.1.2 Preparation for delivery (see 5).

Categories	Characteristics	Method of Inspection

Critical: None defined

Major:

101. Preservation, packaging and packing in accordance with MIL-STD-1169.....Visual
102. Marking in accordance with MIL-STD-1169.....Visual

Minor:

201. Evidence of poor workmanship (see 3.6).....Visual

4.2.3 Testing. All tests shall be performed. Tests need not performed in the order specified below:

Test	Test classification
a. Static load	Major
b. Paint adhesion	Major

None of these tests are considered destructive and samples so tested may be returned to the lot.

4.2.3.1 Static load and paint adhesion. Each handling tool shall be tested in accordance with 4.3.1 and 4.3.2. If any item fails to comply with 3.3 and 3.4, the item shall be rejected and removed from the lot.

4.2.4 Acceptance inspection equipment.

4.2.4.1 Critical and major characteristics and test. Inspection and testing shall be performed with the acceptance

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

inspection equipment, operating instructions, and calibration instructions specified on the Equipment List (EL) (See EL-8817627). When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column of the EL (see 6.1.2).

4.2.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.3 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.3.1 Static load. A 75 pound static weight shall be suspended from the bends of the handling tool. This assembly shall be lifted by the handling tool handle and suspended for a minimum of 1 minute.

4.3.2 Paint adhesion. The test shall be performed on all sections of the warhead section, after a minimum of 24 hours drying unless otherwise specified. Water resistant, pressure sensitive adhesive tape (3/4 inch width) conforming to the requirements of PPP-T-60, Type II or III, Grade A or B, shall be used. Press a 2 inch length of a somewhat longer piece firmly on to a flat or cylindrical surface of the item rubbing out all air bubbles under the tape. Allow approximately 10 seconds for the test area to return to room temperature. Gasp a free end of the tape and at a rapid speed strip it from the item or specimen by pulling the tape back upon itself 180 degrees (in such a manner that the tape is folded back to back during the procedure). Observe for bare spots where the paint is removed. Disregard flecks of paint on tape of removal of paint has not been complete through to the metal.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level. The handling tool shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169 (MU).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

5.1.2 Level C. The handling tool shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169 (MU).

5.2 Packing.

5.2.1 Levels A and C. The handling tool shall be packed in accordance with the applicable instructions contained in MIL-STD-1169 (MU).

5.3 Marking. Marking shall be in accordance with MIL-STD-1169 (MU).

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.2.4.1). Data specified in 4.2.4.1 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.2.4.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 17801, ATTN: SARPA-QA-N-I.

6.4 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-2330 dated 11 December 1961.

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No. NUOR-A017

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.