INCH-POUND
MIL-PRF-22885/81B
28 April 2004
SUPERSEDING
MIL-PRF-22885/81A
20 August 1987


PERFORMANCE SPECIFICATION SHEET

SWITCHES, PUSH BUTTON, ILLUMINATED, 5 AMPERES, 1-LAMP, DRIPPROOF

INACTIVE FOR NEW DESIGN AFTER 20 August 1987

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for procuring the product described herein shall consist of this specification sheet and MIL-PRF-22885.




Action	A
Momentary	2.61
Alternate	2.90

Inches	mm	Inches	mm
.050	1.27	.940	23.88
.625	15.88	1.042	26.47
.660	16.76	1.200	30.48
.730	18.54	2.61	66.29
.750	19.05	2.90	73.66
.890	22.61		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified tolerances are ±.005 (.13 mm).
4. Switches shall mount on .062 (1.57 mm) to .225 (5.72 mm) thick panels.
5. Design configuration is optional within the maximum dimensions specified.

FIGURE 1. Dimensions and configurations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:26Z
Check the source to verify that this is the current version before use.



Inches	mm
.002	0.05
.003	0.07
.005	0.12
.065	1.59
.125	3.06
.45	11.0
.60	14.7
.63	15.4

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. When mounting with keying washer, the tab on the keying washer requires a hole depth of .055. This hole cannot penetrate the panel, or the drip proof integrity of the panel will be lost.

FIGURE 2. Recommended panel mounting hole patterns.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:26Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and configuration: See figures 1 and 2.

Enclosure design: 2 (dripproof)

Temperature characteristics: 1 (-55°C to +85°C).

Vibration grade 2 (10-500 Hz, 10 g peak).

Operation: See Table I.

Color: See table II.

Luminance: see table II.

Display type: C (colored background).

Military part number: See table I.

TABLE I. Military part number.

Military part number M22885/81- Silver contacts	Switch circuitry	Lens color
01R 01G 01Y 01B 01W	2 pole momentary	Red Green Yellow Blue White
02R 02G 02Y 02B 02W	2 pole alternate action	Red Green Yellow Blue White
03R 03G 03Y 03B 03W	4 pole momentary	Red Green Yellow Blue White
04R 04G 04Y 04B 04W	2 pole alternate action	Red Green Yellow Blue White

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:26Z
Check the source to verify that this is the current version before use.

TABLE II. Chromaticity and luminance

Lens color	Color symbol	Chromaticity 1/		Luminace 2/ (foot lamberts)
		x	y	
Red	R	.715 S.L. .650 S.L.	.260 .270 .325 .335	32 minimum
Green	G	.180 .265 .055 .140	.485 .580 .605 .695	12 minimum
Yellow	Y	.580 S.L. .510 S.L.	.380 .400 .455 .470	224 minimum
Blue	B	.220 .220 .080 .080	.280 .365 .280 .365	6 minimum
White	W	.530 .530 .420 .420	.365 .425 .365 .425	170 minimum

1/ Illuminated chromaticity limits based on source illuminate of 2200° Kelvin. The specified chromaticity values are the “X” and “Y” coordinates on the CIE chromaticity bound by the specified coordinates.

2/ Luminance values are based upon using T-1 ¾ lamps which have a calibrated mean spherical candlepower of .34±.02.

Plastic: Shall be capable of meeting UL burning rate code 94HB in accordance with UL-94.

Finish: Bushing and mounting hardware shall have a lusterless finish.

Weight: .125 pound maximum.

Basic switch: In accordance with MIL-PRF-22885/2 (category I or II), part number M22885-2, except may have integral leaf or lever actuators and reverse identification of NO and NC terminals.

Lamps: switch shall accept one T 1-3/4 miniature flange base lamp.

Strength of actuator: Not applicable.

Lamp retention: The lamp shall be held captive within the mounting bushing.

Electrical rating: See table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:26Z
Check the source to verify that this is the current version before use.

TABLE III. Electrical ratings (silver contacts). 1/

Load	Sea level		50,000 feet
	28 V dc	115 V ac, 60 Hz	28 V dc
	Amperes	Amperes	Amperes
Resistive	5	5	5
Inductive	3	5	2.5
Lamp	2.4	1.5	2.4

1/ Silver contacts; Contacts I which the mating surfaces are silver or silver alloy throughout the rated life of the switch.

Quality Assurance”

Qualification: Table IV applies for group submission.

Group B inspection: Not applicable.

TABLE IV. Qualification inspection.

Qualification inspection (MIL-PRF-22885)	Test switch	Other inspections	Extent of approval
Group I (All samples) Visual and mechanical examination 1/ Contact resistance Operating characteristics **Group II** (4 samples) Strength of actuating means 2/ Strength of mounting bushing 2/ Lamp retention Thermal shock Vibration Shock Moisture resistance Dielectric withstanding voltage Operating characteristics Seal Marking visibility **Group III** (2 samples) Salt spray **Group VII** (2 samples) Low-level life Operating characteristics Seal **Group VIII** (2 samples each color) Illuminated colors Luminace Field of view	M22885/81-04x	M22885/81-01x, -02x, -03x (1 sample each) Visual and mechanical examination[Operating characteristics	All Part numbers

1/ Only one sample shall be measured for physical dimensions.
2/ Two sample units only

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:26Z
Check the source to verify that this is the current version before use.

Referenced documents:
MIL-PRF-22885
MIL-PRF-22885/2
MS25081
MS25082
NASM35333
UL94

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5930-1813)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at www.dodssp.daps.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:26Z
Check the source to verify that this is the current version before use.