S-F-695G
INT. AMENDMENT-2(Army-GL)
March 28, 1984

FEDERAL SPECIFICATION

FRYERS, DEEP-FAT (ELECTRIC)

This interim amendment was developed by the U.S. Army Natick Research and Development Center (GL), Natick, MA 01760, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this interim amendment as a valid exception to Federal specification S-F-695G, dated June 25, 1981, and Amendment-1, dated December 15, 1983.

PAGE 3

2.1, under "Federal Specifications": Delete "QQ-S-698 - Steel, Sheet and Strip, Low-Carbon".

PAGE 4

2.2, under "American Society for Testing and Materials (ASTM)": Add "A 366 - Steel, Carbon, Cold Rolled Sheet, Commercial Quality".

PAGE 5

3.4.1, line 2: Delete "QQ-S-698" and substitute "ASTM A 366".

PAGE 6

3.5, line 7, after "(submarine use)": Add "The height of the type VI fryer from the deck to the top of the removable cover shall be 36 ± 1/2 inches."

PAGE 7

3.5.2.2.1, line 4, following "fryer." delete the period and: Add "except that test switches which are used periodically to test the safety thermostat circuit may be located elsewhere provided they are located for safe and convenient access from the front of the fryer."

3.6.1.1, line 3, following "stainless steel": Add "or nickel plated steel".

PAGE 10

3.6.8: Delete and substitute:

FSC 7310

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

PAGE 10 (cont'd)

"3.6.8 Thermostat. An adjustable thermostat shall be provided with a minimum range from 200° to 275°F and a maximum range from 375° to 400°F. The thermostat shall have a positive "OFF" position and be marked at 50 degree intervals. A separate "ON-OFF" switch may be provided in addition to, or in lieu of, the positive "OFF" position to control power to the thermostat. Thermostat and switch shall be located so as to be readily accessible to the operator. The thermostat shall maintain an average temperature of 375 ± 5°F when tested as specified in 4.4.2.1. The temperature amplitude of the thermostat shall not exceed 25°F when tested as specified in 4.4.2.2. Instructions for calibrating the thermostat shall be provided with each fryer (see 3.8.2). The thermostat shall limit the maximum temperature to 425°F."

3.6.8.1, line 6, following "4.4.3": Delete the sentence beginning "In lieu of" and insert: "A means shall be provided to facilitate checking the operation of the over-temperature thermostat by rendering the first thermostat inoperative. A signal light shall indicate when the overtemperature thermostat is operated when tested as specified in 4.4.3."

PAGE 11

3.6.8.1 (cont'd), line 8: Delete "not exceeding 430°F" and substitute "of 430°F through 460°F".

3.6.8.1.1: Delete first sentence and substitute: "For Naval Shipboard use (see 6.2), the deep fat fryer shall be provided with a primary thermostat shunt by pass assembly."

PAGE 12

3.6.9.3, first sentence, following "above": Delete "and shall be capable of recovery to 375°F prior to completion of frying cycle".

PAGE 14

3.9, line 2: Delete "dimensional requirements for fryers shall be as specified in figures 1, 2, and 3 and".

3.9.2: Delete and substitute:

"3.9.2 Legs and mountings. The bottom of the legs for the type I, size 1, type II and type VI fryers shall be provided with holes for the mountings. The type I fryer shall have 3/8 - 16 threaded leg mounting holes. The type II and type VI fryers shall have 9/16 inch diameter leg mounting holes for 1/2 inch diameter bolts. All legs shall be fabricated of stainless steel and the thickness shall not be less than 16 gauge. Legs shall be reinforced without cross bracing to form a rigid assembly."



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

PAGE 15

Add new paragraph:

3.9.11 U.L. requirement. The unique requirement for fryers to be connected to a remote shunt trip disconnect (see 3.6.8.1) is recognized to preclude overall U. L. approval of the complete fryer. In lieu thereof, the fryer shall be constructed of U. L. approved components and in such a manner that the fryer could be U. L. approved upon incorporation of an integral over temperature thermostat control system. When style 2 swing-up heating elements are supplied in fryers, the thermostatic controls may be mounted in the tilting head."

PAGE 17

Table IV, under "Examine" and following "Signal light or lights": Delete listed defect and substitute "Not provided (power "ON" and "overtemperature thermostat" lights)".

PAGE 18

4.2.2.3, line 2, after "and": Add "when required for shipboard use."

PAGE 19

4.4.3: Delete the second and third sentences and substitute: "The first thermostat shall be rendered inoperative in accordance with the manufacturer's operating instructions. The hydrogenated vegetable oil temperature shall be increased until the overtemperature thermostat specified in 3.6.8.1 opens the heating element circuit."

PAGE 20

4.4.3 (cont'd), line 4, after "times": Add a period and delete the remainder of the sentence.

Line 5: Delete "sall" and substitute "shall".

4.4.4.2 (a) last sentence: Delete.

PAGE 23

6.2 (i) line 1, after "3.6.8.1": Add ", 3.6.8.1.1".



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

S-F-695G
Int. Amendment-2(Army-GL)

PAGES 24 and 25

Delete Figures 1, 2 and 3.

Custodian:

Army - GL

Preparing activity:

Army - GL

Project No. 7310-A688



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.