T-M-00566(GSA-FSS)
May 14, 1964

INTERIM FEDERAL SPECIFICATION

MOP, DUSTING, GENERAL USE, WITH DISPOSABLE PADS

This Interim Federal Specification was developed by the Federal Supply Service, General Services Administration, Washington, D.C. 20407, based upon currently available technical information. It has been partially coordinated with industry, but has not been coordinated with government agencies and is subject to modification. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers a general use, dry type dusting mop with disposable pads (rectangular - 22 inches overall length) with handle and handle extension.

1.2 Classification.

1.2.1 Type and grade. Dusting mops shall be of one type and grade.

2. APPLICABLE SPECIFICATIONS AND STANDARDS

2.1 Specifications and standards. The following specifications and standards, of the issues in effect on date of invitation for bids, form a part of this specification to the extent specified herein.

Federal Specifications:

CCC-T-191 - Textile Test Methods.
PPP-B-636 - Box, Fiberboard.

Federal Standards:

Fed. Std. No. 102 - Preservation, Packaging, and Packing Levels.
Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C., 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Preproduction sample. When specified (6.1), before production is commenced, a preproduction sample of the dusting mop shall be submitted to the contracting officer for approval.

3.2 Materials. Material shall be as hereinafter specified. Materials not specifically defined shall be as regularly used by the manufacturer.

3.2.1 Handle and extension. The handle and handle extension shall be wood containing not less than 8 nor more than 12 percent moisture content, and shall be not less than 11/16 inch in diameter. The wood handle shall measure not less than 4 feet overall with an approximate 4 foot handle extension. There shall be a means for attachment of the extension to the handle. The wood handle and extension shall have a baked enamel finish or coated with a clear lacquer, varnish or similar surface preparation. The handle shall be free from imperfections such as warp, decay, knots, checks or any defects which will affect serviceability.

3.2.2 Frame and holder. The mop shall have a frame and pad holder, either constructed as a single integral unit or the frame and holder may be constructed as separate components. The frame shall be permanently and securely attached to one end of the wood handle. When the frame and holder are constructed as separate components, there shall be means for secure attachment of the holder to the frame. The frame and pad holder as an integral unit or as separate components shall be made of non-corrosive metal, or metal treated for non-corrosion, or of rigid and durable plastic material. The pad holder may consist of one or two sections and when assembled shall accommodate one approximately 22 inch front pad or two approximately 11-inch pads (3.2.3) placed end to end to give a 22 inch front for dusting. The pad holder shall have means for secure attachment of disposable pads, including sliding, clipping, tieing or comparable method, so that pads may be easily removed and replaced.

3.2.3 Dusting pads. The dusting pads shall be made of cotton batting, lamb's wool, cotton yarn head, or comparable material, so constructed that a proper dusting operation can be performed, and shall be rectangular.

3.3 *Workmanship. The finished dusting mop shall conform* to the quality of product established by this specification. The occurrence of defects shall not exceed the acceptable quality levels.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Preproduction sample inspection. When required, examination and testing of the preproduction sample shall be made of the completed duster for all the provisions of this specification.

4.3 Inspection for acceptance. Inspection shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated.

4.3.1 Inspection of the end item. The defects found during examination shall be classified in accordance with table I. The lots shall be inspected in accordance with 4.3.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects

Examine	Defect	Classification Major	Minor
Handle and extension	Any knot hole, loose knot, fracture, split or other defect affecting serviceability.	X	
	Not baked enamel finish, coated with clear lacquer, varnish or similar surface preparation.		X
	Dirt or foreign matter imbedded in finish.		X
	Wet or tacky, area of no finish.		X
	Out of round.		X
Frame and holder	Material not as specified.	X	
	Fractured, split or otherwise impaired.	X	
	Rough or sharp places.	X	
	Damaged.	X	
	Holder, when separate component, not securely attached to frame.	X	
	Frame not permanently and securely attached to handle.	X	
	Holder construction inadequate for attachment of pads.	X	
Dusting pads	Rancid or objectionable odor.		X
	Insect infestation.	X	
	Spotted, soiled or stained.		X
	Any weakening material defect such as hole, cut, tear or other defect which will affect serviceability.	X	

4.3.1.1 Inspection levels and acceptable quality levels (AQL's). Inspection levels and acceptable quality levels, expressed in defects per hundred units, shall be as follows:

	Inspection level		AQL
For examination applicable to Table I -	I	Major	2.5
		Total	6.5

All completed dusting mops presented at one time for delivery shall be considered a lot for the purpose of acceptance, inspection and tests. When refill pads are ordered separately, any defect shall be cause for rejection of the entire inspection lot.

4.3.2 Inspection of preparation for delivery requirements. An inspection shall be made to determine that packaging, packing and marking requirements of section 5 of this specification are complied with. Defects shall be scored in accordance with table II below. For examination of contents the sample unit shall be one shipping container fully prepared for delivery selected just prior to the closing operations. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 4.0 defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of Preparation for Delivery Defects

Examine	Defects
Markings (exterior and interior)	Omitted; incorrect; illegible; or improper size, location, sequence, or method of application.
Materials	Any component missing, or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose bands, inadequate sealings. Bulging or distortion of container.

4.4 Testing of the end item. Sample dusting mops selected for tests shall conform to the requirements specified herein. Any deviation from requirements shall be considered cause for rejection of the entire lot. Tests for textile components as applicable, shall be in accordance with methods specified in CCC-T-191.

5. PREPARATION FOR DELIVERY

(For civil agency procurement the definitions and applications of the levels of packaging and packing shall be in accordance with Fed. Std. No. 102).

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.1).

5.1.1 Level A. Twelve complete mops, with handles disassembled, or 72 refill pads (see 6.1), shall be packaged in a box conforming to PPP-B-636, class 2, W5c, style optional. Each box shall be closed in accordance with the appendix to the box specification.

5.1.2 Level B. Twelve complete mops, with handles disassembled, or 72 refill pads (see 6.1), shall be packaged as specified in 5.1.1, except waterproof sealing with tape shall not be required. Closure shall be in accordance with the appendix to the box specification.

5.1.3 Level C. The mops and refill pads shall be packaged in accordance with the suppliers commercial practice.

5.2 Packing. Packing shall be level A, B, or C as specifidd (see 6.1).

5.2.1 Level A. Four unit packages of mops or twelve unit packages of refill pads shall be packed in a box conforming to PPP-B-636, class 2, V3c, style RSC. Each box shall be closed, waterproof sealed with tape and reinforced with bands of filament tape in accordance with the appendix to the box specification.

5.2.2 Level B. Four unit packages of mops or twelve unit packages of refill pads shall be packed as specified in 5.2.1, except that waterproof sealing with tape and reinforcing with bands of filament tape shall not be required. Closure shall be in accordance with the appendix to the box specification.

5.2.3 Level C. The mops and refill pads shall be packed to insure carrier acceptance and safe delivery to destination in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 Marking.

5.3.1 Civil agencies. In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military activities. In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. Purchasers should exercise any desired options offered herein and procurement documents should specify the following:

(a) Title, number, and date of this specification.

(b) When preproduction sample is required (3.1).

(c) When refill pads are ordered separately, specify dimensions (length, width and depth), type of attachment and whether cotton batting, lamb's wool or cotton yarn head.

(d) Applicable levels of packaging and packing (5.1 and 5.2).

GSA DC 84-18158

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.