INTERIM AMENDMENT TO

FEDERAL SPECIFICATION

MOP, DUSTING, COTTON, UNIVERSAL ACTION SWIVEL

This Interim Amendment was developed by General Services Administration, Federal Supply Service, Washington 25, D.C. The primary purpose of this amendment is to change requirements of the steel for the sliding lock key and requirements for the hex nut of construction B mop. The use of this amendment is authorized by GSA for procurement purposes by all Federal agencies as a part of Federal Specification T-M-550a, dated September 19, 1961.

Page 1, paragraph 3.1.2, line 2: Delete the word "type" and substitute the word "construction."

Page 2, figures 1 and 2: Delete the word "Type" and substitute the word "Construction."

Page 3, paragraph 3.1.2.1: Delete the word "Type" and substitute the word "Construction."

Page 3, paragraph 3.1.2.2, line 1: Delete the word "Type" and substitute the word "Construction."

Page 4, paragraph 3.1.2.2.4, first sentence: Delete and substitute: "The sliding lock key shall be cold rolled steel, stainless steel, or cadmium or zinc plated steel, and shall measure 1-5/16 inches long, 3/16 inch thick, and approximately 1/2 inch wide."

Page 4, paragraph 3.1.2.2.6, first sentence: Delete and substitute: "The base plate shall be not less than 17-gauge stainless steel or cadmium or zinc plated steel to resist rust, and shall be not less than 4-1/4 inches in length, and shall be 3-13/32 ± 1/16 inches wide (outside to outside width in the completed form)."

Page 4, paragraph 3.1.2.2.8, first sentence: Delete and substitute: "The base (3.1.2.2.1) of the tee section shall be bolted to the base plate with two 7/32-inch diameter flat-headed bolts and 3/4-inch standard brass hex nuts covered with a durable rubber compound."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

Page 4, paragraph 3.1.2.2.6 - continued.

Fourth sentence: Delete and substitute: "The shank of the socket (3.1.2.2.3) shall be inserted in the upper yoke (3.1.2.2.2.2) and together with the sliding lock key (3.1.2.2.4), attached by a 7/32-inch diameter bolt and 3/4-inch standard brass hex nut covered with a durable rubber compound."

Page 4, paragraph 3.1.3, line 2: Following the word "parts" insert "except the sliding lock key and."

Page 5, paragraph 4.1: Delete and substitute: "4.1 Inspection responsibility. Unless otherwise specified the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements."

Page 5, paragraph 4.3, line 3: Delete the word "type" and substitute the word "construction."

Page 6, table of Classification of Defects, under "Examine": Delete the word "Type" and substitute the word "Construction." Under "Defect", line 19: Delete "cadmium or zinc plated steel" and substitute "steel."

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:19Z
Check the source to verify that this is the current version before use.