T-M-567a
INTERIM AMENDMENT-1
February 11, 1959

INTERIM AMENDMENT TO

FEDERAL SPECIFICATION T-M-567a

MOP, DUSTING, COTTON, RECTANGULAR

AND TRIANGULAR

This Interim Amendment was developed by General Services Administration, Federal Supply Service, Washington 25, D.C. The primary purpose of this amendment is to make immediate corrections of typographical errors and to include requirements for a handle fitting. Until such time when this amendment is promulgated as a regular amendment, the GSA authorizes the use of this document for procurement purposes by all Federal agencies as a part of Federal Specification T-M-567a, dated June 2, 1958.

Pages 2 and 3, following paragraph 3.1.1.3, add the following:

"3.1.1.4 Handle fitting. - The 5/16-inch hole in the ferrule end of the handle, for receiving the fetter drive screw extension shank, shall contain a threaded stamped female fitting made from stainless steel, cadmium plated steel, or copper, and shall be 0.015 ± 0.002 inch in thickness. The female fitting shall have barbs stamped in the sides so that when the fitting is inserted in the handle, it will securely attach itself to the inner wall. The ends of the female fitting shall be bent to form four prongs that fit on the end of the handle and are secured under the lip of the ferrule.

Page 3, paragraph 3.1.2.1, lines 5 and 6: Delete "wood screw by lag screw threaded" and substitute "fetter drive screw".

Page 3, paragraph 3.1.3.2, lines 11 and 15: Delete "24" and substitute"23"

Page 4, paragraph 3.1.3.6, lines 3 and 6: Delete "20 ± 1/4" and "20" respectively, and in both instances substitute "19 ± 1/4 inches".

Page 9, paragraph 5.2.2.1, line 5: Delete "RSC" and substitute "QLC".

FSC 7920

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:19Z
Check the source to verify that this is the current version before use.