
MILITARY SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR-157/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the crystal unit described herein shall consist of this document and the latest issue of Specification MIL-C-3098.

Pertinent characteristics: 0.8 to 20 MHz; fundamental; noncontrolled; series.



INCHES	MM
.002	.05
.008	.20
.030	.76
.317	8.05
.486	12.34
.125	16.42
.757	19.23
.775	19.69
1.500	38.10
.352	8.94

NOTES:
1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. The wire leads shall be tinned, suitable for soldering.

FSC 5955

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:00Z
Check the source to verify that this is the current version before use.

TABLE I. Requirements.

Requirement	Specified value or condition	
Holder	HC-33/U (MIL-H-10056/20)	
Dimensions, marking, and configuration	See figure	
Frequency range	0.8 to 20 MHz, inclusive	
Frequency tolerance	±0.005 percent	
Equivalent resistance	See table III	
Mode of oscillation	Fundamental	
Operating temperature range	-55° to +105° C, inclusive	
Test set, calibration values, and rated drive level	See table II	
Capacitance, shunt	7 pf, maximum	
Shock:	0.8 to 2.0 MHz	2.0 + to 20 MHz
Frequency change permitted	±0.001 percent	±0.0005 percent
Equivalent resistance change permitted	+15 percent	±10 percent
Vibration: 1/	0.8 to 2.0 MHz	2.0 + to 20 MHz
Frequency change permitted	±0.001 percent	±0.0005 percent
Equivalent resistance change permitted	±15 percent	±10 percent
Temperature cycling:	0.8 to 2.0 MHz	2.0 + to 20 MHz
Frequency change permitted	±0.001 percent	±0.0005 percent
Equivalent resistance change permitted	±15 percent	±10 percent
Aging:		
Frequency change permitted	0.0005 percent	

1/ Method 201 of MIL-STD-202.

TABLE II. Test set, calibration values, and rated drive level.

Government reference standard test set	Band of specified frequencies, inclusive	Calibration values			Rated drive level
		Resistance	Crystal current	Resistor voltage drop	
	MHz	Ohms	ma	Volt	mw
TS-330/TSM	0.8 to 1.5	100	10	---	10.0 + 2.0
	1.5+ to 2.25	50	15	---	
	2.25+ to 3.4	40	15	---	
	3.4+ to 5.1	25	20	---	
	5.1+ to 7.5	14	25	---	
	7.5+ to 10	11	30	---	
	10+ to 15	13	20	---	5.0 1.0
TS-683/TSM	15+ to 20	10	--	0.22	5.0 1.0

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:00Z
Check the source to verify that this is the current version before use.

TABLE III. Equivalent resistance.

Frequency range, inclusive	Maximum resistance	Frequency range, inclusive	Maximum resistance
MHz	Ohms	MHz	Ohms
0.8 to 0.85	520	2.12+ to 2.25	150
0.85+ to 0.9	480	2.25+ to 2.6	130
0.9+ to 1	440	2.6+ to 3	90
1+ to 1.12	400	3+ to 3.4	70
1.12+ to 1.25	380	3.4+ to 3.75	52
1.25+ to 1.37	340	3.75+ to 4	45
1.37+ to 1.5	300	4+ to 5	37
1.5+ to 1.62	280	5+ to 7	25
1.62+ to 1.75	250	7+ to 10	20
1.75+ to 1.87	220	10+ to 15	18
1.87+ to 2.0	190	15+ to 20	15
2+ to 2.12	170		

NOTE:

1. This item has the same electrical parameters as the CR-19/U, latest version.

Custodians:
Army - EL
Navy - EC
Air Force - 84

Review activities:
Army - EL, MI, MU, SM
Navy - EC
Air Force - 11, 85
DSA - ES

User activities:
Army -
Navy - AS, MC, SH
Air Force - 17, 19, 84

Preparing activity:
Army - EL

(Project 5955-0403)

☆ U.S. GOVERNMENT PRINTING OFFICE: 1973-713-145 893

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:00Z
Check the source to verify that this is the current version before use.