# MILITARY SPECIFICATION

## BOTTLE, SCREW CAP, IDENTIFICATION, BURIAL

This specification is approved for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 This specification covers one type and size of Bottle, Screw Cap, Identification, Burial containing an instruction sheet.

## 2. APPLICABLE DOCUMENTS

* 2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

| | | |
|---|---|---|
| PPP-B-636 | - | Boxes, Shipping, Fiberboard. |
| PPP-T-45 | - | Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing. |

STANDARDS

MILITARY

| | | |
|---|---|---|
| MIL-STD-105 | - | Sampling Procedures and Tables for Inspection by Attributes. |
| MIL-STD-129 | - | Marking for Shipment and Storage. |
| MIL-STD-147 | - | Palletized Unit Loads for 40" x 48" Pallets. |

(Copies of specifications, standard, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

FSC 8125

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:16Z
Check the source to verify that this is the current version before use.

LAWS AND REGULATIONS

U. S. Postal Service Manual

(Copies of the manual may be obtained from the Superintendent of Documents, U. S. Government Printing Office, Washington, DC 20402.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

* 3.1 Standard product. The burial bottle delivered under this specification shall be the manufacturer's commercial product, except for any changes necessary to comply with specification requirements. All like items furnished on any one contract, including parts and subassemblies thereof, shall be new and interchangeable.

3.2 Materials.

* 3.2.1 Bottle. The bottle shall be made from either a lime or lead flint glass. It shall be colorless, emerald green or amber color. The bottle shall be properly annealed and of such composition that when tested as specified in 4.4.1 and 4.4.2, there shall be no chipping, cracking or showing of scum or corrosion.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:16Z
Check the source to verify that this is the current version before use.

* 3.2.2 Screw cap. The screw cap shall be made from either a melamine or a phenol formaldehyde compound.

* 3.2.3 Liners. The screw caps shall have cemented in rubber liners, poly-seal or equivalent liners, or vinyl liners.

* 3.3 Construction. The burial identification bottle shall be a wide mouth straight side bottle 3-3/4 inches ± 1/8 inch high by 1-1/4 inch ± 1/8 inch outside width. There shall be six screw threads to the inch.

* 3.3.1 Cap to bottle fitness. The bottle and cap shall be constructed to withstand any hand-screwing of the cap without rupture or breakage. The cap shall firmly fit the bottle with screw threads to match those on the bottle.

* 3.3.2 Leakage. Bottles shall not show any evidence of leakage when tested as specified in 4.4.3.

* 3.4 Instruction sheet. The instructions shall be printed or typed on a sheet of white paper, approximately 5 inches by 3 inches, using elite type or equal with the following legend:

BOTTLE, SCREW CAP, IDENTIFICATION, BURIAL;
Federal Stock number 8125-223-7844

Fill out GR Form No. 1, or write identifying information on any suitable piece of paper, seal within the bottle, place bottle in left arm pit, and bury with the body. Wrapping of the body should be secured to prevent movement of the bottle.

When immediate erection of a marker is impracticable, use second bottle containing like information, and place in the grave, in the center at its head; secure to prevent washing away by rain until a marker can be erected.

To effect water-tight closure of the bottle, securely screw cap on bottle, forcing bottle top into liner within cap.

* 3.5 Marking for identification. Each burial bottle shall be permanently and distinctly marked on the bottom with molded or pressed figures showing the supplier's name or trademark of such known character as to be readily identified with the supplier.

3.6 Workmanship. The bottles shall be free from imperfections such as rough seams, edges or surfaces, bubbles, blisters, cracks, nicks,



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:16Z
Check the source to verify that this is the current version before use.

chips, pinholes, scratches or flow lines. The bottles shall be clean and free from grit or any foreign material embedded in the bottle or cap. The bottles shall conform to the quality and grade of product established by this specification. The occurrence of defects shall not exceed the applicable acceptable quality levels established herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Certificate of compliance. Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.2 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.2.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.2.1.1 Testing of components. Tests shall be performed on samples of components and materials used in the fabrication of the end item for the applicable characteristics listed in table I. The sample unit shall be as indicated in table I. The lot size shall be expressed in units of one unfilled cap and bottle. There shall be no failure of any sample unit to meet the requirements as specified. All test reports shall contain the individual values utilized in expressing the final result. The inspection sampling plan shall be as follows:

| Lot size | Sample size |
|---|---|
| 800 or less | 2 |
| 801 to 22,000 inclusive | 3 |
| 22,001 and over | 5 |



Source: https://assist.dla.mil -- Downloaded: 202610-16T13:16Z
Check the source to verify that this is the current version before use.

* 4.2.1.2 Certification. Components and materials listed below may be accepted on the basis of a supplier's certificate of compliance for requirements specified ments specified in applicable paragraphs of this specification:

| Component | Characteristic | Requirement paragraph |
|---|---|---|
| Bottle | Class composition | 3.2.1 |
| Cap liner | Composition | 3.2.3 |



Source: https://assist.dla.mil -- Downloaded: 202610-16T13:16Z
Check the source to verify that this is the current version before use.

TABLE I. Instructions for testing (sample unit)

| Component | Characteristic | Specification reference | | Requirements applicable to | | Number determinations per sample unit | Results reported as | | |
|---|---|---|---|---|---|---|---|---|---|
| | | Requirement | Test method | Sample unit | Lot aver. | | Pass or fail | Numerically to nearest | Sample unit |
| Bottle | Boiling test | 3.2.1 | 4.4.1 | X | - | 1 | X | - | 5 bottles |
| | Sudden heat | 3.2.1 | 4.4.2 | X | - | 1 | X | - | 5 bottles |
| Bottle with screw cap | Leakage | 3.3.2 | 4.4.3 | X | - | Average of 3 | - | 0.1 percent | 5 bottles with screw caps |



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:16Z
Check the source to verify that this is the current version before use.

4.3 Inspection of the end item. The end item shall be examined in accordance with the classification of defects listed in table II. The lot shall consist of all the completed burial bottles offered for inspection at one time. The sample unit shall be one burial bottle.

4.3.1 Visual examination. The burial bottles shall be examined for the defects listed in table II. The inspection level shall be level I with an AQL of 4.0 defects, expressed in terms of defects per hundred units.

TABLE II. Classification of defects

| Examine | Defect |
|---|---|
| Design | Not as specified |
| Appearance | Not symmetrical in shape |
| | Not wide mouth bottle |
| | Not straight side bottle |
| Construction and workmanship | |
| Bottles | Not clear, clean or dry |
| | Not colorless or not of a green or amber color |
| | Any rough seam, edge or surface |
| | Any bubble, blister, crack, nick, chip, pinhole, scratch or flow line |
| | Any dirt, grit or foreign material embedded in bottle or cap |
| Caps | Missing |
| | Do not firmly fit the bottle |
| | Cap and bottle do not withstand hand screwing of cap without rupture or breakage |
| Threads | Not required number per inch as required |
| | Distorted in bottle or cap |
| | Threads in cap do not fit bottle |
| Liners | Liners in caps missing |
| | Not material specified |
| | Not tight fitting |
| Instruction sheet | Omitted |
| | Not in accordance with requirements |



Source: https://assist.dla.mil -- Downloaded: 202610-16T13:16Z
Check the source to verify that this is the current version before use.

* 4.3.1.1 Dimensional examination. Inspection shall be made of the bottle and cap for compliance with specified dimensions. Any dimension that is not within the specified tolerances shall be classified as a defect. The inspection level shall be S-2 with an AQL of 2.5 defects, expressed in terms of defects per hundred units.

* 4.3.2 Examination of preparation for delivery requirements. An examination shall be made to determine that the packaging, packing and marking complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery except that it need not be closed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 with an AQL of 2.5 defects, expressed in terms of defects per hundred units.

| Examine | Defects |
|---|---|
| Markings (exterior and interior) | Omitted; incorrect; illegible; of improper size, location, sequence or method of application |
| Materials | Any component missing, damaged or not as specified |
| Workmanship | Inadequate application of components, such as: incomplete closure of container flaps, improper taping, loose strapping, inadequate stapling<br>Bulged or distorted container |
| Contents | Number of screw cap bottles per package or shipping container is more or less than required |

* 4.3.3 Examination for palletization. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully prepared for delivery. The lot size shall be the number of palletized unit loads in the end item inspection lot. The inspection level shall be S-1 with an AQL of 6.5 defects, expressed in terms of defects per hundred units.

| Examine | Defects |
|---|---|
| Finished dimension | Length, width or height exceeds specified maximum requirement |



Source: https://assist.dla.mil -- Downloaded: 202610-16T13:16Z
Check the source to verify that this is the current version before use.

| Examine | Defects |
|---|---|
| Palletization | Not as specified<br>Pallet pattern not as specified<br>Interlocking of loads not as specified<br>Load not bonded with required straps as specified |
| Weight | Exceeds maximum load limits |
| Marking | Omitted; incorrect; illegible; of improper size, location, sequence, or method of application |

4.4 Test methods.

* 4.4.1 Boiling test. Test specimens of the uncapped glass bottles shall be completely immersed in distilled water in a closed vessel having a small steam vent and boiled continuously at 212 F for 6 hours, boiling water being occasionally added to compensate for evaporation loss. The bottles shall be suspended in the water so that they do not come in contact with the containing vessel. Any bottle which shows corrosion, scumming, chipping or cracking as a result of the boiling, shall be considered as having failed the test and shall be cause for rejection of the lot.

4.4.2 Sudden heat test. Test specimens of the uncapped glass bottles shall be immersed in tap water at 65 ± 5 F and allowed to remain a minimum of 10 minutes for the bottles to reach a uniform temperature of 65 ± 5 F. The bottles shall then be transferred suddenly into a hot water bath, maintained at a temperature of 155 ± 5 F, for a period of 10 minutes. This cycle shall be repeated four times to give a total of five such cycles. The bottles shall be removed from the hot water and cooled slowly before returning to the tap water at 65 F. Cracking or chipping of the bottles during test shall constitute failure and shall be cause for rejection of the lot.

* 4.4.3 Leakage. Bottles shall be capped and placed in a container of water so that they are covered by water for a period of one hour. Any evidence of leakage shall be cause for rejection of the lot.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

* 5.1.1 Level A. Each bottle with cap containing an instruction sheet shall have the cap screwed on finger-tight. Twenty-four bottles of one color only, shall be packaged in a fiberboard box conforming to style RSC, type CF (variety SW), class domestic, grade 175 of PPP-B-636. Each fiberboard box shall be provided with one set of half-slotted, full-height partitions, fabricated from



Source: https://assist.dla.mil -- Downloaded: 202640-16T13:16Z
Check the source to verify that this is the currentversion before use.

the same material as the box, and so designed as to provide individual cells for each bottle. Each set of partitions shall be designed to contain six bottles in length and four bottles in width. The bottles, together with the instruction sheets specified in 3.4, shall be placed upright in the individual cells. Inside dimensions of each fiberboard box shall be 9-1/4 inches in length, 6-1/4 inches in width, and 4 inches in depth. Box closure shall be secured with 2-inch minimum width gummed paper tape conforming to type III, grade A of PPP-T-45.

* 5.1.2 Level C (Commercial Packaging). Bottles with caps containing instruction sheets shall be packaged to afford adequate protection against physical damage during shipment from the supplier to the first receiving activity. The package and the quantity per package shall be the same as that normally used by the supplier for retail distribution.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

* 5.2.1 Level A. Two-hundred and eighty-eight bottles of one color only, packaged as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC, grade V2s of PPP-B-636. Level A packages shall be packed flat, two in length, two in width, and three in depth within the shipping container. Inside dimensions of the shipping container shall approximate 19-3/4 inches in length, 13-3/4 inches in width, and 13-3/4 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed, in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636.

* 5.2.2 Level B. Two-hundred and eighty-eight bottles of one color only, packaged as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC, type CF (variety SW) or type SF, class domestic, grade 275 of PPP-B-636. Level A packages shall be packed flat, two in length, two in width, and three in depth within the shipping container. Inside dimensions of the shipping container shall approximate 19-3/4 inches in length, 13-3/4 inches in width, and 13-3/4 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

* 5.2.2.1 When specified (see 6.2), the shipping container shall be a grade V3c, V3s or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of the container specification.

* 5.2.3 Level C (Commercial Packing). Bottles packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The quantity per shipping container shall be the same as that normally used by



Source: https://assist.dla.mil -- Downloaded: 202640-16T13:16Z
Check the source to verify that this is the currentversion before use.

the supplier for retail distribution. Containers shall comply with the U. S. Postal Service Manual, Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

* 5.3 Palletization. When specified (see 6.2), bottles packed as specified in 5.2, shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract or order, interior packages, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129.

5.4.1 Special marking. The top of each interior package shall be plainly marked in capital letters not less than three-quarters of an inch in height as follows:

READ INCLOSED

INSTRUCTION SHEET

5.4.2 Precautionary marking. Each shipping container shall have fragile marking applied in accordance with MIL-STD-129. In addition, the top of each shipping container shall be plainly marked in capital letters not less than three-quarters of an inch in height as follows:

GLASS

HANDLE WITH CARE

6. NOTES

6.1 Intended use. The Bottle, Screw Cap, Identification, Burial is intended for use as a container for information relative to the identification of a body in the grave until a permanent marker is practical or possible.

* 6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:16Z
Check the source to verify that this is the current version before use.

(c) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
(d) When palletization is not required (see 5.3).

6.3 Marginal notations. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - MS
Air Force - 69

Review activity:

Army - MD

User activity:

Navy - MC

Preparing activity:

Army - GL

Project No. 8125-0367



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:16Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

US ARMY NATICK ~~LABORATORIES~~ Development Center

NATICK, MA 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STSNL-TDG

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

Commander
US Army Natick ~~Laboratories~~ Development Center
ATTN: STSNL-TD G
Natick, MA 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:16Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

Bottle, Screw Cap, Identification, Burial MIL-B-1406C

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:16Z
Check the source to verify that this is the current version before use.