MIL-C-1417F
6 June 1977
SUPERSEDING
MIL-C-1417E
30 December 1970

MILITARY SPECIFICATION

COOK SET, FIELD, 5-MAN

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a 5-man cook set for field use.

2. APPLICABLE DOCUMENTS

* 2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

QQ-A-250/2	-	Aluminum Alloy 3003, Plate and Sheet
PPP-B-26	-	Bag, Plastic, (General Purpose)
PPP-B-636	-	Boxes, Shipping, Fiberboard

MILITARY

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-147	-	Palletized Unit Loads, for 40" x 48" Pallets

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Command, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 7360

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:17Z
Check the source to verify that this is the current version before use.

DRAWINGS

US ARMY NATICK RESEARCH AND DEVELOPMENT COMMAND

2-2-119 - Cook Set, Field, 5-Man; Assembly and Details
2-2-120 - Cook Set, Field, 5-Man; Details

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 167 - Stainless and Heat-Resisting Chromium - Nickel Steel Plate, Sheet, and Strip

A 313 - Chromium-Nickel Stainless and Heat-Resisting Steel Spring wire

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, PA 19103.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036).

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:17Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

* 3.1 First article. When specified (see 6.2) the contractor shall furnish a sample for first article inspection and approval (see 4.3 and 6.3)

3.2 Materials. Materials shall be as specified herein. Materials not definitely specified shall be of the quality normally used by the manufacturer for his cooking outfits provided the completed cooking outfits conform to all provisions of this specification.

3.2.1 Aluminum. Aluminum shall conform to temper O of QQ-A-250/2.

* 3.2.2 Stainless steel. Stainless steel shall conform to type 302 or 304 of ASTM A167 or ASTM A313, as applicable.

3.3 Design and construction. The design and construction of the cook set shall conform to the design, details, dimensions, and material classifications shown on Drawings 2-2-119 and 2-2-120. The cook set shall consist of an outer and inner pot and a body cover.

3.3.1 Pots and cover. The pots and covers shall each be formed from one piece of metal. The pots and covers shall have no seam or welds and shall not be galled by the forming operations. The pots and covers shall have round rolled beads tight enough to prevent the insertion of a 1/64-inch (0.4 mm) feeler gage.

3.4 Finish.

3.4.1 Aluminum. Aluminum parts shall have a uniform frosted finish and all stains, dirt, and watermarks shall be removed.

3.4.2 Stainless steel. Stainless steel parts shall be given a uniform dull frosted finish.

3.5 Identification marking. The letters "U.S." and the manufacturer's name, tradename, or trade-mark of such known character easily identifiable with the manufacturer shall be indented on the pots and cover in the size and location shown on Drawings 2-2-119 and 2-2-120.

Source: https://assist.dla.mil -- Downloaded: 20260-16T13:17Z
Check the source to verify that this is the current version before use.

3.6 Workmanship. The completed cooking outfits shall be clean and free of sharp edges, sharp corners, scratches, burrs, slivers, dents, and deformities.

3.6.1 Rivets. Rivet heads and peened ends shall be round and in full contact with the joined metal surfaces. Rivets shall be tight. There shall be no bent rivets or empty rivet holes.

3.6.2 Application of markings. The surfaces opposite the indented markings shall show no visible signs of penetration, uneveness, or distortion. Markings shall be legible.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

1. First article inspection (see 4.3)
2. Quality conformance inspection (see 4.4)

4.3 First article inspection. When a first article is required, it shall be examined for the defects in table I and for compliance with dimensions specified. The presence of any of the defects listed in table I or any dimension not within specified requirements shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:17Z
Check the source to verify that this is the current version before use.

4.4.2 End item inspection. The inspection lot shall consist of all cook sets offered for inspection at one time. The sample unit shall be one complete cook set.

4.4.2.1 Visual examination. Examination shall be made of the cook sets for the defects listed in table I. The inspection level shall be II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE I. Classification of defects

Examine	Defect	Classification Major	Minor
Finish	Dirty		X
	Aluminum parts stained or have water marks		X
	Parts not frosted, where applicable		X
Construction workmanship	Any component missing	X	
	Seams or welds in pots or covers	X	
	Pots or covers galled		X
	Beads on pots and cover allow insertion of 1/64-inch (0.4 mm) feeler gage	X	
	Sharp edges, sharp corners, burrs, slivers, dents, deformities	X	
Rivets	Heads or peened ends not round		X
	Not in full contact with metal surfaces; loose, bent, or missing	X	
Identification marking	Missing, incomplete, illegible, or not as specified		X
	Distortion or penetration on surface opposite marking	X	

4.4.2.2 Dimensional examination. Examination shall be made to determine compliance with dimensions specified. Any nonconformance shall be considered a defect. The inspection level shall be S-2 with an AQL of 4.0, expressed in terms of defects per hundred units.

4.4.3 Inspection of packaging. An examination shall be made to determine that preservation-packaging and packing, as required by section 5 is complied with. Defects shall be as specified in table II. The sample unit shall be one shipping container fully prepared for delivery except it need not be closed. The lot shall be the number of containers offered for inspection at one time. The inspection level shall be S-2 with an AQL of 4.0, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:17Z
Check the source to verify that this is the current version before use.

TABLE II. Examination of packaging

Examine	Defect
Markings	Missing; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Component missing, damaged, or otherwise defective
Contents	Number per container is more or less than required
Workmanship	Bulged or distorted containers Polyethylene bag closure not heat sealed Air not expelled from bag

4.4.3.1 Examination of shipping containers. When shipping containers are required to be in accordance with PPP-B-636, examination for defects in closure, waterproofing and reinforcing shall be in accordance with the appendix of PPP-B-636.

4.3.3.2 Examination of palletization. When applicable, an examination shall be made to determine that palletization is in compliance with section 5 of this specification. Defects shall be as specified in table III. The sample unit for this examination shall be one palletized unit load ready for shipment. The lot shall be the number of palletized unit loads submitted for inspection at one time. The inspection level shall be S-1 with an AQL of 6.5 expressed in terms of defects per hundred units.

TABLE III. Examination of palletization

Examination	Defect
Finished dimension	Length, width, or height exceeds specified maximum requirements
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Load not bonded with straps specified
Weight	Exceeds maximum load limits
Markings	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:17Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be level A or Commercial as specified, (see 6.2).

5.1.1 Level A. Each cook set, with the inside pot and cover in place and the handles in the closed position, shall be placed in a snug-fitting polyethylene bag conforming to type I, style 1 of PPP-B-26. The film for the polyethylene bag shall be nominal 0.003-inch (0.076 mm) thick. Prior to, or during the final closure operation, excess air within the bag shall be expelled.

* 5.1.2 Commercial. Cook sets shall be preserved-packaged to afford adequate protection against damage during shipment from the supply source to the first receiving activity. The package and the quantity per package shall be the same as that normally used by the contractor for retail distribution.

5.2 Packing. Packing shall be level A, B, or Commercial as specified, (see 6.2).

* 5.2.1 Level A packing. Thirty cook sets, preserved-packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, type SF, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with a liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Level A packages shall be packed flat, three long, two wide, and five deep. The inside dimensions of each shipping container shall approximate 24-1/2 inches (620 mm) in length, 16-1/4 inches (410 mm) in width, and 22 inches (560 mm) in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636.

* 5.2.2 Level B packing. Thirty cook sets, preserved-packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, type CF, variety optional or type SF, class domestic, grade 275 of PPP-B-636. The inside of each fiberboard shipping container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Level A packages shall be packed flat, three long, two wide, and five deep. The inside dimensions of each shipping container shall approximate 24-1/2 inches (620 mm) in length, 16-1/4 inches (410 mm) in width, and 22 inches (560 mm) in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 20260-16T13:17Z
Check the source to verify that this is the current version before use.

* 5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the fiberboard shipping container shall be a grade V3c, V3s, or V4s box, fabricated in accordance with PPP-B-636, and closed in accordance with method III as specified in the appendix of PPP-B-63[illegible].

* 5.2.3 Commercial packing. Cook sets, preserved-packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The quantity per shipping container shall be the same as that normally used by the supplier for retail distribution. Containers shall be in accordance with Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.3 Palletization. When specified (see 6.2), cook sets packed as specified in 5.2, shall be palletized in accordance with Load Type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

* 5.4 Marking. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The cook set covered by this specification is intended for field use by groups of two to five men for cooking rations, heating water, and melting snow.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) When a first article is required for inspection and approval (see 3.1, 4.3 and 6.3).
(c) Selection of applicable levels of preservation-packaging and packing (see 5.1 and 5.2).
(d) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
(e) When palletization is required (see 5.3).

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:17Z
Check the source to verify that this is the currentversion before use.

shall be scored in accordance with Table IV. The sample [illegible]

6.3 First article. When a first article is required, it shall be examined and approved under the appropriate provisions of 7-104.55 of the Armed Services Procurement Regulation. The first article should be a preproduction sample. The first article should consist of one complete cooking outfit. The contracting officer should include specific instructions in all procurement instruments, regarding arrangements for examination and approval of the first article.

6.4 Changes from previous issue. The margins of this specification have been marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) were made to previous issue. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - MC
Air Force - 99

Preparing activity:

Army - GL

Project No. 7360-0102

Review activities:

Army - MD
Navy - YD
DLA-GS

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:17Z
Check the source to verify that this is the current version before use.

...ers shall be packaged ... Bottle and pump...

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS. The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable p... ...cts at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, g... ...rnment activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
MIL-C-1417F - Cook Set, Field, 5-Man

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:17Z
Check the source to verify that this is the current version before use.