MIL-C-1476G
24 August 1988
SUPERSEDING
MIL-C-1476F
23 February 1983

MILITARY SPECIFICATION

CREEPERS, ICE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers adjustable ice creepers.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

V-T-285	-	Thread, Polyester
QQ-S-700	-	Steel Sheet and Strip, Medium and High Carbon
QQ-W-461	-	Wire, Steel, Carbon (Round, Bare, and Coated)
RR-C-271	-	Chains and Attachments, Welded and Weldless
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-T-45	-	Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8465

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:21Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-C-496	-	Clips, End, Strap
MIL-W-530	-	Webbing, Textile, Cotton, General Purpose, Natural or in Colors
MIL-B-543	-	Buckle, Tongueless and Web Strap
MIL-R-3390	-	Rings, Dee
* MIL-L-35078	-	Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage

STANDARDS

FEDERAL

FED-STD-751	-	Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-130	-	Identification Marking of US Military Property
MIL-STD-147	-	Palletized Unit Loads
* MIL-STD-731	-	Quality of Wood Members for Containers and Pallets

* (Copies of specifications, standards, and handbooks required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

* 2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of solicitation.

DRAWING

* US ARMY NATICK RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

5-6-3	-	Creepers, Ice; Assembly and Details

* (Copies of drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:21Z
Check the source to verify that this is the current version before use.

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

A 576 - Steel Bars, Carbon, Hot-Wrought, Special Quality
B 633 - Electrodeposited Coatings of Zinc on Iron and Steel
* D 3951 - Standard Practice for Commercial Packaging

(Copies may be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

* (Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

* 2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

* 3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.3).

* 3.2 Material and components. The material and components shall conform to the requirements specified herein. Materials and components not specifically defined shall be of the quality normally used provided that the completed item complies with all the provisions of this document. (See 6.4.)

3.2.1 Steel.

3.2.1.1 Steel bar and sheet. The steel bar shall conform to 1095 of ASTM A 576 and the steel sheet shall conform to cold rolled, annealed 1055 or 1065 of QQ-S-700.

3.2.1.2 Steel wire. Steel wire shall conform to 1015, hard temper, finish 1 of QQ-W-461.

3.2.2 Webbing. The webbing shall conform to type III, class 4, 5/8 inch width of MIL-W-530. The webbing shall be dyed Olive Drab 7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:21Z
Check the source to verify that this is the current version before use.

3.2.3 Thread, polyester. The polyester thread shall conform to type I or II, class 1, sub-class A of V-T-285. Sizes shall be as follows:

For all stitching except overedging	-	Size FF
For overedging	-	Size E

* 3.2.3.1 Color. The thread shall be dyed Olive Drab S-1 (C.A. 66022) and shall show fastness to weathering equal to or better than the standard sample or equal to or better than a rating of "good".

3.2.4 Chain. Chain for the heel strap shall conform to type I, grade C, class 5, style 2 of RR-C-271.

3.2.5 Rings, dee. The dee rings shall conform to configuration X, class 2, style 1, size 7/8 by 3/4 inch of MIL-R-3390.

* 3.2.6 Buckles. The buckles shall conform to type III, style 2, class 1, size 3/4 inch of MIL-B-543. Alternate buckle as specified on Drawing 5-6-3 may be used.

3.2.7 Clips, end, strap. The strap end clips shall conform to type I, class 1, 5/8 inch of MIL-C-496.

* 3.3 Design and construction. The design and construction of the creepers shall conform in all respects to the requirements specified herein, and on Drawing 5-6-3. Prior to assembly, all sharp edges and burrs shall be removed. Prior to assembly and plating the components made of the steels specified in 3.2.1.1 shall be heat treated to Rockwell C20 to C25.

3.3.1 Quadrants. Quadrants shall be fabricated of steel sheet specified in 3.2.1.1. The ends of the quadrants shall be rolled over the dee ring as shown on Drawing 5-6-3 without cracking or fracturing. The dee ring shall move freely without binding in any position.

3.3.2 Clevis pin. The clevis pin shall be fabricated of steel specified in 3.2.1.1. The pin after assembly to clevis and links shall be peened on the bottom of the link as shown on Drawing 5-6-3. The pin shall fit without looseness, but shall be capable of being turned 360 degrees with a hand tool only for adjustability of creepers.

3.3.3 Clevis, links, adjusting link and washers. The clevis, links, adjusting link and washers shall be fabricated of steel sheet specified in 3.2.1.1, except that chemical composition of steel for washer shall be 1025 steel.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:21Z
Check the source to verify that this is the current version before use.

3.3.4 Spikes. The spikes shall be fabricated of steel specified in 3.2.1.1 and shall be securely attached by fully peening the heads. "B" spikes shall be peened to produce a close fit, but shall allow assembled creepers to be adjusted. "A" spikes shall be peened so as to prevent movement of the spikes in any direction. The peened heads shall be oval shaped without cracks or burrs.

3.3.5 Chain loops. Chain loops shall be fabricated of steel wire specified in 3.2.1.2. After forming, the loop ends shall be butted and then welded. The weld shall not be visible after strap and chain are assembled. Welding shall be complete, sound, smooth, uniform and free from crack, or fracture, burn through or reduced area.

3.3.6 End clips. End clips shall be attached by inserting the webbing the full depth of the clip. The clip shall be flattened so that is is securely attached without cutting the webbing. The webbing at point of entrance, after flattening the clip, shall lie flat.

3.3.7 Stitches, seams and stitching. All stitching shall conform to FED-STD-751 as follows:

For all stitching except overedge stitching	Stitch type 301, 6 to 8 stitches per inch.
For overedge stitching	Stitch type 304, 14 to 16 stitches per inch, or type 503 or 504, 8 to 12 stitches per inch.

* 3.3.7.1 Type 301 stitching. Ends of all stitching shall be backstitched or overstitched 1/2 inch minimum except when caught in other stitching or turned under in a hem. Thread tension shall be maintained so that there will be no loose stitching resulting in puckering of material sewn. The lock shall be embedded in the material sewn.

* 3.3.7.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 1 inch behind the end of the stitching. 1/

b. Thread breaks or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch before the

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:21Z
Check the source to verify that this is the current version before use.

defective area and continue a minimum of 1 inch beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be backstitched.

* 3.3.7.2 Type 304 stitching. For type 304 stitching, thread tension shall be maintained so that there will be no loose or excessively tight stitching. Repairs shall be in accordance with 3.3.7.1.1a or 3.3.7.1.1b except that the stitching shall overstitch the defective stitching area a minimum of three stitches onto the existing stitching.

* 3.3.7.3 Types 503 and 504 stitching. Thread tension shall be maintained so that there will be no loose stitching. All repairs shall be in accordance with 3.3.7.1.1a and 3.3.7.1.1b, except substitute 3/4 inch for 1 inch wherever 1 inch appears.

* 3.3.7.4 Automatic stitching. Automatic stitching machines may be used to perform any of the required stitch patterns provided the requirements of the stitch pattern, stitches per inch, and size and type of thread are met, and at least three tying, overlapping, or backstitches are used to secure the ends of the stitching.

* 3.3.7.5 Thread ends. All thread ends that are visible on the finished item shall be trimmed to a length of not more than 1/4 inch.

3.4 Finish. After heat treatment and before assembly, all metal parts except buckles and end clips, shall be given an electrodeposited zinc coating conforming to type I (with a minimum thickness of 13 micrometers) of ASTM B 633.

3.5 Marking for identification. The creepers shall be permanently and legibly marked for identification in accordance with MIL-STD-130. Prior to zinc coating, the marking shall be indent stamped on each creeper in the location and sizes as shown on Drawing 5-6-3. The marking shall be readily identifiable after the zinc coating has been applied.

3.6 Workmanship. The finished and assembled creepers shall conform to the quality of product established by this document and the occurrence of defects shall not exceed the applicable acceptable quality levels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:21Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

* 4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for assuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

* 4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified or qualified in this document or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:21Z
Check the source to verify that this is the current version before use.

4.4.2 In-process inspection.

4.4.2.1 In-process visual examination. Examination shall be made of the loops, prior to plating and assembly, for defects in table I. The lot size shall be expressed in units of loops. The sample unit shall be one loop. The inspection level shall be S-2 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0 for major defects and 10 for total (major and minor combined) defects.

TABLE I. In-process visual defects

Examine	Defect	Classification Major	Minor
Loops	Not butt welded		X
	Not welded	X	
	Weld not complete and sound	X	
	Weld cracked	X	
	Not free from burned or reduced areas		X
	Rust		X
	Weld not smooth or uniform		X
	Loop contains kink, split, crack, or waviness	X	

4.4.2.2 In-process dimensional examination. Examination shall be made of loops, prior to plating and assembly, for dimensions. The lot size shall be expressed in units of loops. The sample unit shall be one loop. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

* 4.4.3 End item visual examination. The end items shall be examined for the defects listed in table II. The lot size shall be expressed in units of one creeper. The sample unit shall be one creeper. The inspection level shall be II and the AQL, expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

TABLE II. End item visual defects

Examine	Defect	Classification Major	Minor
Finish of metal components	Not finished	X	
	Finish is not as specified, e.g., metal parts (except buckles and clips) are not zinc coated	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:21Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Finish of metal components (cont'd)	Brass buckles and end clips are not chemical black finish	X	
	Finish is not adherent, i.e., is flaking, peeling, or blistering	X	
	Any area of no zinc plating	X	
	Any area of no black chemical finish (brass buckles and clips)		X
	Finish is scratched, scuffed, gouged or otherwise damaged		X
	Not smooth and uniform, e.g., is not continuous or contains pit, nodule or foreign matter		X
	Evidence of burning		X
	Indication that zinc plating was applied prior to completion of all machining, forming, cutting, marking, and welding operations	X	
	Evidence of corrosion	X	
	Not clean		X
Design construction and workmanship, general (applicable to all components and assemblies)	Any component (including washer) missing, split, broken, cracked, or fractured	X	
	Quadrant cracked or fractured at roll over dee ring	X	
	Bent out of shape, malformed, or deformed		X
	Hole (except where required)	X	
	Any required operation not performed or not accomplished as specified, e.g., hole in adjusting link missing, misplaced or not specified size	X	
	Sharp edge where not required		X
	Fin, sliver, or burr		X
Webbing	Not specified color		X
	Edge frayed or scalloped		X
	Cut, tear, or hole	X	
	Spotted or stained		X
Stitches and stitching	Loose tension, resulting in a loosely exposed bobbin or top thread; tight resulting in excessive puckering of fabric		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:21Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects (cont'd)

	Examine	Defect	Classification Major	Minor
	Stitches and stitching (cont'd)	More than 8 or less than 6 stitches per inch (type 301)		X
		More than 16 or less than 14 stitches per inch (type 304)		X
		More than 12 or less than 8 stitches per inch (type 503 or type 504)		X
*		Thread break in stitching, two or more consecutive skipped or runoff stitches not overstitched or overstitch is less than 1 inch before break	X	
		Type 301 stitching not overstitched 1/2 inch or more at end except where ends are turned under in a hem or held down by other stitching		X
		Thread break in type 304, 503, or 504 stitching not overstitched as specified		X
		Ends of automatic stitching are not secured or contain less than 3 tying, overlapping or backstitches		X
		Thread ends not trimmed to 1/4 inch maximum length		X
		Less than specified number of rows of stitching	X	
	Buckles	Not specified type, style, class or size	X	
	Clips	Not specified type, class, or size	X	
	Chain	Chain is permanently twisted or kinked, e.g., cannot be untwisted without use of tool	X	
		Less than specified number of links	X	
		More than specified number of links		X
		Not specified type, grade, class, or style	X	
	Assembly	Spike or clevis pin not peened	X	
		Clevis pin peened on top	X	
		Peening is poorly accomplished, e.g., the peen is not symmetrical, is not oval shaped (spike), or contains a rough, cracked, or sharp edge or not as specified	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:21Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Assembly (cont'd)	"A" spikes can be moved in any direction within the quadrant		X
	Peening of "B" spike does not permit sufficient clearance for adjustment of creeper	X	
	Peening of "B" spike results in excessively loose fit, e.g., is looser than necessary to permit adjustment of creeper		X
	Creeper cannot be adjusted to all lengths permitted by the adjusting link	X	
	Clevis pin is loose, e.g., does not retain creeper in the desired position	X	
	Clevis pin cannot be turned 360° by hand tool		X
	Clevis pin can be turned 360° by hand		X
	Loop or dee ring binds in any position	X	
	Chain, loop and heel strap not assembled as shown on drawing	X	
	Weld visible on loop after strap has been assembled		X
	Clip is not a tight fit to webbing	X	
	Webbing not inserted to full depth of clip		X
	Webbing is not flat at entrance to the clip		X
	Webbing cut or torn by assembly of the clip	X	
	Buckle reversed	X	
	Buckle will not accommodate end clip or strap	X	
	Strap cannot be securely held by buckle	X	
	Buckles are not securely attached or are not in specified locations	X	
Marking	Missing, incomplete, misspelled, illegible, not specified type or size, not applied in specified manner, or not in specified location		X
	Plating or finish removed, damaged or marred by marking		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:21Z
Check the source to verify that this is the current version before use.

* 4.4.4 End item dimensional examination. The end items shall be examined for conformance to the dimensions annotated with asterisks on the drawings. Any annotated dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of creepers. The sample unit shall be one creeper. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

* 4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified.
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping or inadequate stapling. Bulged or distorted container.
Content	Number per container is more or less than required.

* 4.4.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1, and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:21Z
Check the source to verify that this is the current version before use.

Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial (see 6.2).

5.1.1 Level A. Creepers, completely assembled and adjusted to their smallest dimensions, shall be arranged in pairs with spikes nested and straps wound around the two creepers. Ten pairs of creepers shall then be packed in a snug-fitting intermediate fiberboard box conforming to style RSC, type CF (variety SW), class domestic, grade 200 of PPP-B-636. The creepers shall be arranged in two layers of five pairs each within the box. Each box shall be securely closed with 2 inch minimum width gummed paper tape conforming to type III, grade B of PPP-T-45.

* 5.1.2 Commercial. Ice creepers shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B or Commercial as specified (see 6.2).

* 5.2.1 Level A. Sixty pairs of creepers, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, grade V2s of PPP-B-636. Each shipping container shall be closed, in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of PPP-B-636 except that the inspection shall be in accordance with 4.4.5. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B. Sixty pairs of creepers, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Each container shall be closed in accordance with method II as specified in the appendix of PPP-B-636 except that the inspection shall be in accordance with 4.4.5.

5.2.2.1 Weather-resistant fiberboard container. When specified (see 6.2), the fiberboard shipping container shall be a grade V3c, V3s or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of the container specification except that the inspection shall be in accordance with 4.4.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:21Z
Check the source to verify that this is the current version before use.

* 5.2.3 Commercial packaging. Ice creepers preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

* 5.3 Palletization. When specified (see 6.2), creepers packed as specified in 5.2.2 and 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet types shall be type I (4-way entry), type IV or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet pattern shall be in accordance with appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course.

* 5.4 Marking. In addition to any special marking required by the contract or purchase order, intermediate packs, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The creepers are intended to provide an individual with efficient and practical means of traveling over ice-covered and hard crusted snow terrain.

6.2 Ordering data. Acquistion documents should specify the following:

a. Title, number and date of this document.
b. When a first article is required (see 3.1, 4.3, and 6.3).
c. Selection of the applicable levels of preservation and packing (see 5.1 and 5.2).
d. Type and class of unit load required (see 5.2.1).
e. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
f. When palletization is required (see 5.3).

* 6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:21Z
Check the source to verify that this is the current version before use.

* 6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this document (see 3.2).

* 6.5 Subject term (key word) listing.

Creepers
Footwear
Ice
Individual equipment

* 6.6 Changes from previous issue. The margins of this document are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content, irrespective of the marginal notations and relationship to the previous issue.

Custodians:

Army - GL
Air Force - 99

Preparing activity:

Army - GL

Project No. 8465-0992

Review activities:

Air Force - 82
DLA - CT

User activity:

Air Force - 45

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:21Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-1476G	CREEPERS, ICE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 20 Nov 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:21Z
Check the source to verify that this is the current version before use.