INCH-POUND

MIL-P-1394F(AR)
AMENDMENT 4
22 May 1998
SUPERSEDING
AMENDMENT 3
28 February 1990

MILITARY SPECIFICATION

PRIMER, ELECTRIC, M52A3B1

MIL-P-1394 was inactivated after 5 June 1996 for New Design.

This amendment forms a part of Military Specification MIL-P 1394F(AR), dated 23 November 1983, and is approved for use by the U.S. Army Armament, Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.2, Under Product and Packaging Drawings

Add: "and Percussion, M36A2" after 9329662 - Box, Setup. . .Electric, M52A3B1.

Add: "and Percussion, M36A2" after 9329663 - Packing and Marking. . .Electric, M52A3B1.

Add: "and Percussion, M36A2" after 9329663 - Packing and Marking. . .Electric, M52A3B1.

* Add: "1575AS300, Cartridge, 20mm, Target Practice, PGU-27/B"

PAGE 3

2.1.2, Under Inspection Equipment Drawings

* Delete: "7259772 - Holding Fixture Primer Electric Sensitivity"
Substitute: "7259772 - Holding Fixture Electric Primer Testing"

* Delete: "7259783 - Holding Fixture Primer Electric Sensitivity"
Substitute: "7259783 - Holding Fixture Electric Primer Testing (M103)"

* Delete: "7259786 - Holding Fixture Primer Electric Sensitivity"
Substitute: "7259786 - Holding Fixture Electric Primer Testing (M21)"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:14Z
Check the source to verify that this is the current version before use.

Delete:

* "7553436 - Machine, Sensitivity, Testing, Small Arms Ammunition, Electric Primer Assembly"
"11075193 - Counter Chronograph",
"11075194 - Oscilloscope", and
"11075227 - Pulse Firing Unit".

Add: "9392532 - Pulse Firing Test Assy",
"9392553 - P C Card",
"9392534 - Chassis",
"9392535 - Art Work Front/Rear Panels",
"9392536 - Front Panel Layout" and
"9392537 - Rear Panel Layout"
* "11075191 - Probe, Ionization, Assembly"
"12597836 - Operating and Calibration Instructions for Pulse Firing Test Assy"

Delete: "9392553 - PC Card" and substitute "9392533 - PC Card".

PAGE 15

4.4.2.5, Title block, add: "and Percussion, M36A2" after Electric, M52A3B1.

PAGE 16

4.4.2.6, Title block, add: "and Percussion, M36A2" after Electric, M52A3B1.

PAGE 17

4.4.2.7, Title block, add: "and Percussion, M36A2" after Electric, M52A3B1.

PAGE 19

4.4.3, TABLE III, Under Test Equipment Number

Add: "or 9392532, 9392533, 9392534, 9392535, 9392536, 9392537, 12597836" after 11075284.

Add: "or 9392532, 9392533, 9392534, 9392535, 9392536, 9392537, 12597836" after 7553436.

Delete: "11075193, 11075194, 11075227"
Substitute: "9392532, 9392533, 9392534, 9392535, 9392536, 9392537, 12597836" after 11075192.

* Delete:

"Electric primer sensitivity 4/ 800 800 7553436 8/ 9/ 3.7/4.5.4"

Substitute:

"Electric primer sensitivity 4/ 800 800 11075192 8/ 9/ 3.7/4.5.4"

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:14Z
Check the source to verify that this is the current version before use.

PAGE 20

* Delete: "9/ Use applicable holding fixtures as indicated below in lieu of 7553437 and 7553438 as shown on 7553436.

a. Holding fixture, primer
b. Holding fixture, primed case (M103)
c. Holding fixture, primed case (M21)"

Substitute: "9/ Ionization probe assembly, 11075191, is not required when performing the Primer Sensitivity Test"

PAGE 21

* 4.5.7 Function and Casualty - Delete in its entirety and substitute the following:

"4.5.7 Function and Casualty. The method of test shall be as specified in AMCR-715-505, Volume 8. The test sample primers shall be inserted into cases that have been previously inspected for depth and diameter of primer pocket and length to shoulder basic diameter. The sample primed cases shall be assembled as Cartridges, 20MM, Target Practice, M55A2, conforming to Dwg. D7258817; or Target Practice, PGU-27, conforming to Dwg 1575AS300. Prior to firing the test cartridges shall be inspected for depth of primer seating, primer crimp missing, loose primer, metal slivers on case head or primer, profile and alignment max., and presence of foreign matter on the primer button. The sample test cartridges shall be fired, at ambient temperature, in bursts of 50 rounds in the quantities and weapons as specified in the table below. The gun barrel(s) shall be at ambient temperature at the beginning of each burst.

Accepted primers will be used in	M61 Weapon (5500 SPM, min)	M39 Weapon(1400 SPM, Min)
20mm PGU Ammunition:	300	
All other 20mm Ammunition:		300*
Primer First Article Test:		1100*

*Customers, through the procuring activity, may substitute the M61 Weapon for acceptance of primers that will be used to fulfill their orders."

PAGE 23

6.2 Delete in its entirety and substitute the following:

"6.2 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit designs as required to Commander, ARDEC, ATTN: AMSTA-AR-QAC-C, Picatinny Arsenal, NJ 07806-5000."

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:14Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire contract irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1305-0190)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:14Z
Check the source to verify that this is the current version before use.