INCH-POUND

MIL-DTL-1462G (GL)
25 August 2025
SUPERSEDING
MIL-B-1462F
6 January 1988

DETAIL SPECIFICATION

BELT, GENERAL OFFICER'S

This document is approved for use by all Departments and Agencies of the Department of Defense (DoD).

1. SCOPE

1.1 Scope. This document covers a leather belt for General Officer's.

1.2 Classification. The belt is of one (1) type in the sizes as specified.

1.2.1 Sizes. The belt is available in the following sizes:

Schedule of sizes.

28	34	40
29	35	41
30	36	42
31	37	43
32	38	44
33	39	45
		46

Comments, suggestions, or questions on this document should be sent to trpsptctstandardiz@dla.mil. Since contact information can change, verify the currency of the address information using Acquisition Streamlining and Standardization Information System (ASSIST) online database https://assist.dla.mil.

AMSC N/A FSC 8440

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:20Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

FEDERAL STANDARDS

FED-STD-311 - Leather, Methods of Sampling and Testing

COMMERCIAL ITEM DESCRIPTIONS

A-A-50178 - Wax, Machine Stitching
A-A-59963 - Thread, Polyester

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-DTL-10884 - Fasteners, Snap
MIL-DTL-32068 - Leather, Cattlehide, Strap, Vegetable Tanned
MIL-B-40006 - Buckle, General Officers' Belt, Gold Plated

(Copies of these documents are available online at https://quicksearch.dla.mil)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation or contract.

DRAWINGS

U.S. ARMY, DEVCOM – SOLDIER CENTER

2-4-54 - Belt, General Officer's; Assembly, Details and Sections

(Copies of drawings are available from the U.S. Army, DEVCOM – Soldier Center, ATTN: FCDD-SCD-PE, 10 General Greene Avenue, Natick, MA 01760-5019)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:20Z
Check the source to verify that this is the current version before use.

(Comments, suggestions, or questions on this document should be addressed to:
U.S. Army, DEVCOM – Soldier Center, ATTN: FCDD-SCD-PEC, 10 General Greene Avenue, Natick, MA 01760-5019)

OTHER GOVERNMENT DOCUMENTS AND PUBLICATIONS

(Copies of specifications, standards, drawings and publications required by contractors in connection with specification procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

AMERICAN ASSOCIATION OF TEXTILE CHEMISTS AND COLORISTS (AATCC)

AATCC EP8 - Evaluation Procedure for AATCC 9-Step Chromatic Transference Scale

(Copies of these documents are available online at https://aatcc.org)

AMERICAN SOCIETY FOR QUALITY (ASQ)

ASQ/ANSI Z1.4 - Sampling Procedures and Tables for Inspection by Attributes

(Copies of this document are available online at https://asq.org)

ASTM INTERNATIONAL

ASTM D5053 - Standard Test Method for Colorfastness to Crocking of Leather
ASTM D6193 - Standard Practice for Stitches and Seams

(Copies of these documents are available online at https://www.astm.org)

2.4 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Unless a specific exemption has been obtained, nothing in this document supersedes applicable laws and regulations.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.3.1.

3.2 Conformance inspection. When specified, a sample shall be subjected to inspection in accordance with 4.3.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:20Z
Check the source to verify that this is the current version before use.

3.3 Standard sample. Unless otherwise indicated, the finished belt shall match the standard sample for shade and appearance and shall be equal to or better than the standard sample with respect to all characteristics for which the standard sample is referenced (see 6.2).

3.4 Recycled, recovered, environmentally preferable, or biobased materials. Recycled, recovered, environmentally preferable, or biobased materials should be used to the maximum extent possible, provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs.

3.5 Design. The design shall be in accordance with Drawing 2-4-54.

3.6 Materials.

3.6.1 Basic material. The basic material shall be full grain cattlehide side leather and shall be chrome tanned, vegetable tanned, or combination tanned with chrome and vegetable tanning agents. The area of the leather side shall be a maximum of 22 square feet. The leather shall be drum dyed and finished shade Black 111 having a two-way boarded appearance and shall match the standard sample (see 4.6.1). The thickness of the leather components shall be as specified on the drawing. All exposed raw edges of the leather in the belt shall be stained to match the color of the grain surface of the leather. The leather shall be tested in accordance with 4.5 for resistance to dry and wet crocking. Staining for dry crocking shall be a minimum of 4.5 and for wet crocking a minimum of 4.0 when tested as specified in 4.5.

3.6.2 Secondary material. The filler strip shall be vegetable tanned cattlehide leather conforming to Type II or III, Class 2 of MIL-DTL-32068 except that the leather shall be flesh splits. The thickness of the filler strip shall be as specified on Drawing 2-4-54. The color shall be natural, and no finish shall be applied. Requirements applicable to colorfastness, cracking, breaking force, and elongation are not applicable.

3.7 Components.

3.7.1 Thread, polyester. The thread shall be Black AA, C.A. 66043, conforming to Type I, Class 1, Subclass C and Size 3 of A-A-59963.

3.7.2 Tape, pressure-sensitive adhesive, 5/8-inch wide. The tape shall be made from a woven base fabric weighing 3 to 4 ounces per square yard and 5/8-inch in the width.

3.7.3 Wax, stitching. The wax shall be black, or clear, or other color as specified in the contract or procurement documents and conform to A-A-50178.

3.7.4 Fasteners, snap. The snap fasteners shall conform to Style 2A, Finish 3 of MIL-DTL-10884. The button and eyelet shall be of sufficient length to ensure a secure clinch.

3.7.5 Staples. The staples shall be 18-gauge cadmium plated steel wire or stainless steel. The stapling machine shall be pre-set to form staples approximately 3/8-inch wide and 3/16-inch leg length. The staples shall be securely clinched.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:20Z
Check the source to verify that this is the current version before use.

3.8 Marking.

3.8.1 Size marking. The belt size shall be indented in the leather on the inner side of belt upon the facing in the character size and in the location shown on Drawing 2-4-54. No other brands or marks shall appear upon the belts.

3.9 Construction. The construction shall conform in all respects to Drawing 2-4-54 and as specified herein.

3.9.1 Stitches, seams and stitching. All stitching shall conform to stitch type 301 of ASTM D6193, with 6 to 8 stitches per inch. Stitching shall be performed on a machine using the hot wax specified in 3.7.3. Thread tension shall be maintained so that there will be no loose stitching resulting in a loose bobbin or top thread or no excessively tight stitching resulting in puckering of the material sewn. The lockstitch will be embedded in the center of the material sewn. All thread ends shall be trimmed to a maximum length of 1/4-inch. Ends of seams and stitching, except on the keeper, when not caught in other seams or stitching shall be overstitched one (1) stitch.

3.9.1.1 Repairs of type 301 stitching. Repairs of stitching shall be as follows:

a. When thread breaks or bobbin run outs occur during sewing, the stitching shall be repaired by restarting the stitching one (1) stitch back of the end of stitching.

b. Thread breaks or two (2) or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start one (1) stitch back of the defective area and continue one (1) stitch beyond the defective area onto the existing stitching. Loose or tight stitching shall be repaired by removing the defective stitching without damaging the material and restitching in the required manner. 1/

1/ When making the above repairs, the ends of stitching are not required to be backstitched.

3.10 Setting of Style 2A snap fasteners. The male or female part of the fastener shall be hole punched smaller than the outside diameter of the fastener tube before inserting so that the tube can be forced through the hole. The fasteners shall be securely clinched.

3.11 Replacement of defective components. During the spreading, cutting, and manufacturing process, components having material defects or damages that are classified as defects in 4.4 shall be removed from production and replaced with non-defective and properly matched components.

3.12 Sizes and finished measurements. The finished belt shall conform to the measurements as specified on Drawing 2-4-54. The belt shall be measured lying flat with face side up.

3.13 Workmanship. The finished belt shall be uniform in quality and shall conform to the quality of product established by this specification. The occurrence of defects as specified in 4.4 shall not exceed the criteria specified in the contract or purchase order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:20Z
Check the source to verify that this is the current version before use.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3.1)
b. Conformance inspection (see 4.3.2)

4.2 Inspection conditions. Unless otherwise specified, excluded, amended, modified or qualified in this specification or applicable procurement documents (see 6.2), all inspections shall be performed in accordance with all the requirements of referenced documents.

4.3 Types of inspections.

4.3.1 First article inspection. The first article, submitted in accordance with 3.1 shall be inspected for appearance, color, finished measurements listed on Drawing 2-4-54, examination for defects in 4.4. If first article is required for the belt, it shall be in accordance with 4.3.1, shall be inspected, examined for appearance, color (see 3.6.1 - 3.6.2), and finished defects as specified in Table I.

4.3.2 Conformance inspection. Conformance inspection shall include the examination of 4.4 through 4.5 as applicable. Sampling for inspection shall be performed in accordance with ASQ/ANSI Z1.4 and with acceptance quality limits as specified in the contract or procurement documents, except where otherwise indicated (see 6.2). FED-STD-311 shall be used for leather sampling.

4.4. Visual examination. The finished belt shall be examined for the defects listed in Table I. The lot size shall be expressed in units of belts. The sample unit shall be one (1) belt.

TABLE I. End item visual defects.

Examine	Defect	Classification	
		Major	Minor
Color and finish of of grain cattlehide leather	Black color does not compare favorably with approved sample or color seriously not uniform affecting appearance	101	
	Color not uniform affecting appearance but not seriously		201
	Not specified boarded finish		202
Thread	Not specified color	102	
Cleanliness	Any permanent stain or spot clearly noticeable, that cannot be removed	103	
	Any spot or stain removable with cleaning agent		203
	Not as specified	104	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:20Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects. – Continued

Examine	Defect	Classification	
		Major	Minor
Belt size	Not as specified		204
Material, general	Any component not fabricated of the specified material	105	
Quality of grain cattlehide leather	Not full grain	106	
	Any hole, cut, or rupture:		
	- seriously affecting serviceability or appearance	107	
	- affecting serviceability or appearance but not seriously		205
	Damage to grain of leather, boney or brittle leather:		
	- seriously affecting serviceability or appearance	108	
	- affecting serviceability or appearance but not seriously		206
	Scar tissue (e.g., badly healed, scratch or brand), abraded grain, flanky leather, heavy fat wrinkle:		
	- seriously affecting serviceability or appearance but not seriously	109	
	- affecting serviceability or appearance but not seriously		207
	Distinct difference in grain structure between leather parts of an assembly		
	- seriously affecting appearance	110	
	- affecting serviceability or appearance but not seriously		208
	Loose or pipey leather:		
	- seriously affecting appearance	111	
	- affecting serviceability or appearance but not seriously		209
Construction and workmanship	Any component or assembly omitted or misplaced, operation omitted or not properly performed: (e.g., belt loop positioned at angle that affects proper closure; snap fastener reversed in assembly of belt)		
	- seriously affecting serviceability or appearance	112	
	- affecting serviceability or appearance but not seriously		210

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:20Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects. – Continued

Examine	Defect	Classification	
		Major	Minor
Construction and workmanship - cont'd	Any part fractured, ripped, punctured, torn, defective, malformed, or damaged:		
	- seriously affecting serviceability or appearance	113	
	- affecting serviceability or appearance but not seriously	114	
	Belt not fabricated with grain side of leather or exterior surfaces		211
	Edges and laps of leather parts not edged and stained as specified or irregularly edged and stained affecting appearance	115	212
	Any part not skived where required		
	Not constructed with proper number of leather pieces		213
Metal components	Any snap fastener or staple not securely set or clinched	116	
	Snap fastener too tightly clinched resulting in cutting of leather	117	
	Snap fastener does not function properly, i.e., fails to snap close, provide a secure closure, or open freely	118	
	Incorrect style snap fastener NOTE: The fastener shall be snapped and unsnapped twice to determine whether parts of fastener separate freely and also effect a secure closure.	119	
	Any sharp burr or metal sliver	120	
Stitches, seams and stitching	Not specified stitch type		214
	Spacing of stitching irregular or not as specified		
	- seriously affecting serviceability or appearance	121	
	- affecting serviceability or appearance but not seriously		215
	Loose stitch tension resulting in a loosely secured seam	122	
	More than three (3) continuous lockstitches exposed on surface of leather but the seam is tight		216
	Tight stitch tension, e.g., stitches rupture leather	123	
	Any row of stitching omitted	124	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:20Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects. – Continued

Examine	Defect	Classification	
		Major	Minor
Stitches, seams and stitching - cont'd	Four (4) or five (5) stitches per inch		217
	Less than four (4) stitches per inch	125	
	More than eight (8) stitches per inch, damaging leather	126	
	Thread ends not trimmed as specified	127	
	Any open seam		218
	Repair of seam not as specified		219
	NOTE: A seam shall be classified as open when one (1) or more stitches joining a seam are broken or when two (2) or more consecutive skipped or run-off stitches occur		
Marking	Missing; incomplete; incorrect; not legible, not specified size, not, in proper location, not accomplished as specified		220

4.4.1 Dimensional examination. The belts shall be examined for conformance to the dimensions specified on Drawing 2-4-54. The lot size shall be expressed in units of belts.

4.5 End item and component testing. The belt materials shall be tested for the characteristics listed in Table II. The methods of testing specified wherever applicable and as listed in Table II shall be followed. All test reports shall contain the individual values utilized in expressing the final results. The leather sampling shall be in accordance with FED-STD-311.

TABLE II. End item and component testing.

Material	Characteristic	Requirement paragraph	Test Method
Leather cattlehide	Colorfastness to crocking: Wet and Dry	3.6.1	ASTM D5053 and EP8

4.6 Methods of inspection.

4.6.1 Visual shade matching (all Classes). The color and appearance of the belt shall match the standard sample when viewed using the AATCC EP 9, Option C, (see 6.6) with a primary light source simulating the spectral quality of average daylight, CIE Illuminant D65, with a color temperature of 6500 (± 200) Kelvin (K) illumination of 100 (± 20) foot candles. Alternatively, the color and appearance of the belt shall match the standard sample with a primary light source simulating artificial daylight, CIE Illuminant D75, with a color temperature of 7500K (± 200) illumination of 100 (± 20) foot candles in lieu of D65. (See 6.6.1). The belt shall also be a good match to the standard sample with a secondary source simulating the spectral quality of incandescent lamplight, CIE Illuminant A, with a color temperature of 2856K (± 200).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:20Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES.

6.1 Intended use. The belt is intended to be used with the gold plated buckle specified in MIL-B-40006 and worn by General Officer's.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Sizes required (see 1.2.1).
c. The specific issue of individual documents referenced (see 2.2).
d. When first article is required (see 3.1).
e. Inspection conditions (see 4.2).
f. Performance inspection with acceptance quality limits (AQL) (see 4.3.2).
g. Packaging (see 5.1).

6.3 First article. When a first article inspection is required (see 3.1), it will be inspected and approved under the appropriate provisions of FAR 52.209-4. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Standard sample. For access to samples and pattern drawings, address the contracting activity issuing the invitation for bids or request for proposal.

6.5 Certificate of compliance. The contracting activity may select to accept a certificate of compliance for that specified requirement.

6.6 Visual shade matching. In 2017, Option A of AATCC Evaluation Procedure 9, Visual Assessment of Color Difference of Textiles was changed to Option C. NOTE: In case of confusion, the viewing geometry should be "The specimen plane and illumination source will be parallel to each other and aligned so that the light flux is incident at the center of the specimen plane, which is set at a 35 (± 5°) angle relative to the horizontal. The observer will view the specimens at a 90° angle, relative to the plane of the specimens".

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:20Z
Check the source to verify that this is the current version before use.

6.6.1 In 2022, the U.S. Military (All Services) accepted D65 as the new preferred light source for visual shade matching due to the supply chain issues with D75. DD1222's should reflect which light source is used. If the light source is not indicated on the DD1222, D65 will be assumed by the Government Shade Laboratory.

6.7 Subject term (key word) listing.

Accessory
Cattlehide
Leather
Trousers
Uniform

6.8 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Army - GL

Review activities:
Air Force - 11

Preparing activity:

Army - GL

(Project 8440-2025-003)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:20Z
Check the source to verify that this is the current version before use.