MIL-F-1461H
31 December 1985
SUPERSEDING
MIL-F-1461G
23 May 1974

MILITARY SPECIFICATION

FRAME SECTIONS, TENT, MAINTENANCE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers the frame sections of the maintenance tent. The complete maintenance tent frame consists of one section No. 1 (bottom), one section No. 2 (middle), and one section No. 3 (top).

1.2 Classification. Sections of the frame shall be classified as follows (see 6.2):

Section No. 1 - Bottom (consists of three arch assemblies).
Section No. 2 - Middle (consists of four eave strut assemblies).
Section No. 3 - Top (consists of one ridge pole assembly).

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

QQ-S-700 - Steel Sheet and Strip, Medium and High Carbon

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to U.S. Army Natick Research and Development Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8340

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:19Z
Check the source to verify that this is the current version before use.

QQ-S-741 - Steel, Carbon: Structural Shapes; Plates; and Bars
QQ-S-763 - Steel Bars, Wire, Shapes, and Forgings, Corrosion-Resisting
QQ-S-781 - Strapping, Steel, and Seals
TT-C-490 - Cleaning Methods for Ferrous Surfaces and Pretreatments for Organic Coatings
TT-E-529 - Enamel, Alkyd, Semigloss
TT-P-636 - Primer Coating, Alkyd, Wood and Ferrous Metal
PPP-S-760 - Strapping, Nonmetallic (and Connectors)

MILITARY

MIL-C-52950 - Crates, Wood, Open and Covered

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-1186 - Cushioning, Anchoring, Bracing, Blocking and Waterproofing; with Appropriate Test Methods

DRAWINGS

U.S. ARMY NATICK RESEARCH AND DEVELOPMENT CENTER

5-4-205 - Frame Sections, Tent, Maintenance; Illustration
5-4-206 - Front View
5-4-207 - Side View
5-4-208 - Section No. 1 and Section No. 2
5-4-209 - Section No. 3
5-4-210 - End Post Assembly and Details
5-4-211 - Right and Left Truss Assembly and Details
5-4-212 - Right and Left Truss Details
5-4-213 - Ridge Pole Half Assembly and Cross Sections
5-4-214 - Ridge Pole Details
5-4-215 - Ridge Pole Details and Coupling Link Assembly and Details
5-4-216 - Ridge Pole Knee Brace Assembly and Details
5-4-217 - Truss Brace Assembly and Details
5-4-218 - Eave Strut and Details
5-4-219 - Eave Strut Knee Brace Assembly and Details

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:19Z
Check the source to verify that this is the current version before use.

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

AMERICAN IRON AND STEEL INSTITUTE (AISI)

Steel Specialty Tubular Products

(Application for copies should be addressed to American Iron and Steel Institute, 150 East Forty-Second Street, New York, NY 10017.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 108 - Steel Bars, Carbon, Cold Finished, Standard Quality
A 512 - Cold-Drawn Buttweld Carbon Steel Mechanical Tubing
A 513 - Electric-Resistance-Welded Carbon and Alloy Steel Mechanical Tubing
A 519 - Seamless Carbon and Alloy Steel Mechanical Tubing
A 569 - Steel, Carbon (0.15 Maximum, Percent), Hot-Rolled Sheet and Strip, Commercial Quality
A 575 - Merchant Quality Hot-Rolled Carbon Steel Bars
A 582 - Free-Machining Stainless and Heat-Resisting Steel Bars, Hot-Rolled or Cold-Finished
D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified, a sample shall be subjected to first article inspection (see 4.2, 6.2, and 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:19Z
Check the source to verify that this is the current version before use.

* 3.2 Materials. Materials shall conform to the referenced documents and requirements specified herein. Where materials are not definitely specified, they shall be of the quality and type normally used by the manufacturer, provided that the completed item complies with all provisions of this document. Recycled material may be used (see 6.4).

3.2.1 Carbon steel.

* 3.2.1.1 Sheet and strip. Steel sheet and strip shall conform to hot rolled, commercial quality in accordance with ASTM A 569 and hot rolled in accordance with QQ-S-700, as applicable.

* 3.2.1.2 Bar. Steel bar shall conform to either ASTM A 108 or ASTM A 575.

3.2.1.3 Angles. Steel angles for the end post clip shall conform to QQ-S-741.

* 3.2.1.4 Tube. Steel tube shall conform to ASTM A 512, ASTM A 513, or ASTM A 519.

3.2.2 Corrosion-resisting steel.

* 3.2.2.1 Bar. Corrosion-resisting steel bar shall conform to class 430 of QQ-S-763 or type 430F of ASTM A 582, as applicable.

3.2.2.2 Tube. Corrosion-resisting steel tube shall conform to American Iron and Steel Institute (AISI) type 304 or 430 (see 2.2).

3.2.3 Bolts, nuts, rivets and washers. Bolts, nuts, rivets, and washers shall be of the materials, kind, and size specified in the drawings. Where carbon steel is specified, the part shall be cadmium or zinc plated in accordance with the manufacturer's practice for these commercial items.

3.2.4 Primer. The primer shall conform to composition G or L, as applicable, of TT-P-636.

3.2.5 Enamel. The enamel shall be olive drab color No. 24087 and shall conform to class A or B, composition G or L, as applicable, of TT-E-529.

3.3 Design and construction. The frame sections Nos. 1, 2, and 3 are designed to provide a support for the maintenance tent that is 25 feet 8 1/2 inches long by 13 feet 5 inches high by 17 feet 10 inches wide. The construction of the frame sections shall conform to Drawings 5-4-205 through 5-4-219 and as specified herein. After assembly, spacers and bolts, as applicable, shall be staked or peened as shown on the applicable drawing. The frame sections shall be capable of being erected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:19Z
Check the source to verify that this is the current version before use.

3.3.1 Welding. All welding shall be complete, sound, smooth, uniform, and free from burn-through area, pits, slag inclusion, porosity, crack, fracture, weld spatter, flash, or excess flux deposit. Rough or projecting edges shall be ground smooth prior to finishing.

3.3.2 Riveting. All rivets shall be securely and neatly set or attached as indicated on Drawing 5-4-210.

3.3.3 Optional construction. At the option of the contractor, commercial seamless or electric welded steel square tube, 2 inches by 2 inches by 0.083 inch wall thickness, will be permitted in lieu of the 2 inches by 2 inches by 0.0747 inch wall thickness formed square steel tube identified on referenced drawings. The optional tube shall conform to the chemical composition of the formed tube specified on the drawings.

3.4 Finish of frame sections. After complete fabrication of the metal components of the frame sections, all surfaces shall be thoroughly cleaned and treated by any method and type of TT-C-490. All threads of bolts and nuts shall be protected from primer, enamel, and damage by a commercial thread protector or covering. All exposed surfaces, except cadmium-plated steel spring pins, shall be given a coat of primer specified in 3.2.4. The prime coat shall be allowed to dry prior to the application of the enamel. All primed surfaces shall be thoroughly coated with enamel specified in 3.2.5. The enamel coating shall level out to an adherent continuous uniform film and shall be free from blisters, peeling, flaking, area of no film, scratch, scuff, dig, abrasion, gouge, soft run, dirt, or foreign matter embedded in finish, and wet or tacky paint. The contractor shall touch up areas of finish damaged during examination, erection, and disassembly of the frame sections.

3.5 Marking for identification. One of the assemblies of each frame section shall be permanently and distinctly stamped or marked in a suitable place. Pressure sensitive labels (mylar or its equal) are permitted. The name of the manufacturer, brand, or mark of such known character as to be identifiable with the manufacturer and the number and year of the contract shall be in characters a minimum of 1/2 inch in height. The marking shall be legible after enameling. No other brands or marking shall be shown on the frame sections.

3.6 Workmanship. Components of the frame sections shall be free from split, puncture, burrs, rough and sharp edges, and shall not be bent out of shape. Fastening strap of right end post shall be semiloose, as shown on Drawing 5-4-210, and shall be capable of rotating on rivet shaft. Threads of bolts and nuts shall not be stripped or damaged.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:19Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3. First article inspection. When a first article is required, the frame sections shall be examined in accordance with table II, 4.4.3.2, and 4.4.3.3. The presence of any visual, dimensional, or frame section erection defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.2 In-process inspection. Examination shall be made during the manufacturing process for the requirements listed in table I to establish that no deviation is made from the indicated requirements. Whenever a nonconformance is noted, correction shall be made to affected items and process.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:19Z
Check the source to verify that this is the current version before use.

TABLE I. In-process examination

Requirement, operation, or assembly	Requirement reference
Welds are complete, sound, smooth, uniform, and free from burn-through area, pits, slag inclusion, porosity, crack, fracture, weld spatter, flash, or excess flux deposit	3.3.1
Rough and projecting edges are ground smooth prior to finishing	3.3.1
Cleaning and treatment of surfaces of components prior to application of primer	3.4
Application of primer prior to enameling	3.4
Drying of prime coat prior to application of enamel	3.4

4.4.3 End item inspection. The frame sections shall be examined for visual defects, proper dimensions, and defects in erecting. Unless otherwise specified, the inspection lot shall be all of the frame sections No. 1 (bottom), No. 2 (middle), or No. 3 (top), as applicable, that are submitted for inspection at one time. The sample unit for this inspection shall be one frame section No. 1 (bottom), No. 2 (middle), or No. 3 (top), as applicable.

* 4.4.3.1 Visual examination. Visual examination shall be made of the frame sections for defects listed in table II. The inspection level shall be I, and the acceptable quality level (AQL) shall be 15 for major defects, 40 for major and minor A defects combined, and 100 for total combined major and minor defects, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:19Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects.

Examine	Defect	Classification		
		Major	Minor A	Minor B
Finish of exposed surfaces (except spring pins and threads of bolts and nuts)	Not finished	101		
	Color of finish is not as specified			201
	Coating is not adherent (e.g., is blistered, peeled, or flaky)			202
	Coating is not continuous (i.e., not coated or area of no film):			
	a. Area greater than 1/2 sq. in. exposing bare metal	102		
	b. Area 1/2 sq. in. or less exposing bare metal		203	
	c. Area greater than 1 sq. in. exposing prime coat			204
	Scratch, scuff, dig, abrasion, or gouge:			
	a. Greater than 2 inches in length exposing bare metal	103		
	b. 2 inches or less in length exposing bare metal		205	
	c. Greater than 1 inch in length exposing prime coat			206
	Finish is not dry (i.e., wet or tacky to touch)			207
	Dirt or foreign matter is embedded in finish			208
	Soft run			209

NOTE: Defects in finish attributable to inspection or flexing of movable joints during examination will not be scored as a defect. However, the contractor shall touch up areas of finish damaged during inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:19Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects - Continued

Examine	Defect	Classification		
		Major	Minor A	Minor B
Construction and workmanship	Component is missing	104		
	Component is not specified type or size		210	
	Any part or component is not fabricated of applicable referenced material	105		
	Spacer or bolt is not staked or peened as shown on applicable drawing		211	
	Component is split, punctured, malformed, deformed, fractured, or bent out of shape:			
	a. Affecting serviceability	106		
	b. Not affecting serviceability		212	
	Component misplaced or not in proper alignment		213	
	Any functional component is inoperative or will not operate as intended, such as:			
	- fastening strap not capable of rotating on rivet shaft			214
	- retaining nut of braces not capable of turning freely		215	
	Any operation is omitted or not properly performed (e.g., weep hole missing where required)		216	
	Connection or joining not as specified or attachment is poorly accomplished		217	
	Assembly hole is missing, not oval (slotted), or not round as required	107		
	Burr, rough or sharp edge			218
	Sharp corner not broken or rounded where required			219
	Stripped or damaged threads of bolt or nut		220	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:19Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects - Continued

Examine	Defect	Classification		
		Major	Minor A	Minor B
Construction and workmanship (continued)	Threads of bolt or nut are not protected from primer and enamel with covering or protector (e.g., evidence of paint)			221
	Spring pin is not protected from primer or enamel (e.g., evidence of paint)			222
Welding	Weld (other than tack or spot) is missing where required	108		
	Tack or spot weld is missing where required		223	
	Not type specified	109		
	Incomplete or unsound	110		
	Not smooth or not uniform			224
	Burn-through area, pits, slag inclusion, or porous	111		
	Crack, fracture, or otherwise not fused	112		
	Flash or excess flux deposit has not been removed			225
	Rough or projecting edges are not ground smooth			226
Pins and rivets	Pins are not chamfered where required		227	
	Hole for spring pin is missing, misplaced, or not the specified size		228	
	Pin is not securely attached		229	
	Rivet is not peened or not attached as specified		230	
	Rivet is not adequately peened or not attached (e.g., may become detached)			231
	Rough or sharp edges resulting from peening rivets			232

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:19Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects - Continued

Examine	Defect	Classification		
		Major	Minor A	Minor B
Identification markings	Missing		233	
	Not specified type or size			234
	Illegible, incorrect, incomplete, or not affixed in the specified manner			235

4.4.3.2 Dimensional examination. Examination shall be made of the frame sections to determine compliance with dimensional requirements on drawings. Any dimension not within the specified requirements shall be classified as a defect. The inspection level shall be S-1, and the AQL shall be 15, expressed in terms of defects per hundred units.

4.4.3.3 Examination of frame sections for defects in erection. When complete maintenance-tent frames (section Nos. 1, 2, and 3) are acquired, samples of each section shall be selected and erected to determine facility of assembly and the fit of mating parts. Defects shall be scored in accordance with table III. The inspection level shall be S-1, and the AQL shall be 6.5, expressed in terms of defects per hundred units.

TABLE III. Examination for defects in erection

Examine	Defect
Assembly	Any subassembly that cannot be connected or joined with companion assembly
	Not readily assembled (i.e., assembling requires realignment of parts, drilling or enlargement of holes, use of drift pin or other mechanical means)
	Assembly hole is missing or misplaced

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:19Z
Check the source to verify that this is the current version before use.

TABLE III. Examination for defects in erection - Continued

Examine	Defect
Assembly (continued)	
	Special tool is required to effect assembly Buckles, bent out of shape, or otherwise damaged Any component missing (check all bolts, nuts, pins, and washers) Component too loose or does not fit properly in mating component Component out of alignment
NOTE:	The contractor shall touch up areas of finish damaged during erection and disassembly of the frame sections.

4.4.4 Packaging inspection. An examination shall be made to determine that preservation, packing, and markings are in compliance with the section 5 requirements. Defects shall be as specified in table IV. The lot shall be the number of containers offered for inspection at one time. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2, and the AQL shall be 15, expressed in terms of defects per hundred units.

TABLE IV. Packaging inspection

Examine	Defect
Marking	Missing, incorrect, illegible, or of improper size, location, sequence, or method of application
Materials	Any nonconforming component, component missing, damaged, or otherwise defective

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:19Z
Check the source to verify that this is the current version before use.

TABLE IV. Packaging inspection - Continued

Examine	Defect
Workmanship	Arch assembly is not folded as specified and secured with the fastening strap Barrier material is not properly applied where required Truss brace is loose in bundle Strapping on bundle is not applied as specified Eave strut knee brace or ridge pole assembly is not folded as specified and not secured with tape or ties Skid is not applied as specified
Content	Number of components per bundle or container is more or less than required

5. PACKAGING

5.1 Preservation. Packaging shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Frame section No. 1 (bottom). Each arch assembly shall be compactly folded and secured with the fastening strap provided. The ends of the folded arch assembly shall be wrapped or cushioned with neutral, waterproof barrier material suitable to prevent damage to finish. Three folded arch assemblies shall be placed adjacent to each other to form a bundle. The three truss braces shall be positioned within the bundle in such a manner as to prevent movement during transit. Each bundle shall then be strapped with two flat steel straps not less than 5/8 by 0.020 inch conforming to type I, finish A of QQ-S-781 placed around the bundle and positioned approximately 12 inches in from each end. Alternatively, nonmetallic strapping conforming to type II, not less than 5/8 by 0.030 inch of PPP-S-760, may be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:19Z
Check the source to verify that this is the current version before use.

5.1.1.2 Frame section No. 2 (middle). Each eave strut assembly the knee brace folded parallel to the strut and secured with tape wire ties. The ends of the folded eave strut assembly shall be wr cushioned as specified in 5.1.1.1. Four folded eave strut assembl placed adjacent to each other to form a bundle and then strapped a in 5.1.1.1.

5.1.1.3 Frame section No. 3 (top). The right half ridge pole a shall be folded parallel to the left half ridge pole assembly. Th ridge pole knee brace assemblies shall be folded parallel to the f pole to form a bundle and secured with tape or plastic wire ties. the folded ridge pole assembly shall be wrapped or cushioned as sp 5.1.1.1. The bundle shall be strapped as specified in 5.1.1.1.

* 5.1.2 Commercial. The frame sections shall be preserved in acc ASTM D 3951.

5.2 Packing. Packing shall be level A or Commercial, as specif 6.2).

5.2.1 Level A packing.

* 5.2.1.1 Frame section No. 1 (bottom). One frame section No. 1, as specified in 5.1, shall be packed in a nailed wood unsheathed c conforming to type II, style A of MIL-C-52950, except that t iz shall be waived and lumber dimensions shall be as follows: The en not less than 1 1/8 inches thick, with cleats not less than 3 5/8 by 1 1/8 inches thick; the sides shall be full sheathed and made o less than 3/4 inch thick. The top and bottom shall consist of fiv members not less than 5 5/8 inches wide by 3/4 inch thick, with on adjacent to each end and three equally spaced and four diagonal br less than 3 5/8 inches wide by 3/4 inch thick, one located at each between the cross members. Anchoring of contents, closure, and st shall be in accordance with the appendix of MIL-C-52950. Alternat anchoring of contents may be in accordance with MIL-STD-1186.

5.2.1.2 Frame section No. 2 (middle). One frame section No. 2, as specified in 5.1, shall be packed in a nailed wood crate as spe 5.2.1.1, except that top and bottom shall consist of four cross me three diagonal braces.

5.2.1.3 Frame section No. 3 (top). One frame section No. 3, pr specified in 5.1, shall be packed in a nailed wood crate as specif 5.2.1.1, except that top and bottom shall consist of four cross me three diagonal braces.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:19Z
Check the source to verify that this is the current version before use.

* 5.2.2 Commercial packing. The frame sections, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Marking. In addition to any special marking required by the contract or purchase order, shipping containers shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The metal tent frame sections are designed to support the maintenance tent specified in MIL-T-10069 that is used for housing motor vehicles undergoing repair.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Section required, as applicable (see 1.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).

* 6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for inspection and approval of the first article.

* 6.4 Recycled material. The contractor is encouraged to use recycled material when practical, provided that it meets the requirements of this document (see 3.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:19Z
Check the source to verify that this is the current version before use.

6.5 Changes from previous issue. The margins of this document are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - NU
Air Force - 99

Preparing activity:

Army - GL

Project No. 8340-0468

Review activities:

Air Force - 82
DLA-CT

User activities:

Navy - MC
Air Force - 45

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:19Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DOD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
US Army Natick Research and Development Center
Natick, Massachusetts 01760

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Center
ATTN: STRNC-ES
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:19Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-F-1461H	Frame Sections, Tent, Maintenance

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 1 Apr 84

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:19Z
Check the source to verify that this is the current version before use.