MIL-M-1519D
26 September 1986
SUPERSEDING
MIL-M-1519C
31 December 1968

MILITARY SPECIFICATION

MUZZLE, DOG, LEATHER

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers leather dog muzzles.

1.2 Classification. Muzzles shall be of the following types as specified (see 6.2):

Type I - Standard, all purpose muzzle
Type II - Safety muzzle (attack training only)

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Documents. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

V-T-285 - Thread, Polyester

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3770

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:23Z
Check the source to verify that this is the current version before use.

FF-R-556	- Rivet, Solid, Small; Rivet, Split, Small; Rivet, Tubular, Small; Flat Washer (Burr); and Cap, Rivet; General Purpose
KK-L-201	- Leather, Cattlehide, Lace, and Cut Laces
QQ-P-416	- Plating, Cadmium (Electrodeposited)
PPP-B-601	- Boxes, Wood, Cleated-Plywood
PPP-B-636	- Boxes, Shipping, Fiberboard
PPP-F-320	- Fiberboard: Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes

MILITARY

MIL-L-35078	- Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For
MIL-W-43061	- Wax, Machine Stitching

STANDARDS

FEDERAL

FED-STD-751	- Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	- Marking for Shipment and Storage
MIL-STD-147	- Palletized Unit Loads
MIL-STD-731	- Quality of Wood Members for Containers and Pallets

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

2-4-60	- Muzzle, Dog, Leather, Type I; Assembly and Details
2-4-73	- Muzzle, Dog, Leather, Type II; Assembly and Details

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:23Z
Check the source to verify that this is the current version before use.

* 2.2 Other publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 545 - Steel Wire, Carbon, Cold-Heading Quality, for Machine Screws
D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal Agencies.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Alternate components. Components offered as equivalent to components specified herein and on the referenced drawings as a specific manufacturer's part number or equal shall be functionally equal to the manufacturer's part number identified, and of equal or better quality. The incorporation and inclusion of such a component in the design of the specified end product shall not require modification or change to any other specified component and shall not reduce ease of maintenance to it or any other components, unless such modification or change is specifically approved by the contracting officer. Prior to manufacture of the preproduction sample or, if none, the initial production unit, the contractor shall submit for the contracting officer's approval a list identifying each proposed alternate component, together with proof that each listed component complies with requirements specified above. The contracting officer, at his option, may require a physical sample of the proposed substitution. Approval of the submitted listing, together with the necessary supporting data, authorizes the commencement of manufacture of the preproduction sample or initial production unit, as applicable, and does not relieve the contractor of the responsibility that these components perform in

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:23Z
Check the source to verify that this is the current version before use.

accordance with specified requirements when incorporated into the end product. All items delivered under one contract shall be identical in quality, materials, design, and workmanship.

3.2 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.3).

3.3 Materials and components.

* 3.3.1 Leather. The leather shall be commercial, vegetable tanned or combination tanned with vegetable and alum or vegetable and chrome tanning agents. The leather shall be in the form of backs, natural color, in the thickness specified on Drawings 2-4-60 and 2-4-73. The leather shall meet the elongation and breaking force requirements of KK-L-201, except that elongation for 7/64 and 8/64 inch thick leather shall be measured under a load of 140 pounds, and breaking force value for 7/64 and 8/64 inch thick leather shall be not less than 210 pounds.

* 3.3.2 Thread, polyester. The thread for all stitching shall conform to type I, class 1, subclass C, size 3, or, as an alternate, unwaxed type II, class I, size 3 thread conforming to V-T-285. The thread shall be shade S-1 (Cable No. 66022) and shall show fastness to weathering equal to or better than the standard shade sample (see 6.4).

3.3.3 Gum tragacanth. The gum tragacanth for burnishing edges and laps of leather shall be a natural commercial grade No. 3.

3.3.4 Wax (machine stitching). The wax shall be golden color conforming to type II of MIL-W-43061.

3.3.5 Buckles, center-bar. The 5/8 inch and 3/4 inch center-bar buckles with imitation roller shall be malleable iron, nickel plated and shall conform to No. 414, North and Judd Manufacturing Co.; No. 414, Covert Manufacturing Co.; or equal.

* 3.3.6 Rivets with caps. Tubular rivets shall conform to type XII, class 1, grade E, 9/64 inch nominal diameter, and caps shall conform to type II of FF-R-556, except that the rivets and caps shall be fabricated from low carbon, condition 3 steel of ASTM A 545. Rivets and caps shall be given a cadmium-plated finish in accordance with class 2, type II of QQ-P-416. The length of the rivets shall be such as to provide a secure clinch.

3.3.7 Steel reinforcement. The strip steel reinforcement shall be fabricated from cold-rolled steel in the design and dimensions shown on Drawing No. 2-4-60.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:23Z
Check the source to verify that this is the current version before use.

3.4 Construction. The muzzles shall be constructed as shown on Drawings 2-4-60 and 2-4-73 and as specified herein.

3.4.1 Stitching. All stitching shall conform to type 301 of FED-STD-751, 5 to 7 stitches per inch. Stitching shall be performed on a machine using hot stitching wax specified in 3.3.4. The use of cold liquid wax or prewaxed thread is not permitted. Thread tension shall be maintained so there is no loose stitching, and the lock shall be embedded in the sewn materials. All thread ends shall be securely tied and fused. Where two or more consecutively skipped stitches occur, they shall be overstitched not less than 1 inch.

3.4.2 Finishing. The leather shall be edged and finished in accordance with material specified in 3.3.3.

3.5 Marking. The letters "US", manufacturer's name, and year of manufacture shall be stamped in the size characters and in the locations shown on Drawings 2-4-60 and 2-4-73.

* 3.6 Workmanship. Leather components shall be clean and free of unspecified holes, cuts, tears, or defects such as brand marks, grub holes, scar tissue, hip marks, brittle or bony areas, abrasions, scratches, flanky, spongy, or stretchy leather, or fat wrinkles. The leather shall be full grain or full grain lightly snuffed, and the flesh side shall be smooth and free from loose flesh. Buckles, rivets, caps, and steel reinforcement shall have no rough edges.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirement in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:23Z
Check the source to verify that this is the current version before use.

contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.2 and 4.4.3. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

* 4.4.1.1 Leather examination. An examination shall be made to determine that the leather is backs and is a natural color. Any nonconformance shall be cause for rejection of the leather.

* 4.4.2 End item visual examination. The end item shall be examined for defects in table I. The lot size shall be expressed in units of muzzles. The sample unit shall be one muzzle. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

TABLE I. End item visual defects

Examine	Defect	Classification	
		Major	Minor
Leather	Not full grain, or not full grain lightly snuffed	X	
....	Any hole, except where specified	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:23Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects - Continued

Examine	Defect	Classification	
		Major	Minor
Leather - continued	Any cut or rupture	X	
	Brand mark, open grub hole, scar tissue, hip mark, brittle, or bony area	X	
	Abraded, scratched, or other grain damage		X
	Flanky, spongy, or stretchy leather	X	
	Fat wrinkles	X	
	Flesh side not smooth or contains loose flesh		X
	Not skived where required		X
	Not edged or irregularly edged		X
Hardware	Any hardware component broken or malformed	X	
	Rough edges, burrs, or slivers; protecting finish omitted or corroded	X	
Buckles	Unsound casting (i.e., porous, warped, cracked, fractured, or contains blow holes or sink marks)	X	
	Body or tongue malformed or bent out of shape	X	
Tubular rivets and caps	Loosely set (i.e., shank not fully spread and anchored within cap)	X	
	Not set straight (i.e., one side of head or cap embedded in leather)		X
	Rivet inserted from wrong side (i.e., cap on inside)		X
Construction and workmanship	Any component missing	X	
	Any buckle strap assembly not as specified	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:23Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects - Continued

Examine	Defect	Classification	
		Major	Minor
Seams and stitching	Loose stitch tension resulting in a loosely secured seam, or locks exposed on surface of leather	X	
	Tight stitch tension (i.e., stitches rupture or cut leather)	X	
	Any row of stitching omitted	X	
	One stitch less than minimum specified		X
	Two or more stitches less than minimum specified	X	
	One or more stitches in excess of maximum specified	X	
	Thread ends not tied and trimmed		X
	Any open seam	X	
	NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken, or two or more consecutive skipped stitches or run-offs occur.		
Cleanness	Grease or oil stains		X
Marking	Omitted, incomplete, incorrect, not legible, not specified size, not in proper location, or not accomplished as specified		X

* 4.4.3 End item dimensional examination. The end item shall be examined for location of all rivets as specified on the applicable drawing. The contractor shall include in his quality control/inspection plan in-process examination(s) for dimensions with the following minimum requirements to be accomplished on a sampling basis acceptable to the contracting officer or his representative. The lot size shall be expressed in units of muzzles of one

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:23Z
Check the source to verify that this is the current version before use.

type. The sample unit shall be one muzzle. Any deviation from the specified requirements shall constitute a defect. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

Length, width, and thickness of all straps
Size and location of holes and slots, including holes on the steel reinforcement
Length, width, and thickness requirements of the nose cover and reinforcement cover
Size and location of cutouts on the nose section
Thickness and length (from radius) of the steel reinforcement pieces
Location of fold lines on the nose/buckle straps
All straps should be included in the sampling plan(s)

4.4.4 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Open and noncontinuous heat-sealed seam of polyethylene bag Omission of vent hole in polyethylene bag Bulging or distorted container
Content	Number of intermediate containers is more or less than specified Number of muzzles per intermediate container is more or less than specified 1/

1/ For this defect one intermediate container shall be examined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:23Z
Check the source to verify that this is the current version before use.

4.4.5 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1, and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Load not bonded with required straps as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Unit packing. Each muzzle shall be neatly folded to approximate dimensions of 6 by 6 by 3 inches. Each folded muzzle shall be inserted in a snug-fitting flat or square style clear polyethylene film bag of 0.001-inch minimum thickness. The polyethylene bag shall be formed with heat sealed seams that are straight, continuous, and parallel to each other and to the formed edges of the bag. The bag closure shall be effected by heat sealing with the heat seal as close as possible to the open end. A 1/4-inch diameter hole shall be made at one corner of each bag to allow excess air to escape. Alternatively, a mechanical tie (e.g., paper or plastic covered soft steel wire or aluminum band) shall be applied to close the bag opening.

5.1.1.2 Intermediate packing. Five unit packs shall be placed in a snug-fitting fiberboard box conforming to grade W5c of PPP-B-636. Boxes shall be of same size and shall be closed in accordance with the appendix of the PPP-B-636.

* 5.1.2 Commercial. Muzzles shall be preserved in accordance with ASTM D 3951.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:23Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

* 5.2.1 Level A packing. Unless otherwise specified (see 6.2), muzzles of one type only, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC, grade V2s of PPP-B-636. Level A packages shall be packed flat, five in length, three in width, and six in depth within a shipping container. Inside dimensions of each shipping container shall be approximately 30 inches in length, 18 inches in width, and 18 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed, waterproofed, and reinforced with flat strapping or tape banding in accordance with the appendix of PPP-B-636. Larger quantities of muzzles may be packed in overseas type of PPP-B-601. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Ninety muzzles, of one type only, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC, type CF or SF, variety SW, class domestic, grade 275 of PPP-B-636. Level A packages shall be packed flat, five in length, three in width, and six in depth within a shipping container. Inside dimensions of each shipping container shall be approximately 30 inches in length, 18 inches in width, and 18 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall be closed in accordance with method II in the appendix of PPP-B-636.

5.2.2.1 Weather-resistant shipping container. When specified (see 6.2) the fiberboard shipping container shall be grade V3C or V3s fiberboard box, fabricated in accordance with PPP-B-636 and closed in accordance with the appendix of PPP-B-636. The box material may also be grade V4s of PPP-F-320.

* 5.2.3 Commercial packing. Muzzles, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

* 5.3 Palletization. When specified (see 6.2), muzzles, packed as specified in 5.2.2 and 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, II, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. The pallet pattern shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:23Z
Check the source to verify that this is the current version before use.

* 5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, intermediate packs, shipping containers and palletized loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

5.4.1 Polyethylene bagged unit packs. Polyetheylene bagged unit packs shall have the required information specified in 3.5 legibly printed or stamped in black directly on the bag across the center face or on a white paper label inserted within the bag so as to permit ready identification. The bag or label shall indicate the following information:

Stock number
Nomenclature
Quantity

6. NOTES

6.1 Intended use. The muzzles are intended for use by dog training centers.

* 6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Type of muzzle required (see 1.2).
c. When a first article is required (see 3.2., 4.3, and 6.3).
d. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
e. Level A requirements when other than as specified (see 5.2.1).
f. Type and class of unit load required (see 5.2.1).
g. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
h. When palletization is required (see 5.3).

* 6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

6.4 Standard sample. For access to a standard shade sample of thread, address the contracting activity issuing the invitation for bids.

6.5 Attack training use. For attack training, only the Safety Muzzle or equal may be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:23Z
Check the source to verify that this is the current version before use.

* 6.6 Subject term (key word) listing.

Dog
Leather
Muzzle

6.7 Changes from previous issue. The margins of this document have been marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content, as written, irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Air Force - 99

Review activities:

Army - MD
Air Force - 84
DLA - CS

User activity:

Navy - MC

Preparing activity:

Army - GL

Project No. 3770-0128

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:23Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
US Army Natick Research and Development Center
Natick, Massachusetts 01760

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Center
ATTN: STRNC-ES
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:23Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-M-1519D	Muzzle, Dog, Leather

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 1 Apr 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:23Z
Check the source to verify that this is the current version before use.