MIL-T-1547E
28 December 1983
SUPERSEDING
MIL-T-1547D
4 June 1973

MILITARY SPECIFICATION

THIMBLES, ROPE (SOLID)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers one type of cast malleable iron rope thimble.

1.2 Classification. Rope thimbles shall be of the following sizes, as specified (see 6.2 and 6.3).

Size - 1-1/2 inches
Size - 1-3/4 inches
Size - 2 inches
Size - 2-1/4 inches
Size - 2-1/2 inches
Size - 3 inches

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-621 - Boxes, Wood, Nailed, and Lock-Corner

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Center, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 4030

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:24Z
Check the source to verify that this is the current version before use.

PPP-B-636 - Boxes, Shipping, Fiberboard

MILITARY

MIL-L-10547 - Liners, Case and Sheet, Overwrap, Water-Vapor-proof or Waterproof, Flexible

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

DRAWINGS

US ARMY NATICK RESEARCH AND DEVELOPMENT CENTER

4-1-105 - Thimbles, Rope (Solid)

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A-47 - Malleable Iron Castings
D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:24Z
Check the source to verify that this is the current version before use.

3.2 Materials (see 6.5). The materials shall conform to the applicable document and requirements specified herein.

3.2.1 Iron casting, malleable. The malleable iron, zinc-coated, galvanized castings shall conform to A-47.

3.3 Construction. The rope thimbles shall be cast of material specified in 3.2.1, to the dimensions shown on Drawing 4-1-105 and as specified herein.

3.4 Marking for identification. All thimbles shall be marked with the manufacturer's name, trade name or trade mark, and rope size in characters 1/32-inch high minimum. The markings shall be depressed and cast integrally and legible.

3.5 Workmanship. The finished thimble shall be smooth, clean, sound and free from any crack, burr, sharp edge, lump, blister, and uncoated area.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.2 and 4.4.3. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:24Z
Check the source to verify that this is the current version before use.

4.4.2 End item visual examination. The end item shall be examined for the defects listed below. The lot size shall be expressed in units of one thimble. The sample unit shall be one thimble. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0 for major defects and 10.0 for total (major and minor combined) defects.

Examine	Defect	Classification Major	Minor
Construction and workmanship	Not smooth or sound	X	
	Not clean		X
	Crack or sharp edge	X	
	Burr, lump, blister		X
	Blistered or uncoated area	X	
Identification markings	Missing, incomplete, illegible, or incorrect		X

4.4.3 End item dimensional examination. The end item shall be examined for conformance to the dimensions specified on the drawing. Any dimension not within the specified tolerance shall be classified as a defect. The sample unit shall be one thimble. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.4 Packaging inspection. An examination shall be made to determine that preservation, packing and marking comply with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully packaged with the exception that it need not be closed. Examination of closure defects listed below shall be made on shipping containers fully packaged. The lot size shall be the number of containers in the inspection lot. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Material	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components such as incomplete closure of container flaps, improper taping, loose strapping, or inadequate stapling, bulged or distorted container

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:24Z
Check the source to verify that this is the current version before use.

Examine	Defect
Contents (exterior and interior container)	Weight per container is more than specified

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A. Thimbles of one size only, shall be packed in the most compact manner in a intermediate fiberboard box conforming to style RSC, type CF, variety SW, or type SF, class domestic, grade 200 of PPP-B-636. The weight of contents for each box shall not exceed 20 pounds. Closure shall be in accordance with PPP-B-636.

5.1.2 Commercial. The thimble shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

5.2.1 Level A packing. Thimbles of one size only, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style FTC, V2s of PPP-B-636, except that the weight limitations shall be waived; or a nailed wood shipping container conforming to class 2, style 2 or 4 of PPP-B-621. Each nailed wood shipping container shall be provided with a type I or II, grade C case liner conforming to MIL-L-10547. The weight of contents for shipping containers shall not exceed 120 pounds. Each shipping container shall be closed and reinforced with strapping or tape banding in accordance with the appendix of the applicable container specification.

5.2.2 Level B packing. Thimbles of one size only, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style FTC, type CF, variety DW, class domestic, grade 350 of PPP-B-636, or nailed wood container conforming to class 1, style 2 or 4 of PPP-B-621. Each fiberboard shipping container shall be closed and reinforced as specified in 5.2.1. The weight of contents of each shipping container shall not exceed 120 pounds.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix thereto.

5.2.3 Commercial packing. Thimbles preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Marking. In addition to any special marking required by the contract or purchase order, intermediate packs and shipping containers shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:24Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The rope thimble covered by this document is for use with Military tent lines and other similar equipment.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number and date of this document.
(b) Size of thimble required (see 1.2).
(c) When a first article is required (see 3.1, 4.3 and 6.4).
(d) Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
(e) Whether weather-resistant class fiberboard shipping containers are required for level B packing (see 5.2.2.1).

6.3 Thimble sizes. The following are the compatible rope and thimble sizes:

Rope diameter (inches)	Rope thimble size (inches)
5/16	1-1/2
3/8	1-3/4
7/16	2
1/2	2-1/4
9/16	2-1/2
3/4	3

6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of DAR 7-104.55. The first article should be a preproduction sample consisting of one size thimble. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for inspection and approval of the first article.

6.5 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.2).

6.6 Changes from the previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - SH
Air Force - 99

Preparing activity:

Army - GL

Project No. 4030-0148

Review activities:

Army - MD, ME
DLA - IS

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:24Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7, and send to preparing activity.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-T-1547E	2. DOCUMENT **DATE (YYYYMMDD)** 19831228

3. DOCUMENT TITLE **THIMBLES, ROPE (SOLID)**

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON *(if applicable)*	7. DATE SUBMITTED (YYYYMMDD)

8. PREPARING ACTIVITY

NAME	b. TELEPHONE *Include Area Code)* (1) Commercial (2) AUTOVON
c. ADDRESS *(Include Zip Code)*	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Standardization Program Office (DLSC-LM) 8725 John J. Kingman road, Suite 2533, Ft. Belvoir, VA 22060-2533 Telephone (703) 767-6888 AUTOVON 427-6888

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:24Z
Check the source to verify that this is the current version before use.