INCH-POUND

MIL-DTL-11484/313
18 February 2005

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, IRAQ CAMPAIGN MEDAL

This specification is approved for use by all Departments and Agencies
of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-11484.



MATERIAL: 85/15 Rich-Low Brass (or better)

FINISH: Hard Enameled or Epoxied, Gold Plated, Mirror-like Polished, and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 6.

DIMENSIONS:

HEIGHT: 9/64 inch (REF)
WIDTH: 21/32 inch (REF)
THICKNESS (at edge): 0.065 ± 0.005 inch (approximately)

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T12:16Z
Check the source to verify that this is the current version before use.

2. Attaching device shall be prong with pick and wing type clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

3. Enameled/epoxied areas shall be as shown. When hard enamel is used, the material requirement shall be 95/5 gilding metal. When epoxy is used, the material requirement shall be 85/15 rich-low brass (or better). Colors shall conform to TIOH Hard Enamel Color Chip Numbers listed below:

COLOR	CHIP NUMBER
Scarlet	1
Green	12
Black	26
Sand	35
White	28

Custodian:
Army - IH
AF - 11
Navy - NU

Preparing activity:
Army - IH
(Project No. 8455-0170/002)

Review activities:
DLA - CT
Navy - MC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T12:16Z
Check the source to verify that this is the current version before use.