INCH-POUND

MIL-PRF-19500/516H
w/AMENDMENT 2
8 July 2026
SUPERSEDING
MIL-PRF-19500/516H
w/AMENDMENT 1
14 April 2023

The documentation and process conversion measures necessary to comply with this revision shall be completed by 8 October 2026.

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, DIODE, SILICON, BIPOLAR TRANSIENT VOLTAGE SUPPRESSOR, TYPES 1N6102 THROUGH 1N6173, 10 AND 5 PERCENT VOLTAGE TOLERANCE, ENCAPSULATED (THROUGH-HOLE AND SURFACE MOUNT PACKAGES) AND UN-ENCAPSULATED, QUALITY LEVELS JAN, JANTX, JANTXV, JANS, JANHC, AND JANKC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for bipolar 500 watt and 1,500 watt peak pulse power transient voltage suppressor diodes with voltage tolerances of either 10 or 5 percent. Four levels of product assurance (JAN, JANTX, JANTXV, and JANS) are provided for each encapsulated device. Two levels of product assurance (JANHC and JANKC) are provided for each unencapsulated device (die).

1.2 Package outlines. The device package outlines are as follows: axial leaded through hole package in accordance with figure 1, square end-cap surface mount US package in accordance with figure 2, and surface mount URS package in accordance with figure 3 for all encapsulated device types. See figures 4 and 5 for unencapsulated devices.

1.3 Maximum ratings. Maximum ratings are as shown in columns 4, 6, and 7 of the electrical characteristics table herein and as follows:

a. $P_{M(AV)}$ = 2 W (1N6102 through 1N6137 (including A, US, and URS suffix versions)) and 3 W (1N6138 through 1N6173 (including A, US, and URS suffix versions)) at T_A = +25°C (see figure 6 for derating).

b. $P_{M(AV)}$ = 3 W (1N6102 through 1N6137 (including A, US, and URS suffix versions)) and 5 W (1N6138 through 1N6173 (including A, US, and URS suffix versions)) at T_L = +75°C for L = 0.375 inch (9.53 mm) (figure 7).

c. P_{PP} = 500 W (1N6102 through 1N6137 (including A, US, and URS suffix versions)) and 1,500 W (1N6138 through 1N6173 (including A, US, and URS suffix versions)) at t_p = 1 ms (see figure 8).

d. -55°C ≤ T_{OP} ≤ +175°C, -55°C ≤ T_{STG} ≤ +175°C (ambient temperatures).

1.4 Primary electrical characteristics. Primary electrical characteristics are as listed in 3.6.2.

Comments, suggestions, or questions on this document should be addressed to DLA Weapons Support, ATTN: VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A
FSC 5961
DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.

1.5 Part or Identifying Number (PIN). The PIN is in accordance with MIL-PRF-19500, and as specified herein. See 6.4 for PIN construction example and 6.5 for a list of available PINs.

1.5.1 JAN certification mark and quality level.

1.5.1.1 JAN certification mark and quality level for encapsulated devices. The quality level designators for encapsulated devices that are applicable for this specification sheet from the lowest to the highest level are as follows: "JAN", "JANTX", "JANTXV" and "JANS".

1.5.1.2 JAN certification mark and quality level for unencapsulated devices (die). The quality level designators for unencapsulated devices (die) that are applicable for this specification sheet from the lowest to the highest level are as follows: "JANHC" and "JANKC".

1.5.2 Device type. The designation system for the device types of diodes covered by this specification sheet are as follows.

1.5.2.1 First number and first letter symbols. The diodes of this specification sheet use the first number and letter symbols "1N".

1.5.2.2 Second number symbols. The second number symbols for the diodes covered by this specification sheet are as follows: "6102", "6103", "6104", "6105", "6106", "6107", "6108" "6109" "6110" "6111", "6112", "6113", "6114" "6115", "6116", "6117", "6118", "6119", "6120", "6121", "6122", "6123", "6124", "6125" "6126" "6127", "6128" "6129", "6130", "6131", "6132", "6133", "6134", "6135", "6136", "6137", "6138", "6139", "6140", "6141", "6142", "6143", "6144", "6145", "6146", "6147", "6148", "6149", "6150", "6151", "6152", "6153", "6154", "6155", "6156", "6157", "6158", "6159", "6160", "6161", "6162", "6163", "6164", "6165", "6166", "6167", "6168", "6169", "6170", "6171", "6172", and "6173".

1.5.3 Suffix symbols. The following suffix letters are incorporated in the PIN as applicable.

1.5.3.1 Modified version designator. The suffix letter "A" is used on devices that have a 5 percent voltage tolerance. Devices with no "A" suffix have a 10 percent voltage tolerance.


1.5.3.2 Package designators. The suffix symbols (or lack thereof) that designate the package outline for the devices covered by this specification sheet are as follows:

	A blank package designators indicates a through hole mount, axial package. (see figure 1)
US	Indicates a surface mount, square endcap package (see figure 2).
URS	Indicates a surface mount, 1 round endcap and 1 square endcap package (see figure 3).

1.5.4 Lead finish. The lead finishes applicable to this specification sheet are listed on QPDSIS-19500.

1.5.5 Die identifiers for unencapsulated devices (manufacturers and critical interface identifiers). The manufacturer die identifiers that are applicable for this specification sheet are "A" and "B" (see figures 4, 5, and 6.5.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.




SCHEMATIC SYMBOL

Symbol	Dimensions								Notes
	1N6102 through 1N6137 1N6102A through 1N6137A				1N6138 through 1N6173 1N6138A through 1N 6173A				
	inch	inch	mm	mm	inch	inch	mm	mm	
	Min	Max	Min	Max	Min	Max	Min	Max	
BD	.085	.140	2.16	3.56	.135	.185	3.43	4.70	2
BL	.140	.185	3.56	4.70	.140	.195	3.56	4.95	
LD	.026	.033	0.66	0.84	.036	.042	0.91	1.07	
LL	1.00	1.30	25.40	33.02	1.00	1.30	25.40	33.02	
LU		.030		0.76		.030		0.76	3

NOTES:
1. Dimensions are in inches. Millimeters are given for general information only.
2. Dimension BD shall be measured at the largest diameter. Package contour optional within dimensions BD and length BL.
3. Dimension LU lead diameter uncontrolled in this area.

FIGURE 1. Physical dimensions of round body, axial leaded package.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.




SCHEMATIC SYMBOL

	Dimensions								
Symbol	1N6102US through 1N6137US 1N6102AUS through 1N6137AUS				1N6138US through 1N6173US 1N6138AUS through 1N 6173AUS				Notes
	inch	inch	mm	mm	inch	inch	mm	mm	
	Min	Max	Min	Max	Min	Max	Min	Max	
BD	.137	.148	3.48	3.76	.183	.202	4.65	5.13	2
BL	.200	.225	5.08	5.72	.205	.245	5.21	6.22	
ECT	.019	.028	0.48	0.71	.019	.028	0.48	0.71	
S	.003		0.08		.003		0.08		3

NOTES:
1. Dimensions are in inches. Millimeters are given for general information only.
2. Dimensions are pre-solder dip.
3. The S dimension is minimum clearance of glass body to mounting surface on all orientations.

FIGURE 2. Physical dimensions of round body, square end-cap surface mount (US) package.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.




	Dimensions								
Symbol	1N6102URS through 1N6137URS 1N6102AURS through 1N6137AURS				1N6138URS through 1N6173URS 1N6138AURS through 1N 6173AURS				Notes
	inch	inch	mm	mm	inch	inch	mm	mm	
	Min	Max	Min	Max	Min	Max	Min	Max	
BD	.137	.148	3.48	3.76	.183	.202	4.65	5.13	2
BL	.200	.225	5.08	5.72	.205	.245	5.21	6.22	
ECT	.019	.028	0.48	0.71	.019	.028	0.48	0.71	
S	.003		0.08		.003		0.08		3

NOTES:
1. Dimensions are in inches. Millimeters are given for general information only.
2. Dimensions are pre-solder dip.
3. One end-cap shall be square and the other end-cap shall be round.
4. See figures 1 or 2 for schematic symbol.

FIGURE 3. Physical dimensions of round and square end-cap surface mount (URS) package.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.




A - version

	Dimensions							
Symbol	1N6102 through 1N6137 1N6102A through 1N6137A				1N6138 through 1N6173 1N6138A through 1N6173A			
	inch	inch	mm	mm	inch	inch	mm	mm
	Min	Max	Min	Max	Min	Max	Min	Max
øA	.087	.093	2.21	2.36	.124	.130	3.15	3.30
B	.030	.040	0.76	1.02	.030	.040	0.76	1.02

NOTES:
1. Dimensions are in inches. Millimeters are for general information only.
2. Silver plate 250 microinches (6.3 mm) nominal on all surfaces of three discs.

FIGURE 4. Physical dimensions of JANHC and JANKC die (A-version).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.



	Dimensions							
Symbol	1N6103 through 1N6137 1N6103A through 1N6137A				1N6138 through 1N6173 1N6138A through 1N6173A			
	inch	inch	mm	mm	inch	inch	mm	mm
	Min	Max	Min	Max	Min	Max	Min	Max
øA	.087	.093	2.21	2.36	.123	.128	3.12	3.25
B	.110	.120	2.79	3.05	.110	.120	2.79	3.05

NOTES:
1. Dimensions are in inches. Millimeters are for general information only.
2. Silver thickness 120 microinches (3 mm) nominal on all discs.

FIGURE 5. Physical dimensions of JANHC and JANKC die (B-version).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.

2. APPLICABLE PUBLICATIONS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 – Semiconductor Devices, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 – Test Methods for Semiconductor Devices.

(Copies of these documents are available online at https://quicksearch.dla.mil).

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturers list before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500 and as follows.

$I_{(BR)}$	Reverse breakdown current at the specified condition.
$V_{c(max)}$	Maximum clamping voltage. The maximum peak voltage appearing across the device when subjected to the peak pulse current I_{PP}.

3.4 Interface and physical dimensions. Interface and physical dimensions shall be as specified in MIL-PRF-19500 and on figures 1, 2, 3, 4 and 5 herein.

3.4.1 Lead finish. Lead finish shall be solderable in accordance with MIL-PRF-19500, MIL-STD-750, and herein. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

3.4.2 Metallurgical bond construction. Devices shall be metallurgically bonded, thermally matched, non-cavity, double-plug construction in accordance with the requirements of category I (see MIL-PRF-19500), and herein. The "US" and "URS" version shall be structurally identical to the axial leaded type except for lead configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.

3.5 Marking. Marking shall be in accordance with MIL-PRF-19500. Polarity marking is not required. All device marking (including all marking which is omitted on the device), except for serial numbers, shall appear on the unit package used as the initial protection for delivery.

3.5.1 Marking of US and URS version devices. At the option of the manufacturer, US and URS version devices may include laser marking on an end-cap, to include PIN and lot date code for all levels. JANS levels shall also include serialization.

3.5.2 Device marking abbreviations. The prefixes JAN, JANTX, JANTXV, or JANS may be abbreviated as J, JX, JV, or JS, respectively. (For example: The PIN JANS1N6102AURS may be reduced to JS6102A).

3.6 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, tables I, and II herein.

3.6.1 Maximum ratings. Maximum ratings shall be in accordance with columns 5 through 8 of table II.

3.6.2 Primary electrical characteristics. Primary electrical characteristics are shown in columns 2 and 4 of table II herein.

3.7 Electrical test requirements. The electrical test requirements shall be the subgroups specified in tables I and II.

3.8 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4. VERIFICATION

4.1 Classification of Inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3)

c. Conformance inspection (see 4.4, tables I, II and III).

d. Element evaluation of un-encapsulated die (see 4.6).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500. A separate qualification shall be required for the 500-watt and 1,500-watt peak pulse power device, respectively.

4.2.1 JANHC and JANKC die. JANHC and JANKC die shall be qualified in accordance with MIL-PRF-19500.

4.2.2 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not require the performance of table III tests, the tests specified in table III herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.

4.3 Screening (JANS, JANTX, and JANTXV levels only). Screening shall be in accordance with table E-IV of MIL-PRF-19500, and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen	Measurements for JANS level	Measurements for JANTX and JANTXV levels
5	Not applicable	Not applicable
9, 10, 11	Not applicable	Not applicable
12	See 4.5.1	See 4.5.1
13	Interim electrical, delta, and group A, subgroup 2, electrical parameters not applicable for this screen (performed in screen 12).	Interim electrical, delta, and group A, subgroup 2, electrical parameters not applicable for this screen (performed in screen 12).

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500, and as specified herein. A separate quality conformance inspection shall be required for the 500-watt and 1,500-watt peak pulse power devices, respectively.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-PRF-19500 and table I herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VIA (JANS) and table E-VIB (JAN, JANTX, and JANTXV) of MIL-PRF-19500, and as follows. Electrical measurements (end-points) and delta measurements shall be performed twice (once in each direction), in accordance with table I, subgroup 2 and the applicable steps of table IV herein.

4.4.2.1 Quality level JANS, table E-VIA of MIL-PRF-19500.

Subgroup	Method	Condition
B4		Not applicable.
B5	1027	T_A = +100°C minimum (see 4.5.2 and 4.5.3).

4.4.2.2 Quality levels JAN, JANTX and JANTXV, table E-VIB of MIL-PRF-19500.

Subgroup	Method	Condition
B3	1027	See 4.5.1.
B5		Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VII of MIL-PRF-19500, and as follows. Electrical measurements (end-points) and delta measurements shall be performed twice (once in each direction), in accordance with table I, subgroup 2 and the applicable steps of table IV herein.

Subgroup	Method	Condition
C2	2036	Axial leaded devices only. The details for terminal strength shall be as follows: Tension (condition A). Applicable for all types using the following details: For 1N6102 through 1N6137, 12 pounds (5.4 kg), t = 15 seconds minimum. For 1N6138 through 1N6173, 20 pounds (9.1 kg), t = 15 seconds minimum. Lead fatigue (condition E). Applicable for all types, 2 pounds (0.91 kg),
C2	2038	US, URS devices only. The details for end-cap bond integrity shall be as follows: Tab pull (condition B). Applicable for all types using the following details: Suitable fixtures may be used to pull the end-caps in a manner which does not aid construction. Reference to axial lead may be interpreted as end-cap with fixtures used for mounting. For 1N6102 through 1N6137, 12 pounds (5.4 kg). For 1N6138 through 1N6173, 20 pounds (9.1 kg).
C6	1026	See 4.5.1 and 4.5.3.
C8	4071	Conditions for temperature coefficient of $V_{(BR)}$ (see col 8 of table II) are as follows: $I_{(BR)}$ = column 3 of table II, T_1 = +25°C ±3°C, T_2 = T_1 +100°C; sampling plan shall be 45 devices, c = 0; $\alpha_{V(BR)}$ = column 8 of table II.
C9	See 4.5.3.	Conditions for maximum peak pulse current are as follows: 20 µs pulse only, 10 pulses; n = 22, c = 0.

4.4.4 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-IX of MIL-PRF-19500 and table III herein. Electrical measurements (end-points) and delta measurements shall be performed twice (once in each direction), in accordance with table I, subgroup 2 or the applicable steps of table IV as specified in table III herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.

4.5 Methods of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Power burn-in and steady-state operation life test conditions. For the purposes of this test, the direction in which the device is first pulsed shall be considered polarity A and the reverse direction polarity B. The test conditions and order of events shall be as follows:

a. Pulse in accordance with 4.5.3, in polarity A 5 times for screening and group B and 50 times for group C at T_A = +25°C.

b. Pulse in accordance with 4.5.3, in polarity B 5 times for screening and group B and 50 times for group C at T_A = +25°C.

c. Read and record I_{D1} and $V_{(BR)}$ in polarities A and B at T_A = +25°C, remove defective devices and record number of failures.

d. Apply the working peak reverse voltage (V_{WM}) (column 4 of table II) in polarity A at T_A = +125°C as follows:

(1) For 48 hours (JANTX and JANTXV) and 120 hours (JANS) for the screening test.

(2) For 170 hours (JAN, JANTX, and JANTXV) for group B steady-state operation life test.

(3) For 500 hours for group C steady-state operation life test.

e. Read I_{D1} in polarity A at T_A = +25°C. Devices with ΔI_{D1} > 50 percent (100 percent for steady-state operation life) of the initial reading or 20 percent of column 5 of table II, whichever is greater, shall be considered defective. Remove defective devices and record the number of failures.

f. Apply the working peak pulse reverse voltage (V_{WM}) (column 4 of table II) in polarity B at T_A = +125°C as follows:

(1) For 48 hours (JANTX and JANTXV) and 120 hours (JANS) for the screening test.

(2) For 170 hours (JAN, JANTX, and JANTXV) for group B steady-state operation life test.

(3) For 500 hours for group C steady-state operation life test.

g. Read I_{D1} in polarity B at T_A = +25°C. Devices with ΔI_{D1} > 50 percent (100 percent for steady-state operation life) of the initial reading or 20 percent of column 5 of table II, whichever is greater, shall be considered defective. Remove defective devices and record the number of failures.

h. Read $V_{(BR)}$ in polarities A and B at T_A = +25°C. Devices with $\Delta V_{(BR)}$ > ±2 percent (±5 percent for steady-state operation life) of the initial reading shall be considered defective. Remove defective devices and record the number of failures.

i. Read ΔI_{D1} in polarity A at T_A = +25°C, remove defective devices and record the number of failures.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.

4.5.1.1 Group C steady-state operation life test (alternate procedure). When the group B 340-hour life test is continued on test to 1,000 hours to satisfy the group C life test requirements, the test shall be performed as given in 4.5.1 with the following exceptions:

a. In 4.5.1, steps a and b shall be moved and performed following step g.

b. In 4.5.1, steps e and g shall be repeated after steps a and b are performed and before step h is completed (step i may be omitted when this procedure is used).

4.5.2 Accelerated steady-state operation life. This test shall be conducted with the devices subjected to the breakdown current specified in column 3 of table II in opposite polarities for 48 +8, -4 hours in each polarity. At the beginning of the test and at the end of each time period, the devices shall be temperature stabilized at T_A = +25°C and subjected to pulse conditions at the rate of one pulse per minute (max) for 10 pulses each, in accordance with 4.5.3 as specified.

4.5.3 Maximum peak pulse current (I_{PP}). The peak pulse currents specified in column 7 of table II shall be applied simultaneously maintaining a bias voltage, not less than the applicable voltage in column 4 of table II, in the same polarity as the peak pulse current. The maximum clamping voltage ($V_{C(MAX)}$) shall be as specified in 4.5.4. The peak pulse current shall be applied with a current versus time waveform (1 pulse per minute maximum) such that the pulse current shall reach 100 percent of I_{PP} at t ≤ 10 µs and decay to 50 percent of I_{PP} at t ≥ 1 ms for t_p = 1 ms (see figure 9).

NOTE: Tolerance on time (t) shall be +10, -0 percent.

4.5.4 Clamping voltage. The peak pulse clamping voltage shall be measured across the device in a 1 ms time interval. The response detector shall demonstrate equipment accuracy of ±3 percent. The peak clamping voltage, as specified in column 6 of table II herein, shall be applicable to the 1 ms pulse of 4.5.3 only.

4.6 Element evaluation of un-encapsulated die. The element evaluation of unencapsulated die shall be in accordance with appendix G of MIL-PRF-19500. As a minimum, die shall be 100-percent probed to ensure compliance with table I, subgroup 2. Burn-in duration for the JANKC level follows JANS requirements; the JANHC follows JANTX requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limit	Limit	Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical examination	2071					
Subgroup 2 2/						
Standby current	4016	Condition A or B, $V_R = V_{WM}$ (column 4 of table II)	I_{D1}		Column 5 of table II	µA dc
Breakdown voltage	4022	$I_{(BR)}$ = column 3 of table II, $t_P \leq 300$ ms, duty cycle ≤ 2 percent	$V_{(BR)1}$	Column 2 of table II		V dc
Subgroup 3 2/						
High temperature operation		T_A = +150°C				
Standby current	4016	Condition A or B, $V_R = V_{WM}$ (column 4 of table II)	I_{D2}		Column 9 of table II	µA dc
Subgroup 4 2/						
Clamping voltage maximum (pulsed)	See 4.5.4	t_P = 1 ms (see 4.5.3), I_{PP} = column 7 of table II	$V_{C(max)}$		Column 6 of table II	V (pk)
Subgroups 5 and 6						
Not applicable						

1/ For sampling plan, see MIL-PRF-19500.
2/ All electrical testing shall be performed twice, once in each direction.
3/ Column references are to table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.

TABLE II. Electrical characteristics and ratings for 500 W and 1,500 W series diodes (limits apply in both directions).

Column 1		Column 2	Column 3	Column 4	Column 5		Column 6	Column 7		Column 8	Column 9	
Series type		$V_{(BR)}$ Breakdown voltage at $I_{(BR)}$	$I_{(BR)}$ Test current	V_{WM} Working peak reverse voltage	I_{D1} Maximum standby current		$V_{C(max)}$ Maximum clamping voltage at I_{PP} t_P = 1 ms	I_{PP} Maximum peak pulse current		$\alpha_{V(BR)}$ Maximum temperature coefficient of $V_{(BR)}$	I_{D2} Maximum standby current at T_A = +150°C	
500 W	1,500 W	Min V dc 1/	mA dc 1/	V dc 1/	µA dc 2/	µA dc 3/	V (pk) 1/	A (pk) 2/	A (pk) 3/	% / °C 1/	µA dc 2/	µA dc 3/
1N6102	1N6138	6.12	175	5.2	100	500	11.0	45.4	136.4	.05	4,000	12,000
1N6102A	1N6138A	6.46	175	5.2	100	500	10.5	47.6	142.8	.05	4,000	12,000
1N6103	1N6139	6.75	175	5.7	50	300	11.8	42.4	127.1	.06	750	3,000
1N6103A	1N6139A	7.13	175	5.7	50	300	11.2	44.6	133.9	.06	750	3,000
1N6104	1N6140	7.38	150	6.2	20	100	12.7	39.4	118.1	.06	500	2,000
1N6104A	1N6140A	7.79	150	6.2	20	100	12.1	41.3	124.0	.06	500	2,000
1N6105	1N6141	8.19	150	6.9	20	100	14.0	35.7	107.1	.06	300	1,200
1N6105A	1N6141A	8.65	150	6.9	20	100	13.4	37.3	111.9	.06	300	1,200
1N6106	1N6142	9.00	125	7.6	20	100	15.2	32.9	98.7	.07	200	800
1N6106A	1N6142A	9.50	125	7.6	20	100	14.5	34.5	103.4	.07	200	800
1N6107	1N6143	9.90	125	8.4	20	20	16.3	30.7	92.0	.07	200	800
1N6107A	1N6143A	10.45	125	8.4	20	20	15.6	32.0	96.2	.07	200	800
1N6108	1N6144	10.80	100	9.1	20	20	17.7	28.2	84.7	.07	150	600
1N6108A	1N6144A	11.40	100	9.1	20	20	16.9	29.6	88.8	.07	150	600
1N6109	1N6145	11.70	100	9.9	20	20	19.0	26.3	78.9	.08	150	600
1N6109A	1N6145A	12.35	100	9.9	20	20	18.2	27.5	82.4	.08	150	600
1N6110	1N6146	13.50	75	11.4	20	20	21.9	22.8	68.5	.08	100	400
1N6110A	1N6146A	14.25	75	11.4	20	20	21.0	23.8	71.4	.08	100	400
1N6111	1N6147	14.40	75	12.2	20	20	23.4	21.4	64.1	.08	100	400
1N6111A	1N6147A	15.20	75	12.2	20	20	22.3	22.4	67.3	.08	100	400
1N6112	1N6148	16.20	65	13.7	1	10	26.3	19.0	57.0	.085	100	400
1N6112A	1N6148A	17.10	65	13.7	1	10	25.1	19.9	59.8	.085	100	400

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.

TABLE II. Electrical characteristics and ratings for 500 W and 1,500 W series diodes (limits apply in both directions) - Continued.

Column 1		Column 2	Column 3	Column 4	Column 5		Column 6	Column 7		Column 8	Column 9	
Series type		$V_{(BR)}$ Breakdown voltage at $I_{(BR)}$	$I_{(BR)}$ Test current	V_{WM} Working peak reverse voltage	I_{D1} Maximum standby current		$V_{C(max)}$ Maximum clamping voltage at I_{PP} t_P = 1 ms	I_{PP} Maximum peak pulse current		$\alpha_{V(BR)}$ Maximum temperature coefficient of $V_{(BR)}$	I_{D2} Maximum standby current at T_A = +150°C	
500 W	1,500 W	Min V dc 1/	mA dc 1/	V dc 1/	µA dc 2/	µA dc 3/	V (pk) 1/	A (pk) 2/	A (pk) 3/	% / °C 1/	µA dc 2/	µA dc 3/
1N6113	1N6149	18.00	65	15.2	1	5	29.0	17.2	51.7	.085	100	400
1N6113A	1N6149A	19.00	65	15.2	1	5	27.7	18.0	54.2	.085	100	400
1N6114	1N6150	19.8	50	16.7	1	5	31.9	15.7	47.0	.085	100	400
1N6114A	1N6150A	20.9	50	16.7	1	5	30.5	16.4	49.2	.085	100	400
1N6115	1N6151	21.6	50	18.2	1	5	34.8	14.4	43.1	.09	100	400
1N6115A	1N6151A	22.8	50	18.2	1	5	33.3	15.0	45.0	.09	100	400
1N6116	1N6152	24.3	50	20.6	1	5	39.2	12.8	38.3	.09	100	400
1N6116A	1N6152A	25.7	50	20.6	1	5	37.4	13.4	40.1	.09	100	400
1N6117	1N6153	27.0	40	22.8	1	5	43.6	11.5	34.4	.09	100	400
1N6117A	1N6153A	28.5	40	22.8	1	5	41.6	12.0	36.0	.09	100	400
1N6118	1N6154	29.7	40	25.1	1	5	47.9	10.4	31.3	.095	100	400
1N6118A	1N6154A	31.4	40	25.1	1	5	45.7	10.9	32.8	.095	100	400
1N6119	1N6155	32.4	30	27.4	1	5	52.3	9.6	28.7	.095	100	400
1N6119A	1N6155A	34.2	30	27.4	1	5	49.9	10.0	30.1	.095	100	400
1N6120	1N6156	35.1	30	29.7	1	5	56.2	8.9	26.7	.095	100	400
1N6120A	1N6156A	37.1	30	29.7	1	5	53.6	9.3	28.0	.095	100	400
1N6121	1N6157	38.7	30	32.7	1	5	62.0	8.1	24.2	.095	100	400
1N6121A	1N6157A	40.9	30	32.7	1	5	59.1	8.5	25.4	.095	100	400
1N6122	1N6158	42.3	25	35.8	1	5	67.7	7.4	22.2	.095	100	400
1N6122A	1N6158A	44.7	25	35.8	1	5	64.6	7.7	23.2	.095	100	400
1N6123	1N6159	45.9	25	38.8	1	5	73.5	6.8	20.4	.095	100	400
1N6123A	1N6159A	48.5	25	38.8	1	5	70.1	7.1	21.4	.095	100	400

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.

TABLE II. Electrical characteristics and ratings for 500 W and 1,500 W series diodes (limits apply in both directions) - Continued.

Column 1		Column 2	Column 3	Column 4	Column 5		Column 6	Column 7		Column 8	Column 9	
Series type		$V_{(BR)}$ Breakdown voltage at $I_{(BR)}$	$I_{(BR)}$ Test current	V_{WM} Working peak reverse voltage	I_{D1} Maximum standby current		$V_{C(max)}$ Maximum clamping voltage at I_{PP} t_P = 1 ms	I_{PP} Maximum peak pulse current		$\alpha_{V(BR)}$ Maximum temperature coefficient of $V_{(BR)}$	I_{D2} Maximum standby current at T_A = +150°C	
500 W	1,500 W	Min V dc 1/	mA dc 1/	V dc 1/	µA dc 2/	µA dc 3/	V (pk) 1/	A (pk) 2/	A (pk) 3/	% / °C 1/	µA dc 2/	µA dc 3/
1N6124	1N6160	50.4	20	42.6	1	5	80.7	6.2	18.6	.095	100	400
1N6124A	1N6160A	53.2	20	42.6	1	5	77.0	6.5	19.5	.095	100	400
1N6125	1N6161	55.8	20	47.1	1	5	89.3	5.6	16.8	.100	100	400
1N6125A	1N6161A	58.9	20	47.1	1	5	85.3	5.9	17.6	.100	100	400
1N6126	1N6162	61.2	20	51.7	1	5	98.0	5.1	15.3	.100	100	400
1N6126A	1N6162A	64.6	20	51.7	1	5	97.1	5.1	15.4	.100	100	400
1N6127	1N6163	67.5	20	56.0	1	5	108.1	4.6	13.9	.100	100	400
1N6127A	1N6163A	71.3	20	56.0	1	5	103.1	4.8	14.5	.100	100	400
1N6128	1N6164	73.8	15	62.2	1	5	118.2	4.2	12.7	.100	100	400
1N6128A	1N6164A	77.9	15	62.2	1	5	112.8	4.4	13.3	.100	100	400
1N6129	1N6165	81.9	15	69.2	1	5	131.1	3.8	11.4	.100	100	400
1N6129A	1N6165A	86.5	15	69.2	1	5	125.1	4.0	12.0	.100	100	400
1N6130	1N6166	90.0	12	76.0	1	5	144.1	3.5	10.4	.100	100	400
1N6130A	1N6166A	95.0	12	76.0	1	5	137.6	3.6	10.9	.100	100	400
1N6131	1N6167	99.0	12	83.6	1	5	158.5	3.2	9.5	.100	100	400
1N6131A	1N6167A	104.5	12	83.6	1	5	151.3	3.3	9.9	.100	100	400
1N6132	1N6168	108.0	10	91.2	1	5	172.9	2.9	8.7	.100	100	400
1N6132A	1N6168A	114.0	10	91.2	1	5	165.1	3.0	9.1	.100	100	400
1N6133	1N6169	117.0	10	98.8	1	5	187.3	2.7	8.0	.105	100	400
1N6133A	1N6169A	123.5	10	98.8	1	5	178.8	2.8	8.4	.105	100	400
1N6134	1N6170	135.0	8	114.0	1	5	216.2	2.3	6.9	.105	100	400
1N6134A	1N6170A	142.5	8	114.0	1	5	206.3	2.4	7.3	.105	100	400

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.

TABLE II. Electrical characteristics and ratings for 500 W and 1,500 W series diodes (limits apply in both directions) - Continued.

Column 1		Column 2	Column 3	Column 4	Column 5		Column 6	Column 7		Column 8	Column 9	
Series type		$V_{(BR)}$ 1 Breakdown voltage at $I_{(BR)}$	$I_{(BR)}$ Test current	V_{WM} Working peak reverse voltage	I_{D1} Maximum standby current		$V_{C(max)}$ Maximum clamping voltage at I_{PP} t_P = 1 ms	I_{PP} Maximum peak pulse current		$\alpha_{V(BR)}$ Maximum temperature coefficient of $V_{(BR)}$	I_{D2} Maximum standby current at T_A = +150°C	
500 W	1,500 W	Min V dc 1/	mA dc 1/	V dc 1/	µA dc 2/	µA dc 3/	V (pk) 1/	A (pk) 2/	A (pk) 3/	% / °C 1/	µA dc 2/	µA dc 3/
1N6135	1N6171	144	8	121.6	1	5	228.8	2.2	6.6	.105	100	400
1N6135A	1N6171A	152	8	121.6	1	5	218.4	2.3	6.9	.105	100	400
1N6136	1N6172	162	5	136.8	1	5	257.4	1.9	5.8	.110	100	400
1N6136A	1N6172A	171	5	136.8	1	5	245.7	2.0	6.1	.110	100	400
1N6137	1N6173	180	5	152.0	1	5	286.0	1.7	5.2	.110	100	400
1N6137A	1N6173A	190	5	152.0	1	5	273.0	1.8	5.5	.110	100	400

1/ Applies to both 500 W and 1,500 W series.
2/ Applies to only 500 W series.
3/ Applies to only 1,500 W series.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.

TABLE III. Group E inspection (all quality levels) for qualification or re-qualification only.

Inspection	MIL-STD-750		Sampling plan
	Method	Conditions	
Subgroup 1			45 devices, c = 0
Temperature cycling	1051	500 cycles, condition C, -55°C to +175°C.	
Electrical measurements		See table I, subgroup 2, performed twice, once in each direction.	
Subgroup 2			45 devices, c = 0
Steady-state operation life test	See 4.5.1	1,000 hours.	
Electrical measurements		See table IV, performed twice, once in each direction.	
Subgroups 4, 5, and 6			
Not applicable			
Subgroup 8			
Peak pulse current	See 4.5.3.	I_{PP} shall be characterized by the supplier and this data shall be available to the Government. Test shall be performed on each low and high voltage device for each structurally identical grouping. Test to failure. (See figure 10)	
Electrical measurements		See table IV, performed twice, once in each direction.	


Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.

TABLE IV. Groups B, C and E delta measurements. 1/ 2/ 3/ 4/ 5/ 6/ 7/

Step	Inspection	MIL-STD-750		Symbol	Limit 6/	Limit 6/	Unit
		Method	Conditions		Min	Max	
1.	Standby current	4016	Condition A or B; $V_R = V_{WM}$ column 4 of table II	ΔI_{D1} 6/	100 percent of initial reading or 20 percent of column 5 of table II, whichever is greater.		
2.	Breakdown voltage	4022	$I_{(BR)}$ = column 3, $t_P \leq 300$ ms, duty cycle ≤ 2 percent	$\Delta V_{(BR)}$ 6/	± 5 percent of initial value of column 2 of table II		
3.	Clamping voltage	See 4.5.4	t_P = 1.0 ms (see 4.5.3); I_{PP} = column 7 of table II	$V_{C(MAX)}$		Column 6	V

1/ All electrical testing shall be performed twice, once in each direction.
2/ The electrical measurements taken during group B inspection for quality level JANS (table E-VIA of MIL-PRF-19500) shall be as follows:
   a. In addition to the measurements specified for subgroup 2, the measurements of step 3 of this table shall also be taken.
   b. In addition to the measurements specified for subgroup 5, the measurements of 4.5.1 shall also be taken.
3/ The electrical measurements taken during group B inspection for quality levels JAN, JANTX, and JANTXV (table E-VIB of MIL-PRF-19500) shall be as follows:
   a. In addition to the measurements specified for subgroup 2, the measurements of steps 1 and 2 of this table shall also be taken.
   b. In addition to the measurements specified for subgroup 3, the measurements of 4.5.1 shall also be taken.
   c. In addition to the measurements specified for subgroup 6, the measurements of steps 1 and 2 of this table shall also be taken.
4/ The electrical measurements taken during group C inspection for all quality levels (table E-VII of MIL-PRF-19500) shall be as follows:
   a. In addition to the measurements specified for subgroups 2 and 3, the measurements of steps 1 and 2 of this table shall also be taken.
   b. In addition to the measurements specified for subgroup 6, the measurements of 4.5.1 shall also be taken.
5/ The electrical measurements for group E inspection for all quality levels (table E-IX of MIL-PRF-19500) shall be as follows: In addition to the measurements specified for subgroups 2 and 8, the measurements of steps 1, 2 and 3 of this table shall also be taken.
6/ Column references are to table II.
7/ Devices which exceed the table I limits for this test shall not be accepted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.




NOTES:

1. All devices are capable of operating at ≤ T_J specified on this curve. Any parallel line to this curve will intersect the appropriate current for the desired maximum T_J allowed.
2. Derate design curve constrained by the maximum junction temperature (T_J ≤ 175 °C) and current rating specified. (See 1.3 herein.)
3. Derate design curve chosen at T_J ≤ 125 °C, where the maximum temperature of electrical test is performed.
4. Derate design curves chosen at T_J ≤ 125 °C, and 110 °C to show current rating where most users want to limit T_J in their application.

FIGURE 6. Maximum power versus lead temperature (not applicable to JANHC/JANKC die).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.




NOTES:

1. All devices are capable of operating at ≤ T_J specified on this curve. Any parallel line to this curve will intersect the appropriate current for the desired maximum T_J allowed.
2. Derate design curve constrained by the maximum junction temperature (T_J ≤ 175 °C) and current rating specified. (See 1.3 herein.)
3. Derate design curve chosen at T_J ≤ 125 °C, where the maximum temperature of electrical test is performed.
4. Derate design curves chosen at T_J ≤ 125 °C, and 110 °C to show current rating where most users want to limit T_J in their application.

FIGURE 6. Maximum power versus lead temperature (not applicable to JANHC/JANKC die) - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.




NOTES:

1. All devices are capable of operating at ≤ T_J specified on this curve. Any parallel line to this curve will intersect the appropriate current for the desired maximum T_J allowed.
2. Derate design curve constrained by the maximum junction temperature (T_J ≤ 175 °C) and current rating specified. (See 1.3 herein.)
3. Derate design curve chosen at T_J ≤ 125 °C, where the maximum temperature of electrical test is performed.
4. Derate design curves chosen at T_J ≤ 125 °C, and 110 °C to show current rating where most users want to limit T_J in their application.

FIGURE 7. Maximum power versus lead temperature (not applicable to JANHC/JANKC die).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.



NOTES:

1. All devices are capable of operating at ≤ T_J specified on this curve. Any parallel line to this curve will intersect the appropriate current for the desired maximum T_J allowed.
2. Derate design curve constrained by the maximum junction temperature (T_J ≤ 175 °C) and current rating specified. (See 1.3 herein.)
3. Derate design curve chosen at T_J ≤ 125 °C, where the maximum temperature of electrical test is performed.
4. Derate design curves chosen at T_J ≤ 125 °C, and 110 °C to show current rating where most users want to limit T_J in their application.

FIGURE 7. Maximum power versus lead temperature (not applicable to JANHC/JANKC die) – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.




FIGURE 8. Peak pulse power versus pulse time.





FIGURE 9. Pulse waveform.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.



NOTE: The pulse derating curve of maximum peak pulse power versus junction temperature has been included for reference purposes only.

FIGURE 10. Pulse derating curve (not applicable to JANHC/JANKC die).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Packaging requirements (see 5.1).

c. Lead finish (see 3.4.1).

d. The complete PIN, see 1.5 and 6.5.


e. Destructive physical analysis when requested.

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML 19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from DLA Weapons Support, ATTN: VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil. An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at https://qpldocs.dla.mil.


Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.

6.4 PIN construction example.

6.4.1 Encapsulated devices The PINs for encapsulated devices are constructed using the following form.



6.4.2 Unencapsulated devices. The PINs for un-encapsulated devices are constructed using the following form.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.

6.5 List of PINs.

6.5.1 List of PINs for encapsulated devices. The following is a list of possible PINs for encapsulated devices available on this specification sheet.

PINs for devices of the base quality level	PINs for devices of the "TX" quality level	PINs for devices of the "TXV" quality level	PINs for devices of the "S" quality level
JAN1N6102#$	JANTX1N6102#$	JANTXV1N6102#$	JANS1N6102#$
JAN1N6103#$	JANTX1N6103#$	JANTXV1N6103#$	JANS1N6103#$
JAN1N6104#$	JANTX1N6104#$	JANTXV1N6104#$	JANS1N6104#$
JAN1N6105#$	JANTX1N6105#$	JANTXV1N6105#$	JANS1N6105#$
JAN1N6106#$	JANTX1N6106#$	JANTXV1N6106#$	JANS1N6106#$
JAN1N6107#$	JANTX1N6107#$	JANTXV1N6107#$	JANS1N6107#$
JAN1N6108#$	JANTX1N6108#$	JANTXV1N6108#$	JANS1N6108#$
JAN1N6109#$	JANTX1N6109#$	JANTXV1N6109#$	JANS1N6109#$
JAN1N6110#$	JANTX1N6110#$	JANTXV1N6110#$	JANS1N6110#$
JAN1N6111#$	JANTX1N6111#$	JANTXV1N6111#$	JANS1N6111#$
JAN1N6112#$	JANTX1N6112#$	JANTXV1N6112#$	JANS1N6112#$
JAN1N6113#$	JANTX1N6113#$	JANTXV1N6113#$	JANS1N6113#$
JAN1N6114#$	JANTX1N6114#$	JANTXV1N6114#$	JANS1N6114#$
JAN1N6115#$	JANTX1N6115#$	JANTXV1N6115#$	JANS1N6115#$
JAN1N6116#$	JANTX1N6116#$	JANTXV1N6116#$	JANS1N6116#$
JAN1N6117#$	JANTX1N6117#$	JANTXV1N6117#$	JANS1N6117#$
JAN1N6118#$	JANTX1N6118#$	JANTXV1N6118#$	JANS1N6118#$
JAN1N6119#$	JANTX1N6119#$	JANTXV1N6119#$	JANS1N6119#$
JAN1N6120#$	JANTX1N6120#$	JANTXV1N6120#$	JANS1N6120#$
JAN1N6121#$	JANTX1N6121#$	JANTXV1N6121#$	JANS1N6121#$
JAN1N6122#$	JANTX1N6122#$	JANTXV1N6122#$	JANS1N6122#$
JAN1N6123#$	JANTX1N6123#$	JANTXV1N6123#$	JANS1N6123#$
JAN1N6124#$	JANTX1N6124#$	JANTXV1N6124#$	JANS1N6124#$
JAN1N6125#$	JANTX1N6125#$	JANTXV1N6125#$	JANS1N6125#$
JAN1N6126#$	JANTX1N6126#$	JANTXV1N6126#$	JANS1N6126#$
JAN1N6127#$	JANTX1N6127#$	JANTXV1N6127#$	JANS1N6127#$
JAN1N6128#$	JANTX1N6128#$	JANTXV1N6128#$	JANS1N6128#$
JAN1N6129#$	JANTX1N6129#$	JANTXV1N6129#$	JANS1N6129#$
JAN1N6130#$	JANTX1N6130#$	JANTXV1N6130#$	JANS1N6130#$
JAN1N6131#$	JANTX1N6131#$	JANTXV1N6131#$	JANS1N6131#$
JAN1N6132#$	JANTX1N6132#$	JANTXV1N6132#$	JANS1N6132#$
JAN1N6133#$	JANTX1N6133#$	JANTXV1N6133#$	JANS1N6133#$
JAN1N6134#$	JANTX1N6134#$	JANTXV1N6134#$	JANS1N6134#$
JAN1N6135#$	JANTX1N6135#$	JANTXV1N6135#$	JANS1N6135#$
JAN1N6136#$	JANTX1N6136#$	JANTXV1N6136#$	JANS1N6136#$

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.

6.5.1 List of PINs for encapsulated devices. Continued.

PINs for devices of the base quality level	PINs for devices of the "TX" quality level	PINs for devices of the "TXV" quality level	PINs for devices of the "S" quality level
JAN1N6137#$	JANTX1N6137#$	JANTXV1N6137#$	JANS1N6137#$
JAN1N6138#$	JANTX1N6138#$	JANTXV1N6138#$	JANS1N6138#$
JAN1N6139#$	JANTX1N6139#$	JANTXV1N6139#$	JANS1N6139#$
JAN1N6140#$	JANTX1N6140#$	JANTXV1N6140#$	JANS1N6140#$
JAN1N6141#$	JANTX1N6141#$	JANTXV1N6141#$	JANS1N6141#$
JAN1N6142#$	JANTX1N6142#$	JANTXV1N6142#$	JANS1N6142#$
JAN1N6143#$	JANTX1N6143#$	JANTXV1N6143#$	JANS1N6143#$
JAN1N6144#$	JANTX1N6144#$	JANTXV1N6144#$	JANS1N6144#$
JAN1N6145#$	JANTX1N6145#$	JANTXV1N6145#$	JANS1N6145#$
JAN1N6146#$	JANTX1N6146#$	JANTXV1N6146#$	JANS1N6146#$
JAN1N6147#$	JANTX1N6147#$	JANTXV1N6147#$	JANS1N6147#$
JAN1N6148#$	JANTX1N6148#$	JANTXV1N6148#$	JANS1N6148#$
JAN1N6149#$	JANTX1N6149#$	JANTXV1N6149#$	JANS1N6149#$
JAN1N6150#$	JANTX1N6150#$	JANTXV1N6150#$	JANS1N6150#$
JAN1N6151#$	JANTX1N6151#$	JANTXV1N6151#$	JANS1N6151#$
JAN1N6152#$	JANTX1N6152#$	JANTXV1N6152#$	JANS1N6152#$
JAN1N6153#$	JANTX1N6153#$	JANTXV1N6153#$	JANS1N6153#$
JAN1N6154#$	JANTX1N6154#$	JANTXV1N6154#$	JANS1N6154#$
JAN1N6155#$	JANTX1N6155#$	JANTXV1N6155#$	JANS1N6155#$
JAN1N6156#$	JANTX1N6156#$	JANTXV1N6156#$	JANS1N6156#$
JAN1N6157#$	JANTX1N6157#$	JANTXV1N6157#$	JANS1N6157#$
JAN1N6158#$	JANTX1N6158#$	JANTXV1N6158#$	JANS1N6158#$
JAN1N6159#$	JANTX1N6159#$	JANTXV1N6159#$	JANS1N6159#$
JAN1N6160#$	JANTX1N6160#$	JANTXV1N6160#$	JANS1N6160#$
JAN1N6161#$	JANTX1N6161#$	JANTXV1N6161#$	JANS1N6161#$
JAN1N6162#$	JANTX1N6162#$	JANTXV1N6162#$	JANS1N6162#$
JAN1N6163#$	JANTX1N6163#$	JANTXV1N6163#$	JANS1N6163#$
JAN1N6164#$	JANTX1N6164#$	JANTXV1N6164#$	JANS1N6164#$
JAN1N6165#$	JANTX1N6165#$	JANTXV1N6165#$	JANS1N6165#$
JAN1N6166#$	JANTX1N6166#$	JANTXV1N6166#$	JANS1N6166#$
JAN1N6167#$	JANTX1N6167#$	JANTXV1N6167#$	JANS1N6167#$
JAN1N6168#$	JANTX1N6168#$	JANTXV1N6168#$	JANS1N6168#$
JAN1N6169#$	JANTX1N6169#$	JANTXV1N6169#$	JANS1N6169#$
JAN1N6170#$	JANTX1N6170#$	JANTXV1N6170#$	JANS1N6170#$
JAN1N6171#$	JANTX1N6171#$	JANTXV1N6171#$	JANS1N6171#$
JAN1N6172#$	JANTX1N6172#$	JANTXV1N6172#$	JANS1N6172#$
JAN1N6173#$	JANTX1N6173#$	JANTXV1N6173#$	JANS1N6173#$

(1) The pound sign (#) represents the modified version designator (see 1.5.3.1). The dollar sign ($) represents the package designators (see 1.5.3.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.

6.5.2 List of PINs for unencapsulated devices. The following is a list of possible PINs available on this specification sheet. The qualified die suppliers with the applicable letter version (e.g., JANHCA1N6102) will be identified on the QML.

JANC ordering information (1) (2)		
	Manufacturer CAGE	
PIN (1)	14552	14099
1N6102	JANHCA1N6102	JANHCB1N6102
1N6103	JANHCA1N6103	JANHCB1N6103
1N6104	JANHCA1N6104	JANHCB1N6104
1N6105	JANHCA1N6105	JANHCB1N6105
1N6106	JANHCA1N6106	JANHCB1N6106
1N6107	JANHCA1N6107	JANHCB1N6107
1N6108	JANHCA1N6108	JANHCB1N6108
1N6109	JANHCA1N6109	JANHCB1N6109
1N6110	JANHCA1N6110	JANHCB1N6110
1N6111	JANHCA1N6111	JANHCB1N6111
1N6112	JANHCA1N6112	JANHCB1N6112
1N6113	JANHCA1N6113	JANHCB1N6113
1N6114	JANHCA1N6114	JANHCB1N6114
1N6115	JANHCA1N6115	JANHCB1N6115
1N6116	JANHCA1N6116	JANHCB1N6116
1N6117	JANHCA1N6117	JANHCB1N6117
1N6118	JANHCA1N6118	JANHCB1N6118
1N6119	JANHCA1N6119	JANHCB1N6119
1N6120	JANHCA1N6120	JANHCB1N6120
1N6121	JANHCA1N6121	JANHCB1N6121
1N6122	JANHCA1N6122	JANHCB1N6122
1N6123	JANHCA1N6123	JANHCB1N6123
1N6124	JANHCA1N6124	JANHCB1N6124
1N6125	JANHCA1N6125	JANHCB1N6125
1N6126	JANHCA1N6126	JANHCB1N6126
1N6127	JANHCA1N6127	JANHCB1N6127
1N6128	JANHCA1N6128	JANHCB1N6128
1N6129	JANHCA1N6129	JANHCB1N6129
1N6130	JANHCA1N6130	JANHCB1N6130
1N6131	JANHCA1N6131	JANHCB1N6131
1N6132	JANHCA1N6132	JANHCB1N6132
1N6133	JANHCA1N6133	JANHCB1N6133
1N6134	JANHCA1N6134	JANHCB1N6134
1N6135	JANHCA1N6135	JANHCB1N6135
1N6136	JANHCA1N6136	JANHCB1N6136
1N6137	JANHCA1N6137	JANHCB1N6137
1N6138	JANHCA1N6138	JANHCB1N6138
1N6139	JANHCA1N6139	JANHCB1N6139
1N6140	JANHCA1N6140	JANHCB1N6140
1N6141	JANHCA1N6141	JANHCB1N6141

(1) Applies to "A" suffix versions also.
(2) For JANKC level, replace "JANHC" prefix with "JANKC"

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.

6.5.2 List of PINs for unencapsulated devices. Continued

JANC ordering information (1) (2)		
	Manufacturer CAGE	
PIN (1)	14552	14099
1N6142	JANHCA1N6142	JANHCB1N6142
1N6143	JANHCA1N6143	JANHCB1N6143
1N6144	JANHCA1N6144	JANHCB1N6144
1N6145	JANHCA1N6145	JANHCB1N6145
1N6146	JANHCA1N6146	JANHCB1N6146
1N6147	JANHCA1N6147	JANHCB1N6147
1N6148	JANHCA1N6148	JANHCB1N6148
1N6149	JANHCA1N6149	JANHCB1N6149
1N6150	JANHCA1N6150	JANHCB1N6150
1N6151	JANHCA1N6151	JANHCB1N6151
1N6152	JANHCA1N6152	JANHCB1N6152
1N6153	JANHCA1N6153	JANHCB1N6153
1N6154	JANHCA1N6154	JANHCB1N6154
1N6155	JANHCA1N6155	JANHCB1N6155
1N6156	JANHCA1N6156	JANHCB1N6156
1N6157	JANHCA1N6157	JANHCB1N6157
1N6158	JANHCA1N6158	JANHCB1N6158
1N6159	JANHCA1N6159	JANHCB1N6159
1N6160	JANHCA1N6160	JANHCB1N6160
1N6161	JANHCA1N6161	JANHCB1N6161
1N6162	JANHCA1N6162	JANHCB1N6162
1N6163	JANHCA1N6163	JANHCB1N6163
1N6164	JANHCA1N6164	JANHCB1N6164
1N6165	JANHCA1N6165	JANHCB1N6165
1N6166	JANHCA1N6166	JANHCB1N6166
1N6167	JANHCA1N6167	JANHCB1N6167
1N6168	JANHCA1N6168	JANHCB1N6168
1N6169	JANHCA1N6169	JANHCB1N6169
1N6170	JANHCA1N6170	JANHCB1N6170
1N6171	JANHCA1N6171	JANHCB1N6171
1N6172	JANHCA1N6172	JANHCB1N6172
1N6173	JANHCA1N6173	JANHCB1N6173

(1) Applies to "A" suffix versions also.
(2) For JANKC level, replace "JANHC" prefix with "JANKC".

6.6 Request for new types and configurations. Requests for new device types or configurations for inclusions in this specification sheet should be submitted to: DLA Weapons Support, ATTN: VAC, Post Office Box 3990, Columbus, OH 43218-3990 or by electronic mail at Semiconductor@dla.mil .

6.7 Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army − CR
Navy − SH
Air Force − 85
NASA − NA
DLA − CC

Preparing activity:
DLA - CC

(Project 5961−2026−023)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil .

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T14:27Z
Check the source to verify that this is the current version before use.