MIL-P-47279(MI)
9 August 1974
SUPERSEDING
MIS-16067A
13 June 1967

MILITARY SPECIFICATION
PRIMER, SILICONE ADHESIVE

This specification is approved for use by all departments and agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for a room temperature drying silicone adhesive primer.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-A-25457	Adhesive, Air-Drying, Silicone Rubber

STANDARDS

Federal

FED-STD-141	Paint, Varnish, Lacquer, and Related Materials; Methods of Inspection, Sampling, and Testing

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 8040

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:07Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

American Society for Testing and Materials

ASTM-D-92	Method of Test for Flash and Fire Points
ASTM-D-1298	Test for Specific Gravity of Petroleum Liquids, Hydrometer Method

(Copies of ASTM publications may be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia. Pennsylvania 19103)

Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.

3. REQUIREMENTS

3.1 Preproduction sample. When a preproduction sample is required (see 6.2), it shall meet the requirements of this specification.

3.2 Material. The material shall be a room temperature drying primer for application to metal, plastic, ceramic, and glass to obtain maximum adhesion with silicone rubber conforming to MIL-A-25457.

3.3 Physical properties.

3.3.1 Nonvolatile content. The percentage of nonvolatile solids after 2 hours at plus 105 plus or minus 5 degrees Celsius (C) (plus 221 plus or minus 10 degrees Fahrenheit (F) shall be 2.2 to 4.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:07Z
Check the source to verify that this is the current version before use.

3.3.2 Specific gravity. The specific gravity shall be 0.739 to 0.764 at plus 25 plus or minus 3 degrees C (plus 77 plus or minus 5 degrees F).

3.3.3 Flash point. The flash point shall be not more than plus 27 degrees C (plus 80 degrees F).

3.3.4 Color. The primer shall have a light straw color.

3.3.5 Shelf life. The shelf life of the primer shall be not less than 12 months from the date of manufacture when stored in original unopened containers at a temperature less than 27 degrees C (80 degrees F).

3.4 Workmanship. The workmanship shall be such as to ensure a product which is uniform, in conformance with this specification, and properly packaged and packed. The primer shall be free of dirt, foreign material, or other contamination. Containers shall be clean, uniformly filled, well sealed, and legibly and durably marked.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Preproduction sample. The preproduction sample shall be prepared using the same methods proposed for the preparation of subsequent production lots of primer. Preproduction samples which do not meet the requirements of this specification shall be subject to rejection. Subsequent quantities will not be considered for acceptance until approval of the preproduction sample has been obtained.

4.3 Classification of examinations and tests. Inspection and testing of material shall be classified as follows:

a. Preproduction tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:07Z
Check the source to verify that this is the current version before use.

b. Quality conformance tests.

4.3.1 Preproduction tests. Preproduction tests shall be conducted only on the preproduction sample and shall consist of all the examinations and tests specified herein.

4.3.2 Quality conformance tests. Quality conformance tests for acceptance of primer shall consist of the following examinations and tests:

a. Nonvolatile content.

b. Specific gravity.

c. Appearance.

4.3.2.1 Lot size. Lot size shall consist of all the primer submitted for acceptance at the same time which has been prepared by the same company without a change in materials or processes in one continuous period of operation.

4.3.2.2 Sampling. Unless otherwise specified (see 6.2), 1/2 pint of primer from one unit representative of each lot shall be selected at random for quality conformance testing. Each packaged container shall be considered as a unit of product. Failure of the sample to meet the quality conformance requirements shall be cause for lot rejection.

4.4. Test methods.

4.4.1 Physical property tests.

4.4.1.1 Nonvolatile content. The nonvolatile content of the primer shall be determined in accordance with FED-STD-141, Method 4041. The nonvolatile content shall be as specified in 3.3.1.

4.4.1.2 Specific gravity. The specific gravity shall be determined in accordance with ASTM-D-1298. The specific gravity shall be as specified in 3.3.2.

4.4.1.3 Flash point. The flash point shall be determined in accordance with ASTM-D-92. The flash point shall be as specified in 3.3.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:07Z
Check the source to verify that this is the current version before use.

4.4.1.4 Appearance. The appearance of the primer shall be checked visually. Color shall be as specified in 3.3.4.

4.4.1.5 Shelf life. The primer shall be tested for compliance with all the requirements specified herein after completion of storage period. The manufacturer's certificate of compliance with the shelf life requirement (see 3.3.5) may be accepted during the storage period.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, and packing. Unless otherwise specified in the purchase order, the primer shall be furnished in tinplate cans or pails or in glass jars with metal lids containing an inner seal. Containers shall be nonreactive to the primer. Size of the container shall be as specified in the purchase order. The primer shall be prepared for shipment in such a manner that damage during shipment is prevented.

5.2 Marking. Each container of primer shall be legibly and durably marked. Marking information shall include, but shall not necessarily be limited to, the following:

a. Title, Number and date of this specification.

b. Manufacturer's name and address.

c. Manufacturer's product designation.

d. Lot of batch number

e. Date of manufacture.

f. Shelf life.

5.2.1 Caution note. Each individual container and each shipping container shall bear the following caution label, printed in bold type and securely affixed to the container:

Keep away from heat, sparks and open flame.

Keep container closed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:07Z
Check the source to verify that this is the current version before use.

Provide adequate ventilation.

Avoid prolonged or repeated contact with skin.

6. NOTES

6.1 Intended use. The primer covered by this specification is used to obtain maximum adhesion when adhesive conforming to MIL-A-25457 is applied to metal, glass, ceramics, and plastics. The primer may be applied by dipping, brushing or spraying. The primer and silicone adhesive used as a system should be manufactured by the same company.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.

b. Whether a preproduction sample is required and, if so, pertinent details (see 3.1).

c. Sampling plan if other than specified (4.3.2.2).

d. Container size (see 5.1).

6.3 Supersession data. This specification includes the requirements of Missile Interim Specification MIS-16067A, dated, 13 June 1967.

Custodian:
Army - MI

Preparing Activity:
Army - MI
Project No. 8040-A056 -5

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:07Z
Check the source to verify that this is the current version before use.