MILITARY SPECIFICATION

ROSETTES, GENERAL SPECIFICATION FOR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification establishes the requirements for Rosettes used by the Department of Defense and Various Federal Agencies.

1.2 Classification. The rosettes covered by this specification shall be as specified on the applicable specification sheet (see supplement 1 and 6.2).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

NN-P- 71 - Pallets, Material Handling, Wood, Stringer Construction, 2-way and 4-way (partial)
PPP-B-636 - Boxes, Shipping, Fiberboard

MILITARY

MIL-P-15011 - Pallets, Material Handling, Wood Post Construction, 4-way entry

(See supplement 1 for list of associated specifications)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: Director, The Institute of Heraldry, US Army, Cameron Station, Alexandria, VA 22304-5050, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8455

AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T13:18Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-191 - Textile, Test Methods

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads
MIL-STD-2073-1 - DOD Materiel Procedures for Development and Application of Packaging requirements.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

THE INSTITUTE OF HERALDRY

B- 6- 7 - Rosettes, Metal Forms
B-13-12 - Attaching Devices, Heraldic, Prong and clutch type.

(Copies of specifications, standards, and other Governments documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

THE COLOR ASSOCIATION OF THE UNITED STATES

The Standard Color Reference of America, Tenth Edition.
United States Army Color Card, The Official Colors for Branches, Agencies, etc.
DOD Standard Shades for Heraldic Yarns for Embroidery and Ribbons, 1974.

Source: https://assist.dla.mil -- Downloaded: 202610-22T13:18Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to The Color Association of the United States, Inc., 343 Lexington Avenue, New York, NY 10016.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM-D-3951 - Standard Practice for Commercial Packaging.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia PA 19103.) and (Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets or MS standards) the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Specification sheets. The individual item requirements shall be as specified herein and in accordance with the applicable specification sheets. In the event of any conflict between requirements of this specification and the specification sheets, the latter shall govern.

3.2 Guide samples. Unless otherwise specified (see 6.3), samples shall be furnished by the contracting officer to be used for guidance, information and as a standard for colorfastness. Variation from this specification may appear in the guide samples in which event the specification shall govern.

3.3 First article. Unless otherwise specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.4 and 6.4).

3.4 Materials. Materials shall conform to the referenced specifications and the requirements specified herein.

3.4.1 Copper Base Alloy. The copper base alloys shall be roll polished, free from pits, scale (including red oxide), dents, nicks, cracks, scratches, segregations, and foreign inclusions that will not be removed in later processing. When tested as specified in 4.5.1, the chemical composition of the applicable copper base alloy shall be as specified in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T13:18Z
Check the source to verify that this is the current version before use.

TABLE I. Chemical composition of copper base alloy.

Alloy	Copper	Nickel 1/	Lead (maximum)	Iron (maximum)	Manganese (maximum)	zinc	Others (maximum)
Red Brass	84.0-86.0		.05	.05		Remainder	.15
Gilding Metal	94.0-96.0		.03	.05		Remainder	.13
Free Cutting Brass	60.0-63.0		2.50-3.70			Remainder	
Bronze	89.0-91.0		.05	.05		Remainder	.13
Nickel Silver	63.0-66.5	16.5-19.5	.10	.25	.50	Remainder	

1/ Cobalt counting as nickel.

3.4.2 Yarn. The yarn shall be a continuous filament, bright regenerated cellulose rayon of the viscose or cuprammonium type with not less than 20 filaments for the single yarn. The warp and filling yarn shall be 50/2 denier. The pattern of the ribbon shall be as specified on applicable specification sheet.

3.4.3 Color. The individual colors of the yarns used in the ribbon shall conform to the cable numbers designated by The Color Association of the United State, and specified in individual specification sheets, (see 2.1). The use of sulfur dyes and dyes containing elementary sulfur or compounds capable of oxidication to sulfuric acid is prohibited.

3.4.3.1 Colorfastness. The colors shall show fastness to crocking, wet dry cleaning, water and light equal to or better than the standard sample when tested as specified in 4.5.1.1.

3.4.4 Matching. The color shall match the standard sample when viewed under filtered tungsten lamps which approximate artificial daylight having a correlated color temperature of 7000 plus or minus 500 K, with illumination of 100 plus or minus 20 foot candles, and shall be a good match to the sample under incandescent lamplight at 2300 plus or minus 100 K. The degree of luster shall be equal to the standards established in the DOD Standard Color Card of Official Standardized Shades for Heraldic Yarns for Embroidery and Ribbons, 1974.

3.4.5 Color pattern. The color pattern for the ribbon layout shall be as specified on the applicable specification sheet.

3.4.6 Weave. Except for the Medal of Honor Ribbon, all other ribbon shall have a taffeta or plain weave with no selvage. The Medal of Honor Ribbon shall be as shown on the applicable specification sheet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T13:18Z
Check the source to verify that this is the current version before use.

3.4.7 Thread for tie. Unless a ribbon tie is specified, the thread for the tie shall be polyester or polyester/cotton, 300 denier and shall be an acceptable color match as indicated on the applicable specification sheet.

3.5 Metal forms. The metal forming the cup of the rosettes shall be made of 70/30 soft brass to be not more than .010 inch thick and not less than .0095, draw quality. The cup shall conform to the design and measurements for the type indicated on specification sheet and shown on drawing B-6-7. A hole punched on center to be .035 plus or minus .003 inch diameter.

3.5.1 Backing disc. The metal backing disc, (see B-6-7) is to be any type half/hard brass .025 plus or minus .005 inch thick. A .035 plus or minus .003 inch diameter hole shall be punched on center.

3.5.2 Prong and clutches. The prong shall be a standard commercial post 3/8 inch in length and 0.045 plus or minus .003 inch in diameter. Prong and clutches shall be in accordance with drawing B-12-13.

3.6 Design. The design of the finished each rosette shall conform to the pattern as shown on the individual specification sheet (see supplement 1).

3.7 Construction. The ribbon for the cup specified in the applicable specification sheet shall be used to cover and line the metal form of the rosette. The ribbon shall be smoothly and securely cemented in place with a water insolvable adhesive. After the disc is in place and the post set the rose ribbon shall be pleated, tied in the center, (see 3.4.7) then opened to form a double fan and cemented within the cup with a water insolvable adhesive.

3.7.1 Tinting edges. When applicable, the edges that have warp yarn exposed other than the required shade shall be colored with an opaque, water proof ink to match the base color of the ribbon.

3.8 Workmanship. The finished rosette shall conform to the quality end grade of product established by this specification. The occurrence of defects shall not exceed the acceptable quality levels established by this specification.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspection set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202640-22T13:18Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Certificate of compliance. When certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).

b. Quality conformance inspection (see 4.5).

4.3 Inspection conditions. Unless otherwise specified, all inspections shall be performed in accordance with the test conditions specified in applicable test method document or applicable paragraph(s) in the specification.

4.4 First article inspection. Inspection and testing of the first article sample shall be made on a completely finished rosettes for all provisions of this specification applicable to the end product examination and tests.

4.5 Quality conformance inspection. Inspection shall be in accordance with provisions set forth in MIL-STD-105, except where otherwise indicated.

4.5.1 Quality assurance inspection. Inspection shall be in accordance with the provisions set forth in MIL-STD-105, except when otherwise specified hereafter.

4.5.1.1 Testing of components. In addition to the quality assurance provisions of subsidiary specifications, testing shall be in accordance with test methods specified in FED-STD-191 or FED-STD-151 where applicable, and as specified in table II. When the data in the "number of determinations per unit of product" and the "results reported as" columns are not specified in table II they shall be as required by the referenced test method. The sample size shall be in accordance with inspection level L-1 of Standard MIL-STD-105 and the acceptable quality level (AQL) shall be 6.5 defects per 100 units. The unit of product shall be one yard of the ribbon and the lot size shall be expressed in units of one yard.

Source: https://assist.dla.mil -- Downloaded: 202610-22T13:18Z
Check the source to verify that this is the currentversion before use.

TABLE II. Component tests.

Component	Characteristic	Rqm't para	Test method	#determ per s/u	Results reported as
Cup	Material ident	3.5	111		Nearest 0.1% for each element
Ribbon yarn	Material ident	3.4 1/	1500 or 1520	-	To nearest denier
	Presence of sulfur	3.4.3	4/3 1/	1	Pass or fail
	Crocking	3.4.3.1	5651	-	-
	Wet-dry cleaning	3.4.3.1	5622	-	-
	Water	3.4.3.1	5630	-	-
	Light	3.4.3.1	5660	-	-
Adhesive	Water insolvable type	3.7	1/	-	-

1/ Unless otherwise specified a contractor's certification of compliance may be accepted as evidence of conformance.

4.5.2 Test.

4.5.2.1 Chemical composition test. Chemical composition shall be determined in accordance with test method 111 of FED-STD-151. Results shall be evaluated to determine compliance with the requirements specified in 4.5.1.1.

4.5.3 Inspection of the end item.

4.5.3.1 Visual examination of the end item. Defects found during this examination shall be classified in accordance with 4.5.3.1.1 and 4.5.3.1.2. The lots shall be inspected in accordance with 4.5.3.1.3. The unit of product for these examinations shall be one rosette.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T13:18Z
Check the source to verify that this is the current version before use.

4.5.3.1.1 Examination of rosettes for defects in color material, construction, and workmanship.

Examine	Defect	Classification Major (*)		Minor
Ribbon	Color is not a close match to the required color.	x	-	-
	Color pattern is not as specified, or not as indicated in the standard sample or specification sheet	x	-	-
	Weave not as specified.	x	-	-
	Broken or missing yarn, tear, cut, hole, float, coarse end, knot, slub, uneven texture or other imperfection affecting serviceability or appearance.	x	-	-
Construction and workmanship	Ribbon does not completely cover and line the metal cup.	x	-	-
	Ribbon does not form required design within the cup.	x	-	-
	Ribbon is not smoothly and securely cemented in place, e.g. any wrinkle, pucker, loose end or area of non-adhesion affecting appearance. . .	x	-	-
Metal form	Not type or material used in the standard sample.	-	-	*
	Finish not as on standard sample.	-	-	*
	Malformed, twisted, cracked, bent out of shape or otherwise impaired affecting use.	x	-	-

4.5.3.1.2 Examination of rosettes for defects in dimensions. Any dimension that does not compare favorably with the standard sample shall be classified as a defect.

4.5.3.1.3 Inspection levels and AQL's. The inspection levels and acceptable quality levels (AQL's) expressed in defects per hundred units shall be as follows:

	Inspection level	AQL
For defects applicable to 4.5.3.1.1	II	(One class) 2.5
For defects applicable to 4.5.3.1.2	L-6	(One class) 4.0

4.5.4 Inspection of packaging. An examination shall be made to determine that the packaging, packing and marking requirements of section 5 of this specification are complied with. Defects shall be scored in accordance with list below. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed. Defects of closure

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T13:18Z
Check the source to verify that this is the current version before use.

listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be L-4 and the acceptable quality levels (AQL's) shall be 4.0 defects per hundred units.

Examination	Defects
Markings (exterior and interior)	Missing, incorrect; illegible; of improper size, location, sequence or method of application.
Materials	Any non-conforming component; component missing, damaged, or otherwise defective affecting serviceability.
Workmanship	Each rosette not mounted on white bristol card and placed in individual box or plastic envelope with proper name for identification.
Content (exterior and interior)	Number per container is more or less than the specified or indicated quantity.

4.5.5 Palletization examination. An examination shall be made to determine that the palletization is in compliance with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the inspection lot. The inspection level shall be S-1 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T13:18Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation. Preservation shall be level A, C or commercial as specified (see 6.2).

5.1.1 Level A. Rosettes shall be preserved to the MIL-STD-2073-1 requirements for this level.

5.1.2 Level C. Rosettes shall be preserved to the MIL-STD-2073-1 requirements for this level.

5.1.3 Commercial. Rosettes shall be preserved in accordance with the applicable requirements of ASTM-D-3951.

5.2 Packing. Packing shall be level B, C or commercial as specified (see 6.2).

5.2.1 Level B. Rosettes, preserved as specified in 5.1, shall be packed in exterior type shipping containers conforming to PPP-B-636, class weather resistant. The closure of the shipping container shall be in accordance with the appendix of the applicable shipping container specification.

5.2.2 Level C. Rosettes, preserved as specified in 5.1, shall be packed to the MIL-STD-2073-1 requirements for this level.

5.2.3 Commercial. Rosettes, preserved as specified in 5.1, shall be packed in accordance with the applicable requirements of ASTM-D-3951.

5.3 Palletization. When specified items packed as specified shall be palletized on a 4-way entry pallet in accordance with load type 1A of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance bonding means C, K and L or O or P. Pallet pattern shall be in accordance with the appendix of MIL-STD-147. The pallet shall be 4-way, type I, class 1, style 1, size A, wood group I, II, III, or IV of MIL-P-15011, or 4-way, type IV, V or VIII, class 1, style A, size 2, wood group I, II, III or IV, grade A of NN-P-71. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the patterns specified in MIL-STD-147, the pallet pattern used shall be approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with Standard MIL-STD-129 or ASTM-D-3951 as applicable.

Source: https://assist.dla.mil -- Downloaded: 20260-22T13:18Z
Check the source to verify that this is the current version before use.

6. NOTES.

6.1 Intended use. Rosettes required by this specification are intended for wear on civilian clothes to indicate award of a specific decoration.

6.2 Ordering data.

6.2.1 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.
b. Item and applicable specification sheet (2.1).
c. When guide sample will not be furnished (3.2).
d. When a first article is not required (3.3).
e. Selection of applicable level of packaging (see 5.1 and 5.2).
f. When palletization is required.

6.3 Samples. For access to standard samples, address the contracting activity issuing the invitation for bids.

6.4 First article. When a first article inspection is required, the item should be a first article sample or it may be a standard production item from the contractor's current inventory as specified in 4.4). The first article should consist of one completed rosette. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

6.5 Changes from previous issue. Asterisks or vertical lines are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of changes. Authorization for manufacture of medals by the zinc diecast method has been deleted in this revision.

6.6 Subject term (keyword) listing.

Rosettes
Attaching devices
Heraldic
Prong and clutch type
Ribbon
Decoration

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T13:18Z
Check the source to verify that this is the current version before use.

Custodians:
Army - IH
Air Force - 11
Navy - NU

Review activities:
Air Force - 82,99
Navy - MC

User activities:
Air Force - 45

Preparing activity:
Army - IH

(Project No. 8455 - 0226)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T13:18Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-R-14649	Rosettes, General Specification for

3a. NAME OF SUBMITTING ORGANIZATION

b. ADDRESS *(Street, City, State, ZIP Code)*

4. TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional

b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional

c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional

8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T13:18Z
Check the source to verify that this is the current version before use.