MILITARY SPECIFICATION

DISPLAYS, DIODE, LIGHT EMITTING, SOLID STATE, RED, NUMERIC AND HEXADECIMAL, WITH ON BOARD DECODER/DRIVER

This amendment forms a part of Military Specification MIL-D-87157/1, dated 19 May 1983, and is approved for use by the US Army Electronics Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.2.3, delete and substitute:

"1.2.3 Luminous intensity code. The luminous intensity code for devices1/ 01, 02, and 04 shall be as follows:

Luminous intensity code	Minimum luminous intensity µcd	–	Maximum luminous intensity µcd
C	44		79
D	59		106
E	79		142
F	106		190
G	142		255
H	190		342
I	257		462
J	343		617
K	457		821
X	2/		2/

1/ Due to the 03 device design, the external drive conditions of the device determine the brightness of the device, therefore the luminous intensity code shall not be marked on the device.

2/ The luminous intensity code "X" shall not be marked on the display or its packaging. This designation is provided for use in drawings, part lists, purchase orders, and other documentation. Where a luminous intensity code is required, it shall be specified in the contract or order (due to the overlapping of the luminous intensity codes, it is recommended that the two adjacent categories be specified)."

PAGE 2

FIGURE 1, dimensions table, row L, Max inches column: Delete ".815" and substitute ".615".

PAGE 9

4.2, screen 7, Conditions column: Delete "Subgroups 1 and 7" and substitute "I_V of subgroup 7 and Subgroup 1".

PAGE 10

4.2.1, delete and substitute:

"4.2.1 Internal visual (precap) inspection. Internal visual (precap) inspection shall be in accordance with method 2072 of MIL-STD-750."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:52Z
Check the source to verify that this is the current version before use.

PAGE 13

4.5.3, add to the end of the paragraph:

"Initial conditioning shall be in accordance with 4.5.2 herein, except only one bend shall be required."

PAGE 24

TABLE I, Subgroup 7, Luminous intensity per LED average, Conditions column: Delete "V_{CC} = 5.0 V dc" and substitute "V_{CC} = 5.0 V dc (device types 01, 02, and 04), I_F = 6.0 mA dc (device type 03)"; Max limits column: Delete "342" and substitute "821".

TABLE I, Subgroup 7, Functional test, Conditions column, delete and substitute:

"Logic low level = 0.8 V dc (device types 01, 02, and 04)
Logic high level = 2.0 V dc (device types 01, 02, and 04)
I_F = 6.0 mA dc (device type 03)".

Custodian:
Army - ER

Agent:
DLA - ES

Preparing activity:
Army - ER

(Project 5961-A889)

☆U.S. GOVERNMENT PRINTING OFFICE: 1984 — 705-040/A4075

Source: https://assist.dla.mil Downloaded: 2026-10-23T11:52Z
Check the source to verify that this is the current version before use.