The documentation and process conversion measures necessary to comply with this amendment shall be completed by 27 May 1997

INCH POUND

MIL-D-87157/1(ER)
AMENDMENT 2
26 March 1997
SUPERSEDING
AMENDMENT 1
13 August 1984

MILITARY SPECIFICATION

DISPLAYS, DIODE, LIGHT EMITTING, SOLID STATE, RED NUMERIC AND HEXADECIMAL, WITH ON BOARD DECODER/DRIVER

This amendment forms a part of MIL-D-87157/1(ER), dated 19 May 1983, and is approved for use by the US Army Electronics Research and developement Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.2.3, delete and substitute:

"1.2.3 Luminous intensity code. The luminous intensity code for devices 1/ 01, 02, and 04 shall be as follows:

Luminous intensity code	Minimum luminous intensity µcd	Maximum luminous intensity µcd
C	44	79
D	59	106
E	79	142
F	106	190
G	142	255
H	190	342
I	257	462
J	343	617
K	457	821
X	2/	2/

1/ Due to the 03 device design, the external drive conditions of the device determine the brightness of the device, therefore the luminous intensity code shall not be marked on the device.

2/ The luminous intensity code "X" shall not be marked on the display or its packaging. This designation is provided for use in drawings, parts lists, purchase orders, and other documentation. Where a luminous intensity code is required, it shall be specified in the contract or order (due to the overlaping of the luninous intensity codes, it is recommended that the two adjacent categories be specified.

PAGE 2

FIGURE 1, dimensions table, row L, Max inches column: Delete ".815" and substitute ".615".

PAGE 9

4.2 screen &, Conditions column: Delete "Subgroups 1 and 7" and substitute "I_V of subgroup 7 and subgroup !".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:52Z
Check the source to verify that this is the current version before use.

PAGE 10

4.2.1, delete and substitute:

" 4.2.1 Internal visual (precap) inspection. Internal visual (precap) inspection shall be in accordance with method 2072 of MIL-STD-750.

PAGE 12

* FIGURE 3. Burn in circuits continued, note 3; delete and substitute as follows:

"3. Current limiting resistors; 2 %, ¼ W: R_1 = R_8 = 114 ohms, R_2 = 75 ohms, R_3 = R_4 = 421 ohms

PAGE 13

4.5.3 add to the end of the paragraph:

"Initial conditioning shall be in accordance with 4.5.2 herein, except only one bend shall be required."

PAGE 24

"TABLE I, Subgroup 7, luminous intensity per LED average, Conditions column: Delete "V_{CC} = 5.0 V dc" and substitute "V_{CC} = 5.0 V dc (device types 01, 02, and 04), I_F = 6.0 mA dc (device type 03)"; Max limits column: Delete "342" and substitute "821+

TABLE 1, subgroup &, function test, Conditions column, delete and substitute:

"Logic low level = 0.8 V dc (device types 01, 02, and 04). Logic high level = 2.0 V dc (device types 01, 02 and 04).), I_F = 6.0 mA dc (device type 03).

PAGE 22

* Concluding material: Delete and substitute as printed in this amendment.

NOTE: The margin of this amendment is marked with asterisks to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - CR
Air Force - 17

Preparing activity:
DLA -ES

(Project 5980-0017)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:52Z
Check the source to verify that this is the current version before use.