NOTE. The document identifier and heading has been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

MIL-PRF-39012/85B
3 October 1988
SUPERSEDING
MIL-C-39012/85A
28 July 1983


PERFORMANCE SPECIFICATION

CONNECTORS, RECEPTACLES, ELECTRICAL, COAXIAL, RADIO FREQUENCY, SERIES QSC (CABLED, SOCKET CONTACT, JAM NUT MOUNTED, REAR MOUNTED, CLASS 2)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the connectors described herein shall consist of this specification and the latest issue of MIL-PRF-39012.

MARKING IMPLEMENTATION DATE, CATEGORY B, SEE TABLE III



Inches	mm	Inches	mm
.022	0.56	.755	19.18
.098	2.49	.760	19.30
.260	6.60	1.000	25.40
.338	8.59	1.077	27.36
.341	8.66	1.091	27.71
.343	8.71	1.160	29.48
.346	8.79	2.000	50.80
.750	19.05		

NOTES:
1. Dimension "B" is the largest overall diameter of the connector.
2. For dimensions "A" and "B" see table I and II.
3. Dimension 1.160 defines the overall diameter.
4. Wrench flats to accommodate standard wrench opening in accordance with FED-STD-H28, appendix 10.
5. Dimension 2.000 defines the maximum length of the connector when assembled to the appropriate cable
6. All undimensioned pictoral configurations are for reference purposes only.
7. Series QSC, socket contact interface per MIL-STD-348.

FIGURE 1. General configuration

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:10Z
Check the source to verify that this is the current version before use.

TABLE I. Dash number and usage cross-reference.

Dash number 1/	Applicable cable no. 6
CATEGORY A - FIELD SERVICEABLE 4/ (NO SPECIAL TOOLS REQUIRED)	
0001 5/	M17/2-RG006Δ M17/112-RG304Ø M17/171-00001Ø M17/73-RG212* M17/162-00001Ø
0002 5/	M17/74-RG213 M17/163-00001Ø M17/75-RG214* M17/164-00001Ø M17/77-RG216Δ RG2250
0003 5/	M17/78-RG217* M17/165-00001Ø
0004 5/	M17/72-RG211* M17/161-00001Ø
0005 5/	M17/79-RG218* M17/166-00001Ø
CATEGORY C - FIELD REPLACEABLE (MIL-C-22520/5-01 BASIC CRIMP TOOL) 2/	
0013 3/	M17/112-RG304*Ø≠ M17/171-00001≠Ø
0014 3/	M17/173-RG212*≠ M17/162-00001≠Ø
0015 3/	M17/74-RG213*≤ M17/163-00001≤Ø
0016 3/	M17/75-RG214*≤ M17/164-00001≤Ø
0017 3/	RG225*Ø≤
0018 3/	M17/6-RG011*Δ≤
0019 3/	M17/65-RG165*Ø≤ M17/159-00001≤Ø

1/ Typical mating connectors for each dash number are those connectors of MIL-C-39012/63 which are of the same category and utilize the cable.

2/ Category C connectors are assembled by means of the applicable crimping tool per MIL-C-22520 to the specified cable stripped in accordance with figure 2.

3/ These connectors have captivated center contacts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:10Z
Check the source to verify that this is the current version before use.

4/ Inactive for new design. Not for Air Force or Navy use.

5/ These connectors shall be furnished with noncaptive center contacts.

¤ The latest version of each cable shall be applicable.

* Cable to be used when performing tests requiring cable except as in notes 0 and Δ.

0 Cable to be used for the +200°C thermal shock tests.


Δ These are not 50 ohm cables, therefore, when attached to the specified connectors, VSWR, RF leakage and insertion loss are not applicable.

≠ M22520/5-35 Closure A or M22520/5-55 Closure A

< M22520/5-61

∂ Caution is directed to the application of this cable above 400 MHz. Attenuation is tested only at 400 MHz. SRL and power handling capabilities are not stipulated herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:10Z
Check the source to verify that this is the current version before use.



Inches	mm
.187	4.75
.396	10.06
.416	10.57
.490	12.45
.510	12.95
.677	17.20
.697	17.70

NOTES:
1. Dimensions are inches.
2. Metric equivalents are given for general information only.

FIGURE 2. Cable stripping dimensions for category C connectors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:10Z
Check the source to verify that this is the current version before use.

ENGINEERING DATA:

Nominal impedance: 50 ohms.

Frequency range: 0 to 11,000 MHz.

Voltage rating:

1,500 volts rms maximum working voltage at sea level.

325 volts rms maximum at 70,000 feet.

Temperature rating: -65°C to +165°C.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Force to engage and disengage:

Longitudinal force - Not applicable.

Torque - 2-1/2 inch-pounds maximum.

Coupling proof torque: 15 inch-pounds minimum.

Inspection conditions: 6 to 10 inch-pounds.

Mating characteristics:

See MIL-STD-348.

Center contact (socket):

Oversize test pin - .098 diameter minimum (nonclosed entry contacts only).

Insertion depth - .125 minimum.

Number of insertions - One.

Insertion force test - Steel test pin diameter .092 minimum.

Test pin finish - 16 microinches.

Insertion force - 2 pounds maximum.

Withdrawal force test - Steel test pin diameter .090 maximum.

Withdrawal force - 2 ounces minimum.

Test pin finish - 16 microinches.

Hermetic seal: Not applicable.

Leakage (pressurized connectors): Not applicable.

Insulation resistance: Method 302 of MIL-STD-202, test condition B. 5,000 megohms minimum.

Center contact retention: 6 pounds minimum axial force. Applicable to captivated-center-contact connectors only.

Corrosion (salt spray): Method 101 of MIL-STD-202, test condition B.

Voltage standing wave ratio (VSWR):

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:10Z
Check the source to verify that this is the current version before use.

From 500 to 11,000 MHz, or approximately 80 percent of upper cutoff frequency of the cable, whichever is lower. 1.30 maximum.

Swept frequency VSWR test setup:

Item 6 - VSWR shall be less than 1.015 + .005 F (F in GHz).

Item 16 - VSWR shall be less than 1.015 + .005 F (F in GHz).

Second step of VSWR checkout procedure - VSWR shall be less than 1.045 + .015 F (F in GHz).

Group B inspection - VSWR shall be less than 1.01 +.01 F (F in GHz).

Group C inspection - VSWR shall not exceed 1.1.

Connector durability:

500 cycles minimum at 12 cycles/minute maximum. The mating force shall not diminish by more than 10 percent.

Contact resistance: In milliohms maximum.

	Initial	After environment
Center contact:	1.0	1.5
Outer contact:	.20	Not applicable
Braid to body:	.05	Not applicable

Dielectric withstanding voltage: Method 301 of MIL-STD-202. 4,000 volts rms at sea level.

Vibration, high frequency: Method 204 of MIL-STD-202, test condition B.

Shock: Method 213 of MIL-STD-202, test condition G.

Thermal shock: Method 107 of MIL-STD-202, test condition B, except test high temperature shall be +85°C. High temperature shall be +200°C for connectors using +200°C cables (see table I and II).

Moisture resistance: Method 106 of MIL-STD-202. No measurements at high humidity. Insulation resistance shall be at least 200 megohms within 5 minutes after removal from humidity.

Corona level:

Altitude - 70,000 feet.

Voltage - 750 volts minimum.

RF high potential withstanding voltage:

Voltage and frequency - 2,500 volts rms at 5 MHz.

Leakage current - Not applicable.

Cable retention force:

Non-crimp assemblies: 75 pounds minimum.

Crimp assemblies:

50 pounds minimum for cables .155-.189 OD.
60 pounds minimum for cables .190-.229 OD.
75 pounds minimum for cables .230-.249 OD.
90 pounds minimum for cables .250-and larger.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:10Z
Check the source to verify that this is the current version before use.

Coupling mechanism retention force: Not applicable.

RF leakage: -90 dB minimum, tested at a frequency between 2 and 3 GHz.

Insertion loss: 0.15 dB maximum at 10 GHz.

Qualification not required.

Part number: M39012/85 (dash number from table I or "B" number from table II).

TABLE II. Category B-nonfield replaceable (special tools may be required).

NOT FOR AIR FORCE OR NAVY USE. FOR OEM USE ONLY

M39012/85B 1/ 2/ 3/	Applicable cable
10006	MI77112-RG304*@ M17/171-00001ø
10007	MI77173-RG212* M17/162-00001ø
10008	MI7774-RG213* M17/163-00001ø
10009	MI7775-RG214* M17/164-00001ø
10010	RG225*@
10011	MI76-RG011*Δ
10012	MI7765-RG165*@ M17/159-00001ø

1/ Typical mating connectors for each dash number are those connectors of MIL-C-39012/63 which are of the same category and utilize the cable.

2/ These connectors shall be furnished with noncaptive center contacts.

3/ Inactive for new design.

≡ The latest version of each cable shall be applicable.

* Cable to be used when performing tests requiring cable except as in notes @ and Δ.

@ Cable to be used for the +200°C thermal shock tests.

Δ These are not 50 ohm cables, therefore, when attached to the specified connectors, VSWR, RF leakage and insertion loss are not applicable.

ø Caution is directed to the application of this cable above 400 MHz. Attenuation is tested only at 400 MHz. SRL and power handling capabilities are not stipulated herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:10Z
Check the source to verify that this is the current version before use.

TABLE III. Cross-reference of part numbers.

Part number 1/ M39012/85B	Superseded part number M3912/85-
0006	0006
0007	0007
0008	0008
0009	0009
0010	0010
0011	0011
0012	0012

1/ The new "B" part numbers will be required marking 6 months after the date of this specification. The previous part number may be used in the interim.

Revision letters are not used to denote changes due to the extensiveness of the changes.

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - MI, EA
Navy - SH
Air Force - 11, 17, 80, 99
DLA - ES

User activities:
Army - AT, AV
Navy - AS, MC, OS
Air Force - 19

Preparing activity:
Army - CR

Agent:
DLA - ES

(Project 5935-3519-32)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:10Z
Check the source to verify that this is the current version before use.