NOTE The document identifier and heading has been changed on this page to reflect that this is a performance specification There are no other changes to this document The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised

MIL-PRF-39012/90
AMENDMENT 1
1 November 1979

PERFORMANCE SPECIFICATION

CONNECTORS, COAXIAL, RADIO FREQUENCY,
SERIES QNC (UNCABLED) - RECEPTACLE, SOCKET CONTACT,
JAM NUT, FRONT AND REAR MOUNTED, CLASS 2)

This amendment forms a part of Military Specification Sheet MIL-PRF-39012/90, dated 16 May 1973, and is approved for use by all Departments and Agencies of the Department of Defense

PAGE 1

FIGURE 1, under MOUNTING HOLE Delete the part number and substitute
"M39012/90-0001
M39012/90-0002"

FIGURE 1 below HEX NUTS 096 THK Delete "M39012/ -0001" and "M39012/ -0002" and substitute "M39012/90-0001" and "M39012/90-0002", respectively

FIGURE 1, NOTES Add
"6 There shall be a solid barrier in the socket between the pin entry and the solder pocket to prevent solder wicking "

Custodians
Army - CR
Navy - EC
Air Force - 85

Review activities
Army - MI
Navy - SH
Air Force - 11, 17, 99
DLA - ES

User activities
Army - AM, AT AV
Navy - AS MC, OS
Air Force 19

Preparing activity
Army - CR

Agent.
DLA - ES

(Project 5935-3075-17)

Source: https://assist.dla.mil -- Downloaded: 202610-21T17:11Z
Check the source to verify that this is the current version before use.