NOTE: The document identifier and heading has been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

PERFORMANCE SPECIFICATION SHEET


CONNECTORS, PLUG, ELECTRICAL, COAXIAL, RADIO FREQUENCY, SERIES SMA
(CABLED, CLASS 2, WITHOUT CONTACT, .141 SEMIRIGID CABLE)

This amendment forms a part of MIL-C-39012/92C, dated 14 December 1987, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

FIGURE 2 , delete and substitute the following:

"



Inches	mm
.002	0.05
.015	0.38
.0355	0.902
.0370	0 940
.050	1.27
100	2.54

Notes.
1 Dimensions are in inches.
2 Metric equivalents are given for general information only.
3. Deburring is required

FIGURE 2 Cable stripping dimensions for category E and category F connectors "

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 202640-21T17:11Z
Check the source to verify that this is the current version before use.

TABLE I, delete and substitute as follows

" TABLE I Dash number and applicable cable

Dash number	Applicable cable 1/
CATEGORY A - FIELD SERVICEABLE (NO SPECIAL TOOLS REQUIRED) 2/ 3/ 4/	
3002 3102 5/ 4002 4102 5/	M17/130-RG402 6/ M17/130-00001 Through M17/130-00011
CATEGORY E - FIELD REPLACEABLE (MIL-C-22520 CRIMP TOOL) 2/ 3/ 4/ 9/	
3003 3103 5/ 4003 4103 5/	M17/130-RG402 6/ M17/130-00001 Through M17/130-00011

Dash number	Applicable cable 1/	Tool number	Positioning dies	Locator pins 8/	Crimp dies M22520/5
-	CATEGORY F - FIELD REPLACEABLE (MIL-C-22520 CRIMP TOOL) 2/ 3/ 4/				
3201 9/ 3301 5/ 9/ 4201 9/ 4301 5/ 9/	M17/130-RG402 6/ M17/130-00001 Through M17/130-00011	M22520/36-01	M22520/36-03	M22520/36-06, or -16	----
3202 3302 5/ 4202 4302 5/		M22520/5-01	----	----	-05 or -41 cavity B

1/ MIL-C-17 cables are specified by the basic number The latest version of each cable shall be applicable

2/ Durability for center conductor is limited not to be used in application requiring frequent matings

3/ Coupling nuts shall be corrosion-resistant steel with a passivated finish in accordance with MIL-F-14072 (applies to "-3XXX" series connectors only)

4/ For logistics purposes, only connectors with safety wire holes will be stocked

5/ No safety wire holes

6/ Cable to be used when performing tests requiring cable

7/ All corrosion-resistant steel-bodied connectors shall be gold-plated in accordance with MIL-G-45204, type II, class I, at least in the area of solder attachment

8/ The locators required shall be indicated in the assembly instructions

9/ Not for use in Army equipment "

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:11Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - MI
Navy - SH
Air Force - 11, 17, 99
DLA - ES

User activities
Army - AR, AT, ME
Navy - AS, MC, OS
Air Force - 19

Preparing activity
Army - CR

Agent
DLA - ES

(Project 5935-3920)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:11Z
Check the source to verify that this is the current version before use.