
INCH-POUND
MIL-PRF-55365/12C
23 October 2006
SUPERSEDING
MIL-PRF-55365/12B
23 August 2005

PERFORMANCE SPECIFICATION SHEET
CAPACITORS, CHIP, FIXED, TANTALUM, POLARIZED
ESTABLISHED RELIABILITY AND NONESTABLISHED RELIABILITY,
STYLE CWR15

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-55365.



AMSC N/A
FSC 5910

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:17Z
Check the source to verify that this is the current version before use.

Case size	L + .010 (0.25) - .006 (0.15)	W + .008 (0.20) - .004 (0.10)	H + .008 (0.20) - .004 (0.10)	P + .014 (0.35) - .000 (0.0)
L	.063 (1.60)	.033 (0.85)	.033 (0.85)	.006 (0.15)
R	.079 (2.00)	.053 (1.35)	.053 (1.35)	.006 (0.15)
Case size	L ± .008 (0.20)	W ± .008 (0.20)	H ± .008 (0.20)	P + .014 (0.35) - .000 (0.0)
A	.126 (3.20)	.063 (1.60)	.063 (1.60)	.006 (0.15)
F	.158(4.01)	.116(2.95)	.050(1.27)	.010(0.15)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are in parentheses and given for general information only.
3. These capacitors are designed for mounting by dip soldering, reflow soldering, or other conventional means.
4. The anode (+) terminal shall be identified by a marking on all four sides of the case.
5. Solderable surfaces are only those surfaces designated as such. Termination edges are not considered solderable.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Termination finish: Termination finish K in accordance with MIL-PRF-55365.

DC rated voltage: See table I. Above +85°C, voltage derating is required (see MIL-PRF-55365).

Operating temperature range: -55°C to +125°C.

* Product level designator: In accordance with MIL-PRF-55365 except the Weibull Failure Rate Level grading Failure Count during and after test shall be determined by DC leakage measurements of .0135 X CV or 0.1uA, whichever is greater.

DC leakage (DCL): See table I.

Capacitance: See table I.

Capacitance tolerance: ±5 percent (J), ±10 percent (K), or ±20 percent (M).

Dissipation factor (DF): See table I.

Equivalent series resistance (ESR) at 100 kHz: In accordance with MIL-PRF-55365 (see table I).

Resistance to soldering heat: In accordance with MIL-PRF-55365.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:17Z
Check the source to verify that this is the current version before use.

Stability at low and high temperatures: In accordance with MIL-PRF-55365.

Step 1 (+25°C):	DCL	- See table I.
	Capacitance	- Shall not exceed tolerance of table I value.
	DF	- See table I.
Step 2 (-55°C):	Δ Capacitance	- Shall not exceed ±20 percent of initial measurement.
	DF	- See table I.
Step 3 (+25°C):	DCL	- See table I.
	Δ Capacitance	- Shall not exceed ±10 percent of initial +25°C measurement.
	DF	- See table I.
Step 4 (+85°C):	DCL	- See table I.
	Δ Capacitance	- Shall not exceed ±15 percent of initial +25°C measurement.
	DF	- See table I.
Step 5 (+125°C):	DCL	- See table I.
	Δ Capacitance	- Shall not exceed ±20 percent of initial +25°C measurement.
	DF	- See table I.
Step 6 (+25°C):	DCL	- See table I.
	Δ Capacitance	- Shall not exceed ±10 percent of initial +25°C measurement.
	DF	- See table I.

Surge voltage: In accordance with MIL-PRF-55365.

DCL	- See table I.
Δ Capacitance	- Within ±5 percent of initial value.
DF	- See table I.

Life: Method 108 of MIL-STD-202.

2,000 hours:

At 25°C:	DCL	- See table I.
	Δ Capacitance	- Shall not exceed ±10 percent of initial measured value.
	DF	- See table I.
At 85°C:	DCL	- See table I.
At 125°C:	DCL	- See table I.

10,000 hours:

At 25°C:	DCL	- 200 percent of initial requirement.
	Δ Capacitance	- Shall not exceed ±10 percent of initial measured value.
	DF	- See table I.
At 85°C:	DCL	- 200 percent of initial requirement
At 125°C:	DCL	- 200 percent of initial requirement.

Solderability: In accordance with MIL-PRF-55365 except that following steam aging, test samples may have a 30 minute bake out at 150°C prior to solder dipping and all terminations shall exhibit a continuous solder coating free from defects for a minimum of 75 percent of the critical area of any individual termination.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:17Z
Check the source to verify that this is the current version before use.

*

TABLE I. Style CWR15 characteristics.

Part or identifying number (PIN) 1/	DC rated voltage (+85°C) (Volts)	Cap. (nom) (μF)	DC Leakage (max) (μA)			Dissipation factor (max) (percent)			Max ESR 100 kHz +25°C (Ohms)	Case size
			25°C	+85°C	+125°C	+25°C	+85°C +125°C	-55°C		
CWR15CK685--L-	4	6.8	.5	5	6	8	16	12	10	L
CWR15CK106--R-	4	10	.5	5	6	8	16	12	6	R
CWR15CK156--R-	4	15	.6	6	7	8	16	12	6	R
CWR15CK226--R-	4	22	.9	9	11	8	16	12	6	R
CWR15CK336--R-	4	33	1.3	13	16	10	20	15	6	R
CWR15CK686--A-	4	68	2.7	27	33	15	30	23	1	A
CWR15CK107--F-	4	100	4	40	48	20	40	33	1	F
CWR15DK335--L	6	3.3	.5	5	6	6	12	9	10	L
CWR15DK475--L-	6	4.7	.5	5	6	8	16	12	10	L
CWR15DK685--R-	6	6.8	.5	5	6	8	16	12	6	R
CWR15DK106--R-	6	10	.6	6	7	8	16	12	6	R
CWR15DK156--R-	6	15	.9	9	11	8	16	12	6	R
CWR15DK226--A-	6	22	1.4	14	17	10	20	15	6	A
CWR15DK336--A-	6	33	2.0	20	24	10	20	15	6	A
CWR15DK476--A-	6	47	2.8	28	34	15	30	23	4	A
CWR15DK686--F-	6	68	4	40	48	20	40	33	2	F
CWR15FK474--L-	10	0.47	.5	5	6	6	12	9	12	L
CWR15FK684--L-	10	0.68	.5	5	6	6	12	9	10	L
CWR15FK105--L-	10	1.0	.5	5	6	6	12	9	10	L
CWR15FK155--L-	10	1.5	.5	5	6	6	12	9	10	L
CWR15FK225--L-	10	2.2	.5	5	6	6	12	9	10	L
CWR15FK335--R-	10	3.3	.5	5	6	8	16	12	6	R
CWR15FK475--R-	10	4.7	.5	5	6	8	16	12	6	R
CWR15FK685--R-	10	6.8	.7	7	8.5	8	16	12	6	R
CWR15FK106--R-	10	10	1.0	10	12	8	16	12	6	R
CWR15FK156--A-	10	15	1.5	15	18	10	20	15	6	A
CWR15FK336--F-	10	33	3.3	33	40	15	30	25	6	F
CWR15HK105--L-	15	1.0	.5	5	6	6	12	9	18	L
CWR15HK475--R-	15	4.7	1.0	10	12	8	16	12	12	R
CWR15HK106--A-	15	10	1.5	15	18	10	20	15	12	A
CWR15HK156--F-	15	15	2.25	22.5	27	12	24	20	10	F

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:17Z
Check the source to verify that this is the current version before use.

*

TABLE I. Style CWR15 characteristics. Continued.

Part or identifying number (PIN) 1/	DC rated voltage (+85°C) (Volts)	Cap. (nom) (μF)	DC Leakage (max) (μA)			Dissipation factor (max) (percent)			Max ESR 100 kHz +25°C (Ohms)	Case size
			25°C	+85°C	+125°C	+25°C	+85°C +125°C	-55°C		
CWR15JK474--L-	20	.47	.5	5	6	6	12	9	24	L
CWR15JK335--R-	20	3.3	.5	5	6	8	16	12	18	R
CWR15JK685--A-	20	6.8	1.4	14	17	10	20	15	18	A
CWR15JK106--F-	20	10	2.0	20	24	12	24	20	12	F
CWR15KK334--L-	25	.33	.5	5	6	6	12	9	30	L
CWR15KK155--R-	25	1.5	.5	5	6	6	12	9	24	R
CWR15KK335--A-	25	3.3	.8	8	9.6	6	12	9	18	A
CWR15KK475--F-	25	4.7	1.2	12	14.4	6	12	9	16	F
CWR15MK224--L-	35	.22	.5	5	6	6	12	9	35	L
CWR15MK474--R-	35	.47	.5	5	6	6	12	9	30	R
CWR15MK105--A-	35	1.0	.5	5	6	6	12	9	24	A
CWR15MK225--F-	35	2.2	.8	8	9.6	6	12	9	18	F
CWR15NK104--L-	50	.1	.5	5	6	6	12	9	40	L
CWR15NK334--R-	50	.33	.5	5	6	6	12	9	35	R
CWR15NK684--A-	50	.68	.5	5	6	6	12	9	30	A
CWR15NK155--F-	50	1.5	.75	7.5	9	6	12	9	24	F

1/ Complete PIN shall include additional symbols to indicate capacitance tolerance, product level designator, and surge current option letter. If surge current is not required, the last "-" shall be replaced with the letter Z.

* NOTES:

Reference documents. In addition to MIL-PRF-55365, this specification sheet references the following documents.

MIL-STD-202

(Copies of these documents are available online at http://assist.daps.dla.mil/quicksearch or http://assist.daps.dla.mil or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:17Z
Check the source to verify that this is the current version before use.

CHANGES FROM PREVIOUS ISSUE The margins of this specification are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - EC
Air Force - 11
NASA - NA
DLA - CC

Review activities:
Army - AR, MI
Navy - AS, MC, OS, SH
Air Force - 19, 99

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5910-2006-059)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:17Z
Check the source to verify that this is the current version before use.