MILITARY SPECIFICATION

FIXTURE, DASHPOT INSPECTION, ASSEMBLY

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of fixture for inspection of dashpots used on M422 Projectile.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-A-8625 ---- Anodic Coatings for Aluminum and Aluminum Alloys

STANDARDS

MILITARY

MIL-STD-105 --- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168 -- Lot Numbering of Ammunition

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

DRAWINGS

ORDNANCE CORPS

8797730 -------	Weight
8804713 -------	Arm
8804714 -------	Hanger
8804715 -------	Pan
8804717 -------	Plate, Adapter
8804718 -------	Cylinder
8804719 -------	Plunger
8804720 -------	Support
8804721 -------	Base
8804722 -------	Fixture, Dashpot Inspection Assembly
8806691 -------	Handle
8806692 -------	Pin
8806693 -------	Slide
8806694 -------	Post
8807297 -------	Case, Carrying, for Fixture, Dashpot Inspection Assembly
8807339 -------	Container, Metal, Ammunition for Fixture, Dashpot Inspection, Assembly
EL-8804722 ----	Equipment List

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The fixture and case shall comply with all requirements specified on the drawings (dwgs) 8804722 and 8807297, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

3.3 Protective finish. The following parts shall be coated and tested as specified in 4.4.1.

8804713	Arm	8804720	Support
8804714	Hanger	8804721	Base
8804715	Pan	8806691	Handle
8804717	Plate, Adapter	8806692	Pin
8804718	Cylinder	8806693	Slide
8804719	Plunger	8806694	Post

3.4 Workmanship.

3.4.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.4.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.4.3 Burrs. Parts shall be free from burrs.

3.4.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust corrosion, or any embedded foreign material.

3.4.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection. Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Tables I and II), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Table I

Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131			

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

Table II

Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Support (see dwg 8804720) covering a detail of dwg 8804722.

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major		
101.	Location of pivot pin hole	Gage
102.	Diameter of pivot pin hole, min.	Gage
103.	Material (see 3.1)	Visual
Minor		
201.	Workmanship (see 3.4)	Visual/Manual

4.3.2.1.2 Fixture, dashpot inspection assembly (see dwg 8804722).

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major		
101.	Length from scale pan groove to center of pivot pin, max.	Gage
102.	Total length from base, min.	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

103.	Machine screw below surface of base	Visual
104.	Dial indicator glass not broken or cracked	Visual
105.	No operation missing or incomplete	Visual
106.	Component tight and present	Visual
Minor		
201.	Protective finish no bare spot	Visual
202.	Workmanship (see 3.4)	Visual/Manual

4.3.2.1.3 Case, carrying, for fixture, dashpot inspection assembly (see dwg 8807297) with cover open.

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major		
101.	No wood panel broken	Visual
102.	No pad loose or missing	Visual/Manual
103.	No fixture component loose or missing	Visual/Manual
Minor		
201.	Workmanship (see 3.4)	Visual/Manual

4.3.2.1.4 Case, carrying, for fixture, dashpot inspection assembly (see dwg 8807297).

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major		
101.	Marking present and identifiable	Visual
102.	No hinge loose or improperly assembled	Visual/Manual
103.	No latch loose or improperly assembled	Visual/Manual
104.	No hardware loose or missing	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

Minor
201. Workmanship (see 3.4) ..... Visual/Manual

4.3.2.1.5 Container, metal, less cover and top pad (see dwg 8807339).

Categories	Characteristics	Method of Inspection
Critical: None defined		
Major		
101.	Desiccant bag not broken or missing	Visual
102.	Carrying case tightly packed	Visual/Manual
103.	Packing material thoroughly dry	Visual/Manual
104.	Material (see 3.1)	Visual
Minor		
201.	Workmanship (see 3.4)	Visual/Manual

4.3.2.1.6 Container, metal (see dwg 8807339).

Categories	Characteristics	Method of Inspection
Critical: None defined		
Major		
101.	Marking present, correct and identifiable	Visual
102.	Cover tight and properly assembled	Visual/Manual
Minor		
201.	Workmanship (see 3.4)	Visual/Manual

4.3.3 Testing. All tests shall be performed. Tests need not be performed in the order specified.

Test	Test Classification
a. Corrosion resistance	Major

This test is not considered destructive, and samples so tested may be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

4.3.3.1 Corrosion resistance (see 3.3). Two test panels shall be prepared from the same type of material as the parts they represent for each 40 hours production and subjected to the protective finish process at the same time as the part they represent. The panels shall be prepared for each individual item being processed for protective finish and tested as specified in 4.4.1. If any test fanel fails to comply with 3.3, the parts being represented by the panel shall be rejected.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Critical and major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions and calibration instructions specified on the Equipment Lists (EL's) (See EL-8804722). When either of the conditions listed below exists, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).

b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on EL's. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances, less the accuracy tolerances of the test equipment used.

4.4.1 Corrosion resistance (see 3.3). The test panels for protective finish shall be tested in accordance with MIL-A-8625.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The fixture and case shall be packaged in accordance with dwg 8807339 using the specified moisture barrier.

5.1.2 Level C. The fixture and case shall be packaged in accordance with dwg 8807339, except that the moisture barrier may be omitted.

5.2 Packing.

5.2.1 Levels A and C. The fixture and case shall be packed in accordance with dwg 8807339.

5.3 Marking. Marking shall be as specified in accordance with dwg 8807339.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number and date of this specification.

b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 when specified on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commanding Officer, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SMUPA-QA-N-I.

6.4 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-1594 (Rev 1), dated 15 March 1962.

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 1190-A064

☆ U. S. GOVERNMENT PRINTING OFFICE: 1973-713-146/1385

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION
MIL-F-48208(MU) Fixture, Dashpot Inspection, Assembly

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?
   ☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 56 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding Officer
Picatinny Arsenal
ATTN: SARPA-QA-N-Q
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.