MIL-I-60084E(EA)
15 February 1974
SUPERSEDING
MIL-I-60084D(MU)
9 November 1972

MILITARY SPECIFICATION

INITIATOR, BOMB FUZE, FMU-7C/B

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of initiator.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

QQ-S-781	-	Strapping, Steel Flat and Seals.
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner.
PPP-F-320	-	Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-810	-	Environmental Test Methods.
MIL-STD-1168	-	Lot Numbering of Ammunition.

FSC 1325

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:08Z
Check the source to verify that this is the current version before use.

DRAWINGS

US ARMY ARMAMENT COMMAND

EDGEWOOD ARSENAL

D14-15-918 - Initiator, Bomb Fuze, FMU-7C/B.
IDL14-15-918 - Initiator, Bomb, Fuze, FMU-7C/B Inspection Data List.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing D14-15-918 or on the subsidiary drawings shall conform to the specifications listed thereon or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the initiator shall conform to the specifications and drawings listed on Drawing D14-15-918 and on subsidiary drawings.

3.2 Assembly. The initiator shall be assembled as shown on Drawing D14-15-918.

3.3 Activation. When tested in accordance with 4.4.4.3 and 4.4.4.1 the assembled initiator shall comply with the following:

(a) The force required to withdraw the safety wire from the assembled initiator shall be 1 to 10 pounds.

(b) The force required to pull the initiator cap free from the assembled initiator minus the safety tab shall be 45 ± 20 pounds when applied at the rate of 10 inches per minute. The force shall be applied, pulling on the lanyard in a direction within 15 degrees of parallel to the axis.

(c) The activation time shall be between 0.30 and 0.78 second. Activation time is the interval between the withdrawal of the initiator

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:08Z
Check the source to verify that this is the current version before use.

cap assembly and the recording of an output of 1.3 volts D C across a 2.0 ohm resistance. The 1.3 volts D C minimum shall be maintained for a minimum period of 0.5 seconds.

3.4 Waterproofness. When tested in accordance with 4.4.4.2, the assembled initiator shall show no evidence of leakage under the following conditions:

(a) The assembled initiator shall be immersed in nitrogen under s pressure of 25 + 5 pounds per square inch gage (psig) for a period of 30 + 5 minutes.

(b) Within 30 seconds after removal from the nitrogen, the assembled initiator shall be immersed in water for a period of 60 + 5 seconds. The depth of the water above the initiator shall be 3 + 3 inches. Presence of bubbles indicates leakage.

3.5 Vibration. The initiator shall comply with 3.3 after testing in accordance with 4.4.4.3.

3.6 Lanyard. The lanyard shall withstand a minimum load of 140 pounds pull applied at a rate of 8 to 10 inches per minute to the swivel, Drawing C14-23-34 and to the loop holding the cap, Drawing C14-15-924 when tested in accordance with 4.4.4.4. Withstand is defined as the cable shall not break, fray or slip out of the ferrules nor shall the swivel break or separate.

3.7 Preproduction. Prior to the start of regular production, a preproduction lot of initiators shall be produced in accordance with this specification for examination and test (see 4.3).

3.8 Workmanship. The initiator shall be free from foreign matter (oil, grease or dirt) and damage such as dents, cracks or deformation which could affect its intended use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:08Z
Check the source to verify that this is the current version before use.

otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3)
(b) Quality conformance inspection (see 4.4)

4.3 Preproduction inspection.

4.3.1 Lot. A preproduction lot of 250 initiators shall be manufactured using the same methods, materials, equipment and processes as will be used during regular production.

4.3.2 Sampling.

4.3.2.1 For examination and nondestructive test. Sixty initiators shall be taken at random from the preproduction lot.

4.3.2.2 For destructive tests. Sampling shall be conducted in accordance with table I.

4.3.3 Inspection procedure.

4.3.3.1 For examination and nondestructive test. Sample initiators shall be examined and tested in accordance with the classification of defects. The AQL's do not apply.

4.3.3.2 For destructive tests. Forty of the sample initiators (4.3.2.1) shall be tested in accordance with table I. The remaining sample may be returned to the preproduction lot if acceptable.

4.3.4 Acceptance/rejection criteria. The preproduction sample initiators shall comply with the examinations and tests specified in 4.3.3 to

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:08Z
Check the source to verify that this is the current version before use.

be acceptable. The acceptance number is zero. The supplier shall obtain written approval from the contracting officer prior to proceeding with regular production.

Table I. Preproduction sampling and inspection

Sample (quantity)	Requirement	Inspection
	3.4 Waterproofness	4.4.4.2
	3.3 Activation	4.4.4.1
20	3.6 Lanyard	4.4.4.4
	3.5 Vibration	4.4.4.3
20	3.3 Activation	4.4.4.1

4.4 Quality conformance inspection.

4.4.1 Lotting. Each lot shall be identified and controlled in accordance with MIL-STD-1168. However, no more than one interfix number of thermal batteries from one manufacturer shall be contained in any one lot of assembled initiators.

4.4.2 Sampling.

4.4.2.1 For examination and nondestructive test. Sampling shall be conducted in accordance with MIL-STD-105.

4.4.2.2 For destructive tests. Sampling shall be conducted in accordance with MIL-STD-105, inspection level S-4.

4.4.3 Inspection procedure.

4.4.3.1 For examination and nondestructive test. The sample initiators shall be examined and tested in accordance with the classification of defects and with MIL-STD-105.

4.4.3.2 For destructive tests. The samples shall be tested as follows: (a) Initiators. After vibration (4.4.4.3) test for conformance with 3.3: Activation time and battery life in accordance with 4.4.4.1 and MIL-STD-105 using an AQL of 1.5 percent defective; Safety wire from initiator and initiator cap assembly from initiator in accordance with 4.4.4.1 and MIL-STD-105 using an AQL of 1.0 percent defective. (b) Lanyards. In accordance with 4.4.4.4 (3.6) and MIL-STD-105 using an AQL of 1.0 percent defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:08Z
Check the source to verify that this is the current version before use.

4.4.3.3 For critical defects. Each Initiator in the lot shall be examined for its critical characteristics listed in the classification of defects.

4.4.3.4 Classification of defects.

(a) Initiator, bomb, fuze, FMU-7C/B (Drawing D14-15-918).

Categories	Defects	Acceptance standards
Critical:		
1	Safety tab missing	
2	Safety wire missing	
Major:	AQL 1.0 percent defective	
101	Component missing or incorrectly assembled	
102	Overall length incorrect	
103	Thread incorrect	
104	Material overlap after staking	
105	Waterproofness incorrect	4.4.4.2
106	Workmanship (3.8)	

(b) Spring, firing pin (Drawing B14-15-2430).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Spring load at height of 0.5 inches incorrect

(c) Pin, firing (Drawing C14-15-922).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Firing pin profile incorrect

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:08Z
Check the source to verify that this is the current version before use.

(d) Preparation for delivery (section 5).

Categories	Defects
Critical:	None defined
Major:	AQL 4.0 percent defective
101	Container incorrect
102	Container incorrectly closed
103	Marking missing, incorrect or illegible
104	Strapping missing

4.4.4 Tests. Tests shall be conducted as follows: (See inspection data list IDL14-15-918 for inspection equipment required to perform the tests specified in this section.)

4.4.4.1 Activation.

(a) Attach the safety wire to a measuring device.

(b) Attach the initiator lanyard to a measuring device.

(c) Connect the initiator to a timing device.

(d) Pull the safety wire from the initiator.

(e) Pull the initiator cap assembly free from the initiator as specified and record activation time, voltage and battery life.

4.4.4.2 Waterproofness. The initiator assembly shall be conditioned as required and then submerged in water containing a wetting agent for the required period of time. The water shall be 20° ± 5°F above ambient temperature.

4.4.4.3 Vibration. The initiator minus safety tab shall be conditioned in accordance with method 514.1, table 514.1 VII equipment category g (shipment by common carrier) procedure X and curve AW of MIL-STD-810.

4.4.4.4 Lanyard. A test fixture shall be provided with mounting hooks such that the swivel and loop will be supported by 1/4-inch-diameter cross sections. The actual load required to cause failure of the lanyard shall be recorded.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:08Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging, level A. The initiator shall be packaged, one per can in accordance with Drawing C14-15-1020.

5.2 Packing, level A. The initiators, packaged in accordance with 5.1, shall be packed, 14 per box, in boxes conforming to Class 2, style 4, Grade A, 0-50 lb limit for type 1 or 2 load for overseas shipment, PPP-B-621, having inside dimensions in inches of 19 1/2 by 5 3/4 by 5 1/4 length, width and depth, respectively. Arrangement shall be two rows of seven cans each. Liner pads of fiberboard conforming to either W6C or W5C of PPP-F-320 shall be included to line all six interior faces of the boxes. Additional pads shall be included as necessary to restrict free movement of the cans. Boxes shall be closed and strapped in accordance with the appendix to PPP-B-621. Strapping shall conform to either type I or IV, Class A or B of QQ-S-781.

5.3 Palletization. When specified in the contract or order (see 6.2), the initiator packed as specified in 5.2 shall be palletized in accordance with Drawing D14-15-1000.

5.4 Marking. In conjunction with information furnished in the contract or order, marking shall be as specified herein.

5.4.1 Package. Each can shall be marked with the Federal stock number, Department of Defense ammunition code number, nomenclature, quantity and unit of issue, contract or purchase order number, level of packaging and month and year packaged. Marking shall be applied in accordance with the applicable requirements of MIL-STD-129.

5.4.2 Packing. Boxes shall be marked in accordance with Drawing D14-15-987.

5.4.3 Pallet. Pallet loads shall be marked in accordance with Drawing D14-15-1000.

6. NOTES

6.1 Intended use. This item is intended for use as a component of a bomb fuze.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Palletization when required (mandatory for overseas shipment).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:08Z
Check the source to verify that this is the current version before use.

(c) Pertinent identification marking.
(d) Applicable address marking.
(e) Shipment priority number if applicable.
(f) Transportation control number, project code and required delivery date if applicable.
(g) Any special marking required.
(h) Preproduction:

(1) Time allowed for supplier's submission of samples for Government test and evaluation after award of contract.
(2) Name and address of test facility and shipping instructions when testing is performed by the Government.
(3) Time required for the Government to notify the supplier whether to proceed with production.

6.3 Component. Thermal battery, MIL-B-55291 is a key component required for the complete assembly and proper functioning of the end item.

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 1325-A537

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:08Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding Officer
Edgewood Arsenal
Attn: SMUEA-TS-S
Edgewood Arsenal, MD 21010

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:08Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:08Z
Check the source to verify that this is the current version before use.