MIL-P-60316A(MU)
Amendment 1
20 November 1973

MILITARY SPECIFICATION
PRIMER, PERCUSSION, M32 LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-P-60316A(MU) dated 15 June, 1968.

In paragraph 2.1 under Specifications: Delete "MIL-I-45607 - Inspection Equipment, Supply and Maintenance of"
Add "MIL-C-45662- Calibration System Requirements.

Paragraph 2.1 under Publications:
Delete "ET-8880637 Equipment Tabulation."
Delete Paragraph 3.5 in its entirety
Redesignate Paragraph 3.6 as 3.5.

Delete Paragraph 4.1.1 in its entirety and substitute the following:

4.1.1 Submission of product.-At the time the completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information providied is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.
b. Drawing and specification number and date, together with an identification and date of changes thereto.
c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.
d. Number of items in the lot.
e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organizaiton.

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:27Z
Check the source to verify that this is the current version before use.

In the sub-sections under 4.2.2 make the following changes:
Delete "Code No." and the code numbers "01001" through and including "06008" wherever they appear.

In paragraph 4.2.2.1 Major 101, add "CD" after the word Balance.

In paragraph 4.2.2.2 Major 101, 102, 107 and 108, and Minor 203 and 204, add "CD" after the word Gage.

In paragraph 4.2.3.1- Delete "Code No. 07001"

In paragraph 4.2.3.2.1- Delete "Code No. 02013"

Delete paragraph 4.2.3.2.2 in its entirety and substitute the following:
"4.2.3.2.2 Functioning (see 3.4.2)-Major defect.-Beginning with the first lot produced and continuing until three consecutive lots have complied with the acceptance criteria specified, 500 primers shall be randomly selected from each lot for this test. If 4 or more primers fail to comply with the specified requirement, the lot shall be rejected. If 2 but less than 4 defectives are found a second sample of 500 primers shall be tested. If the combined number of defectives in both the first and second samples is 5 or more, the lot shall be rejected. Any primers in the randomly selected sample missing a component or with an incorrectly assembled component which will result in an end item misfire shall be considered a defective and shall be included in the rejection criteria. The test shall be performed as specified in 4.3.1.2."

Delete paragraph 4.2.3.2.2.1 in its entirety and substitute the following:"4.2.3.2.2.1 After three consecutive lots have met the criteria of 4.2.3.2.2, a sample of 315 primers shall be randomly selected from each lot for this test. If 3 or more primers fail to comply with the specified requirement, the lot shall be rejected. If 1 but less than 3 defectives are found a second sample of 315 primers shall be tested. If the combined number of defectives in both the first and second sample is 4 or more the lot shall be rejected. Any primer in the randomly selected sample missing a component or with an incorrectly assembled component which will result in an end item misfire shall be considered defective and shall be included in the rejection criteria. The test shall be performed as specified in 4.3.1.2."

Delete paragraphs 4.2.3.3 and 4.2.3.3.1 in their entireties.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:27Z
Check the source to verify that this is the current version before use.

In paragraph 4.2.3.4 change "4.2.3.4" to "4.2.3.3"

In paragraph 4.2.3.5 delete "Code No. 05005" and change "4.2.3.5" to "4.2.3.4".

Delete paragraph 4.2.4 in its entirety and substitute the following:

"4.2.4 Inspection Equipment.-The inspection equipment required to perform the examinations and tests prescribed in this section is identified under the "Method of Inspection" headings in 4.2.2 or in the appropriate testing paragraph under 4.3 (see 6.2)."

Delete paragraphs 4.2.4.1 and 4.2.4.2 in their entireties and substitute the following:

"4.2.4.1 Inspection Equipment Capability and Accuracy.- All inspection equipment and facilities shall be of adequate quality and quantity to perform properly and accuractely all the required inspections, measurements and tests. The inspection equipment shall be maintained in satisfactory condition for the continued proper performance of these functions and shall be calibrated in accordance with the provisions of MIL-C-45662."

In paragraph 4.2.4.3 change "4.2.4.3" to "4.2.4.2"

Delete paragraph 4.3.1.1 in its entirety and substitute the following:

"4.3.1.1 Non-functioning.-The primer shall be assembled to a test fixture designed (CD) to drop a weight of 2.95 pounds, minimum, from a height of 3/16 inchs, minimum, on a firing pin to function the firing plug of the primer. The height of drop shall be measured as the height from the top of the firing pin to the bottom of the weight. The firing pin of the test fixture shall be adjusted so that the impact will be on the center of the firing plug of the primer. Any primer which functions shall be classed defective. Primers used in this test shall not be returned to the lot. Appropriate safety precautions shall be observed."

Delete paragraph 4.3.1.2 in its entirety and substitute the following:

"4.3.1.2 Functioning.-The primer shall be assembled to a test fixture designed (CD) to drop a weight of 2.95 pounds, maximum, from a height of 1 3/4 inches, maximum, on a firing pin to function the firing plug of the primer.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:27Z
Check the source to verify that this is the current version before use.

The height of drop shall be measured as the height from the top of the firing pin to the bottom of the weight. The firing pin of the test fixture shall be adjusted so that the impact will be 0.05 inch off center of the firing plug. Any primer which fails to function shall be classed defective. Appropriate safety precautions shall be observed."

Delete paragraph 4.3.2 in its entirety.

Redesignate paragraph 4.3.3 as "4.3.2"

Delete paragraphs 6.2, 6.3, 6.3.1, 6.3.2, 6.3.3, 6.3.4 and 6.3.5 in their entireties and substitute the following:

"6.2 Inspection Equipment Designs.-Inspection equipment designs are of two types-Government Special Inspection Equipment (SIE) designs and Contractor Designs. SIE designs, if available are designated by drawing numbers (on the Equipment Lists referenced on the Equipment Tabulation) or (under the "Method of Inspection" headings in Section 4). Design responsibility for all other inspection equipment is assigned to the Contractor. Equipment to be designed by the Contractor is designated "CD". The Contractor need not furnish any design when a complete Government SIE design is provided. Unless otherwise specified however, the Contractor may submit alternate or modified Contractor designs of SIE in accordance with 6.2.2 and 6.2.3, should he elect to do so."

6.2.1 SIE Designs.-SIE designs may consist of any of the following:

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection equipment.

b. A source control drawing or a specification control drawing as defined in MIL-STD-100.

c. An envelope drawing, as defined in MIL-STD-100, which establishes the criteria which a detail design shall meet. When envelope drawings are specified, the Contractor shall prepare designs which comply with the criteria therein.

6.2.2 Contractor Designs.-Contractor designs are required for all inspection equipment for which SIE designs are not specified, and may include commercial equipment which the Contractor proposes to use. (Commercial equipment is defined as unmodified equipment which is cataloged and available for purchase by the general public). Contractor designs shall include appropriate operating instructions, calibration procedures

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

and maintenance procedures. Commercial equipment shall be fully described by catalog listings or other means which provide sufficient information to permit identification and evaluation by the Government and may include illustrations and engineering data. Designs shall be prepared for any special fixture(s) required to be used with commercial equipment, or with SIE designs, if not otherwise covered thereby (see 6.2.1 c). Designs shall be of the category and form (per MIL-D-1000) specified in the Contract Data Requirements Lists (DD Form 1423). The Contractor is referred to MIL-HDBK-204, "Inspection Equipment Design" for guidance. The specification number, paragraph number and defect number (or other specific identifying information) from Section 4 of this specification shall be referenced on each Contractor design, together with the component or assembly drawing number and revision letter to which the specific design applies.

6.2.3 Submission of Designs for Approval.-Contractor designs shall be approved by the Government prior to fabricating or procuring the equipment. Designs shall be submitted for approval in accordance with the stipulations, time frame and distribution specified in the Contract Data Requirements List (DD Form 1423) or in the contract. Partial submission of inspection equipment is permissible and encouraged. However, the completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will normally be accomplished within one month after receipt.

6.3 New Material Test Sample Requirements.-All requests for permission to use materials other than those specified on applicable drawings or specifications should be accompanied by a sample of the proposed substitute material to permit evaluation by Picatinny Arsenal. Prior to approval, all substitute materials must be tested for compatibility with Black Powder, M9 Propellant and with the M35 Primer charge mixture, in addition to any testing required to evaluate the performance of the proposed substitute."

Delete paragraph 6.4.1.1 in its entirety and substitute the following:

"6.4.1.1 Non-functioning.-The sampling plan and acceptance criteria for this test shall be the same as specified in paragraph 4.2.3.2.1.1. The test shall be performed as specified in 4.3.1.1. Primers used in this test shall not be returned to the lot. Appropriate safety precautions shall be observed."

Delete paragraph 6.4.1.2 in its entirety and substitute the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

"6.4.1.2 Functioning.-The sampling plan and acceptance criteria for this test shall be the same as specified in paragraph 4.2.3.2.2.1. Any primers in the randomly selected sample missing a component or with an incorrectly assembled component which will result in an end item misfire shall be considered a defective and shall be included in the rejection criteria. The test shall be performed as specified in 4.3.1.2. Appropriate safety precautions shall be observed.

Paragraph 6.6-Change "SMUPA-ND to "SARPA-QA-A-A'.

Custodian:
ARMY-PA

Preparing Activity:
ARMY-PA

Project Number: 1375-A-054

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.