NOT MEASUREMENT SENSITIVE

MIL-L-11484/82C
14 January 1994
SUPERSEDING
MIL-L-11484/82B
27 June 1988

MILITARY SPECIFICATION SHEET

LAPEL BUTTON, CIVILIAN SERVICE IN VIETNAM MEDAL

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the *Department of Defense Index of Specifications and Standards* (DODISS) specified in the solicitation: MIL-L-11484.

MATERIAL: Red Brass

FINISH: Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 4.

DIMENSIONS:
DIAMETER: 5/8 inch (1.59 cm) (REF)
THICKNESS (At Edge): 0.055 inch ± 0.005 inch (0.139 cm ± 0.012 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-17T16:33Z
Check the source to verify that this is the current version before use.

2. Attaching device shall be prong with pick and wing type clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

Custodians:
Army - IH
Air Force - 11
Navy - NU
Coast Guard - CG

Review activities:
Air Force - 32, 82, 99
Navy - MC
DLA - CT

User activities:
Air Force - 45

Preparing activity:
Army - IH

(Project No. 8455-0743)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:33Z
Check the source to verify that this is the current version before use.