
MILITARY SPECIFICATION SHEET

CONNECTOR, PLUG, ELECTRICAL, CLASS I

(COAXIAL, SERIES TWIN, TWTNC, RIGHT ANGLE)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the connector described herein shall consist of this document and the latest issue of Specification MIL-C-3655.




INCHES	MM
.4375	11.112
.650	16.51
.800	20.32
.963	24.46
1.218	30.94
1.750	44.45

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.
3. Unless otherwise specified tolerance is ±.005.
4. All undimensioned pictorial configurations are for reference purposes only.
5. Contacts, insulator and shell to be oriented within ±3° of position shown.

FIGURE 1. Type TWTNC, electrical plug connector.


FSC 5935


Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:45Z
Check the source to verify that this is the current version before use.



Dim.	Inches		Millimeters	
	Min	Max.	Min.	Max.
A	.440	-	11.18	-
B	Gage test			
C	.062	.064	1.57	1.63
D	.037	.039	.94	.99
E	.228	.260	5.79	6.60
F	.028	.042	.71	1.07
G	.206	.228	5.23	5.79
J	.035	.065	.89	1.65
K	-	.078	-	1.98
L	.063	-	1.60	-
M	.156	-	3.96	-
P	.032	.062	.81	1.57
R	.264	-	6.71	-
S	.001	.004	.03	.10

INCHES	MM
.010	.25
.015	38
.037	94
.039	99
.061	1.55
064	1 63
.180	4.57
.4375	11 112





CONTACT DETAILS

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.
3. Three holes .027 (.69 mm) minimum diameter equally spaced for safety wiring. Location on coupling nut optional.

FIGURE 2. Type TWTNC, visual mating requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:45Z
Check the source to verify that this is the current version before use.

ENGINEERING DATA:

Nominal impedance 78 ohms.

Frequency range DC to 500 MHz, maximum.

Voltage rating 500 Vrms, maximum

Mating connector M3655/16-0001.

Captive contact retention 6 pounds axial

Intended use Type M3655/17-0001 electrical connector is designed for use with radiofrequency cable M17/45-RG108.

REQUIREMENTS

Design and construction: See figures 1 and 2.

Force to engage/disengage
Torque 2 inch-pounds, maximum
Longitudinal force Not applicable.

Coupling proof torque 15 inch-pounds, minimum.

Mating characteristics (see figures 1 and 2 for dimensions)
Inner contacts (sockets)
Oversize test pin 0.042 inch diameter, minimum (nonclosed entry contact only).
Test pin finish 16 microinches
Insertion depth .093 inch, minimum.
Number of insertions One

Insertion force test
Steel test pin diameter .039 inch, minimum.
Test pin finish 16 microinches.
Insertion depth .093 inch, minimum.
Insertion force 2 pounds, maximum

Withdrawal force test
Steel test pin diameter .037 inch, minimum.
Test pin finish 16 microinches.
Insertion depth .093 inch, minimum.
Withdrawal force 2 ounces, minimum

Permeability Applicable

Hermetic seal Not applicable

Leakage Not applicable.

Insulation resistance 5×10^9 ohms, minimum

Contact insulator captivation Applicable, torque shall be 1 inch-pound.

Salt spray (corrosion) Applicable

Connector durability Applicable

Contact resistance (milliohms, maximum)

	Initial	After environment
Inner conductor contacts	3.0	4.2
Outer conductor contacts	.4	Not applicable
Braid to body	.2	Not applicable

Dielectric withstanding voltage 1,500 Vrms, minimum, at sea level.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:45Z
Check the source to verify that this is the current version before use.

Vibration, high frequency: Applicable.

Shock (specified pulse): Applicable.

Temperature cycling: Applicable.

Humidity. Applicable, but no measurement shall be made at high humidity. Insulation resistance shall be at least 2 x 10^8 ohms within 5 minutes after removal from the humidity chamber.

Cable retention force: 25 pounds, minimum.

Coupling nut retention: Applicable.

Marking: In accordance with MIL-C-3655.
Part number: M3655/17-0001.

Qualification: Required.

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities
Army - MI
Navy - OS
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - AT
Navy - AS, MC, SH
Air Force - 19

Preparing activity
Army - CR

Agent.
DLA - ES

(Project 5935-3087-1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:45Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS This form is provided to solicit beneficial comments which may improve this document and enhance its use DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government Fold on lines on reverse side, staple in corner, and send to preparing activity Attach any pertinent data which may be of use in improving this document If there are additional papers, attach to form and place both in an envelope addressed to preparing activity A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed

NOTE This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-3655/17

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

HQ, USA CORADCOM
ATTN DRDCO-CM-DM
Fort Monmouth, NJ 07703

☐ VENDOR ☐ USER ☐ MANUFACTURER

1 ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDED WORDING CHANGE

C REASON FOR RECOMMENDED CHANGE(S)

2 REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO

DATE

DD FORM 1426
1 OCT 76

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:45Z
Check the source to verify that this is the current version before use.

FOLD

HQ, USA CORADCOM
ATTN: DRDCO-CM-DM
Fort Monmouth, NJ 07703

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID



HQ, USA CORADCOM
ATTN: DRDCO-CM-DM
Fort Monmouth, NJ 07703

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:45Z
Check the source to verify that this is the current version before use.