MILITARY SPECIFICATION SHEET

CONNECTOR, RECEPTACLE, ELECTRICAL, CLASS I

(COAXIAL, SERIES TWIN, TWBNC, BULKHEAD)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the connector described herein shall consist of this specification sheet and the latest issue of MIL-C-3655.




FIGURE 1. Type TWBNC, electrical bulkhead receptacle connector.

FSC 5935


Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:47Z
Check the source to verify that this is the current version before use.

INCHES	MM
.005	.13
.022	.56
.050	1.27
.087	2.21
.099	2.51
.127	3.23
.153	3.89
.156	3.96
.169	4.29
.368	9.35
.375	9.52
.380	9.65
.384	9.75
.4375	11.112
.495	12.57
.500	12.70
.505	12.83
.508	12.90
.516	13.11
.563	14.30
.585	14.86
1.060	26.92

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.
3. Wrench flats to accommodate standard wrench per H-28, app. 10.
4. Unless otherwise specified, tolerance is ±.005 (.13 mm).
5. All undimensioned pictorial representations are for reference purposes only.
6. Full threads to within .063 of shoulder.
7. Contacts, insulator, bayonet studs, and mounting flat shall be oriented within ±3° of position shown.

FIGURE 1. Type TWBNC, electrical bulkhead receptacle connector - Continued.


Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:47Z
Check the source to verify that this is the current version before use.




Dim	Inches		Millimeters	
	Min	Max	Min.	Max.
A	.378	.381	9.60	9.68
B	.345	.356	8 76	9.04
C	.327	.336	8 31	8.53
D	.319	.321	8.10	8 15
E	.037	.039	.94	.99
F	.432	.436	10 97	10 07
G	.329	333	8 36	8.46
H	.075	.081	1 90	2.06
J	.171	.200	4.34	5.08
K	.204	.208	5.18	7.11
L	062	.064	1 57	1 63
N	-	.262	-	6.65
P	.188	.206	4.78	5.23
R	.415	-	10.54	-
S	.015	.030	.38	.76
T	0	.028	.0	.71
U	.001	.004	.03	.10
V	.170	.200	4.32	5 08
W	0	.040	.0	1.02

Ⓐ

INCHES	MM
.005	.13
.010	.25
.015	.38
.037	.94
.039	.99
.061	1.55
.064	1.63
.100	2.54
.180	4.57





CONTACT DETAILS

NOTES
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.
3. Concave depression .100 X .005 deep between studs permitted.

FIGURE 2. Type TWBNC, visual mating requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:47Z
Check the source to verify that this is the current version before use.

ENGINEERING DATA:

Nominal impedance: 78 ohms.

Frequency range: 0 to 500 MHz.

Voltage rating: 500 Vrms, maximum, at sea level; 125 Vrms, maximum at 70,000 feet.

Mating connector: M3655/15-0001.

REQUIREMENTS:

Design and construction: See figures 1 and 2.

Force to engage/disengage:
Torque: One inch-pound, maximum.
Longitudinal force: 3 pounds, maximum.

Coupling proof torque. Not applicable.

Mating characteristics (see figures 1 and 2 for dimensions):
Inner contact (sockets):
Oversize test pin: 0.042 inch diameter, minimum (nonclosed entry contacts only).
Test pin finish: 16 microinches.
Insertion depth: .093 inch, minimum.
Number of insertions: One.

Insertion force test:
Steel test pin diameter. .039 inch, minimum.
Test pin finish: 16 microinches.
Insertion depth: .093 inch, minimum.
Insertion force. 2 pounds, maximum.

Withdrawal force test:
Steel test pin diameter: .037 inch, maximum.
Test pin finish: 16 microinches.
Insertion depth: .093 inch, minimum.
Withdrawal force: 2 ounces, minimum.

Permeability: Applicable.

Hermetic seal: Not applicable.

Leakage: Not applicable.

Insulation resistance: 5×10^9 ohms, minimum.

Contact insulator captivation: Applicable.

Salt spray (corrosion): Applicable.

Connector durability: Applicable.

Contact resistance (milliohms, maximum):

	Initial	After environment
Inner conductor contacts:	3.5	4.7
Outer conductor contacts:	.4	Not applicable

Dielectric withstanding voltage: 1,500 Vrms, minimum, at sea level.

Vibration, high frequency: Applicable.

Shock (specified pulse): Applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:47Z
Check the source to verify that this is the current version before use.

Temperature cycling: Applicable.

Humidity: Applicable, but no measurement shall be made at high humidity. Insulation resistance shall be at least 2 x 10^8 ohms within 5 minutes after removal from the humidity chamber.

Cable retention force: Not applicable.

Coupling nut retention: Not applicable.

Marking: In accordance with MIL-C-3655.
Part number: M3655/23-0001.

Qualification: Required.

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - MI
Navy - OS
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - AT
Navy - AS, MC, SH
Air Force - 19

Agent;:
DLA - ES

Preparing activity:
Army - CR

(Project 5935-3252-5)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:47Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS This form is provided to solicit beneficial comments which may improve this document and enhance its use DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government Fold on lines on reverse side, staple in corner, and send to preparing activity Attach any pertinent data which may be of use in improving this document If there are additional papers, attach to form and place both in an envelope addressed to preparing activity A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed

NOTE This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-3655/23A CONNECTOR, RCEPTACLE, ELECTRICAL, CLASS I

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

HQ, CECOM
ATTN: DRSEL -
Ft. Monmouth, N. J. 07703

☐ VENDOR ☐ USER ☐ MANUFACTURER

1 ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSF OR AMBIGUOUS? PLEASE EXPLAIN BELOW

A GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2 REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:47Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

HQ, CECOM
ATTN: DRSEL-ED-TO
FT. MONMOUTH, N.J. 07703

FOLD

☆ U S. GOVERNMENT PRINTING OFFICE 1982—[illegible]

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:47Z
Check the source to verify that this is the current version before use.