INCH-POUND
W-C-375/20B
04 August 2004
SUPERSEDING
W-C-375/20A
November 18, 1981

FEDERAL SPECIFICATION SHEET

CIRCUIT BREAKERS, MOLDED CASE, BRANCH CIRCUIT AND SERVICE, TYPE III, SERIES TRIP, TWO POLE (10 THROUGH 100 AMPERES)

W-C-375/20B is inactive for new design and is no longer used, except for replacement purposes.

The General Services Administration has authorized the use of this federal specification sheet by all federal agencies.

The complete requirements for procuring circuit breakers described herein shall consist of this document and the latest issue in effect of W-C-375. *



FIGURE. Dimensions and configuration of two pole circuit breaker.

* AMSC N/A

FSC 5925

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:26Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm
.125	3.18	2.1	53.34
.138	3.51	2.12	53.85
.190	4.83	2.25	57.15
.219	5.56	2.265	57.53
.24	6.10	2.46	62.48
.309	7.64	2.609	66.27
.684	17.37	4.75	120.65
1.062	26.97	5.80	147.32
1.125	28.58	6.00	152.40
		6.50	165.10

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
* 3. Tolerance is ±0.01 (0.25 mm) for two-place decimals and ±0.005 (0.13 mm) for three-place decimals.
4. OFF position is also the tripped position.

FIGURE 1. Dimensions and configuration of two pole circuit breaker - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:26Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

* Interface and physical dimensions: See figure 1.

Trip indication: See figure 1.

Electrical:

Interrupting current rating: 5,000 amperes.

Voltage rating: 120/240 V ac.

Current rating - See table I.

Frequency: 60 hertz.

Calibration: At +25°C.

* Enclosure for overload, endurance, and short circuit tests - Cutler-Hammer loadcenter, or equivalent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:26Z
Check the source to verify that this is the current version before use.

TABLE I. Part or Identifying Numbers (PINs) and current rating.

Government PIN	Current rating
WC375/20-001	10
WC375/20-002	15
WC375/20-003	20
WC375/20-004	25
WC375/20-005	30
WC375/20-006	35
WC375/20-007	40
WC375/20-008	50
WC375/20-009	60
WC375/20-010	70
WC375/20-011	100

TABLE II. Supersession and cross reference.

Government part number	Superseded number FSCM 74193
WC375/20-001	2X0411-10-120/240-60-9
WC375/20-002	2X0411-15-120/240-60-9
WC375/20-003	2X0411-20-120/240-60-9
WC375/20-004	2X0411-25-120/240-60-9
WC375/20-005	2X0411-30-120/240-60-9
WC375/20-006	2X0411-35-120/240-60-9
WC375/20-007	2X0411-40-120/240-60-9
WC375/20-008	2X0411-50-120/240-60-9
WC375/20-009	2X0411-60-120/240-60-9
WC375/20-010	2X0411-70-120/240-60-9
WC375/20-011	2X0411-100-120/240-60-9

* The margins of this specification are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:26Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians:
Navy - YD
Air Force - 11
DLA - CC

Review Activities:
Navy - MC, OS
Air Force - 99

CIVIL AGENCY COORDINATING ACTIVITIES:

DC GOVT - DCG
DOI -GES
DOJ - FPI
DOT - ACO
GSA - FSS
HHS - NPPTL
HUD - HSRS
VA - OSS

Preparing activity:
DLA - CC

(Project 5925-0360)

* NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://www.dodssp.daps.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:26Z
Check the source to verify that this is the current version before use.